

# nomencl: A Package to Create a Nomenclature

Boris Veytsman      Bernd Schandl      Lee Netherton  
CV Radhakrishnan      Brian Elmegaard

with contributions by

Stefan Pinnow      Patrick Egan      Rasmus Solmer Eriksen  
Andrea Kern      Christian Faulhammer

Package version v5.0 of 2018/12/29

## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	History . . . . .	3
1.2	Important Notes for Users of Previous Versions . . . . .	3
<b>2</b>	<b>Usage</b>	<b>3</b>
2.1	The Basics . . . . .	3
2.2	The Main Command . . . . .	4
2.3	Package Options . . . . .	6
2.4	Referencing . . . . .	7
2.5	Sorting . . . . .	9
2.6	Subgroups . . . . .	10
2.7	Tabular nomenclature ( <code>nomentbl</code> style) . . . . .	12
2.8	Customization . . . . .	12
	2.8.1 Formatting the Nomenclature . . . . .	12
	2.8.2 Formatting the Entries . . . . .	15
2.9	Tips and Tricks . . . . .	15
	2.9.1 Advanced subgroups . . . . .	15
	2.9.2 Units . . . . .	15
	2.9.3 Expansion . . . . .	16
	2.9.4 Glossary in “Kopka Style” . . . . .	18

2.10	Compatibility Mode	19
2.11	Acknowledgements	19
2.12	Releases and Legal Issues	20
<b>3</b>	<b>Implementation</b>	<b>20</b>
3.1	The <code>L<sup>A</sup>T<sub>E</sub>X</code> Package File	20
3.2	The <code>MakeIndex</code> Style File	29
	<b>Change Log</b>	<b>30</b>
	<b>Index</b>	<b>30</b>
 <b>List of Figures</b>		
1	Input for the simple example	5
2	The typeset output for the simple example	6
3	Explicit references	8
4	Typeset output for Figure 3	8
5	The <code>stdsubgroups</code> option	11
6	Use of <code>nomentbl</code> option	13
7	A simple example with units	16
8	Glossary entry in “Kopka Style”	18

# 1 Introduction

How often did you try to understand a theorem in a book, but just couldn't figure out what all those strange symbols were all about? The `nomenc` package should help authors format a nomenclature. It uses the powerful capabilities of the *MakeIndex* program to generate such a list automatically using information provided by the author throughout the text.

## 1.1 History

This package was written by Boris Veytsman for his paper in AiCHE in 1996. It was improved by Bernd Schandl, Lee Netherton, CV Radhakrishnan, and Brian Elmegaard up to 2006. In 2006 a version of `nomenc` for table-like nomenclature lists was released by Brian Elmegaard as `nomentbl`.

In 2018 Boris Veytsman took over the package, and merged the `nomentbl` fork back. He also changed some code, trying to keep the compatibility with the older `nomenc` and `nomentbl`.

## 1.2 Important Notes for Users of Previous Versions

An update to the `nomenc` package has included some major changes to some of the commands. In particular, the `\makeglossary` and `\printglossary` commands have now been renamed to `\makenomenclature` and `\printnomenclature` respectively. The reason for this change is to increase the package's compatibility with other *MakeIndex* using packages. With this increased compatibility, users will be able to have nomenclatures, glossaries and indexes all in one document.

There is a compatibility option that will allow you to still use your `\makeglossary` and `\printglossary` commands (see section 2.3), but it is advised that you change your `\...glossary` commands to the new `\...nomenclature` commands in your  $\text{\LaTeX}$  files. For more information on the compatibility mode see section 2.10.

# 2 Usage

## 2.1 The Basics

The creation of the nomenclature list is very similar to the creation of an index [6, App. A]. You need to:

- Put `\usepackage[<options>]{nomencl}` in the preamble of your document.
- `\makenomenclature`
- Put `\makenomenclature` in the preamble of your document.
- `\nomenclature`
- Issue the `\nomenclature` command (see Section 2.2) for each symbol you want to have included in the nomenclature list. The best place for this command is immediately after you introduce the symbol for the first time.
- `\printnomenclature`
- Put `\printnomenclature` at the place you want to have your nomenclature list.

Now put your file through  $\text{\LaTeX}$ . The command `\makenomenclature` will instruct  $\text{\LaTeX}$  to open the nomenclature file `<filename>.nlo` corresponding to your  $\text{\LaTeX}$  file `<filename>.tex` and to write the information from your `\nomenclature` commands to this file.

The next step is to invoke *MakeIndex*. You should instruct *MakeIndex* to use `<filename>.nlo` as your input file, use `nomencl.ist` as your style file and write output to the file `<filename>.nls`. How to do this depends on your implementation of *MakeIndex*. For most UNIX implementations you should write something like

```
makeindex <filename>.nlo -s nomencl.ist -o <filename>.nls
```

Now you have the file `<filename>.nls` that contains your nomenclature list properly ordered. The last step is to invoke  $\text{\LaTeX}$  on your master file `<filename>.tex` once more. It will input your `.nls` file and process it accordingly to the current options. That's all!

## 2.2 The Main Command

`\nomenclature` The main command of the `nomencl` package has the following syntax:

```
\nomenclature[<prefix>]{<symbol>}{<description>}
```

where `<prefix>` is used for fine tuning the sort order, `<symbol>` is the symbol you want to describe and `<description>` is the actual description. The sortkey will be `<prefix><symbol>`, where `<prefix>` is either the one from the optional argument or, if no optional argument was given, the default `<prefix>` which may be empty. See Section 2.5 to make sense of this.

Put this command immediately after the equation or text that introduces `<symbol>`. Usually it is a good idea to avoid a space or an unquoted

```

1 \(*sample01.tex)
2 \documentclass{article}
3 \usepackage[nocfg]{nomencl}
4 \makenomenclature
5 \begin{document}
6 \section*{Main equations}
7 \begin{equation}
8   a=\frac{N}{A}
9 \end{equation}%
10 \nomenclature{$a$}{The number of angels per unit area}%
11 \nomenclature{$N$}{The number of angels per needle point}%
12 \nomenclature{$A$}{The area of the needle point}%
13 The equation  $\sigma = m a$ %
14 \nomenclature{$\sigma$}{The total mass of angels per unit area}%
15 \nomenclature{$m$}{The mass of one angel}
16 follows easily.
17 \printnomenclature
18 \end{document}
19 \(/sample01.tex)

```

Figure 1: Input for the simple example

newline just in front of the `\nomenclature` command. Put a `%` at the end of the preceding line if necessary. Don't forget to enclose math in *symbol* in `$` signs.

Let's have a look at a simple example. If your input file looks like the one in Figure 1 then your nomenclature should look like Figure 2.

Note the necessary quoting of newlines to suppress spurious spaces.

Due to the way `\nomenclature` scans its arguments you don't need to `\protect` any macros, but you also must not have any character in front of the first or between the first and the second argument, especially no line break (even with a `%`). So

```

\nomenclature{$x$}%
  {Description}

```

does *not* work. You can have have line breaks in the argument, but also no `%`.

Note that `nomentbl` option described in Section 2.7 changes the syntax of this command.

## Nomenclature

- $\sigma$  The total mass of angels per unit area
- $A$  The area of the needle point
- $a$  The number of angels per unit area
- $m$  The mass of one angel
- $N$  The number of angels per needle point

Figure 2: The typeset output for the simple example

### 2.3 Package Options

The `nomenc1` package has the following options:

- refeq** The phrase “, see equation ( $\langle eq \rangle$ )” is appended to every entry in the nomenclature where  $\langle eq \rangle$  is the number of the last equation in front of the corresponding command `\nomenc1ature`.
- norefeq** No equation reference is printed. (default)
- refpage** The phrase “, page  $\langle page \rangle$ ” is appended to every entry in the nomenclature where  $\langle page \rangle$  is the number of the page on which the corresponding command `\nomenc1ature` appeared.
- norefpage** No page reference is printed. (default)
- prefix** Every sort key is preceded by the letter “a” (changeable); see Sections 2.5 and Section 2.6 to learn why this might make sense. (default)
- noprefix** No prefix is used.
- stdsubgroups** Use standard subgroups in nomenclature, see Section 2.6.
- nostdsubgroups** Do not use standard subgroups in nomenclature, see Section 2.6 (default).
- cfg** A configuration file, by default, `nomenc1.cfg` is loaded, if it exists (default). The variant `cfg=FILENAME` uses the configuration `FILENAME` instead of `nomenc1.cfg`. This is used in the examples in the package documentation.

- nocfg** The configuration file is not loaded.
- intoc** Inserts the nomenclature in the Table of Contents.
- notintoc** No entry for the nomenclature in the Table of Contents. (default)
- compatible** Run in compatibility mode. Older tex files may need this option selected to be able to compile. In the latest version of `nomenc` the commands `\makeglossary` and `\printglossary` were replaced with `\makenomenclature` and `\printnomenclature`. Selecting this option will redefine the old commands, but will lose the compatibility with other glossary packages.
- noncompatible** Do not run in compatibility mode. (default)
- nomentbl** Print nomenclature in the `nomentbl` style, see Section 2.7.
- nonomentbl** Do not print nomenclature in the `nomentbl` style, see Section 2.7 (default).
- croatian, danish, english, french, german, italian, polish, portuguese, russian, spanish, ukrainian** The reference texts and the nomenclature title will appear in the corresponding language. Note that in order to use Russian or Ukrainian, you have to have Cyrillic fonts installed and you might need a replacement for *MakeIndex*, e.g. `xindy`. Please help me out with other languages. (default: english)

## 2.4 Referencing

`\nomrefeq` As explained in Section 2.3, you can turn referencing to equations and pages on/off globally using the package options. But sometimes `\nomrefpage` you might want to change the referencing behavior for single entries. `\nomrefeqpage` The following six macros can be used inside a `\nomenclature` macro: `\nomnorefeq` `\nomrefpage`, `\nomnorefpage`, `\nomrefeqpage`, `\nomnorefeqpage`, `\nomnorefeqpage`. The first four work similarly to the package options, only local to the entry; the last two are shortcuts, so saying `\nomrefeqpage` is equivalent to `\nomrefeq\nomrefpage`.

If we changed the relevant parts of the last example as shown in Figure 3 then the nomenclature should look like Figure 4.

```

\begin{equation}
  a=\frac{N}{A}
\end{equation}%
\nomenclature{ $a$ }{The number of angels per unit area\nomrefeqpage}%
\nomenclature{ $N$ }{The number of angels per needle point\nomrefeq}%
\nomenclature{ $A$ }{The area of the needle point\nomrefeq\nomrefpage}%
The equation  $\sigma = m a$ %
\nomenclature{ $\sigma$ }{The total mass of angels per unit area}%
\nomenclature{ $m$ }{The mass of one angel\nomrefpage}
follows easily.
\printnomenclature
\end{document}

```

Figure 3: Explicit references

## Nomenclature

$\sigma$  The total mass of angels per unit area

$A$  The area of the needle point, see equation (1), page 1

$a$  The number of angels per unit area, see equation (1), page 1

$m$  The mass of one angel, page 1

$N$  The number of angels per needle point, see equation (1)

Figure 4: Typeset output for Figure 3



While these macros do not have to be at the end of the entries, it's probably the most sensible place to put them. Note that such local request always supersedes the package options.

## 2.5 Sorting

The Greek letter  $\sigma$  turned out to be first in the nomenclature list in the examples above because the backslash in `\sigma` precedes any alphabetical character. Sometimes this is not what you want. Then you can use `\langle prefix \rangle` to fine tune the sort order.

Before we describe the usage of `\langle prefix \rangle`, we have to explain how *MakeIndex* sorts entries, see [2]. *MakeIndex* distinguishes three kinds of sort keys:

**Strings** Everything that starts with a alphabetic letter (A...Z, a...z).

**Numbers** Everything that starts and only contains digits (0...9).

**Symbols** Everything else.

Each group is sorted separately (and differently), then the groups are sorted in the order symbols, numbers, strings<sup>1</sup>. For the groups the following algorithm is used:

**Strings** If two letters are compared, the usual ordering is used (`a<C<q`), but if two words are the same except for the capitalization, then an upper case letter precedes the lower case letter (`Tea<tea`). If a letter is compared with a non-letter (digit, symbol), ASCII code is used (`1<A<~`).<sup>2</sup> If two non-letters are compared (which can not happen at the first position of a string), ASCII code is used (`+<1<:<\`). Additionally there is the issue of word ordering (treat spaces as letters with ASCII code smaller than every printable symbol) and letter ordering (ignore spaces). *MakeIndex* uses word ordering by default, but you can change it with some command line option (`-1` on my UNIX).

**Numbers** The natural ordering is used (`8<34<111`).

**Symbols** ASCII code is used (`+<1<:<A<\<a`).

---

<sup>1</sup>With the `-g` switch of *MakeIndex*, they are sorted in the order symbols, strings, numbers.

<sup>2</sup>An exception seems to be that the non-letters between upper and lower case letters (code 91–96) are put just before the capital letters (between code 64 and 65) while the non-letters after the lower case letters (code 123–127) are left there.

Let's consider the following eight nomenclature entries (without the optional argument):  $\sim{Ab}$ ,  $\sim{aa}$ ,  $\backslash{Ab}$ ,  $\backslash{aa}$ ,  $\$Ab$ ,  $\$aa$ ,  $Ab$ ,  $aa$ . Try to understand the following example with the help of the explanation above and an ASCII table.

If you use `nomencl` with its default settings (i. e. “a” is added to every sort key, so every sort key is considered as a string), you will get the sort order  $\backslash{aa}$ ,  $\backslash{Ab}$ ,  $\$aa$ ,  $\$Ab$ ,  $\sim{aa}$ ,  $\sim{Ab}$ ,  $aa$ ,  $Ab$ . Note that  $aa$  is in front of  $Ab$  in all four pairs; note also the order  $\backslash{Ab}$ ,  $\$Ab$ ,  $\sim{Ab}$  which does not agree with the ASCII code.

If you specify the option `noprefix`, then you will get  $\$Ab$ ,  $\backslash{Ab}$ ,  $\backslash{aa}$ ,  $\$aa$ ,  $\sim{Ab}$ ,  $\sim{aa}$ ,  $aa$ ,  $Ab$ . The first six entries are considered as symbols and sorted according to the ASCII code (this time correctly). Note that  $\backslash{Ab}$  is in front of  $\backslash{aa}$  because  $A$  has the smaller ASCII code. The two strings follow at the end.

## 2.6 Subgroups

It often makes sense to separate index entries into several groups according to their meaning. The prefix parameter for the `\nomenclature` command provides a way to do it. The algorithm is:

1. Start prefixes with different letters for different subgroups.
2. Define `\nomgroup` command (see Section 2.8.1 below) to typeset group names.

One of the popular choices, suggested by Brian Elmegaard in `nomentbl` is the following (the corresponding prefixes are in bold):

**A** Latin letters

**G** Greek letters

**X** Superscripts

**Z** Subscripts

This choice is implemented in the `stsubgroups` option of the package, see Figure 5. A further customization is discussed in Section 2.8.

```

20 \langle *sample02.tex\rangle
21 % Example provided by Stefan Pinnow (SP)
22 \documentclass{article}
23 \usepackage[stdsubgroups,nocfg]{nomencl}
24 \usepackage{setspace}
25     \makenomenclature
26 \begin{document}
27 \section*{Main equations}
28 Here an equation
29     \begin{equation}\label{eq:heatflux}
30         \dot{Q} = k \cdot A \cdot \Delta T
31     \end{equation}%
32     \nomenclature[aQ]{\dot{Q}}{heat flux}%
33     \nomenclature[ak]{k}{overall heat transfer
34         coefficient}%
35     \nomenclature[aA]{A}{area}%
36     \nomenclature[aL]{L}{length}%
37     \nomenclature[aT]{T}{temperature}%
38     \nomenclature[aT]{\Delta T}{temperature difference}%
39 or another one
40     \begin{equation}\label{eq:htc}
41         \frac{1}{k} = \left[ \frac{1}{\alpha_{\mathrm{i}}}, r_{\mathrm{i}} +
42             \sum_{j=1}^n \frac{1}{\lambda_j},
43             \ln \frac{r_{\mathrm{a},j}}{r_{\mathrm{i},j}} +
44             \frac{1}{\alpha_{\mathrm{a}}},
45             r_{\mathrm{a}} \right] \cdot r_{\mathrm{reference}}
46     \end{equation}%
47     \nomenclature[ga]{\alpha}{convection heat transfer coefficient}%
48     \nomenclature[zi]{i}{in}%
49     \nomenclature[gl]{\lambda}{thermal conductivity}%
50     \nomenclature[za]{a}{out}%
51     \nomenclature[zn]{n}{number of walls}%
52     \nomenclature[zj]{j}{running parameter}%
53 \onehalfspacing
54 \printnomenclature
55 \end{document}
56 \langle /sample02.tex\rangle

```

Figure 5: The stdsubgroups option

## 2.7 Tabular nomenclature (nomentbl style)

The option `nomentbl` changes the behavior of nomenclature.

`\nomenclature` The command `\nomenclature` now has four, rather than two, mandatory arguments:

```
\nomenclature[⟨prefix⟩]{⟨symbol⟩}{⟨description⟩}{⟨units⟩}{⟨note⟩}
```

Here `[⟨prefix⟩]`, `{⟨symbol⟩}`, and `{⟨description⟩}` have the same meaning as for the usual `\nomenclature` command. The additional arguments are `{⟨units⟩}`, which is internally enclosed in the `\si` command from `siunitx` package, and `\note`, which is an arbitrary note added to the description.

`\setnomtableformat` The list is wrapped in a `longtable` with the default format

```
lp{0.4\textwidth}sp{0.3\textwidth}@{}l
```

The command `\setnomtableformat{⟨format⟩}` can be used to change it, for example,

```
\setnomtableformat{lllll}
```

Note that the table has five columns: symbol, description, units, note, and reference. If you do not use references, you may suppress the last column using `@{}l` declaration. The `s` column is used for units in the `siunitx` format.

Figure 6 provides an example of this option.

## 2.8 Customization

Besides the things you can customize by using the package options, there are a few more commands that you might want to redefine. If you make the same changes in every file, it's probably easier to put all those in a file `nomencl.cfg` which is automatically read by the `nomencl` package whenever it exists in the search path (unless you specified the `nocfg` option). You can experiment with loading alternative configuration files using `cfg=FILENAME` version of this option.

### 2.8.1 Formatting the Nomenclature

`\printnomenclature` Probably the most common change to the nomenclature is a different amount of space for the symbols. By default, the nomenclature is formatted as a list with the label width equal to `\nomlabelwidth` which is initialized

```

57 \langle *sample03.tex\rangle
58 % Example provided by Stefan Pinnow (SP)
59 \documentclass{article}
60 \usepackage[nomentbl, stdsubgroups]{nomencl}
61 \usepackage{setspace}
62 \makenomenclature
63 \begin{document}
64 \section*{Main equations}
65 %
66 Here an equation
67 \begin{equation}\label{eq:heatflux}
68 \quad \dot{Q} = k \cdot A \cdot \Delta T
69 \end{equation}%
70 \nomenclature[aQ]{\dot{Q}}{heat flux}{W}{}%
71 \nomenclature[ak]{k}{overall heat transfer
72 coefficient}{\watt\per(\square\meter\kelvin)}{see
73 eq.~(\ref{eq:ohtc})}%
74 \nomenclature[AA]{A}{area}{\square\meter}{}%
75 \nomenclature[aL]{L}{length}{\meter}{SI base quantity}%
76 \nomenclature[aT]{T}{temperature}{\kelvin}{SI base quantity}%
77 \nomenclature[aT]{\Delta T}{temperature difference}{\kelvin}{SI base quantity}%
78 or another one
79 \begin{equation}\label{eq:ohtc}
80 \quad \frac{1}{k} = \left[ \frac{1}{\alpha_{\mathrm{i}}}, r_{\mathrm{i}} +
81 \sum_{j=1}^n \frac{1}{\lambda_j},
82 \ln \frac{r_{\mathrm{a},j}}{r_{\mathrm{i},j}} +
83 \frac{1}{\alpha_{\mathrm{a}}},
84 r_{\mathrm{a}} \right] \cdot r_{\mathrm{reference}}
85 \end{equation}%
86 \nomenclature[ga]{\alpha}{convection heat transfer
87 coefficient}{\watt\per(\square\meter\kelvin)}{}%
88 \nomenclature[zi]{i}{in}{}%
89 \nomenclature[gl]{\lambda}{thermal conductivity}{\watt\per\kelvin}{}%
90 \nomenclature[za]{a}{out}{}%
91 \nomenclature[zn]{n}{number of walls}{}%
92 \nomenclature[zj]{j}{running parameter}{}%
93
94 \onehalfspacing
95 \printnomenclature
96 \end{document}
97 \langle /sample03.tex\rangle

```

Figure 6: Use of nomentbl option

to 1 cm. You can change this dimension in the `cfg` file or you can use the optional argument of `\printnomenclature`. If you want to have a little more space for the labels (and you don't live in a metric world) you can use `\printnomenclature[0.5in]` instead of the simple `\printnomenclature`.

`thenomenclature` If you don't like the format of the nomenclature at all, you will have to redefine the `thenomenclature` environment. Maybe a look at the documented code of `nomenc1` will help.

`\nomname` In case you don't like the name of the nomenclature, just redefine the `\nomname` macro, e. g.

```
\renewcommand{\nomname}{List of Symbols}
```

Putting an entry for the nomenclature in the table of contents can be done by adding an `intoc` to the package options.

`\nomgroup` Usually, `MakeIndex` inserts the macro `\indexspace` between every character group, i. e. between symbols and numbers, numbers and letters and between every two letter groups. The `nomenc1` package inserts the macro `\nomgroup{<arg>}` instead, where `<arg>` is either the string "Symbols" or the string "Numbers" or the capital letter of the group that is about to start. You can redefine `\nomgroup` to insert some white space `\renewcommand{\nomgroup}[1]{\medskip}`, or to print a fancy divider

```
\renewcommand{\nomgroup}[1]{%
  \item[]\hspace*{-\leftmargin}%
  \rule[2pt]{0.45\linewidth}{1pt}%
  \hfill #1\hfill
  \rule[2pt]{0.45\linewidth}{1pt}}
```

Note that `\nomgroup` is executed in a list environment, so you need to have an `\item` first and then jump back to the beginning of the line with the `\hspace` command.

`\nompreamble` Maybe you want to explain something just between the title of the  
`\nompostamble` nomenclature and the start of the list or at the very end of the list. Just redefine the macros `\nompreamble` and `\nompostamble` which do nothing by default. Note that they are executed *outside* of the list environment.

`\nomitemsep` The skip between two entries in the nomenclature can be adjusted using `\nomitemsep`. This should be done in the preamble or the file `nomenc1.cfg`. Note that if you want no extra skip between entries you have to use `\setlength{\nomitemsep}{-\parsep}`

`\nomprefix` If you want, you can redefine the default prefix that is used for the sortkeys. By default, `\nomprefix` is set to "a"; redefining it supersedes the package options `prefix` and `noprefix`.

## 2.8.2 Formatting the Entries

`\nomlabel` By default, the labels are just shifted to the left within their allocated box. If you want to change this, redefine `\nomlabel` which should get one argument, e.g. `\renewcommand{\nomlabel}[1]{\hfil #1\hfil}` to center the symbols.

`\numentryend` Maybe you would like to have a period at the end of every entry. Just say `\renewcommand{\numentryend}{.}`, and there it is. Section 2.9.2 explains another nice application of this macro.

`\eqdeclaration` If you don't like the text that is used for the references to equations and pages, you can define `\eqdeclaration` and `\pagedeclaration`. Both should accept one argument, namely the equation and page number, respectively. An example is

```
\renewcommand{\eqdeclaration}[1]{, first used in eq.~(#1)}.
```

## 2.9 Tips and Tricks

### 2.9.1 Advanced subgroups

The standard subgroups described in Section 2.6 is just one of the possible ways to separate your index. You can do much more if you play with the `\nomgroup` command. Note that all entries sharing the first letter of prefix as grouped together and preceded by the `\nomgroup[⟨Uppercased first letter⟩]` command. So, for example, if you want to separate constants and variables, you may use prefixes `c...` for constants and `v...` for variables, and then write down (package `ifthen` being loaded by `nomencl`)

```
\renewcommand{\nomgroup}[1]{%
\ifthenelse{\equal{#1}{R}}{\item[\textbf{Variables}]}{%
\ifthenelse{\equal{#1}{G}}{\item[\textbf{Constants}]}{}}
```

### 2.9.2 Units

Besides the obvious possibility of adding units for symbols in the description string, you can also use `\numentryend` to shift the unit to the right margin. With package `siunitx` you can define

```
98 \*sample04.cfg)
99 \newcommand{\nomunit}[1]{%
100 \renewcommand{\numentryend}{\hspace*{\fill}\si{#1}}
101 \*sample04.cfg)
```

and then define nomenclature as

```

102 \(*sample04.tex)
103 \documentclass{article}
104 \usepackage[cfg=sample04.cfg]{nomencl}
105 \usepackage{siunitx}
106 \makenomenclature
107 \begin{document}
108 \section*{Main equations}
109 \begin{equation}
110 a=\frac{N}{A}
111 \end{equation}%
112 \nomenclature{$a$}{The number of angels per unit
113 area\nomunit{\per\square\meter}}%
114 \nomenclature{$N$}{The number of angels per needle point}%
115 \nomenclature{$A$}{The area of the needle
116 point\nomunit{\square\meter}}%
117 The equation  $\sigma = m a$ %
118 \nomenclature{$\sigma$}{The total mass of angels per unit
119 area\nomunit{\kilogram\per\square\meter}}%
120 \nomenclature{$m$}{The mass of one angel\nomunit{\kilogram}}
121 follows easily.
122 \printnomenclature
123 \end{document}
124 \(/sample04.tex)

```

Figure 7: A simple example with units

```
\nomenclature{$l$}{Length\nomunit{\meter}}
```

See Figure 7 for the example of the input file.

Option `nomentbl` allows an alternative way to add units to the nomenclature (Section 2.7).

### 2.9.3 Expansion

The `nomencl` package tries hard to write the arguments of the `\nomenclature` macro verbatim to the glossary file. This is usually the right thing to do because some macros do not like to be expanded at the wrong moment or give weird results if they are. On the other hand, there are occasions where it is good to have the meaning (or expansion) of a macro in the glossary file instead of its name. There are quite some occasions where you will get in trouble with this expansion, for example, if the expansion of a macro contains `@` (`\mathcal` expands to `\@mathcal`) because `@` is a special



character for *MakeIndex* and thus *MakeIndex* will either fail or give unexpected results. You can avoid the expansion on a case by case basis by using `\protect` in front of the macro that should not be expanded.

In order to get macro expansion, the redefinition of the `\nomenclature` macro within the `\makenomenclature` macro has to be changed.

```

125 \(*sample05.cfg)
126 \def\makenomenclature{%
127   \newwrite\@nomenclaturefile
128   \immediate\openout\@nomenclaturefile=\jobname\@outputfileextension
129   \def\@nomenclature{%
130     \ifnextchar[%
131       {\@@@nomenclature}\@@@nomenclature[\nomprefix]}}%
132   \PackageInfo{nomencl}{Writing nomenclature file \jobname\@outputfileextension}%
133   \let\makenomenclature\@empty}

```

The new macro to be called by `\@nomenclature` just writes its arguments to the glossary file without further ado, so they will be expanded.

```

134 \def\@@@nomenclature[#1]#2#3{%
135   \protected@write\@nomenclaturefile{%
136     {\string\nomenclatureentry{#1#2@[#2]}}%
137     \begingroup#3\protect\nomeqref{\theequation}%
138     |nompageref|{\thepage}}}%
139 \(/sample05.cfg)

```

The following file has completely different result when using expanded and non-expanded versions

```

140 \(*sample05.tex)
141 \documentclass{article}
142 \usepackage[cfg=sample05.cfg]{nomencl}
143 \makenomenclature
144 \begin{document}
145 \section*{Main equations}
146 \begin{equation}
147   a=\frac{N}{A}
148 \end{equation}%
149 \newcommand{\magritte}{Not the number }
150 \nomenclature{\$a\$}{\magritte of angels per unit area}%
151 \nomenclature{\$N\$}{\magritte of angels per needle point}%
152 \nomenclature{\$A\$}{The area of the needle point}%
153 The equation  $\sigma = m a$ %
154 \nomenclature{\$\sigma\$}{The total mass of angels per unit area}%
155 \nomenclature{\$m\$}{The mass of one angel}
156 follows easily.
157
158 % We renew the command before printing nomenclature. However, since

```

**Symbol** . . . . . page number  
 Explanation.

Figure 8: Glossary entry in “Kopka Style”

```
159 % our nomencl.cfg uses expansion, it does not affect the result.
160 % Cf. nocfg option
161 \renewcommand{\magritte}{The number }
162 \printnomenclature
163 \end{document}
164 </sample05.tex>
```

#### 2.9.4 Glossary in “Kopka Style”

I was told that the glossary in the L<sup>A</sup>T<sub>E</sub>X book by Kopka looks roughly like in Figure 8. In order to get a glossary like this, there are quite some configurations to do.

First we have to change the macro `\@@@nomenclature` which takes care of writing the glossary entry to the glossary file. The only difference to the original definition is that we hand over the explanation of a symbol (`#3`) and the equation number to `\nompageref` instead of writing it directly after the symbol (`#2`). This is necessary because the explanation should appear after (actually below) the page number.

```
165 (*sample06.cfg)
166 \@printpagereftrue
167 \def\@@@nomenclature[#1]#2#3{%
168   \def\@tempa{#2}\def\@tempb{#3}%
169   \protected@write\@nomenclaturefile{%
170     {\string\nomenclatureentry{#1\nom@verb\@tempa @[\nom@verb\@tempa]}%
171       |nompageref{\begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}}}%
172     {\thepage}}%
173   \endgroup
174   \@esphack}
```

Now we change the definition of `\nompageref` so that it accepts two arguments, the explanation (`#1`) and the page number (`#2`). The page number is only printed if required, otherwise `\null` is used to avoid an error because of the following `\linebreak`. Note that it is *not* possible to turn off the page number locally, because the explanation appears after the page number.

```
175 \def\nompageref#1#2{%
176   \if@printpageref\pagedeclaration{#2}\else\leavevmode\fi
177   \linebreak#1\nomentryend\endgroup}
```

And a few little things. We want dots and a space before the page number appears at the right margin; the explanation should end with a period; and the symbol should be printed in bold face (this only works for regular text, not for formulas).

```
178 \def\pagedeclaration#1{\dotfill\nobreakspace#1}
179 \def\nomentryend{.}
180 \def\nomlabel#1{\textbf{#1}\hfil}
181 \</sample06.cfg
```

## 2.10 Compatibility Mode

With previous versions of the `nomenc1`, the commands `\makeglossary` and `\pringlossary` were used to generate and display the nomenclature. These commands have now been deprecated, and replaced with the `\makenomenclature` and `\printnomenclature` commands. The new commands do exactly the same as the old commands, but because of the name changes, the package is now compatible with other packages which use the `\makeglossary` commands. The previous versions of `nomenc1` also used the file extensions `.glo` and `.gls` for the generated output and input files. These extensions have now been changed to `.nlo` and `.nls` respectively—again, for increased compatibility.

For all of the legacy  $\text{\LaTeX}$  files out there which use the old commands there is a compatibility option available so that the old commands will still work without having to change any of the existing code. To enable the compatibility mode simply supply the **compatible** option when using the package. For example:

```
\usepackage[compatible]{nomenc1}
```

Under compatibility mode, the package will generate and use files with the old-style file extensions (i.e. `.glo` and `.gls`).

It is worth noting that even though the compatibility mode is available, it is highly recommended to update your  $\text{\LaTeX}$  files to use the new nomenclature commands.

## 2.11 Acknowledgements

Since version 5.0 the package incorporates the code from `nomentb1.dtx` by Brian Elmegaard.

The authors want to thank Stefan Böhm and Karl Heinz Marbaise who helped testing this package.

The translations were done by Branka Lončarević (Croatian), Brian Elmegaard (Danish), Denis B. Roegel (French), Sani Egisto (Italian), Artur Gorka (Polish), Pedro Areal (Portuguese), Alejandro Lopez-Valencia (Spanish) and Boris Veytsman (Russian and Ukrainian).

## 2.12 Releases and Legal Issues

This package can be redistributed and/or modified under the terms of the L<sup>A</sup>T<sub>E</sub>X Project Public License distributed from CTAN archives in the directory [macros/latex/base/lppl.txt](https://ctan.org/ctan/packages/macros/latex/base/lppl.txt), see e. g. [3]; either version 1.2 of the license, or (at your option) any later version.

## 3 Implementation

### 3.1 The L<sup>A</sup>T<sub>E</sub>X Package File

At the beginning of this file, the `\ProvidesPackage` macro was executed. So we only need to state that we need L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

```
182 <*package>
183 \NeedsTeXFormat{LaTeX2e}
```

We need `xkeyval` package for some options and `ifthen` for grouping

```
184 \RequirePackage{xkeyval}
185 \RequirePackage{ifthen}
```

```
\if@printeqref We need two switches to decide whether references to equations and pages
\if@printpageref should be printed.
```

```
186 \newif\if@printeqref
187 \newif\if@printpageref
```

```
\if@intoc Another switch to decide whether to add an entry to the TOC.
```

```
188 \newif\if@intoc
```

```
\if@compatibilitymode Another switch to decide whether to run in compatibility mode.
```

```
189 \newif\if@compatibilitymode
```

And the options to set these switches globally.

```
190 \DeclareOptionX{refeq}{\@printeqreftrue}
191 \DeclareOptionX{norefeq}{\@printeqreffalse}
192 \DeclareOptionX{refpage}{\@printpagereftrue}
193 \DeclareOptionX{norefpage}{\@printpagereffalse}
194 \DeclareOptionX{intoc}{\@intoctrue}
```

```

195 \DeclareOptionX{notintoc}{\@intocfalse}
196 \DeclareOptionX{compatible}{\@compatibilitymodetrue}
197 \DeclareOptionX{noncompatible}{\@compatibilitymodefalse}

```

`\nomprefix` It might make sense to add the prefix “a” to every sortkey, see Section 2.5.

```

198 \DeclareOptionX{prefix}{\def\nomprefix{a}}
199 \DeclareOptionX{noprefix}{\def\nomprefix{}}

```

`\if@nomentbl` Whether to use nomentbl format

```

200 \newif\if@nomentbl
201 \DeclareOptionX{nomentbl}{\@nomentbltrue}
202 \DeclareOptionX{norefeq}{\@nomentblfalse}

```

`\if@loadcfg` Another switch and the corresponding options to decide whether we should look for a configuration file.

```

203 \newif\if@loadcfg
204 \DeclareOptionX{cfg}[nomencl.cfg]{\@loadcfgtrue\gdef\@cfgfile{#1}}
205 \DeclareOptionX{nocfg}{\@loadcfgfalse}

```

`\if@stdsubgroups` Whether we use standard subgroups

```

206 \newif\if@stdsubgroups
207 \DeclareOptionX{stdsubgroups}{\@stdsubgroupstrue}
208 \DeclareOptionX{nostdsubgroups}{\@stdsubgroupsfalse}

```

`\eqdeclaration` If you can help out with translations for some other languages, let me know.

```

\pagedeclaration 209 \def\eqdeclaration#1{equation\nobreakspace(#1)}%
  \nomname       210 \def\pagedeclaration#1{\hspace*{2mm}page\nobreakspace#1}%
  \nomAname     211 \def\nomname{Nomenclature}%
  \nomGname     212 \def\nomAname{Latin Letters}%
  \nomXname     213 \def\nomGname{Greek Letters}%
  \nomZname     214 \def\nomXname{Superscripts}%
                215 \def\nomZname{Subscripts}
                216 \DeclareOptionX{croatian}{%
                217 \def\eqdeclaration#1{, vidi jednad\v{z}bu\nobreakspace(#1)}%
                218 \def\pagedeclaration#1{, stranica\nobreakspace#1}%
                219 \def\nomname{Popis simbola}%
                220 \def\nomAname{Latini\v{c}na slova}%
                221 \def\nomGname{Gr\v{c}ka slova}%
                222 \def\nomXname{Exponenats}%
                223 \def\nomZname{Indeksi}}
                224 \DeclareOptionX{danish}{%
                225 \def\eqdeclaration#1{, se ligning\nobreakspace(#1)}%
                226 \def\pagedeclaration#1{, side\nobreakspace#1}%
                227 \def\nomname{Symbolliste}%

```

```

228 \def\nomAname{Romerske bogstaver}%
229 \def\nomGname{Gr{\ae}ske bogstaver}%
230 \def\nomXname{(H{\o}jtstillede) indices}%
231 \def\nomZname{Indices}}
232 \DeclareOptionX{english}{%
233 \def\eqdeclaration#1{, see equation\nobreakspace(#1)}%
234 \def\pagedeclaration#1{, page\nobreakspace#1}%
235 \def\nomname{Nomenclature}%
236 \def\nomAname{Latin Letters}%
237 \def\nomGname{Greek Letters}%
238 \def\nomXname{Superscripts}%
239 \def\nomZname{Subscripts}}
240 \DeclareOptionX{french}{%
241 \def\eqdeclaration#1{, voir \'equation\nobreakspace(#1)}%
242 \def\pagedeclaration#1{, page\nobreakspace#1}%
243 \def\nomname{Liste des symboles}%
244 \def\nomAname{Lettres latines}%
245 \def\nomGname{Lettres grecques}%
246 \def\nomXname{Indices sup{\'}erieurs}%
247 \def\nomZname{Indices}}
248 \DeclareOptionX{german}{%
249 \def\eqdeclaration#1{, siehe Gleichung\nobreakspace(#1)}%
250 \def\pagedeclaration#1{, Seite\nobreakspace#1}%
251 \def\nomname{Symbolverzeichnis}%
252 \def\nomAname{Lateinische Buchstaben}%
253 \def\nomGname{Griechische Buchstaben}%
254 \def\nomXname{(hochgestellte) Indizes}%
255 \def\nomZname{Indizes}}
256 \DeclareOptionX{italian}{%
257 \def\eqdeclaration#1{, vedi equazione\nobreakspace(#1)}%
258 \def\pagedeclaration#1{, pagina\nobreakspace#1}%
259 \def\nomname{Elenco dei simboli}%
260 \def\nomAname{Lettere latine}%
261 \def\nomGname{Lettere greche}%
262 \def\nomXname{Apici}%
263 \def\nomZname{Indici}}
264 \DeclareOptionX{polish}{%
265 \def\eqdeclaration#1{, porownaj rownanie\nobreakspace(#1)}%
266 \def\pagedeclaration#1{, strona\nobreakspace#1}%
267 \def\nomname{Lista symboli}%
268 \def\nomAname{Litery {\l}aci\'nskie}%
269 \def\nomGname{Litery greckie}%
270 \def\nomXname{Indeksy g\'orny}%
271 \def\nomZname{Indeksy dolne}}
272 \DeclareOptionX{portuguese}{%

```

```

273 \def\eqdeclaration#1{, veja equa\c{c}\~ao\nobreakspace(#1)}%
274 \def\pagedeclaration#1{, p\'agina\nobreakspace#1}%
275 \def\nomname{Nomenclatura}%
276 \def\nomAname{Letras latinas}%
277 \def\nomGname{Letras gregas}%
278 \def\nomXname{Sobrescritos}%
279 \def\nomZname{Subscritos}}
280 \DeclareOptionX{russian}{%
281 \def\eqdeclaration#1{, \cyrs\cyrm.\nobreakspace(#1)}%
282 \def\pagedeclaration#1{, \cyrs\cyrt\cyrr.\nobreakspace#1}%
283 \def\nomname{\CYRS\cyrp\cyri\cyrs\cyro\cyrk%
284 \ \cyro\cyrb\cyro\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyri%
285 \cyrishrt}%
286 \def\nomAname{\CYRL\cyra\cyrt\cyri\cyrn\cyrs\cyrk\cyri\cyre\
287 \cyrb\cyru\cyrk\cyrv\cyrery}%
288 \def\nomGname{\CYRG\cyrr\cyre\cyrch\cyre\cyrs\cyrk\cyri\cyre\
289 \cyrb\cyru\cyrk\cyrv\cyrery}%
290 \def\nomXname{\CYRN\cyra\cyrd\cyrs\cyrt\cyrr\cyro\cyrch\cyrn\cyrery\cyre\
291 \cyri\cyrn\cyrd\cyre\cyrk\cyrs\cyrery}%
292 \def\nomZname{\CYRP\cyro\cyrd\cyrs\cyrt\cyrr\cyro\cyrch\cyrn\cyrery\cyre\
293 \cyri\cyrn\cyrd\cyre\cyrk\cyrs\cyrery}}
294 \DeclareOptionX{spanish}{%
295 \def\eqdeclaration#1{, v\'ease la ecuaci\'on\nobreakspace(#1)}%
296 \def\pagedeclaration#1{, p\'agina\nobreakspace#1}%
297 \def\nomname{Nomenclatura}%
298 \def\nomAname{Letras latinas}%
299 \def\nomGname{Letras griegas}%
300 \def\nomXname{Super{\'\i}ndices}%
301 \def\nomZname{Sub{\'\i}ndices}}
302 \DeclareOptionX{ukrainian}{%
303 \def\eqdeclaration#1{, \cyrd\cyri\cyrv.\nobreakspace(#1)}%
304 \def\pagedeclaration#1{, \cyrs\cyrt\cyro\cyrr.\nobreakspace#1}%
305 \def\nomname{\CYRP\cyre\cyrr\cyre\cyrl\cyrii\cyrk%
306 \ \cyrp\cyro\cyrz\cyrn\cyra\cyrch\cyre\cyrn\cyrsftsn}%
307 \def\nomAname{\CYRL\cyra\cyrt\cyri\cyrn\cyrs\cyrsftsn\cyrk\cyrii\
308 \cyrl\cyrii\cyrt\cyre\cyrr\cyri}%
309 \def\nomGname{\CYRG\cyrr\cyre\cyrc\cyrsftsn\cyrk\cyrii\
310 \cyrl\cyrii\cyrt\cyre\cyrr\cyri}%
311 \def\nomXname{\CYRV\cyre\cyrr\cyrh\cyrn\cyrii\
312 \cyrii\cyrn\cyrd\cyre\cyrk\cyrs\cyri}%
313 \def\nomZname{\CYRII\cyrn\cyrd\cyre\cyrk\cyrs\cyri}}

```

Finally set the default options and process everything.

```

314 \ExecuteOptionsX{noncompatible,notintoc,norefeq,norefpage,prefix,cfg,english,nostdsubg
315 \ProcessOptionsX\relax

```

In the `nomentbl` mode we need a couple more packages

```
316 \if@nomentbl
317 \RequirePackage{array,longtable, siunitx}
318 \fi
```

`\@outputfileextension` The default file extension for the output and input nomenclature files are  
`\@inputfileextension` `.nlo` and `.nls` respectively. In compatibility mode, these are changes to  
`.glo` and `.gls`.

```
319 \if@compatibilitymode%
320   \def\@outputfileextension{.glo}%
321   \def\@inputfileextension{.gls}%
322 \else%
323   \def\@outputfileextension{.nlo}%
324   \def\@inputfileextension{.nls}%
325 \fi%
```

`\makenomenclature` The definition of `\makenomenclature` is pretty much the same as in the  
L<sup>A</sup>T<sub>E</sub>X kernel for `\makeglossary`, we only use `\@nomenclature` instead of  
`\glossary`.

```
326 \def\makenomenclature{%
327   \newwrite\@nomenclaturefile
328   \immediate\openout\@nomenclaturefile=\jobname\@outputfileextension
329   \def\@nomenclature{%
330     \bsphack
331     \begingroup
332     \@sanitize
333     \ifnextchar[%
334       {\@@@nomenclature}{\@@@nomenclature[\nomprefix]}}%
335   \PackageInfo{nomencl}{Writing nomenclature file \jobname\@outputfileextension}%
336   \let\makenomenclature\@empty}
```

`\makeglossary` The `\makeglossary` command has been depreciated, and is only available  
in compatibility mode.

```
337 \if@compatibilitymode\let\makeglossary\makenomenclature\fi%
```

`\nom@verb` The macro `\nom@verb`, which is copied from [4] and [5, p. 382], makes it  
possible to use `\nomenclature` in another macro.

```
338 \def\nom@verb{\expandafter\strip@prefix\meaning}
```

`\nomenclature` This macro just protects the “real” `\@nomenclature` macro. I am not  
sure whether this makes sense because you shouldn’t use `\nomenclature`  
in something like `\section` anyway, but it doesn’t hurt.

```
339 \def\nomenclature{\protect\@nomenclature}
```



`\@nomenclature` Without an executed `\makenomenclature`, `\@nomenclature` will only change some catcodes and call the macro `\@@nomenclature` to gobble its arguments.

```

340 \def\@nomenclature{%
341   \@bsphack
342   \begingroup
343   \@sanitize
344   \@ifnextchar[%
345     {\@nomenclature}\@nomenclature[\nomprefix]}}
346 \if@nomentbl
347   \def\@@nomenclature[#1]#2#3#4#5{\endgroup\@esphack}
348 \else
349   \def\@@nomenclature[#1]#2#3{\endgroup\@esphack}
350 \fi

```

`\@@@nomenclature` If `\makenomenclature` was already executed, then `\@nomenclature` calls the macro `\@@@nomenclature` which writes to the nomenclature file. It puts the prefix in front of the entry, adds brackets `[]` around the entry (because it will be the argument of an `\item`) and adds possible references at the end of the entry description. A group is started to keep changes to the reference switches local. The arguments are written using `\nom@verb` so they will not be expanded, even when `\nomenclature` is used within another macro. By the way, `\@bsphack` and `\@esphack` makes `\nomenclature` disappear between two spaces; unfortunately this doesn't work if `\nomenclature` is the first thing in a line.

```

351 \if@nomentbl
352   \def\@@@nomenclature[#1]#2#3#4#5{%
353     \def\@tempa{#2}\def\@tempb{#3}%
354     \protected@write\@nomenclaturefile{%
355       {\string\nomenclatureentry{#1\nom@verb\@tempa @&{\nom@verb\@tempa}&%
356         \begingroup\nom@verb\@tempb\endgroup &\begingroup#4\endgroup&%
357         \begingroup#5\endgroup&\begingroup\protect\nomeqref{\theequation}%
358         |nompageref}{\thepage}}%
359     \endgroup
360     \@esphack}
361 \else
362   \def\@@@nomenclature[#1]#2#3{%
363     \def\@tempa{#2}\def\@tempb{#3}%
364     \protected@write\@nomenclaturefile{%
365       {\string\nomenclatureentry{#1\nom@verb\@tempa @[{\nom@verb\@tempa}]%
366         \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
367         |nompageref}{\thepage}}%
368     \endgroup

```

```

369   \@esphack}
370 \fi

```

`\nomgroup` The next macro is executed between each character group in the nomenclature. The argument is the first character of the group.

```

371 \if@stdsubgroups
372   \if@nomentbl
373   \def\nomgroup#1{%
374     \ifthenelse{equal{#1}{A}}{%
375       \item&\multicolumn{5}{@{}1}{\textbf{\nomAname}}}%
376     \ifthenelse{equal{#1}{G}}{%
377       \item&\multicolumn{5}{@{}1}{\textbf{\nomGname}}}%
378     \ifthenelse{equal{#1}{X}}{%
379       \item&\multicolumn{5}{@{}1}{\textbf{\nomXname}}}%
380     \ifthenelse{equal{#1}{Z}}{%
381       \item&\multicolumn{5}{@{}1}{\textbf{\nomZname}}}%
382     {}}}}
383   \else
384     \def\nomgroup#1{%
385       \ifthenelse{equal{#1}{A}}{%
386         \item[\textbf{\nomAname}]}%
387       \ifthenelse{equal{#1}{G}}{%
388         \item[\textbf{\nomGname}]}%
389       \ifthenelse{equal{#1}{X}}{%
390         \item[\textbf{\nomXname}]}%
391       \ifthenelse{equal{#1}{Z}}{%
392         \item[\textbf{\nomZname}]}%
393       {}}}}
394   \fi
395 \else
396   \def\nomgroup#1{}
397 \fi

```

`\nomlabelwidth` This is the default label width for the nomenclature. It can be changed e.g. in the `cfg` file.

```

398 \newdimen\nomlabelwidth
399 \nomlabelwidth1cm\relax

```

`\nom@tempdim` The optional argument is read and assigned to `\nom@tempdim`. Then the `gls` file is read.

```

\printnomenclature
\@printnomenclature 400 \newdimen\nom@tempdim
401 \def\printnomenclature{%
402   \@ifnextchar[%
403     {\@printnomenclature}{\@printnomenclature[\nomlabelwidth]}

```

```

404 \def\@printnomenclature[#1]{%
405   \nom@tempdim#1\relax
406   \@input@{\jobname\@inputfileextension}}

```

`\printglossary` The `\printglossary` command has been depreciated, and is only available in compatibility mode.

```

407 \ifcompatibilitymode\let\printglossary\printnomenclature\fi%

```

`\nomlabel` Now some bells and whistles to format the nomenclature: the definition of the label, the preamble, the postamble and the symbol that is added at the end of an entry. The last three are defined to do nothing by default.

```

\nompreamble
\nompostamble
\numentryend
408 \def\nomlabel#1{#1\hfil}
409 \def\nompreamble{}
410 \def\nompostamble{}
411 \def\numentryend{}

```

`\nomitemsep` The skip between two items is adjustable by changing `\nomitemsep`. It defaults to `\itemsep`.

```

412 \newskip\nomitemsep
413 \nomitemsep\itemsep

```

`\setnomtableformat` The format of the nomenclature table. We insert an empty left column due to the way  $\TeX$  sees `\multicolumn` in `\nomgroup` command.

```

414 \def\setnomtableformat#1{\def\@nomtableformat{1@{ }#1}}
415 \setnomtableformat{lp{0.45\textwidth}sp{0.3\textwidth}@{ }1}

```

`thenomenclature` The `thenomenclature` environment formats its title and optionally inserts an item in the TOC, both are dependant on whether the `\chapter` command is available or not. After printing the preamble, a list is started with the `\labelwidth` being set to the value defined in the optional argument of `\printnomenclature`, unless `nomentbl` is chosen. In the latter case we start a longtable. Note that each row of the table starts with `\item`, so we need to make the first `\item` noop, and all the subsequent ones to produce `\cr`. We also add `\cr` at the end of the table.

```

416 \def\thenomenclature{%
417   \@ifundefined{chapter}%
418   {
419     \section*{\nomname}
420     \if@intoc\addcontentsline{toc}{section}{\nomname}\fi%
421   }%
422   {
423     \chapter*{\nomname}

```

```

424 \markboth{\nomname}{\nomname}%
425 \if@intoc\addcontentsline{toc}{chapter}{\nomname}\fi%
426 }%
427
428 \nompreamble
429 \if@nomentbl
430 \let\itemOrig=\item
431 \def\item{\gdef\item{\}}%
432 \expandafter\longtable\expandafter{\@nomtableformat}
433 \else
434 \list{ }{%
435 \labelwidth\nom@tempdim
436 \leftmargin\labelwidth
437 \advance\leftmargin\labelsep
438 \itemsep\nomitemsep
439 \let\makelabel\nomlabel}%
440 \fi
441 }
442 \def\endthenomenclature{%
443 \if@nomentbl
444 \item\endlongtable
445 \global\let\item=\itemOrig
446 \else
447 \endlist
448 \fi
449 \nompostamble}

```

`\nomrefeq` These are the switches to turn referencing on or off locally for a single entry.

```

\refpage 450 \def\nomrefeq{\@printeqreftrue}
\refeqpage 451 \def\nomrefpage{\@printpagereftrue}
\norefeq 452 \def\nomrefeqpage{\@printeqreftrue\@printpagereftrue}
\norefpage 453 \def\nomnorefeq{\@printeqreffalse}
\norefpage 454 \def\nomnorefpage{\@printpagereffalse}
\norefpage 455 \def\nomnorefeqpage{\@printeqreffalse\@printpagereffalse}

```

`\nomeqref` The equation is only referenced if the corresponding switch is true. Since *MakeIndex* tends to insert a line break just before the page number, we have to add `\ignorespaces` at the end.

```

456 \def\nomeqref#1{\if@printeqref\eqdeclaration{#1}\fi\ignorespaces}

```

`\nompageref` The page is also only referenced if requested. Then the end symbol is added and finally the group started in `\@@@nomenclature` is closed.

```

457 \def\nompageref#1{\if@printpageref\pagedeclaration{#1}\fi%
458 \nomentryend\endgroup}

```

The commands defined in the `.ist` file

Read the config file if it exists and the corresponding option was given.

```
459 \if@loadcfg
460 \InputIfFileExists{\@cfgfile}{%
461   \PackageInfo{nomenc1}{Using the configuration file \@cfgfile}}{}
462 \fi
```

The end.

```
463 </package>
```

### 3.2 The *MakeIndex* Style File

The “magic word” for *MakeIndex* in the input file is `\nomenclatureentry`.

```
464 (*idxstyle)
465 %% ---- for input file ----
466 keyword    "\nomenclatureentry"
467 % We use % as a quote character since " is active in some languages
468 quote     '%'
```

Define what is printed at the beginning and the end of the file and the skip between groups. Since we already write `\nomgroup` between groups, we define `group_skip` to just input an empty line.

```
469 %% ---- for output file ----
470 preamble   "\n\\begin{thenomenclature} \n"%
471 postamble  "\n\n\\end{thenomenclature}\n" group_skip "\n"
```

Since we can't handle multiple pages for an entry anyway, we also don't need any delimiters.

```
472 delim_0   ""
473 delim_1   ""
474 delim_2   ""
```

Now the macro between the groups. Since the flag is positive, the character will be inserted as a capital letter. As the comment states, this will cause some warnings. If someone has a better solution, let me know.

```
475 %% The next lines will produce some warnings when
476 %% running Makeindex as they try to cover two different
477 %% versions of the program:
478 lethead_prefix "\nomgroup{"
479 lethead_suffix "}"
480 lethead_flag   1
481 heading_prefix "\nomgroup{"
482 heading_suffix "}"
483 headings_flag  1
484 line_max 1000
```

## References

- [1] Braams, Johannes; Carlisle, David; Jeffrey, Alan; Lamport, Leslie; Mittelbach, Frank; Rowley, Chris; Schöpf, Rainer (1996). `ltxidxglo.dtx` – 1996/01/20 v1.1e LaTeX Kernel (Index and Glossary). [CTAN/macros/latex/base/ltxidxglo.dtx](http://ctan.org/macros/latex/base/ltxidxglo.dtx).
- [2] Chen, Pehong; Harrison, Michael A. (1987). Automating Index Preparation. Report UCB/CSD 87/347, Computer Science Division, University of California, Berkeley, CA.
- [3] Comprehensive T<sub>E</sub>X Archive Network CTAN. [ftp://ctan.tug.org/tex-archive/](http://ctan.tug.org/tex-archive/).
- [4] Jones, David M. (1995). A new implementation of L<sup>A</sup>T<sub>E</sub>X’s indexing commands, Version v4.1beta of 1995/09/28. [CTAN/macros/latex/contrib/supported/camel/index.dtx](http://ctan.org/macros/latex/contrib/supported/camel/index.dtx).
- [5] Knuth, Donald E. (1984). *The T<sub>E</sub>Xbook*. Addison-Wesley Publishing Company, Reading, MA.
- [6] Lamport, Leslie (1994). *L<sup>A</sup>T<sub>E</sub>X: A Document Preparation System*. Addison-Wesley Publishing Company, Reading, MA.
- [7] Veytsman, Boris (1996). Package `nomencl`, Version 4.0. <http://sarovar.org/projects/nomencl> (2000/09/15).

## Change History

v2.2 (1996/11/25)	v2.6 (1999/04/02)
General: Last version released by Boris Veytsman . . . . . 1	<code>\nomZname</code> : Added French . . . 21
v2.5 (1999/03/13)	Use <code>\nobreakspace</code> instead of <code>~</code> in package options . . . 21
General: Complete rewrite of the package and the documentation . . . . . 1	General: Use <code>\GetFileInfo</code> . . . 1
v2.5a (1999/03/22)	v2.6a (1999/04/06)
<code>\nomZname</code> : Added Danish . . . 21	<code>\nomZname</code> : Added Russian, Spanish, Ukrainian . . . . . 21

v2.6b (1999/04/10)		v3.1b (2001/09/30)	
\name: Added Polish . . . . .	21	General: Explain how to get toc	
General: Documentation change		entry . . . . .	14
concerning line breaks		WWW address changed	
between arguments . . . . .	5	(again) . . . . .	1
v2.7 (1999/05/14)		v3.1c (2001/10/02)	
\@nomenclature: More		General: Minor documentation	
robust by using \nameverb	25	changes . . . . .	1
\nameverb: Added macro . . . . .	24	v4.0 (2005/03/31)	
\@nomenclature: Protected . . . . .	24	General: Improved compatibility	
General: Mention need to		with other	
change quote character for		Glossary/MakeIndex	
German users . . . . .	4	packages. Added option to	
v2.7a (1999/07/07)		insert Nomenclature into	
\name: Added Italian . . . . .	21	toc. Amended	
General: Merged licence.txt		documentation accordingly. . . . .	1
into README . . . . .	1	TOC entries now added with	
v2.8 (1999/09/09)		package option . . . . .	14
\nameitemsep: New skip		v4.0 (2005/04/07)	
\nameitemsep . . . . .	27	\name: Updated Italian	
General: Email changed . . . . .	1	option (thanks to Lapo	
v2.9 (1999/11/23)		Mori) . . . . .	21
\name@tempdim: New temporary		v4.1 (2005/04/27)	
dimension . . . . .	26	General: Improvements to the	
v3.0 (2000/03/05)		documentation, including	
General: New options		hyperref support . . . . .	1
cfg/nocfg . . . . .	6	v5.0	
WWW address changed . . . . .	1	\@nomenclature: Nomentbl	
v3.1 (2000/09/15)		option . . . . .	25
\name: Added Croatian . . . . .	21	\@nomenclature: Nomentbl	
General: Do not read cfg file in		option . . . . .	25
documentation . . . . .	1	\ifloadcfg: Added settable	
Expansion example added . . . . .	16	cfg file . . . . .	21
Kopka example added . . . . .	18	\ifnomentbl: New macro . . . . .	21
Sample cfg files for most		\ifstdsubgroups: New macro . . . . .	21
examples . . . . .	15	\name: Added defaults . . . . .	21
WWW address changed		\namegroup: Rewrote . . . . .	26
(again) . . . . .	1	\setnomtableformat: Added	
v3.1a (2000/12/03)		macro . . . . .	27
\name: Added Portuguese . . . . .	21	General: Added ifthen package	20
		Moved to xkeyval . . . . .	20
		Rewrote documentation . . . . .	1

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	
<code>\@@@nomenclature</code> . . . . .	<a href="#">351</a>
<code>\@@nomenclature</code> . . . . .	<a href="#">340</a>
<code>\@inputfileextension</code> . . . . .	<a href="#">319</a>
<code>\@nomenclature</code> . . . . .	<a href="#">340</a>
<code>\@outputfileextension</code> . . . . .	<a href="#">319</a>
<code>\@printnomenclature</code> . . . . .	<a href="#">400</a>
<b>E</b>	
environments:	
<code>thenomenclature</code> . . . . .	<i>14</i> , <a href="#">416</a>
<code>\eqdeclaration</code> . . . . .	<a href="#">209</a>
<b>I</b>	
<code>\if@compatibilitymode</code> . . . . .	<a href="#">189</a>
<code>\if@intoc</code> . . . . .	<a href="#">188</a>
<code>\if@loadcfg</code> . . . . .	<a href="#">203</a>
<code>\if@nomentbl</code> . . . . .	<a href="#">200</a>
<code>\if@printeqref</code> . . . . .	<a href="#">186</a>
<code>\if@printpageref</code> . . . . .	<a href="#">186</a>
<code>\if@stdsubgroups</code> . . . . .	<a href="#">206</a>
<b>M</b>	
<code>\makeglossary</code> . . . . .	<a href="#">337</a>
<code>\makenomenclature</code> . . . . .	<a href="#">326</a>
<b>N</b>	
<code>\nom@tempdim</code> . . . . .	<a href="#">400</a>
<code>\nom@verb</code> . . . . .	<a href="#">338</a>
<code>\nomAname</code> . . . . .	<a href="#">209</a>
<code>\nomenclature</code> . . . . .	<a href="#">339</a>
<code>\nometryend</code> . . . . .	<a href="#">408</a>
<code>\nomeqref</code> . . . . .	<a href="#">456</a>
<code>\nomGname</code> . . . . .	<a href="#">209</a>
<code>\nomgroup</code> . . . . .	<a href="#">371</a>
<code>\nomitemsep</code> . . . . .	<a href="#">412</a>
<code>\nomlabel</code> . . . . .	<a href="#">408</a>
<code>\nomlabelwidth</code> . . . . .	<a href="#">398</a>
<code>\nomname</code> . . . . .	<a href="#">209</a>
<code>\nompageref</code> . . . . .	<a href="#">457</a>
<code>\nompostamble</code> . . . . .	<a href="#">408</a>
<code>\nom preamble</code> . . . . .	<a href="#">408</a>
<code>\nomprefix</code> . . . . .	<a href="#">198</a>
<code>\nomrefeq</code> . . . . .	<a href="#">450</a>
<code>\nomXname</code> . . . . .	<a href="#">209</a>
<code>\nomZname</code> . . . . .	<a href="#">209</a>
<code>\norefeq</code> . . . . .	<a href="#">450</a>
<code>\norefeqpage</code> . . . . .	<a href="#">450</a>
<code>\norefpage</code> . . . . .	<a href="#">450</a>
<b>P</b>	
<code>\pagedeclaration</code> . . . . .	<a href="#">209</a>
<code>\printglossary</code> . . . . .	<a href="#">407</a>
<code>\printnomenclature</code> . . . . .	<a href="#">400</a>
<b>R</b>	
<code>\refeqpage</code> . . . . .	<a href="#">450</a>
<code>\refpage</code> . . . . .	<a href="#">450</a>
<b>S</b>	
<code>\setnomtableformat</code> . . . . .	<a href="#">414</a>
<b>T</b>	
<code>thenomenclature</code> (environment) . . . . .	<i>14</i> , <a href="#">416</a>