

The fithesis4 class for the typesetting of theses written at the Masaryk University in Brno

Daniel Marek, Jan Pavlovič, Vít Novotný, Tereza Vrabcová, Petr Sojka

October 17, 2021

Abstract

This document details the design and the implementation of the fithesis4 document class. It contains technical information for anyone who wishes to extend the class with their locale or style files.

Contents

1	Required classes and packages	4
2	Public API	5
2.1	Options	5
2.2	The <code>\thesissetup</code> macro	5
2.2.1	The <code>basePath</code> key	5
2.2.2	The <code>logoPath</code> key	5
2.2.3	The <code>stylePath</code> key	6
2.2.4	The <code>localePath</code> key	6
2.2.5	The <code>declaration</code> key	7
2.2.6	The <code>gender</code> key	7
2.2.7	The <code>author</code> key	8
2.2.8	The <code>id</code> key	8
2.2.9	The <code>type</code> key	8
2.2.10	The <code>university</code> key	9
2.2.11	The <code>faculty</code> key	9
2.2.12	The <code>department</code> key	10
2.2.13	The <code>departmentEn</code> key	10
2.2.14	The <code>programme</code> key	10
2.2.15	The <code>programmeEn</code> key	10
2.2.16	The <code>field</code> key	11
2.2.17	The <code>fieldEn</code> key	11
2.2.18	The <code>universityLogo</code> key	11
2.2.19	The <code>facultyLogo</code> key	11

2.2.20	The style key	12
2.2.21	The styleInheritance key	12
2.2.22	The locale key	12
2.2.23	The localeInheritance key	13
2.2.24	The date key	13
2.2.25	The place key	15
2.2.26	The title key	15
2.2.27	The TeXtitle key	15
2.2.28	The titleEn key	15
2.2.29	The TeXtitleEn key	16
2.2.30	The keywords key	16
2.2.31	The TeXkeywords key	16
2.2.32	The keywordsEn key	16
2.2.33	The TeXkeywordsEn key	16
2.2.34	The abstract key	17
2.2.35	The abstractEn key	17
2.2.36	The advisor key	17
2.2.37	The thanks key	17
2.2.38	The assignment key	17
2.2.39	The bib key	18
2.2.40	The autoLayout key	18
2.2.41	The extra key	19
2.3	The \thesislong macro	21
2.4	The \thesisload macro	22
3	Private API	24
3.1	File manipulation macros	24
3.2	String manipulation macros	25
3.3	General purpose macros	26
3.4	Locale files	27
3.4.1	Interface	27
3.4.2	English locale files	29
3.4.2.1	The locale/fithesis-english.def file	29
3.4.2.2	The locale/mu/fithesis-english.def file	30
3.4.2.3	The locale/mu/law/fithesis-english.def file	31
3.4.2.4	The locale/mu/fsps/fithesis-english.def file	32
3.4.2.5	The locale/mu/fss/fithesis-english.def file	32
3.4.2.6	The locale/mu/econ/fithesis-english.def file	32
3.4.2.7	The locale/mu/med/fithesis-english.def file	33
3.4.2.8	The locale/mu/fi/fithesis-english.def file	33
3.4.2.9	The locale/mu/phil/fithesis-english.def file	34
3.4.2.10	The locale/mu/ped/fithesis-english.def file	34
3.4.2.11	The locale/mu/sci/fithesis-english.def file	34
3.4.2.12	The locale/mu/pharm/fithesis-english.def file	34
3.4.3	Czech locale files	35
3.4.3.1	The locale/fithesis-czech.def file	35

3.4.3.2	The locale/mu/fithesis-czech.def file	37
3.4.3.3	The locale/mu/law/fithesis-czech.def file . . .	38
3.4.3.4	The locale/mu/fsp/fithesis-czech.def file . .	39
3.4.3.5	The locale/mu/fss/fithesis-czech.def file . . .	39
3.4.3.6	The locale/mu/econ/fithesis-czech.def file . .	39
3.4.3.7	The locale/mu/med/fithesis-czech.def file . . .	40
3.4.3.8	The locale/mu/fi/fithesis-czech.def file	40
3.4.3.9	The locale/mu/phil/fithesis-czech.def file . .	41
3.4.3.10	The locale/mu/ped/fithesis-czech.def file . . .	42
3.4.3.11	The locale/mu/sci/fithesis-czech.def file . . .	42
3.4.3.12	The locale/mu/pharm/fithesis-czech.def file . .	43
3.4.4	Slovak locale files	43
3.4.4.1	The locale/fithesis-slovak.def file	43
3.4.4.2	The locale/mu/fithesis-slovak.def file	46
3.4.4.3	The locale/mu/law/fithesis-slovak.def file . .	47
3.4.4.4	The locale/mu/fsp/fithesis-slovak.def file . .	47
3.4.4.5	The locale/mu/fss/fithesis-slovak.def file . .	47
3.4.4.6	The locale/mu/econ/fithesis-slovak.def file . .	48
3.4.4.7	The locale/mu/med/fithesis-slovak.def file . .	48
3.4.4.8	The locale/mu/fi/fithesis-slovak.def file . . .	49
3.4.4.9	The locale/mu/phil/fithesis-slovak.def file . .	49
3.4.4.10	The locale/mu/ped/fithesis-slovak.def file . .	50
3.4.4.11	The locale/mu/sci/fithesis-slovak.def file . .	51
3.4.4.12	The locale/mu/pharm/fithesis-slovak.def file .	51
3.5	Style files	51
3.5.1	Interface	51
3.5.2	Base style files	52
3.5.2.1	The style/fithesis-base.sty file	52
3.5.2.2	The style/mu/fithesis-base.sty file	52
3.5.2.3	The style/mu/fithesis-10.clo file	74
3.5.2.4	The style/mu/fithesis-11.clo file	75
3.5.2.5	The style/mu/fithesis-12.clo file	76
3.5.3	The style files of the Faculty of Informatics	83
3.5.3.1	The style/mu/fithesis-fi.sty file	83
3.5.4	The style files of the Faculty of Science	84
3.5.4.1	The style/mu/fithesis-sci.sty file	84
3.5.5	The style files of the Faculty of Arts	86
3.5.5.1	The style/mu/fithesis-phil.sty file	86
3.5.6	The style files of the Faculty of Education	88
3.5.6.1	The style/mu/fithesis-ped.sty file	88
3.5.7	The style files of the Faculty of Social Studies	89
3.5.7.1	The style/mu/fithesis-fss.sty file	89
3.5.8	The style files of the Faculty of Law	90
3.5.8.1	The style/mu/fithesis-law.sty file	90
3.5.9	The style files of the Faculty of Economics and Administration	92
3.5.9.1	The style/mu/fithesis-econ.sty file	92

3.5.10	The style files of the Faculty of Medicine	97
3.5.10.1	The style/mu/fithesis-med.sty file	97
3.5.11	The style files of the Faculty of Sports Studies	100
3.5.11.1	The style/mu/fithesis-fsps.sty file	100
3.5.12	The style files of the Faculty of Pharmacy	103
3.5.12.1	The style/mu/fithesis-pharm.sty file	103

1 Required classes and packages

`\thesis@backend` The class requires the class specified in `\thesis@backend`, whose default value is `[a4paper]{rapport3}`. If a different base class is desired, it can be specified by redefining `\thesis@backend` prior to loading the `fithesis4` class.

```

1 \ProvidesClass{fithesis4}[\thesis@version]
2 \ifx\thesis@backend\undefined
3   \def\thesis@backend{[a4paper]{rapport3}}
4 \fi\expandafter\LoadClass\thesis@backend

```

The class also requires the following packages:

- `keyval` – Adds support for parsing comma-delimited lists of key-value pairs.
- `etoolbox` – Adds support for expanding code after the preamble using the `\AtPreamble` hook.
- `ltxcmds` – Implements several commands from the \LaTeX kernel. Used for the `\ltx@ifpackageloaded` command, which – unlike its `\@ifpackageloaded` counterpart – can be used outside the preamble.
- `ifxetex` – Used to detect the $X_{\text{e}}\LaTeX$ engine.
- `ifluatex` – Used to detect the $\text{Lua}\LaTeX$ engine.
- `inputenc` – Used to enable the input UTF-8 encoding. This package does not get loaded under the $X_{\text{e}}\LaTeX$ and $\text{Lua}\LaTeX$ engines.
- `xpatch` – Used to redefine parts of code in macros without redefining the whole macro.

The `hyperref` package is also conditionally loaded during the expansion of the `\thesis@load` macro (see Section 2.4). Other packages may be required by the style files (see Section 3.5) you are using.

```

5 \RequirePackage{keyval}
6 \RequirePackage{etoolbox}
7 \RequirePackage{ltxcmds}
8 \RequirePackage{ifxetex}
9 \RequirePackage{ifluatex}
10 \ifxetex\else\ifluatex\else
11   \RequirePackage[utf8]{inputenc}
12 \fi\fi
13 \RequirePackage{xpatch}

```

2 Public API

2.1 Options

Any [*options*] passed to the class will be handed down to the loaded style files. The supported options are therefore documented in the subsections of Section 3.5 dedicated to the respective style files.

The class options specify the *form* of the document.

2.2 The `\thesissetup` macro

`\thesissetup` The main public macro is the `\thesissetup{<keyvals>}` command, where *keyvals* is a comma-delimited list of *key=value* pairs as defined by the `keyval` package. This macro needs to be included prior to the beginning of a \LaTeX document. When the macro is expanded, the *key=value* pairs are processed.

Contrary to the class options, the *key=value* pairs of the `\thesissetup` macro specify meta-information about the document.

```
14 \long\def\thesissetup#1{%
15   \setkeys{thesis}{#1}}
```

2.2.1 The `basePath` key

`\thesis@basepath` The `{<basePath=path>}` pair sets the *path* containing the class files. The *path* is prepended to every other path (`\thesis@logopath`, `\thesis@stylepath` and `\thesis@localepath`) used by the class. If non-empty, the *path* gets normalized to *path/*. The normalized *path* is stored within the `\thesis@basepath` macro, whose implicit value is `fithesis/`.

```
16 \def\thesis@basepath{fithesis/}
17 \define@key{thesis}{basePath}{%
18   \ifx\thesis@empty#1\thesis@empty
19   \def\thesis@basepath{}%
20   \else
21   \def\thesis@basepath{#1/%}
22   \fi}
```

`\thesis@logopath` **2.2.2 The `logoPath` key**

The `{<logoPath=path>}` pair sets the *path* containing the logo files, which is used by the style files to load the university and faculty logos. The *path* is normalized using the `\thesis@subdir` macro and stored within the `\thesis@logopath` macro, whose implicit value is `\thesis@basepath` followed by `logo/\thesis@university/`. By default, this expands to `fithesis/logo/mu/`.

```
23 \def\thesis@logopath{\thesis@basepath logo/\thesis@university/}
24 \define@key{thesis}{logoPath}{%
25   \def\thesis@logopath{\thesis@subdir#1%
26     \empty\empty\empty\empty}}
```

`\thesis@stylepath` **2.2.3 The stylePath key**

The `{\stylePath=path}` pair sets the *path* containing the style files. The *path* is normalized using the `\thesis@subdir` macro and stored within the `\thesis@stylepath` macro, whose implicit value is `\thesis@basepath style/`. By default, this expands to `fithesis/style/`.

```
27 \def\thesis@stylepath{\thesis@basepath style/}
28 \define@key{thesis}{stylePath}{%
29   \def\thesis@stylepath{\thesis@subdir#1%
30     \empty\empty\empty\empty}}
```

`\thesis@localepath` **2.2.4 The localePath key**

The `{\localePath=path}` pair sets the *path* containing the locale files. The *path* is normalized using the `\thesis@subdir` macro and stored within the `\thesis@localepath` macro, whose implicit value is `\thesis@basepath` followed by `locale/`. By default, this expands to `fithesis/locale/`.

```
31 \def\thesis@localepath{\thesis@basepath locale/}
32 \define@key{thesis}{localePath}{%
33   \def\thesis@localepath{\thesis@subdir#1%
34     \empty\empty\empty\empty}}
```

`\thesis@subdir` The `\thesis@subdir` macro returns `/` unchanged, coerces `./`, `././`, `/path`, `./path` and `../path` to `./`, `././`, `/path/`, `./path/` and `../path/`, respectively, and prefixes any other *path* with `\thesis@basepath`.

```
35 \def\thesis@subdir#1#2#3#4\empty{%
36   \ifx#1\empty%           <empty> -> <basepath>
37     \thesis@basepath
38   \else
39     \if#1/%
40       \ifx#2\empty%       / -> /
41         /%
42       \else%              /<path> -> /<path>/
43         #1#2#3#4/%
44     \fi
45   \else
46     \if#1.%
47       \ifx#2\empty%       . -> ./
48         ./%
49       \else
50         \if#2.%
51           \ifx#3\empty%   .. -> ../
52             ../%
53           \else
54             \if#3/%       ../<path> -> ../<path>/
55               ../#4/%
56             \else
57               \thesis@basepath#1#2#3#4/%
```

```

58         \fi
59         \fi
60     \else
61         \if#2/%      ./<path> -> ./<path>/
62         ./#3#4/%
63     \else
64         \thesis@basepath#1#2#3#4/%
65     \fi
66     \fi
67     \fi
68 \else
69     \thesis@basepath#1#2#3#4/%
70 \fi
71 \fi
72 \fi}

```

`\thesis@def` The `\thesis@def[key]{name}` macro defines the `\thesis@name` macro to expand to either `«key»`, if specified, or to `«name»`. The macro serves to provide placeholder strings for macros with no default value.

```

73 \newcommand{\thesis@def}[2][]{%
74   \expandafter\def\csname thesis@#2\endcsname{%
75     <<\ifx\thesis@empty#1\thesis@empty#2\else#1\fi>>}}

```

`\thesis@declaration` 2.2.5 The declaration key

The `{(declaration=text)}` pair sets the declaration *text* to be included into the document. The *text* is stored within the `\thesis@declaration` macro, whose implicit value is `\thesis@@{declaration}`.

```

76 \def\thesis@declaration{\thesis@@{declaration}}
77 \long\def\KV@thesis@declaration#1{%
78   \long\def\thesis@declaration{#1}}

```

`\ifthesis@woman` 2.2.6 The gender key

The `{(gender=char)}` pair sets the author's gender to either a male, if *char* is the character `m`, or to a female. The gender can be tested using the `\ifthesis@woman ... \else ... \fi` conditional. The implicit gender is male.

```

79 \newif\ifthesis@woman\thesis@womanfalse
80 \define@key{thesis}{gender}{%
81   \def\thesis@male{m}%
82   \def\thesis@arg{#1}%
83   \ifx\thesis@male\thesis@arg
84     \thesis@womanfalse
85   \else
86     \thesis@womantrue
87   \fi}

```

`\thesis@author` **2.2.7 The author key**

The `{(author=name)}` pair sets the author's full name to *name*. The *name* is parsed using the `\thesis@parseAuthor` macro and stored within the following macros:

- `\thesis@author` • `\thesis@author` – The full name of the author.
- `\thesis@author@head` • `\thesis@author@head` – The first space-delimited part of the name. This corresponds to the author's first name.
- `\thesis@author@tail` • `\thesis@author@tail` – The full name without the first space-delimited part of the name. This corresponds to the author's surname.

`\author` The standard L^AT_EX `\author` macro also sets this key.

```
88 \def\thesis@parseAuthor#1{%
89   \def\thesis@author{#1}%
90   \def\thesis@author@head{\expandafter\expandafter\expandafter
91     \@gobble\thesis@head#1 \relax}%
92   \def\thesis@author@tail{\thesis@tail#1 \relax}}
93 \thesis@def{author}%
94 \thesis@def[author]{author@head}%
95 \thesis@def[author]{author@tail}%
96 \define@key{thesis}{author}{%
97   \thesis@parseAuthor{#1}}
98 \let\author\thesis@parseAuthor
```

`\thesis@id` **2.2.8 The id key**

The `{(id=identifier)}` pair sets the identifier of the thesis author to *identifier*. This usually corresponds to the unique identifier of the author within the information system of the given university.

```
99 \thesis@def{id}
100 \define@key{thesis}{id}{%
101   \def\thesis@id{#1}}
```

`\thesis@type` **2.2.9 The type key**

The `{(type=type)}` pair sets the type of the thesis to *type*. The following types of theses are recognized:

The thesis type	The value of <i>type</i>
Seminar paper	sem
Bachelor's thesis	bc
Master's thesis	mgr
Thesis proposal	prop
Doctoral thesis	d
Rigorous thesis	r

The *type* is stored within the `\thesis@type` macro, whose implicit value is `bc`. For the ease of testing of the thesis type via `\ifx` conditions within style and locale files, the `\thesis@sempaper`, `\thesis@bachelors`, `\thesis@masters`, `\thesis@proposal`, `\thesis@doctoral` and `\thesis@rigorous` macros containing the corresponding *type* values are available as a part of the private API.

```

\thesis@sempaper
\thesis@bachelors
\thesis@masters
\thesis@proposal
\thesis@doctoral
\thesis@rigorous
102 \def\thesis@sempaper{sem}
103 \def\thesis@bachelors{bc}
104 \def\thesis@masters{mgr}
105 \def\thesis@proposal{prop}
106 \def\thesis@doctoral{d}
107 \def\thesis@rigorous{r}
108 \let\thesis@type\thesis@bachelors
109 \define@key{thesis}{type}{%
110   \def\thesis@type{#1}}

```

`\thesis@university` 2.2.10 The university key

The `{(university=identifier)}` pair sets the identifier of the university, at which the thesis is being written, to *identifier*. The *identifier* is stored within the `\thesis@university` macro, whose implicit value is `mu`. This value corresponds to the Masaryk University in Brno.

```

111 \def\thesis@university{mu}
112 \define@key{thesis}{university}{%
113   \def\thesis@university{#1}}

```

`\thesis@faculty` 2.2.11 The faculty key

The `{(faculty=identifier)}` pair sets the faculty, at which the thesis is being written, to *domain*. The following faculty *identifiers* are recognized at the Masaryk University in Brno:

The faculty	The <i>domain</i> name
The Faculty of Informatics	fi
The Faculty of Science	sci
The Faculty of Law	law
The Faculty of Economics and Administration	econ
The Faculty of Social Studies	fss
The Faculty of Medicine	med
The Faculty of Education	ped
The Faculty of Arts	phil
The Faculty of Sports Studies	fsps
The Faculty of Pharmacy	pharm

The *identifier* is stored within the `\thesis@faculty` macro, whose implicit value is `fi`.

```

114 \def\thesis@faculty{fi}
115 \define@key{thesis}{faculty}{%
116   \def\thesis@faculty{#1}}

```

`\thesis@department` **2.2.12 The department key**

The `{(department=name)}` pair sets the name of the department, at which the thesis is being written, to *name*. Unlike the university and faculty identifiers, `fithesis4` does not prescribe the format of the *name*; the style files may internally parse it, or typeset it as-is. The *name* is stored within the `\thesis@department` macro.

```

117 \thesis@def{department}
118 \define@key{thesis}{department}{%
119   \def\thesis@department{#1}}

```

`\thesis@departmentEn` **2.2.13 The departmentEn key**

The `{(departmentEn=name)}` pair sets the English name of the department, at which the thesis is being written, to *name*. The *name* is stored within the `\thesis@departmentEn` macro.

```

120 \thesis@def{departmentEn}
121 \define@key{thesis}{departmentEn}{%
122   \def\thesis@departmentEn{#1}}

```

`\thesis@programme` **2.2.14 The programme key**

The `{(programme=name)}` pair sets the name of the author's study programme to *name*. Unlike the university and faculty identifiers, the programme *name* is only used for typesetting and it should therefore be specified in plain language with optional \TeX macros. The *name* is stored within the `\thesis@programme` macro.

```

123 \thesis@def{programme}
124 \define@key{thesis}{programme}{%
125   \def\thesis@programme{#1}}

```

`\thesis@programmeEn` **2.2.15 The programmeEn key**

The `{(programmeEn=name)}` pair sets the English name of the author's study programme to *name*. The *name* is stored within the `\thesis@programmeEn` macro.

```

126 \thesis@def{programmeEn}
127 \define@key{thesis}{programmeEn}{%
128   \def\thesis@programmeEn{#1}}

```

`\thesis@field` **2.2.16 The field key**

The `{\field=name}` pair sets the name of the author's field of study to *name*. Unlike the university and faculty identifiers, the *name* of the field of study is only used for typesetting and it should therefore be specified in plain language with optional \TeX macros. The *name* is stored within the `\thesis@field` macro.

```
129 \thesis@def{field}
130 \define@key{thesis}{field}{%
131   \def\thesis@field{#1}}
```

`\thesis@fieldEn` **2.2.17 The fieldEn key**

The `{\fieldEn=name}` pair sets the English name of the author's field of study to *name*. The *name* is stored within the `\thesis@fieldEn` macro.

```
132 \thesis@def{fieldEn}
133 \define@key{thesis}{fieldEn}{%
134   \def\thesis@fieldEn{#1}}
```

`\thesis@universityLogo` **2.2.18 The universityLogo key**

The `{\universityLogo=filename}` pair sets the filename of the logo file to be used as the university logo to *filename*. The *filename* is stored within the `\thesis@universityLogo` macro, whose implicit value is `fithesis-base-\thesis@locale`. The `fithesis-` prefix serves to prevent package clashes with other similarly named files within the \TeX directory structure. The logo file is loaded from the `\thesis@logopath\thesis@universityLogo` path.

```
135 \def\thesis@universityLogo{fithesis-base-\thesis@locale}
136 \define@key{thesis}{universityLogo}{%
137   \def\thesis@universityLogo{#1}}
```

`\thesis@facultyLogo` **2.2.19 The facultyLogo key**

The `{\facultyLogo=filename}` pair sets the filename of the logo file to be used as the faculty logo to *filename*. The *filename* is stored within the `\thesis@facultyLogo` macro, whose implicit value is `fithesis-\thesis@faculty-\thesis@locale`. The `fithesis-` prefix serves to prevent package clashes with other similarly named files within the \TeX directory structure. The logo file is loaded from the `\thesis@logopath\thesis@facultyLogo` path.

```
138 \def\thesis@facultyLogo{fithesis-\thesis@faculty-\thesis@locale}
139 \define@key{thesis}{facultyLogo}{%
140   \def\thesis@facultyLogo{#1}}
```

`\thesis@style` **2.2.20 The style key**

The `{\style=filename}` pair sets the filename of the style file to be used to *filename*. The *filename* is stored within the `\thesis@style` macro, whose implicit value is `\thesis@university/fithesis-\thesis@university-\thesis@faculty`. When the *filename* is an empty token string, no style files will be loaded during the main routine (see Section 2.4).

```
141 \def\thesis@style{\thesis@university/fithesis-\thesis@university-\thesis@faculty}
142 \define@key{thesis}{style}{%
143   \def\thesis@style{#1}}
```

`\thesis@style@inheritance` **2.2.21 The styleInheritance key**

The `{\styleInheritance=bool}` pair either enables, if *bool* is true or unspecified, or disables the inheritance for style files. The setting affects the function of the `\thesis@requireStyle` macro (see Section 3.1) and can be tested using the `\ifthesis@style@inheritance ... \else ... \fi` conditional. Inheritance is enabled for style files by default.

```
144 \newif\ifthesis@style@inheritance\thesis@style@inheritancetrue
145 \define@key{thesis}{styleInheritance}[true]{%
146   \begingroup
147   \def\@true{true}%
148   \def\@arg{#1}%
149   \ifx\@true\@arg
150     \endgroup\thesis@style@inheritancetrue
151   \else
152     \endgroup\thesis@style@inheritancefalse
153   \fi}
```

`\thesis@locale` **2.2.22 The locale key**

The `{\locale=name}` pair sets the name of the main locale to *name*. The *name* is stored within the `\thesis@locale` macro, whose implicit value is the main language of either the `babel` or the `polyglossia` package, or `english`, when undefined. When the *name* is an empty token string, no locale files will be loaded during the main routine (see Section 2.4).

```
154 \def\thesis@locale{%
155   % Babel / polyglossia detection
156   \ifx\languagename\undefined
157     english\else\languagename\fi}
158 \define@key{thesis}{locale}{%
159   \def\thesis@locale{#1}}
```

`\ifthesis@english` The English locale is special. Several parts of the document will typically be typeset in both the current locale and English. However, if the current locale is English, this would result in duplicity. To avoid this, the `\ifthesis@english ... \else`

...`\fi` conditional is made available for testing, whether or not the current locale is English.

```

160 \def\ifthisis@english{
161   \expandafter\def\expandafter\@english\expandafter{\string
162     \english}%
163   \expandafter\expandafter\expandafter\def\expandafter
164     \expandafter\expandafter\@locale\expandafter\expandafter
165     \expandafter{\expandafter\string\csname\thesis@locale\endcsname}%
166   \expandafter\csname\expandafter i\expandafter f\ifx\@locale
167     \@english
168     true%
169   \else
170     false%
171   \fi\endcsname}

```

`\thesis@locale@inheritance` 2.2.23 The `localeInheritance` key

The `{\langle localeInheritance=bool\rangle}` pair either enables, if *bool* is true or unspecified, or disables the inheritance. The setting affects the function of the `\thesis@requireLocale` macro (see Section 3.1) and can be tested using the `\ifthisis@locale@inheritance ...\else ...\fi` conditional. Inheritance is enabled for locale files by default.

```

172 \newif\ifthisis@locale@inheritance\thesis@locale@inheritancetrue
173 \define@key{thesis}{localeInheritance}[true]{%
174   \begingroup
175   \def\@true{true}%
176   \def\@arg{#1}%
177   \ifx\@true\@arg
178     \endgroup\thesis@locale@inheritancetrue
179   \else
180     \endgroup\thesis@locale@inheritancefalse
181   \fi}

```

2.2.24 The `date` key

The `{\langle date=date\rangle}` pair sets the date of the thesis submission to *date*, where *date* is a string in the YYYY/MM/DD format, where YYYY stands for full year, MM stands for month and DD stands for day. The *date* is parsed and stored using the `\thesis@parseDate` macro within the following macros:

- | | | |
|--------------------------------|---|--|
| <code>\thesis@parseDate</code> | | |
| <code>\thesis@date</code> | | |
| <code>\thesis@year</code> | • <code>\thesis@date</code> – The entire <i>date</i> | • <code>\thesis@month</code> – The MM of <i>date</i> |
| <code>\thesis@month</code> | • <code>\thesis@year</code> – The YYYY of <i>date</i> | • <code>\thesis@day</code> – The DD of <i>date</i> |
| <code>\thesis@day</code> | | |
| <code>\thesis@season</code> | • <code>\thesis@season</code> – Expands to either: | |
| | – spring if $2 < MM < 9$, | |

– fall if $MM \leq 2$ or $MM \geq 9$.

- `\thesis@seasonYear`
- `\thesis@seasonYear` – The year of the given semester:
 - $YYYY - 1$ if $MM \leq 2$.
 - $YYYY$ if $MM > 2$

- `\thesis@academicYear`
- `\thesis@academicYear` – The academic year of the given semester:
 - $YYYY - 1/YYYYY$ if $MM < 9$.
 - $YYYY/YYYYY + 1$ if $MM \geq 9$

To set up the default values, the `\thesis@parseDate` macro is called with the fully expanded `\the\year/\the\month/\the\day` string, which equals the current date.

```
182 \def\thesis@parseDate#1/#2/#3|{{
183 % Set the basic macros
184 \gdef\thesis@date{#1/#2/#3}%
185 \gdef\thesis@year{#1}%
186 \gdef\thesis@month{#2}%
187 \gdef\thesis@day{#3}%
188
189 % Set the season
190 \newcount\@month\expandafter\@month\thesis@month\relax
191 \ifnum\@month>8\gdef\thesis@season{fall}
192 \else\ifnum\@month<3\gdef\thesis@season{fall}
193 \else \gdef\thesis@season{spring}
194 \fi\fi
195
196 % Set the academic year
197 \newcount\@year\expandafter\@year\thesis@year\relax
198 \ifnum\@month>8%
199 \edef\@yearA{\the\@year}%
200 \advance\@year 1\edef\@yearB{\the\@year}%
201 \advance\@year-1
202 \else
203 \advance\@year-1\edef\@yearA{\the\@year}%
204 \advance\@year 1\edef\@yearB{\the\@year}%
205 \fi
206 \global\edef\thesis@academicYear{\@yearA/\@yearB}
207
208 % Set the season year
209 \ifnum\@month>2\else
210 \advance\@year-1
211 \fi
212 \global\edef\thesis@seasonYear{\the\@year}}
213
214 \edef\thesis@date{\the\year/\the\month/\the\day}%
215 \expandafter\thesis@parseDate\thesis@date|
216
```

```

217 \define@key{thesis}{date}{%
218   \edef\@date{#1}%
219   \expandafter\thesis@parseDate\@date|}}

```

`\thesis@place` **2.2.25 The place key**

The `{\place=place}` pair sets the location of the faculty, at which the thesis is being prepared, to *place*. The *place* is stored within the `\thesis@place` macro, whose implicit value is Brno.

```

220 \def\thesis@place{Brno}
221 \define@key{thesis}{place}{%
222   \def\thesis@place{#1}}

```

`\thesis@title` **2.2.26 The title key**

The `{\title=title}` pair sets the title of the thesis to *title*. The *title* is stored within the `\thesis@title` macro. The standard L^AT_EX `\title` macro also sets this key.

```

223 \thesis@def{title}
224 \define@key{thesis}{title}{%
225   \def\thesis@title{#1}}
226 \def\title#1{\def\thesis@title{#1}}

```

`\maketitle` The standard L^AT_EX `\maketitle` macro is defined, but disabled.

```
227 \let\maketitle\relax
```

`\thesis@TeXtitle` **2.2.27 The TeXtitle key**

The `{\TeXtitle=title}` pair sets the T_EX title of the thesis to *title*. The *title* is used, when typesetting the title, whereas `\thesis@title` is a plain text, which gets included in the PDF header of the resulting document. The *title* is stored within the `\thesis@TeXtitle` macro, whose implicit value is `\thesis@title`.

```

228 \def\thesis@TeXtitle{\thesis@title}
229 \define@key{thesis}{TeXtitle}{%
230   \def\thesis@TeXtitle{#1}}

```

`\thesis@titleEn` **2.2.28 The titleEn key**

The `{\titleEn=title}` pair sets the English title of the thesis to *title*. The *title* is stored within the `\thesis@titleEn` macro.

```

231 \thesis@def{titleEn}
232 \define@key{thesis}{titleEn}{%
233   \def\thesis@titleEn{#1}}

```

`\thesis@TeXtitleEn` **2.2.29 The TeXtitleEn key**

The `{\TeXtitleEn=title}` pair sets the English T_EX title of the thesis to *title*. The *title* is used, when typesetting the title, whereas `\thesis@titleEn` is a plain text, which gets included in the PDF header of the resulting document. The *title* is stored within the `\thesis@TeXtitleEn` macro, whose implicit value is `\thesis@titleEn`.

```
234 \def\thesis@TeXtitleEn{\thesis@titleEn}
235 \define@key{thesis}{TeXtitleEn}{%
236   \def\thesis@TeXtitleEn{#1}}
```

`\thesis@keywords` **2.2.30 The keywords key**

The `{\keywords=list}` pair sets the keywords of the thesis to the comma-delimited *list*. The *list* is stored within the `\thesis@keywords` macro.

```
237 \thesis@def{keywords}
238 \define@key{thesis}{keywords}{%
239   \def\thesis@keywords{#1}}
```

`\thesis@TeXkeywords` **2.2.31 The TeXkeywords key**

The `{\TeXkeywords=list}` pair sets the T_EX keywords of the thesis to the comma-delimited *list*. The *list* is used, when typesetting the keywords, whereas `\thesis@keywords` is a plain text, which gets included in the PDF header of the resulting document. The *list* is stored within the `\thesis@TeXkeywords` macro.

```
240 \def\thesis@TeXkeywords{\thesis@keywords}
241 \define@key{thesis}{TeXkeywords}{%
242   \def\thesis@TeXkeywords{#1}}
```

`\thesis@keywordsEn` **2.2.32 The keywordsEn key**

The `{\keywordsEn=list}` pair sets the English keywords of the thesis to the comma-delimited *list*. The *list* is stored within the `\thesis@keywordsEn` macro.

```
243 \thesis@def{keywordsEn}
244 \define@key{thesis}{keywordsEn}{%
245   \def\thesis@keywordsEn{#1}}
```

`\thesis@TeXkeywordsEn` **2.2.33 The TeXkeywordsEn key**

The `{\TeXkeywordsEn=list}` pair sets the English T_EX keywords of the thesis to the comma-delimited *list*. The *list* is used, when typesetting the keywords, whereas `\thesis@keywordsEn` is a plain text, which gets included in the PDF header of the resulting document. The *list* is stored within the `\thesis@TeXkeywordsEn` macro.

```
246 \def\thesis@TeXkeywordsEn{\thesis@keywordsEn}
247 \define@key{thesis}{TeXkeywordsEn}{%
248   \def\thesis@TeXkeywordsEn{#1}}
```


`\thesis@abstract` **2.2.34 The abstract key**

The `{\abstract=text}` pair sets the abstract of the thesis to *text*. The *text* is stored within the `\thesis@abstract` macro.

```
249 \thesis@def{abstract}
250 \long\def\KV@thesis@abstract#1{%
251   \long\def\thesis@abstract{#1}}
```

`\thesis@abstractEn` **2.2.35 The abstractEn key**

The `{\abstractEn=text}` pair sets the English abstract of the thesis to *text*. The *text* is stored within the `\thesis@abstractEn` macro.

```
252 \thesis@def{abstractEn}
253 \long\def\KV@thesis@abstractEn#1{%
254   \long\def\thesis@abstractEn{#1}}
```

`\thesis@advisor` **2.2.36 The advisor key**

The `{\advisor=name}` pair sets the thesis advisor's full name to *name*. The *name* is stored within the `\thesis@advisor` macro.

```
255 \thesis@def{advisor}
256 \define@key{thesis}{advisor}{\def\thesis@advisor{#1}}
```

`\thesis@thanks` **2.2.37 The thanks key**

The `{\thanks=text}` pair sets the acknowledgements text to *text*. The *text* is stored within the `\thesis@thanks` macro.

```
257 \long\def\KV@thesis@thanks#1{%
258   \long\def\thesis@thanks{#1}}
```

`\thesis@assignmentFiles` **2.2.38 The assignment key**

The `{\assignment=list}` pair sets the comma-delimited list of paths to the PDF files containing the thesis assignment to *list*. The *list* is stored within the `\thesis@assignmentFiles` macro.

```
259 \define@key{thesis}{assignment}{%
260   \def\thesis@assignmentFiles{#1}}
```

When the `\thesis@assignmentFiles` macro is defined and non-empty, the style files should take that as a cue that the user wishes to typeset the thesis assignment.

`\thesis@bibFiles` **2.2.39 The bib key**

The `{(bib=list)}` pair sets the comma-delimited list of paths to the BIB files containing the bibliography databases to *list*. The *list* is stored within the `\thesis@bibFiles` macro.

```
261 \define@key{thesis}{bib}{%
262   \def\thesis@bibFiles{#1}}
```

When the `\thesis@bibFiles` macro is defined and non-empty, the style files should take that as a cue that the user wishes to typeset the bibliography.

`\ifthesis@auto` **2.2.40 The autoLayout key**

The `{(autoLayout=bool)}` pair either enables, if *bool* is true or unspecified, or disables autolayout. Autolayout injects the `\thesis@preamble` and `\thesis@postamble` macros at the beginning and at the end of the document, respectively. The setting can be tested using the `\ifthesis@auto ... \else ... \fi` conditional. The autolayout is enabled by default.

```
263 \newif\ifthesis@auto\thesis@autotrue
264 \define@key{thesis}{autoLayout}[true]{%
265   \def\@true{true}%
266   \def\@arg{#1}%
267   \ifx\@true\@arg
268     \thesis@autotrue
269   \else
270     \thesis@autofalse
271   \fi}
```

`\thesis@pages@preamble` The `\thesis@pages@preamble` macro contains the last page number within the preamble of the document. During the first \TeX compilation, the macro expands to ??.

```
272 \ifx\thesis@pages@preamble\undefined
273   \def\thesis@pages@preamble{??}\fi
```

`\thesis@pages@postamble` The `\thesis@pages@postamble` macro contains the last page number prior to the postamble of the document. During the first \TeX compilation, the macro expands to ??.

```
274 \ifx\thesis@pages@postamble\undefined
275   \def\thesis@pages@postamble{??}\fi
```

`\thesis@preamble`
`\thesis@postamble`
`\thesis@blocks@preamble`
`\thesis@blocks@postamble` The `\thesis@preamble` and `\thesis@postamble` macros temporarily switch to the hyphenation patterns and the `csquotes` style of the main locale and typeset the contents of the `\thesis@blocks@preamble` or `\thesis@blocks@postamble` macros, respectively; the latter two macros are to be redefined by the loaded style files.

After expanding `\thesis@blocks@preamble` inside a \TeX group, the `\thesis@preamble` macro defines the `\thesis@pages@preamble` macro, writes the definition to the auxiliary file, and clears the page. After leaving the group, the `\thesis@preamble`

`\thesis@blocks@mainMatter` sets up the style of the main matter by expanding the `\thesis@blocks@mainMatter` macro.

```

276 \def\thesis@preamble{%
277   {\thesis@selectLocale{\thesis@locale}%
278   \thesis@blocks@preamble
279   \gdef\thesis@pages@preamble{\thepage}
280   \write\@auxout{\noexpand\gdef\noexpand
281     \thesis@pages@preamble{\thepage}}
282   \clearpage}
283   \thesis@blocks@mainMatter}
284
285 \let\thesis@blocks@preamble\relax
286 \let\thesis@blocks@mainMatter\relax

```

Before expanding `\thesis@blocks@postamble` inside a TeX group, the `\thesis@postamble` macro defines the `\thesis@pages@postamble` macro, writes the definition to the auxiliary file, and clears the page.

```

287 \def\thesis@postamble{%
288   \gdef\thesis@pages@postamble{\thepage}
289   \immediate\write\@auxout{\noexpand\gdef\noexpand
290     \thesis@pages@postamble{\thepage}}
291   {\thesis@selectLocale{\thesis@locale}%
292   \thesis@blocks@postamble}}
293
294 \let\thesis@blocks@postamble\relax

```

2.2.41 The extra key

The `{\extra={\keyvals}}` pair enables the definition of extra data fields, where *keyvals* is a comma-delimited list of *key=value* pairs as defined by the `keyval` package. For each *key=value* pair, a `\thesis@extra@key` is defined to be *value*. These extra data fields are provided as a unified interface for passing additional data to the style and locale files.

```

295 \def\thesis@extra@KV@prefix{KV@thesis@extra@}
296 \def\thesis@extra@XKV@fams{thesis@extra}
297 \long\def\KV@thesis@extra#1{%

```

Patch the `xKEYVAL` package to support unknown keys.

```

298   \long\def\XKV@s@tk@ys##1=##2=##3\@nil{%
299     \XKV@g@tkeyname##1=\@nil\XKV@tkey
300     \expandafter\KV@sp@def\expandafter\XKV@tkey\expandafter{\XKV@tkey}%
301     \ifx\XKV@tkey\@empty
302       \XKV@toks{##2}%
303       \ifcat$\the\XKV@toks$\else
304         \XKV@err{no key specified for value ‘\the\XKV@toks’}%
305       \fi
306     \else
307       \@expandtwoargs\in@{,\XKV@tkey,}{,\XKV@na,}%
308     \ifin@\else

```

```

309 \XKV@knftrue
310 \KV@sp@def\XKV@tempa{##2}%
311 \ifXKV@preset\XKV@st@k@ys@{##3}\else
312 \ifXKV@pl
313 \XKV@for@eo\XKV@fams\XKV@tfam{%
314 \XKV@makehd\XKV@tfam
315 \XKV@st@k@ys@{##3}%
316 }%
317 \else
318 \XKV@whilst\XKV@fams\XKV@tfam\ifXKV@knf\fi{%
319 \XKV@makehd\XKV@tfam
320 \XKV@st@k@ys@{##3}%
321 }%
322 \fi
323 \fi
324 \ifXKV@knf
325 \ifXKV@inpx
326 \ifx\XKV@doxs\relax
327 \ifx\@current\@clsextension\else
328 \let\CurrentOption\XKV@tkey\@unknownoptionerror
329 \fi
330 \else\XKV@doxs\fi
331 \else
332 \ifXKV@st
333 \XKV@addtolist@o\XKV@rm\CurrentOption
334 \else
335 \ifx\XKV@fams\thesis@extra@XKV@fams
336 \expandafter\long\expandafter\def\csname%
337 thesis@extra@\XKV@tkey\endcsname{##2}%
338 \else
339 \XKV@err{'\XKV@tkey' undefined in families
340 '\XKV@fams'}%
341 \fi
342 \fi
343 \fi
344 \else
345 \ifXKV@inpx\ifx\XKV@testclass\XKV@documentclass
346 \expandafter\XKV@useoption\expandafter{\CurrentOption}%
347 \fi\fi
348 \fi
349 \fi
350 \fi
351 }%
352 \setkeys{thesis@extra}{#1}%
353 \def\KV@prefix{KV@thesis@}

```

Patch the KEYVAL package to support unknown keys.

```

354 \long\def\KV@split#1=#2=#3\relax{%
355 \KV@sp@def\@tempa{#1}%
356 \ifx\@tempa\@empty\else

```

```

357 \expandafter\let\expandafter\@tempc
358   \csname\KV@prefix\@tempa\endcsname
359 \ifx\@tempc\relax
360   \ifx\KV@prefix\thesis@extra@KV@prefix
361     \KV@sp@def\@tempb{#2}%
362     \expandafter\let\csname thesis@extra@\@tempa\endcsname
363       \@tempb%
364   \else
365     \KV@errx
366     {\@tempa\space undefined}%
367   \fi
368 \else
369   \ifx\@empty#3\@empty
370     \KV@default
371   \else
372     \KV@sp@def\@tempb{#2}%
373     \expandafter\@tempc\expandafter{\@tempb}\relax
374   \fi
375 \fi
376 \fi}

```

`\thesis@def@extra` The `\thesis@def@extra[definition]{name}` macro defines the `\thesis@extra@name` macro to expand to either *definition*, if specified, or to `\thesis@placeholder@extra@name`, where `\thesis@placeholder@extra@name` is defined to expand to «*extra@name*». If `\thesis@extra@name` has already been defined by the user, `\thesis@def@extra` has no effect.

```

377 \newcommand{\thesis@def@extra}[2][{}]{%
378   \expandafter\ifx\csname thesis@extra@#2\endcsname\relax
379   \def\thesis@placeholder@extra{<<extra@#2>>}%
380   \expandafter\let\csname thesis@placeholder@extra@#2\endcsname
381     \thesis@placeholder@extra
382   \def\thesis@arg{#1}%
383   \ifx\empty\thesis@arg
384     \expandafter\let\csname thesis@extra@#2\endcsname
385       \thesis@placeholder@extra
386   \else
387     \expandafter\def\csname thesis@extra@#2\endcsname{#1}%
388   \fi
389 \fi}

```

2.3 The `\thesislong` macro

`\thesislong` The public macro `\thesislong[key]{value}`, can be used as an alternative to the `\thesissetup[key] = {value}` public macro:

```

390 \long\def\thesislong#1#2{%
391   \csname KV@thesis@#1\endcsname{#2}}

```

This macro is a relict of the time when `\thesissetup` did not accept multi-paragraph input.

2.4 The `\thesisload` macro

`\thesisload` The `\thesisload` macro is responsible for preparing the environment for, and consequently loading, the necessary locale and style files. By default, the `\thesisload` macro gets expanded at the end of the preamble, but it can be expanded manually prior to that point, if necessary to prevent package clashes. The `\ifthesisloaded` macro ensures that the expansion is only performed once. For backwards compatibility, the `\thesis@load` macro can be used to the same effect.

```
392 \newif\ifthesisloaded\thesisloadedfalse
393 \BeforeBeginEnvironment{document}{\thesisload}
394 \def\thesis@load{\thesisload}
395 \def\thesisload{%
396   \ifthesisloaded\else
397     \thesisloadedtrue
398     \makeatletter
```

First, the name of the main locale file is fully expanded and loaded using the `\thesis@requireLocale` macro. If the user specified an explicit empty string as the value of `\thesis@locale`, do nothing.

```
399   \ifx\thesis@locale\empty\else
400     \edef\thesis@locale{\thesis@locale}
401     \thesis@requireLocale{\thesis@locale}
402   \fi
```

Coerce Lua \TeX into defining `\l@locale` for *locales* with known hyphenation patterns, unless `babel` or `polyglossia` have been loaded. In that case, `\l@locale` has already been defined.

```
403   \ifluatex
404     \ltx@ifpackageloaded{babel}{}{
405       \ltx@ifpackageloaded{polyglossia}{}{
406         \thesis@require{babel}}}{
407   \fi
```

Fix the value of the `\ifthesis@english` macro.

```
408 \ifthesis@english
409   \expandafter\expandafter\expandafter\let\expandafter\expandafter
410   \csname ifthesis@english\endcsname\csname iftrue\endcsname
411 \else
412   \expandafter\expandafter\expandafter\let\expandafter\expandafter
413   \csname ifthesis@english\endcsname\csname iffalse\endcsname
414 \fi
```

Consequently, the style files are loaded. If the user specified an explicit empty string as the value of `\thesis@style`, do nothing.

```
415   \ifx\thesis@style\empty\else
416     \thesis@requireStyle{\thesis@style}
417   \fi
```

If the `babel` or `polyglossia` locale is identical to the thesis locale, the `\thesis@selectLocale` macro will be used to globally set up the `csquotes` style appropriate for the given locale.

```

418 \ifx\languagename\empty\else
419   \begingroup
420   \edef\@doclocale{\languagename}%
421   \ifx\@doclocale\thesis@locale
422     \endgroup
423     \AtBeginDocument{%
424       \thesis@selectLocale{\thesis@locale}}%
425   \else
426     \endgroup
427   \fi
428 \fi

```

With the placeholder strings loaded from the locale files, we can now inject meta-data into the resulting PDF file. To this end, the hyperref package is conditionally included with the unicode option. Consequently, the following values are assigned to the PDF headers:

- Title is set to `\thesis@title`.
- Author is set to `\thesis@author`.
- Keywords is set to `\thesis@keywords`.
- Creator is set to `2021/10/17 v1.0.2 fithesis4 MU thesis class`.

```

429   \thesis@require{hyperref}
430   \hypersetup{
431     unicode=true,
432     pdfencoding=auto,
433     pdftitle=\thesis@title,
434     pdfauthor=\thesis@author,
435     pdfkeywords=\thesis@keywords,
436     pdfcreator=\thesis@version}

```

If autolayout is enabled, the `\thesis@preamble` and `\thesis@postamble` macros are scheduled for expansion at the beginning and at the end of the document, respectively. The definition of the `\thesis@pages` macro is also scheduled to be written to the auxiliary file at the end of the document.

```

437   \ifthesis@auto
438     \AtBeginDocument{\thesis@preamble}
439     \AtEndDocument{%
440       \thesis@postamble
441       \immediate\write\@auxout{%
442         \noexpand\gdef\noexpand\thesis@pages{\thepage}}
443     \else
444       \AtEndDocument{%
445         \immediate\write\@auxout{%
446           \noexpand\gdef\noexpand\thesis@pages{\thepage}}
447     \fi
448   \makeatother
449 \fi}

```

3 Private API

3.1 File manipulation macros

`\thesis@exists` The `\thesis@exists{<file>}{<tokens>}` macro is used to test for the existence of a given *file*. If the *file* exists, the macro expands to *tokens*. Otherwise, a class warning is written to the output.

```
450 \def\thesis@exists#1#2{%
451   \IfFileExists{#1}{#2}{%
452     \ClassWarning{fithesis4}{File #1 doesn't exist}}
```

`\thesis@input` The `\thesis@input{<file>}` macro inputs the given *file*, if it exists.

```
453 \def\thesis@input#1{%
454   \thesis@exists{#1}{\input{#1}}
```

`\thesis@require` The `\thesis@require[<options>]{<package>}` expands to `\RequirePackage[<options>]{<package>}`, if the specified *package* has not yet been loaded.

```
455 \newcommand\thesis@require[2][{}]{%
456   \@ifpackageloaded{#2}{\RequirePackage[#1]{#2}}
```

`\thesis@requireIfExists` The `\thesis@requireIfExists[<options>]{<package>}` expands to `\thesis@require[<options>]{<package>}`, if the specified *package* exists and has not yet been loaded.

```
457 \newcommand\thesis@requireIfExists[2][{}]{%
458   \thesis@exists{#2.sty}{\thesis@require[#1]{#2}}
```

`\thesis@requireStyle` If inheritance is enabled for style files, then the `\thesis@requireStyle{<style>}` macro sequentially loads each of the following files, provided they exist:

1. `\thesis@stylepath fithesis-base.sty`
2. `\thesis@stylepath\thesis@university/fithesis-\thesis@university-base.sty`
3. `\thesis@stylepath style.sty`

If inheritance is disabled for style files, then only the last listed file is loaded. The `fithesis-` prefix serves to prevent package clashes with other similarly named package files within the TeX directory structure.

```
459 \def\thesis@requireStyle#1{%
460   \ifthesis@style@inheritance
461     \thesis@requireIfExists{\thesis@stylepath fithesis-base}%
462     \thesis@requireIfExists{\thesis@stylepath\thesis@university
463       /fithesis-\thesis@university-base}
464   \fi
465   \thesis@requireIfExists{\thesis@stylepath#1}}
```

`\thesis@requireLocale` If inheritance is enabled for style files, then the `\thesis@requireLocale{<locale>}` macro sequentially loads each of the following locale files, provided they exist:

1. `\thesis@localepath fithesis-locale.def`

2. `\thesis@localepath\thesis@university/fithesis-locale.def`
3. `\thesis@localepath\thesis@university/\thesis@faculty/fithesis-locale.def`

If inheritance is disabled for locale files, then only the first listed file is loaded. The `fithesis-` prefix serves to prevent clashes with other similarly named files within the \TeX directory structure. To prevent undesirable side effects from locale files being loaded multiple times, the `\thesis@locale@required` macro is defined as a flag, which prevents future invocations with the same *locale*. The macro can be used within both locale and style files, although the usage within locale files is strongly discouraged to prevent circular dependencies.

If the `polyglossia` package is being used, its definitions for the respective locale get loaded as well. As a consequence, this command may not be used within the document, but only in the preamble.

```

466 \def\thesis@requireLocale#1{%
467   % Ignore redundant requests
468   \expandafter\ifx\csname thesis@#1@required\endcsname\relax
469   \expandafter\def\csname thesis@#1@required\endcsname{%
470     \ifpackageloaded{polyglossia}{\setotherlanguage{#1}}{}
471     \thesis@input{\thesis@localepath fithesis-#1.def}%
472     \ifthesis@locale@inheritance
473       \thesis@input{\thesis@localepath\thesis@university/%
474         fithesis-#1.def}%
475       \thesis@input{\thesis@localepath\thesis@university/%
476         \thesis@faculty/fithesis-#1.def}%
477     \fi
478   \fi}

```

3.2 String manipulation macros

`\thesis@` The `\thesis@{<name>}` macro expands to `\thesis@name`, where *name* gets fully expanded and can therefore contain active characters and command sequences.

```

479 \def\thesis@#1{\csname thesis@#1\endcsname}

```

`\thesis@@` The `\thesis@@{<name>}` macro expands to `\thesis@locale@name`, where *locale* corresponds to the name of the current locale. The *name* gets fully expanded and can therefore contain active characters and command sequences.

```

480 \def\thesis@@#1{\thesis@{\thesis@locale @#1}}

```

`\thesis@lower`
`\thesis@upper` The `\thesis@lower` and `\thesis@upper` macros are used for upper- and lowercasing within locale files. To cast the `\thesis@name` macro to the lower- or uppercase, `\thesis@lower{<name>}` or `\thesis@upper{<name>}` would be used, respectively. The *name* gets fully expanded and can therefore contain active characters and command sequences.

```

481 \def\thesis@lower#1{%
482   \let\ea\expandafter
483   \ea\MakeLowercase\ea{\csname thesis@#1\endcsname}}
484 \def\thesis@upper#1{%

```

```

485 \let\ea\expandafter
486 \ea\MakeUppercase\ea{\csname thesis@#1\endcsname}}
\thesis@@lower The \thesis@@lower and \thesis@upper macros are used for upper- and low-
\thesis@upper   ercasing current locale strings within style files. To cast the \thesis@locale@name
macro to the lower- or uppercase, \thesis@@lower{name} or \thesis@upper{name}
would be used, respectively. The name gets fully expanded and can therefore con-
tain active characters and command sequences.
487 \def\thesis@@lower#1{\thesis@lower{\thesis@locale @#1}}
488 \def\thesis@upper#1{\thesis@upper{\thesis@locale @#1}}
\thesis@head The \thesis@head and \thesis@tail macros are used for retrieving the head or
\thesis@tail   the tail of space-separated token sequences that end with \relax.
489 \def\thesis@head#1 #2{%
490   \ifx\relax#2%
491     \expandafter\@gobbletwo
492   \else
493     \ #1%
494   \fi
495   \thesis@head#2}%
496 \def\thesis@tail#1 #2{%
497   \ifx\relax#2%
498     #1%
499     \expandafter\@gobbletwo
500   \fi
501   \thesis@tail#2}%

```

3.3 General purpose macros

```

\thesis@pages The \thesis@pages macro contains the last page number within the document.
During the first TEX compilation, the macro expands to ??.
502 \ifx\thesis@pages\undefined\def\thesis@pages{??}\fi
\thesis@selectLocale \thesis@selectLocale{locale} macro redefines the \thesis@locale macro to
locale, switches to the hyphenation patterns of locale, and starts using the
\thesis@locale@csquotesStyle style of the csquotes package. The respective locale
files and polyglossia locale definitions should be loaded beforehand using the
\thesis@requireLocale macro.

```

This macro should always be used within a group, so that the locale, csquotes, and hyphenation settings return back to what the user has specified after the localized blocks of typographic material.

```

503 \def\thesis@selectLocale#1{%
504   \edef\thesis@locale{#1}%
505   \ltx@ifpackageloaded{csquotes}{%
506     \csq@setstyle{\thesis@@{csquotesStyle}}%
507   }{%
508   \ltx@ifpackageloaded{polyglossia}{%
509     \selectlanguage{\thesis@locale}
510   }{%

```

```

511 \language\csname l@thesis@locale\endcsname
512 }}

```

`\thesis@patch` The `\thesis@patch{<versions>}{<patch>}` macro expands *patch*, if `\thesis@version@number` (defined at the top of the file `fithesis4.cls`) matches any of the comma-delimited *versions*. This macro enables the simple deployment of version-targeted patches.

```

513 \def\thesis@patch#1#2{%
514 \def\thesis@patch@versions{#1}%
515 \def\thesis@patch@action{#2}%
516 \def\thesis@patch@next##1,{%
517 \def\thesis@patch@arg{##1}%
518 \def\thesis@patch@relax{\relax}%
519 \ifx\thesis@patch@arg\thesis@version@number
520 \def\thesis@patch@next###1\relax,{}%
521 \expandafter\thesis@patch@action
522 \expandafter\thesis@patch@next
523 \else\ifx\thesis@patch@arg\thesis@patch@relax\else
524 \expandafter\expandafter\expandafter\thesis@patch@next
525 \fi\fi}%
526 \expandafter\expandafter\expandafter\thesis@patch@next
527 \expandafter\thesis@patch@versions\expandafter,\relax,}

```

`\thesis@xpatch` The `\thesis@xpatch{<command>}{<search>}{<replace>}` macro is used to to replace *search* with *replace* in the definition of *command*. If the replacement fails, a class error is written to the output.

```

528 \long\def\thesis@xpatch#1#2#3{%
529 \xpatchcmd{#1}{#2}{#3}{%
530 {\ClassError{fithesis4}{%
531 Command \string#1 does not contain the searched text}}}}

```

3.4 Locale files

Locale files contain macro definitions for various locales. They live in the `locale/` subtree and they are loaded during the main routine (see Section 2.4).

When creating a new locale file, it is advisable to create one self-contained dtx file, which is then partitioned into locale files via the `docstrip` tool based on the respective ins file. A macro `\file{<filename>}` is available for the sectioning of the documentation of various files within the dtx file. For more information about dtx files and the `docstrip` tool, consult the `dtxtut`, `docstrip`, `doc` and `ltxdoc` manuals.

Mind that the name of the locale is also used to load hyphenation patterns, which is why it shouldn't be arbitrary. To see the names of the hyphenation patterns, consult the `hyph-utf8` manual.

3.4.1 Interface

The union of locale files loaded via the locale file inheritance scheme (see the definition of the `\thesis@requireLocale` macro in Section 3.1) needs to globally

define the following macros:

- `\thesis@locale@csquotesStyle` – The name of the style of the csquotes package that matches this locale
- `\thesis@locale@universityName` – The name of the university
- `\thesis@locale@facultyName` – The name of the faculty
- `\thesis@locale@assignment` – The instructions to replace the current page with the official thesis assignment
- `\thesis@locale@declaration` – The thesis declaration text
- `\thesis@locale@fieldTitle` – The title of the field of study entry
- `\thesis@locale@advisorTitle` – The title of the advisor entry
- `\thesis@locale@authorTitle` – The title of the author entry
- `\thesis@locale@abstractTitle` – The title of the abstract section
- `\thesis@locale@keywordsTitle` – The title of the keywords section
- `\thesis@locale@thanksTitle` – The title of the acknowledgements section
- `\thesis@locale@declarationTitle` – The title of the declaration section
- `\thesis@locale@idTitle` – The title of the thesis author’s identifier field
- `\thesis@locale@spring` – The name of the spring semester
- `\thesis@locale@fall` – The name of the fall semester
- `\thesis@locale@semester` – The full name of the current semester
- `\thesis@locale@typeName` – The name of the thesis type
- `\thesis@locale@authorSignature` – The label of the author’s signature field
- `\thesis@locale@formattedDate` – A formatted date
- `\thesis@locale@advisorSignature` – The label of the author’s signature field

where *locale* is the name of the locale.

3.4.2 English locale files

3.4.2.1 The locale/fithesis-english.def file

This is the base file of the English locale.

```
532 \ProvidesFile{fithesis/locale/fithesis-english.def}[2021/02/26]
```

The locale file defines all the private macros mandated by the locale file interface.

```
533
534 % Placeholders
535 \gdef\thesis@english@universityName{University name}
536 \gdef\thesis@english@facultyName{Faculty name}

537 \gdef\thesis@english@assignment{%
538   This is where a copy of the official signed thesis assignment
539   is located in the printed version of the document.}
540 \gdef\thesis@english@declaration{Declaration text ...}
541
542 % Csquotes style
543 \gdef\thesis@english@csquotesStyle{english}
544
545 % Time strings
546 \gdef\thesis@english@spring{Spring}
547 \gdef\thesis@english@fall{Fall}
548 \gdef\thesis@english@semester{%
549   \thesis@{english@\thesis@season} \thesis@seasonYear}
550 \gdef\thesis@english@formattedDate{%
551   \thesis@day.
552   \newcount\@month\expandafter\@month\thesis@month\relax
553   \ifnum\@month=1%
554     January
555   \else\ifnum\@month=2%
556     February
557   \else\ifnum\@month=3%
558     March
559   \else\ifnum\@month=4%
560     April
561   \else\ifnum\@month=5%
562     May
563   \else\ifnum\@month=6%
564     June
565   \else\ifnum\@month=7%
566     July
567   \else\ifnum\@month=8%
568     August
569   \else\ifnum\@month=9%
570     September
571   \else\ifnum\@month=10%
572     October
573   \else\ifnum\@month=11%
574     November
```

```

575 \else\ifnum\@month=12%
576     December
577 \else
578     <<unknown month (\the\@month)>>
579 \fi\fi\fi\fi\fi\fi
580 \fi\fi\fi\fi\fi\fi
581 \thesis@year}}
582

583% Miscellaneous
584\gdef\thesis@english@authorSignature{Author's signature}

585\gdef\thesis@english@advisorSignature{Signature of Thesis
586 \thesis@english@advisorTitle}
587\gdef\thesis@english@fieldTitle{Field of Study}
588\gdef\thesis@english@advisorTitle{Advisor}
589\gdef\thesis@english@authorTitle{Author}
590\gdef\thesis@english@abstractTitle{Abstract}
591\gdef\thesis@english@keywordsTitle{Keywords}

592\gdef\thesis@english@thanksTitle{Acknowledgements}
593\gdef\thesis@english@declarationTitle{Declaration}
594\gdef\thesis@english@summaryTitle{Summary}
595\gdef\thesis@english@idTitle{ID}
596\gdef\thesis@english@typeName@sempaper{Seminar Paper}
597\gdef\thesis@english@typeName@bachelors{Bachelor's Thesis}
598\gdef\thesis@english@typeName@masters{Master's Thesis}
599\gdef\thesis@english@typeName@proposal{Thesis Proposal}
600\gdef\thesis@english@typeName@doctoral{Doctoral Thesis}
601\gdef\thesis@english@typeName@rigorous{Rigorous Thesis}
602\gdef\thesis@english@typeName{%
603 \ifx\thesis@type\thesis@sempaper
604 \thesis@english@typeName@sempaper
605 \else\ifx\thesis@type\thesis@bachelors
606 \thesis@english@typeName@bachelors
607 \else\ifx\thesis@type\thesis@masters
608 \thesis@english@typeName@masters
609 \else\ifx\thesis@type\thesis@proposal
610 \thesis@english@typeName@proposal
611 \else\ifx\thesis@type\thesis@doctoral
612 \thesis@english@typeName@doctoral
613 \else\ifx\thesis@type\thesis@rigorous
614 \thesis@english@typeName@rigorous
615 \else
616 <<Unknown thesis type (\thesis@type)>>%
617 \fi\fi\fi\fi\fi\fi}

```

3.4.2.2 The locale/*mu*/fithesis-english.def file

This is the English locale file specific to the Masaryk University in Brno. It replaces the `universityName` placeholder with the correct value and defines the

declaration and idTitle strings.

```
618 \ProvidesFile{fithesis/locale/mu/fithesis-english.def}[2017/07/09]
619 \gdef\thesis@english@universityName{Masaryk University}
620 \gdef\thesis@english@declaration{%
621   Hereby I declare that this paper is my original authorial work,
622   which I have worked out on my own. All sources, references, and
623   literature used or excerpted during elaboration of this work are
624   properly cited and listed in complete reference to the due source.}
625
626 % Placeholders

627 \gdef\thesis@english@assignment{%
628   \ifthesis@digital@
629   \else
630   \fi}

631 \gdef\thesis@english@assignment{%
632   \ifthesis@blocks@assignment@hideIfDigital@
633   \ifthesis@digital@
634     This is where a copy of the official signed thesis assignment
635     is located in the printed version of the document.
636   \else
637     Replace this page with a copy of the official signed thesis
638     assignment.
639   \fi
640 \else
641   Set the PDF document containing the official signed thesis
642   assignment using the <<assignment>> key.
643 \fi}
644
645 % Bibliographic entry
646 \gdef\thesis@english@bib@title{Bibliographic record}
647 \gdef\thesis@english@bib@pages{p}

648 \global\let\thesis@english@bib@author\thesis@english@authorTitle
649 \gdef\thesis@english@bib@thesisTitle{Title of Thesis}
650 \gdef\thesis@english@bib@advisor{Supervisor}

651 \gdef\thesis@english@bib@programme{Degree Programme}
652 \global\let\thesis@english@bib@field\thesis@english@fieldTitle
653 \gdef\thesis@english@bib@academicYear{Academic Year}
654 \gdef\thesis@english@bib@pages{Number of Pages}
655 \global\let\thesis@english@bib@keywords\thesis@english@keywordsTitle
656
657 % Miscellaneous
658 \gdef\thesis@english@idTitle{UČO}
```

3.4.2.3 The locale/mu/law/fithesis-english.def file

This is the English locale file specific to the Faculty of Law at the Masaryk University in Brno. It replaces the facultyName placeholder with the correct value

and defines the `facultyLongName` required by the `\thesis@blocks@cover` and the `\thesis@blocks@titlePage` blocks.

```
659 \ProvidesFile{fithesis/locale/mu/law/fithesis-english.def}[2015/06/26]
660 \gdef\thesis@english@facultyName{Faculty of Law}
661 \gdef\thesis@english@facultyLongName{The Faculty of Law of the
662 Masaryk University}
```

3.4.2.4 The `locale/mu/fsps/fithesis-english.def` file

This is the English locale file specific to the Faculty of Sports Studies at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `fieldTitle` string in accordance with the common usage at the faculty.

```
663 \ProvidesFile{fithesis/locale/mu/fsps/fithesis-english.def}[2017/06/02]
664
665 % Placeholders
666 \gdef\thesis@english@facultyName{Faculty of Sports Studies}
667
668 % Miscellaneous
669 \gdef\thesis@english@fieldTitle{Specialization}
```

3.4.2.5 The `locale/mu/fss/fithesis-english.def` file

This is the English locale file specific to the Faculty of Social Studies at the Masaryk University in Brno. It replaces the `facultyName` and assignment strings with the correct values.

```
670 \ProvidesFile{fithesis/locale/mu/fss/fithesis-english.def}[2016/05/25]
671
672 % Placeholders
673 \gdef\thesis@english@facultyName{Faculty of Social Studies}
674 \gdef\thesis@english@assignment{%
675   \ifthesis@digital@
676     This is where a copy of the official signed thesis assignment
677     or a copy of the Statement of an Author or both are located
678     in the printed version of the document.
679   \else
680     Replace this page with a copy of the official signed thesis
681     assignment or a copy of the Statement of an Author or both,
682     depending on the requirements of the respective department.
683   \fi}
```

3.4.2.6 The `locale/mu/econ/fithesis-english.def` file

This is the English locale file specific to the Faculty of Economics and Administration at the Masaryk University in Brno. It replaces the `facultyName` and `abstractTitle` placeholders with the correct value. The locale file also defines the private macros required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-econ.sty` style file.

```
684 \ProvidesFile{fithesis/locale/mu/econ/fithesis-english.def}[2017/06/02]
```



```

685
686% Placeholders
687\gdef\thesis@english@facultyName{Faculty of Economics
688 and Administration}
689
690% Miscellaneous
691\gdef\thesis@english@abstractTitle{Annotation}

```

3.4.2.7 The locale/mu/med/fithesis-english.def file

This is the English locale file specific to the Faculty of Medicine at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` string with the common usage at the faculty. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-med.sty` style file.

```

692\ProvidesFile{fithesis/locale/mu/med/fithesis-english.def}[2016/03/23]
693
694% Placeholders
695\gdef\thesis@english@facultyName{Faculty of Medicine}
696
697% Miscellaneous
698\gdef\thesis@english@abstractTitle{Annotation}

```

3.4.2.8 The locale/mu/fi/fithesis-english.def file

This is the English locale file specific to the Faculty of Informatics at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the string in accordance with the requirements of the faculty.

```

699\ProvidesFile{fithesis/locale/mu/fi/fithesis-english.def}[2021/02/26]
700
701% Placeholders
702\gdef\thesis@english@facultyName{Faculty of Informatics}
703\gdef\thesis@english@assignment{Replace this page with a copy
704 of the official signed thesis assignment and a copy of the
705 Statement of an Author.}
706\gdef\thesis@english@assignment{%
707 \ifthesis@digital@
708 This is where a copy of the official signed thesis assignment
709 and a copy of the Statement of an Author is located in the
710 printed version of the document.
711 \else
712 Replace this page with a copy of the official signed thesis
713 assignment and a copy of the Statement of an Author.
714 \fi}
715
716% Others
717\gdef\thesis@english@typeName@proposal{Ph.D. Thesis Proposal}

```

3.4.2.9 The locale/mu/phil/fithesis-english.def file

This is the English locale file specific to the Faculty of Arts at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. It also defines the `departmentName` string, which is used by the `style/mu/fithesis-phil.sty` style file, when typesetting the names of known departments.

```
718 \ProvidesFile{fithesis/locale/mu/phil/fithesis-english.def}[2016/03/22]
719 \gdef\thesis@english@facultyName{Faculty of Arts}
720 \gdef\thesis@english@departmentName{%
721   \ifx\thesis@department\thesis@departments@kisk
722     Division of Information and Library Studies%
723   \else
724     <<Unknown department (\thesis@department)>>%
725   \fi}
```

3.4.2.10 The locale/mu/ped/fithesis-english.def file

This is the Slovak locale file specific to the Faculty of Education at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-ped.sty` style file.

```
726 \ProvidesFile{fithesis/locale/mu/ped/fithesis-english.def}[2016/03/22]
727
728 % Placeholders
729 \gdef\thesis@english@facultyName{Faculty of Education}
```

3.4.2.11 The locale/mu/sci/fithesis-english.def file

This is the English locale file specific to the Faculty of Science at the Masaryk University in Brno. It defines the private macros required by the `\thesis@blocks@bibEntryEn` block defined within the `style/mu/fithesis-sci.sty` style file. It also replaces the `facultyName` placeholder with the correct value and redefines the `advisorTitle` string in accordance with the formal requirements of the faculty.

```
730 \ProvidesFile{fithesis/locale/mu/sci/fithesis-english.def}[2017/06/02]
731
732 % Placeholders
733 \gdef\thesis@english@facultyName{Faculty of Science}
734
735 % Miscellaneous
736 \global\let\thesis@english@advisorTitleEn=\thesis@english@bib@advisor
737
```

3.4.2.12 The locale/mu/pharm/fithesis-english.def file

This is the English locale file specific to the Faculty of Pharmacy at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` in accordance with the guidelines of the faculty.

```

738 \ProvidesFile{fithesis/locale/mu/pharm/fithesis-english.def}[2021/03/26]
739
740 % Placeholders
741 \gdef\thesis@english@facultyName{Faculty of Pharmacy}
742
743 % Miscellaneous
744 \gdef\thesis@english@abstractTitle{Annotation}

```

3.4.3 Czech locale files

3.4.3.1 The locale/fithesis-czech.def file

This is the base file of the Czech locale.

```
745 \ProvidesFile{fithesis/locale/fithesis-czech.def}[2021/02/26]
```

The locale file defines all the private macros mandated by the locale file interface.

\thesis@czech@gender@koncovka The locale file also defines the \thesis@czech@gender@koncovka macro, which expands to the correct verb ending based on the value of the \thesis@ifwoman macro and the

\thesis@czech@typeName@akuzativ \thesis@czech@typeName@akuzativ containing the accusative case of the thesis type name.

```

746
747 % Pomocná makra
748 \gdef\thesis@czech@gender@koncovka{%
749   \ifthesis@woman a\fi}
750
751 % Csquotes styl
752 \gdef\thesis@czech@csquotesStyle{german}
753
754 % Zástupné texty
755 \gdef\thesis@czech@universityName{Název univerzity}
756 \gdef\thesis@czech@facultyName{Název fakulty}

757 \gdef\thesis@czech@assignment{%
758   Na tomto místě se v~tištěné práci nachází oficiální podepsané
759   zadání práce.}
760 \gdef\thesis@czech@declaration{Text prohlášení ...}
761
762 % Časové údaje
763 \gdef\thesis@czech@spring{jaro}
764 \gdef\thesis@czech@fall{podzim}
765 \gdef\thesis@czech@semester{%
766   \thesis@{czech@\thesis@season} \thesis@seasonYear}
767 \gdef\thesis@czech@formattedDate{{}%
768   \thesis@day.
769   \newcount\@month\expandafter\@month\thesis@month\relax
770   \ifnum\@month=1%
771     ledna

```

```

772 \else\ifnum \@month=2%
773     února
774 \else\ifnum \@month=3%
775     března
776 \else\ifnum \@month=4%
777     dubna
778 \else\ifnum \@month=5%
779     května
780 \else\ifnum \@month=6%
781     června
782 \else\ifnum \@month=7%
783     července
784 \else\ifnum \@month=8%
785     srpna
786 \else\ifnum \@month=9%
787     září
788 \else\ifnum \@month=10%
789     října
790 \else\ifnum \@month=11%
791     listopadu
792 \else\ifnum \@month=12%
793     prosince
794 \else
795     <<neznámý měsíc (\the \@month)>>
796     \fi\fi\fi\fi\fi\fi
797     \fi\fi\fi\fi\fi\fi
798     \thesis@year}}
799
800 % Různé
801 \gdef\thesis@czech@authorSignature{%
802     Podpis autor\ifthesis@woman ky\else a\fi}

803 \gdef\thesis@czech@advisorSignature{Podpis vedoucího}
804 \gdef\thesis@czech@fieldTitle{Obor}
805 \gdef\thesis@czech@advisorTitle{Vedoucí práce}
806 \gdef\thesis@czech@authorTitle{Autor}
807 \gdef\thesis@czech@abstractTitle{Shrnutí}
808 \gdef\thesis@czech@keywordsTitle{Klíčová slova}
809 \gdef\thesis@czech@thanksTitle{Poděkování}
810 \gdef\thesis@czech@declarationTitle{Prohlášení}
811 \gdef\thesis@czech@summaryTitle{Resumé}
812 \gdef\thesis@czech@idTitle{ID}
813 \gdef\thesis@czech@typeName@sempaper{Seminární práce}
814 \gdef\thesis@czech@typeName@bachelors{Bakalářská práce}
815 \gdef\thesis@czech@typeName@masters{Diplomová práce}
816 \gdef\thesis@czech@typeName@proposal{Teze závěrečné práce}
817 \gdef\thesis@czech@typeName@doctoral{Disertační práce}
818 \gdef\thesis@czech@typeName@rigorous{Rigorózní práce}
819 \gdef\thesis@czech@typeName{%

```

```

820 \ifx\thesis@type\thesis@sempaper
821   \thesis@czech@typeName@sempaper
822 \else\ifx\thesis@type\thesis@bachelors
823   \thesis@czech@typeName@bachelors
824 \else\ifx\thesis@type\thesis@masters
825   \thesis@czech@typeName@masters
826 \else\ifx\thesis@type\thesis@proposal
827   \thesis@czech@typeName@proposal
828 \else\ifx\thesis@type\thesis@doctoral
829   \thesis@czech@typeName@doctoral
830 \else\ifx\thesis@type\thesis@rigorous
831   \thesis@czech@typeName@rigorous
832 \else
833   <<Neznámý typ práce (\thesis@type)>>%
834 \fi\fi\fi\fi\fi\fi}
835 \gdef\thesis@czech@typeName@akuzativ@sempaper{Seminární práci}
836 \gdef\thesis@czech@typeName@akuzativ@bachelors{Bakalářskou práci}
837 \gdef\thesis@czech@typeName@akuzativ@masters{Diplomovou práci}
838 \gdef\thesis@czech@typeName@akuzativ@proposal{Tezi závěrečné práce}
839 \gdef\thesis@czech@typeName@akuzativ@doctoral{Disertační práci}
840 \gdef\thesis@czech@typeName@akuzativ@rigorous{Rigorózní práci}
841 \gdef\thesis@czech@typeName@akuzativ{%
842   \ifx\thesis@type\thesis@sempaper
843     \thesis@czech@typeName@akuzativ@sempaper
844   \else\ifx\thesis@type\thesis@bachelors
845     \thesis@czech@typeName@akuzativ@bachelors
846   \else\ifx\thesis@type\thesis@masters
847     \thesis@czech@typeName@akuzativ@masters
848   \else\ifx\thesis@type\thesis@proposal
849     \thesis@czech@typeName@akuzativ@proposal
850   \else\ifx\thesis@type\thesis@doctoral
851     \thesis@czech@typeName@akuzativ@doctoral
852   \else\ifx\thesis@type\thesis@rigorous
853     \thesis@czech@typeName@akuzativ@rigorous
854   \else
855     <<Neznámý typ práce (\thesis@type)>>%
856   \fi\fi\fi\fi\fi\fi}

```

3.4.3.2 The locale/mu/fithesis-czech.def file

This is the Czech locale file specific to the Masaryk University in Brno. It replaces the universityName placeholder with the correct value and defines the declaration and idTitle strings.

```

857 \ProvidesFile{fithesis/locale/mu/fithesis-czech.def}[2017/07/09]
858
859 % Zástupné texty
860 \gdef\thesis@czech@universityName{Masarykova univerzita}
861 \gdef\thesis@czech@declaration{Prohlašuji, že jsem
862   \thesis@lower{czech@typeName@akuzativ} zpracoval%
863   \thesis@czech@gender@koncovka\ samostatně a~%

```

```

864 použil\thesis@czech@gender@koncovka\ jen prameny
865 uvedené v~seznamu literatury.}

866 \gdef\thesis@czech@assignment{%
867 \ifthesis@blocks@assignment@hideIfDigital@
868 \ifthesis@digital@
869     Na tomto místě se v~tištěné práci nachází oficiální podepsané
870     zadání práce.
871 \else
872     Místo tohoto listu vložte kopii oficiálního podepsaného zadání
873     práce.
874 \fi
875 \else
876     Nastavte pomocí klíče <<assignment>> název PDF souboru
877     s~oficiálním podepsaným zadáním práce.
878 \fi}
879
880% Bibliografický záznam
881 \gdef\thesis@czech@bib@title{Bibliografický záznam}
882 \gdef\thesis@czech@bib@pages{str}

883 \global\let\thesis@czech@bib@author\thesis@czech@authorTitle
884 \gdef\thesis@czech@bib@thesisTitle{Název práce}
885 \global\let\thesis@czech@bib@advisor\thesis@czech@advisorTitle

886 \gdef\thesis@czech@bib@programme{Studijní program}
887 \global\let\thesis@czech@bib@field\thesis@czech@fieldTitle
888 \gdef\thesis@czech@bib@academicYear{Akademický rok}
889 \gdef\thesis@czech@bib@pages{Počet stran}
890 \global\let\thesis@czech@bib@keywords\thesis@czech@keywordsTitle
891
892% Různé
893 \gdef\thesis@czech@idTitle{UČO}

```

3.4.3.3 The locale/mu/law/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Law at the Masaryk University in Brno. It replaces the facultyName placeholder with the correct value, defines the facultyLongName required by the \thesis@blocks@cover and the \thesis@blocks@titlePage blocks and replaces the abstractTitle string in accordance with the requirements of the faculty.

```

894 \ProvidesFile{fithesis/locale/mu/law/fithesis-czech.def}[2015/06/26]
895
896% Různé
897 \gdef\thesis@czech@abstractTitle{Abstrakt}
898
899% Zástupné texty
900 \gdef\thesis@czech@facultyName{Právnická fakulta}
901 \gdef\thesis@czech@facultyLongName{Právnická fakulta Masarykovy
902 univerzity}

```

3.4.3.4 The locale/mu/fsps/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Sports Studies at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `fieldTitle` string in accordance with the common usage at the faculty. The locale file also redefines the `declaration` string in accordance with the requirements of the faculty.

```
903 \ProvidesFile{fithesis/locale/mu/fsps/fithesis-czech.def}[2017/05/15]
904
905 % Zástupné texty
906 \gdef\thesis@czech@facultyName{Fakulta sportovních studií}
907 \gdef\thesis@czech@declaration{Prohlašuji, že jsem
908 \thesis@lower{czech@typeName@akuzativ} vypracoval%
909 \thesis@czech@gender@koncovka\ samostatně a~na základě
910 literatury a~pramenů uvedených v~použitých zdrojích.}
911
912 % Různé
913 \gdef\thesis@czech@fieldTitle{Specializace}
```

3.4.3.5 The locale/mu/fss/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Social Studies at the Masaryk University in Brno. It replaces the `facultyName` and `assignment` placeholders with the correct values.

```
914 \ProvidesFile{fithesis/locale/mu/fss/fithesis-czech.def}[2016/05/25]
915
916 % Zástupné texty
917 \gdef\thesis@czech@facultyName{Fakulta sociálních studií}
918 \gdef\thesis@czech@assignment{%
919 \ifthesis@digital@
920 Na tomto místě se v~tištěné práci nachází oficiální podepsané
921 zadání práce, prohlášení autora školního díla nebo obojí.
922 \else
923 Místo tohoto listu vložte kopie oficiálního podepsaného zadání
924 práce nebo prohlášení autora školního díla nebo obojí
925 v~závislosti na požadavcích příslušné katedry.
926 \fi}
927
```

3.4.3.6 The locale/mu/econ/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Economics and Administration at the Masaryk University in Brno. It replaces the `facultyName` and `abstractTitle` placeholders with the correct values. The locale file also redefines the `declaration` string in accordance with the requirements of the faculty and defines the private macros required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-econ.sty` style file.

```
928 \ProvidesFile{fithesis/locale/mu/econ/fithesis-czech.def}[2017/07/09]
929
```

```

930% Zástupné texty
931\gdef\thesis@czech@facultyName{Ekonomicko-správní fakulta}
932
933% Různé
934\gdef\thesis@czech@abstractTitle{Anotace}

```

The following extra data field is defined for declaration string:

- `advisorCsGenitiv` – the advisor’s name in genitive following Czech morphology.

```

935\thesis@def@extra{advisorCsGenitiv}
936\gdef\thesis@czech@declaration{Prohlašuji, že jsem
937 \thesis@lower{czech@typeName@akuzativ} \thesis@title{} zpracoval%
938 \thesis@czech@gender@koncovka\ samostatně pod vedením
939 \thesis@extra@advisorCsGenitiv\
940 a~uvedl\thesis@czech@gender@koncovka\ v~ní všechny
941 odborné zdroje v~souladu s~právními předpisy, vnitřními
942 předpisy Masarykovy univerzity a~vnitřními akty řízení
943 Masarykovy univerzity a~Ekonomicko-správní fakulty MU.}

```

3.4.3.7 The locale/mu/med/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Medicine at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` string in accordance with the common usage at the faculty. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-med.sty` style file.

```

944\ProvidesFile{fithesis/locale/mu/med/fithesis-czech.def}[2016/03/23]
945
946% Zástupné texty
947\gdef\thesis@czech@facultyName{Lékařská fakulta}
948
949% Různé
950\gdef\thesis@czech@abstractTitle{Anotace}

```

3.4.3.8 The locale/mu/fi/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Informatics at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `declaration` string in accordance with the requirements of the faculty.

```

951\ProvidesFile{fithesis/locale/mu/fi/fithesis-czech.def}[2021/02/26]
952
953% Zástupné texty
954\gdef\thesis@czech@facultyName{Fakulta informatiky}
955\gdef\thesis@czech@assignment{%
956 \ifthesis@digital@

```



```

957 Na tomto místě se v~tištěné práci nachází oficiální podepsané
958 zadání práce a~prohlášení autora školního díla.
959 \else
960 Místo tohoto listu vložte kopie oficiálního podepsaného zadání
961 práce a~prohlášení autora školního díla.
962 \fi}
963 \gdef\thesis@czech@declaration{%
964 Prohlašuji, že tato \thesis@lower{czech@typeName} je mým
965 původním autorským dílem, které jsem vypracoval%
966 \thesis@czech@gender@koncovka\ samostatně. Všechny zdroje,
967 prameny a~literaturu, které jsem při vypracování
968 používal\thesis@czech@gender@koncovka\ nebo z~nich
969 čerpal\thesis@czech@gender@koncovka, v~práci řádně cituji
970 s~uvedením úplného odkazu na příslušný zdroj.}
971
972 % Ostatní
973 \gdef\thesis@czech@typeName@proposal{Teze disertační práce}
974 \gdef\thesis@czech@typeName@akuzativ@proposal{Tezi disertační práce}

```

3.4.3.9 The locale/mu/phil/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Arts at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. It also re-defines the `declaration`, `typeName` and `typeName@akuzativ` strings in accordance with the requirements of the faculty.

The locale file also defines the `departmentName` string, which is used by the `style/mu/fithesis-phil.sty` style file, when typesetting the names of known departments.

```

975 \ProvidesFile{fithesis/locale/mu/phil/fithesis-czech.def}[2016/03/22]
976
977 % Zástupné texty
978 \gdef\thesis@czech@facultyName{Filozofická fakulta}
979 \gdef\thesis@czech@departmentName{%
980 \ifx\thesis@department\thesis@departments@kisk
981 Kabinet informačních studií a knihovnictví%
982 \else
983 <<Neznámé oddělení (\thesis@department)>>%
984 \fi}
985 \gdef\thesis@czech@declaration{%
986 \ifx\thesis@department\thesis@departments@kisk
987 Prohlašuji, že jsem předkládanou práci zpracoval%
988 \thesis@czech@gender@koncovka\ samostatně a~použil%
989 \thesis@czech@gender@koncovka\ jen uvedené prameny a~%
990 literaturu. Současně dávám svolení k~tomu, aby elektronická
991 verze této práce byla zpřístupněna přes informační systém
992 Masarykovy univerzity.%
993 \else
994 Prohlašuji, že jsem \thesis@lower{czech@typeName@akuzativ}
995 vypracoval\thesis@czech@gender@koncovka\ samostatně s~využitím

```

```

996   uvedené literatury.%
997   \fi}
998
999% Ostatní
1000\global\let\thesis@czech@typeName@super
1001 \thesis@czech@typeName
1002\gdef\thesis@czech@typeName{%
1003 \ifx\thesis@type\thesis@bachelors
1004   Bakalářská diplomová práce%
1005 \else\ifx\thesis@type\thesis@masters
1006   Magisterská diplomová práce%
1007 \else
1008   \thesis@czech@typeName@super
1009 \fi\fi}
1010
1011\global\let\thesis@czech@typeName@akuzativ@super
1012 \thesis@czech@typeName@akuzativ
1013\gdef\thesis@czech@typeName@akuzativ{%
1014 \ifx\thesis@type\thesis@bachelors
1015   Diplomovou práci%
1016 \else\ifx\thesis@type\thesis@masters
1017   Diplomovou práci%
1018 \else
1019   \thesis@czech@typeName@akuzativ@super
1020 \fi\fi}

```

3.4.3.10 The locale/mu/ped/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Education at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-ped.sty` style file.

```

1021\ProvidesFile{fithesis/locale/mu/ped/fithesis-czech.def}[2017/10/28]
1022
1023% Zástupné texty
1024\gdef\thesis@czech@facultyName{Pedagogická fakulta}

```

3.4.3.11 The locale/mu/sci/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Science at the Masaryk University in Brno. It defines the private macros required by the `\thesis@blocks@bibEntryCs` block defined within the `style/mu/fithesis-sci.sty` style file. It also replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` and `declaration` strings in accordance with the formal requirements of the faculty.

```

1025\ProvidesFile{fithesis/locale/mu/sci/fithesis-czech.def}[2017/06/02]
1026
1027% Zástupné texty

```

```

1028 \gdef\thesis@czech@facultyName{Přirodovědecká fakulta}
1029
1030 % Ostatní
1031 \gdef\thesis@czech@abstractTitle{Abstrakt}
1032 \gdef\thesis@czech@declaration{%
1033   Prohlašuji, že jsem svoji \thesis@lower{czech@typeName@%
1034   akuzativ} vypracoval\thesis@czech@gender@koncovka\ samo%
1035   statně s~využitím informačních zdrojů, které jsou v~práci
1036   citovány.}
1037

```

3.4.3.12 The locale/mu/pharm/fithesis-czech.def file

This is the Czech locale file specific to the Faculty of Pharmacy at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` accordance with the guidelines of the faculty.

```

1038 \ProvidesFile{fithesis/locale/mu/pharm/fithesis-czech.def}[2021/03/26]
1039
1040 % Zástupné texty
1041 \gdef\thesis@czech@facultyName{Farmaceutická fakulta}
1042
1043 % Ostatní
1044 \gdef\thesis@czech@abstractTitle{Anotace}

```

3.4.4 Slovak locale files

3.4.4.1 The locale/fithesis-slovak.def file

This is the base file of the Slovak locale.

```

1045 \ProvidesFile{fithesis/locale/fithesis-slovak.def}[2021/02/26]

```

The locale file defines all the private macros mandated by the locale file interface.

`\thesis@slovak@gender@koncovka` The locale file also defines the `\thesis@slovak@gender@koncovka` macro, which expands to the correct verb ending based on the value of the `\thesis@ifwoman` macro and the

`\thesis@slovak@typeName@akuzativ` `\thesis@slovak@typeName@akuzativ` containing the accusative case of the thesis type name.

```

1046
1047 % Pomocná makrá
1048 \gdef\thesis@slovak@gender@koncovka{%
1049   \ifthesis@woman a\fi}
1050
1051 % Csquotes štýl
1052 \gdef\thesis@slovak@csquotesStyle{german}
1053
1054 % Zástupné texty
1055 \gdef\thesis@slovak@universityName{Názov univerzity}
1056 \gdef\thesis@slovak@facultyName{Názov fakulty}

```

```

1057 \gdef\thesis@slovak@assignment{%
1058   Na tomto mieste sa v~tlačenej práci nachádza oficiálne
1059   podpísané zadanie práce.}
1060 \gdef\thesis@slovak@declaration{Text vyhlásenie ...}
1061
1062 % Časové údaje
1063 \gdef\thesis@slovak@spring{jar}
1064 \gdef\thesis@slovak@fall{jeseň}
1065 \gdef\thesis@slovak@semester{%
1066   \thesis@{slovak@\thesis@season} \thesis@seasonYear}
1067 \gdef\thesis@slovak@formattedDate{%
1068   \thesis@day.
1069   \newcount\@month\expandafter\@month\thesis@month\relax
1070   \ifnum\@month=1%
1071     januára
1072   \else\ifnum\@month=2%
1073     februára
1074   \else\ifnum\@month=3%
1075     marca
1076   \else\ifnum\@month=4%
1077     apríla
1078   \else\ifnum\@month=5%
1079     mája
1080   \else\ifnum\@month=6%
1081     júna
1082   \else\ifnum\@month=7%
1083     júla
1084   \else\ifnum\@month=8%
1085     augusta
1086   \else\ifnum\@month=9%
1087     septembra
1088   \else\ifnum\@month=10%
1089     októbra
1090   \else\ifnum\@month=11%
1091     novembra
1092   \else\ifnum\@month=12%
1093     decembra
1094   \else
1095     <<neznámy mesiac (\the\@month)>>
1096   \fi\fi\fi\fi\fi\fi
1097   \fi\fi\fi\fi\fi\fi
1098   \thesis@year}}
1099
1100 % Rôzne
1101 \gdef\thesis@slovak@authorSignature{%
1102   Podpis autor\ifthesis@woman ky\else a\fi}
1103 \gdef\thesis@slovak@advisorSignature{Podpis vedúceho}
1104 \gdef\thesis@slovak@fieldTitle{Odbor}

```

```

1105 \gdef\thesis@slovak@advisorTitle{Vedúci práce}
1106 \gdef\thesis@slovak@authorTitle{Autor}
1107 \gdef\thesis@slovak@abstractTitle{Zhrnutie}
1108 \gdef\thesis@slovak@keywordsTitle{Kľúčové slová}
1109 \gdef\thesis@slovak@thanksTitle{Poďakovanie}
1110 \gdef\thesis@slovak@declarationTitle{Vyhlásenie}
1111 \gdef\thesis@slovak@summaryTitle{Resumé}
1112 \gdef\thesis@slovak@idTitle{ID}
1113 \gdef\thesis@slovak@typeName@sempaper{Seminárna práca}
1114 \gdef\thesis@slovak@typeName@bachelors{Bakalárska práca}
1115 \gdef\thesis@slovak@typeName@masters{Diplomová práca}
1116 \gdef\thesis@slovak@typeName@proposal{Tézy záverečnej práce}
1117 \gdef\thesis@slovak@typeName@doctoral{Dizertačná práca}
1118 \gdef\thesis@slovak@typeName@rigorous{Rigorózna práca}
1119 \gdef\thesis@slovak@typeName{%
1120   \ifx\thesis@type\thesis@sempaper
1121     \thesis@slovak@typeName@sempaper
1122   \else\ifx\thesis@type\thesis@bachelors
1123     \thesis@slovak@typeName@bachelors
1124   \else\ifx\thesis@type\thesis@masters
1125     \thesis@slovak@typeName@masters
1126   \else\ifx\thesis@type\thesis@proposal
1127     \thesis@slovak@typeName@proposal
1128   \else\ifx\thesis@type\thesis@doctoral
1129     \thesis@slovak@typeName@doctoral
1130   \else\ifx\thesis@type\thesis@rigorous
1131     \thesis@slovak@typeName@rigorous
1132   \else
1133     <<Neznámy typ práce (\thesis@type)>>%
1134   \fi\fi\fi\fi\fi\fi}
1135 \gdef\thesis@slovak@typeName@akuzativ@sempaper{Seminárnu prácu}
1136 \gdef\thesis@slovak@typeName@akuzativ@bachelors{Bakalársku prácu}
1137 \gdef\thesis@slovak@typeName@akuzativ@masters{Diplomovú prácu}
1138 \gdef\thesis@slovak@typeName@akuzativ@proposal{Tézy záverečnej práce}
1139 \gdef\thesis@slovak@typeName@akuzativ@doctoral{Dizertačnú prácu}
1140 \gdef\thesis@slovak@typeName@akuzativ@rigorous{Rigoróznú prácu}
1141 \gdef\thesis@slovak@typeName@akuzativ{%
1142   \ifx\thesis@type\thesis@sempaper
1143     \thesis@slovak@typeName@akuzativ@sempaper
1144   \else\ifx\thesis@type\thesis@bachelors
1145     \thesis@slovak@typeName@akuzativ@bachelors
1146   \else\ifx\thesis@type\thesis@masters
1147     \thesis@slovak@typeName@akuzativ@masters
1148   \else\ifx\thesis@type\thesis@proposal
1149     \thesis@slovak@typeName@akuzativ@proposal
1150   \else\ifx\thesis@type\thesis@doctoral
1151     \thesis@slovak@typeName@akuzativ@doctoral
1152   \else\ifx\thesis@type\thesis@rigorous
1153     \thesis@slovak@typeName@akuzativ@rigorous
1154   \else

```

```
1155 <<Neznámy typ práce (\thesis@type)>>%
1156 \fi\fi\fi\fi\fi\fi}
```

3.4.4.2 The locale/mu/fithesis-slovak.def file

This is the Slovak locale file specific to the Masaryk University in Brno. It replaces the universityName placeholder with the correct value and defines the declaration and idTitle strings.

```
1157 \ProvidesFile{fithesis/locale/mu/fithesis-slovak.def}[2018/02/11]
1158
1159 % Zástupné texty
1160 \gdef\thesis@slovak@universityName{Masarykova univerzita}

1161 \gdef\thesis@slovak@declaration{%
1162   Vyhlasujem, že som predloženú \thesis@lower{%
1163     slovak@typeName@akuzativ} vypracoval%
1164   \thesis@slovak@gender@koncovka\ samostatne len s~použitím
1165   uvedenej literatúry a prameňov.}

1166 \gdef\thesis@slovak@assignment{%
1167   \ifthesis@blocks@assignment@hideIfDigital@
1168     \ifthesis@digital@
1169       Na tomto mieste sa v~tlačenej práci nachádza oficiálne
1170       podpísané zadanie práce.
1171     \else
1172       Namiesto tejto stránky vložte kópiu oficiálneho podpísaného
1173       zadania práce.
1174     \fi
1175   \else
1176     Nastavte pomocou klúča <<assignment>> názov súboru PDF
1177     s~oficiálnym podpísaným zadanim práce.
1178   \fi}
1179
1180 % Bibliografický záznam
1181 \gdef\thesis@slovak@bib@title{Bibliografický záznam}
1182 \gdef\thesis@slovak@bib@pages{str}

1183 \global\let\thesis@slovak@bib@author\thesis@slovak@authorTitle
1184 \gdef\thesis@slovak@bib@thesisTitle{Názov práce}
1185 \global\let\thesis@slovak@bib@advisor\thesis@slovak@advisorTitle

1186 \gdef\thesis@slovak@bib@programme{Študijný program}
1187 \global\let\thesis@slovak@bib@field\thesis@slovak@fieldTitle
1188 \gdef\thesis@slovak@bib@academicYear{Akademický rok}
1189 \gdef\thesis@slovak@bib@pages{Počet strán}
1190 \global\let\thesis@slovak@bib@keywords\thesis@slovak@keywordsTitle
1191
1192 % Rôzne
1193 \gdef\thesis@slovak@idTitle{UČO}
```

3.4.4.3 The locale/mu/law/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Law at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value, defines the `facultyLongName` required by the `\thesis@blocks@cover` and the `\thesis@blocks@titlePage` blocks and replaces the `abstractTitle` string in accordance with the requirements of the faculty.

```
1194 \ProvidesFile{fithesis/locale/mu/law/fithesis-slovak.def}[2015/06/26]
1195
1196 % Rôzne
1197 \gdef\thesis@slovak@abstractTitle{Abstrakt}
1198
1199 % Zástupné texty
1200 \gdef\thesis@slovak@facultyName{Právnická fakulta}
1201 \gdef\thesis@slovak@facultyLongName{Právnická fakulta Masarykovej
1202 univerzity}
```

3.4.4.4 The locale/mu/fsps/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Sports Studies at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `fieldTitle` string in accordance with the common usage at the faculty. The locale file also redefines the `declaration` string in accordance with the requirements of the faculty.

```
1203 \ProvidesFile{fithesis/locale/mu/fsps/fithesis-slovak.def}[2017/05/15]
1204
1205 % Zástupné texty
1206 \gdef\thesis@slovak@facultyName{Fakulta športových štúdií}
1207 \gdef\thesis@slovak@declaration{%
1208 Vyhlasujem, že som \thesis@lower{%
1209 slovak@typeName@akuzativ} vypracoval%
1210 \thesis@slovak@gender@koncovka\ samostatne a~na základe
1211 literatúry a~prameňov uvedených v~použitých zdrojoch.}
1212
1213 % Rôzne
1214 \gdef\thesis@slovak@fieldTitle{Špecializácie}
```

3.4.4.5 The locale/mu/fss/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Social Studies at the Masaryk University in Brno. It replaces the `facultyName` and `assignment` strings with the correct values.

```
1215 \ProvidesFile{fithesis/locale/mu/fss/fithesis-slovak.def}[2016/05/25]
1216
1217 % Zástupné texty
1218 \gdef\thesis@slovak@facultyName{Fakulta sociálnych štúdií}
1219 \gdef\thesis@slovak@assignment{%
1220 \ifthesis@digital@
1221 Na tomto mieste sa v~tlačenej práci nachádza oficiálne
```

```

1222   podpísané zadanie práce alebo vyhlásenie autora školského
1223   diela alebo obidve.
1224   \else
1225     Namiesto tejto stránky vložte kópiu oficiálneho podpísaného
1226     zadania práce alebo vyhlásenie autora školského diela alebo
1227     obidve v~závislosti na požiadavkách príslušnej katedry.
1228   \fi}

```

3.4.4.6 The locale/mu/econ/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Economics and Administration at the Masaryk University in Brno. It replaces the `facultyName` and `abstractTitle` placeholders with the correct values. The locale file also redefines the declaration string in accordance with the requirements of the faculty and defines the private macros required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-econ.sty` style file.

```

1229 \ProvidesFile{fithesis/locale/mu/econ/fithesis-slovak.def}[2017/07/09]
1230
1231 % Zástupné texty
1232 \gdef\thesis@slovak@facultyName{Ekonomicko-správná fakulta}
1233
1234 % Rôzne
1235 \gdef\thesis@slovak@abstractTitle{Anotácie}

```

The following extra data field is defined for the declaration string:

- `advisorSkGenitiv` – the advisor’s name in genitive following Slovak morphology.

```

1236 \thesis@def@extra{advisorSkGenitiv}
1237 \gdef\thesis@slovak@declaration{Vyhlasujem, že som
1238   \thesis@lower{slovak@typeName@akuzativ} \thesis@title{} spracoval%
1239   \thesis@slovak@gender@koncovka\ samostatne pod vedením
1240   \thesis@extra@advisorSkGenitiv\
1241   a~uvied\ifthesis@woman la\else ol\fi\ v~nej všetky
1242   odborné zdroje v~súlade s~právnymi predpismi, vnútornými
1243   predpismi Masarykovej univerzity a~vnútornými aktmi riadenia
1244   Masarykovej univerzity a~Ekonomicko-správnej fakulty MU.}

```

3.4.4.7 The locale/mu/med/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Medicine at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` string in accordance with the common usage at the faculty. The file also defines the `bib@title` and `bib@pages` strings required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-med.sty` style file.

```

1245 \ProvidesFile{fithesis/locale/mu/med/fithesis-slovak.def}[2016/03/23]
1246

```



```

1247% Zástupné texty
1248\gdef\thesis@slovak@facultyName{Lekárska fakulta}
1249
1250% Rôzne
1251\gdef\thesis@slovak@abstractTitle{Anotácie}

```

3.4.4.8 The locale/mu/fi/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Informatics at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the declaration string in accordance with the requirements of the faculty.

```

1252\ProvidesFile{fithesis/locale/mu/fi/fithesis-slovak.def}[2021/02/26]
1253
1254% Zástupné texty
1255\gdef\thesis@slovak@facultyName{Fakulta informatiky}
1256\gdef\thesis@slovak@assignment{%
1257  \ifthesis@digital@
1258    Na tomto mieste sa v~tlačenej práci nachádza oficiálne
1259    podpísané zadanie práce a vyhlásenie autora školského diela.
1260  \else
1261    Namiesto tejto stránky vložte kópiu oficiálneho podpísaného
1262    zadania práce a vyhlásenie autora školského diela.
1263  \fi}
1264\gdef\thesis@slovak@declaration{%
1265  Vyhlasujem, že táto \thesis@lower{slovak@typeName} je mojím
1266  pôvodným autorským dielom, ktoré som vypracoval%
1267  \thesis@slovak@gender@koncovka\ samostatne. Všetky zdroje,
1268  pramene a literatúru, ktoré som pri vypracovaní
1269  používal\thesis@slovak@gender@koncovka\ alebo z~nich
1270  čerpal\thesis@slovak@gender@koncovka, v~práci riadne citujem
1271  s~uvedením úplného odkazu na príslušný zdroj.}
1272
1273% Rôzne
1274\gdef\thesis@slovak@typeName@proposal{Tézy dizertačnej práce}
1275\gdef\thesis@slovak@typeName@akuzativ@proposal{Tézy dizertačnej práce}

```

3.4.4.9 The locale/mu/phil/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Arts at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. It also defines the declaration string and redefines the `typeName` and `typeName@akuzativ` strings in accordance with the requirements of the faculty.

The locale file also defines the `departmentName` string, which is used by the `style/mu/fithesis-phil.sty` style file, when typesetting the names of known departments.

```

1276\ProvidesFile{fithesis/locale/mu/phil/fithesis-slovak.def}[2016/03/22]
1277
1278% Zástupné texty

```

```

1279 \gdef\thesis@slovak@facultyName{Filozofická fakulta}
1280 \gdef\thesis@slovak@departmentName{%
1281   \ifx\thesis@department\thesis@departments@kisk
1282     Kabinet informačných štúdií a knihovníctva%
1283   \else
1284     <<Neznáme oddelenie (\thesis@department)>>%
1285   \fi}
1286 \gdef\thesis@slovak@declaration{%
1287   \ifx\thesis@department\thesis@departments@kisk
1288     Vyhlasujem, že som predkladanú prácu spracoval%
1289     \thesis@slovak@gender@koncovka\ samostatne~a použil%
1290     \thesis@slovak@gender@koncovka\ len uvedené pramene~a
1291     literatúru. Súčasne dávam súhlas k~tomu, aby elektronická
1292     verzia tejto práce bola sprístupnená cez informačný
1293     systém Masarykovej univerzity.%
1294   \else
1295     Vyhlasujem, že som predloženú \thesis@lower{%
1296     slovak@typeName@akuzativ} vypracoval%
1297     \thesis@slovak@gender@koncovka\ samostatne na základe vlastných
1298     zistení a len s~použitím uvedenej literatúry a prameňov.%
1299   \fi}
1300
1301 % Rôzne
1302 \global\let\thesis@slovak@typeName@super
1303   \thesis@slovak@typeName
1304 \gdef\thesis@slovak@typeName{%
1305   \ifx\thesis@type\thesis@bachelors
1306     Bakalárska diplomová práca%
1307   \else\ifx\thesis@type\thesis@masters
1308     Magisterská diplomová práca%
1309   \else
1310     \thesis@slovak@typeName@super
1311   \fi\fi}
1312
1313 \global\let\thesis@slovak@typeName@akuzativ@super
1314   \thesis@slovak@typeName@akuzativ
1315 \gdef\thesis@slovak@typeName@akuzativ{%
1316   \ifx\thesis@type\thesis@bachelors
1317     Diplomovú prácu%
1318   \else\ifx\thesis@type\thesis@masters
1319     Diplomovú prácu%
1320   \else
1321     \thesis@slovak@typeName@akuzativ@super
1322   \fi\fi}

```

3.4.4.10 The locale/mu/ped/fithesis-slovak.def file

This is the Slovak locale file specific to the Faculty of Education at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value. The file also defines the `bib@title` and `bib@pages` strings required by the

`\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-ped.sty` style file.

```
1323 \ProvidesFile{fithesis/locale/mu/ped/fithesis-slovak.def}[2017/06/02]
1324
1325 % Zástupné texty
1326 \gdef\thesis@slovak@facultyName{Pedagogická fakulta}
```

3.4.4.11 The `locale/mu/sci/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Science at the Masaryk University in Brno. The locale file also defines the private macros required by the `\thesis@blocks@bibEntry` block defined within the `style/mu/fithesis-sci.sty` style file. It also replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` and `declaration` strings in accordance with the formal requirements of the faculty.

```
1327 \ProvidesFile{fithesis/locale/mu/sci/fithesis-slovak.def}[2017/05/21]
1328
1329 % Zástupné texty
1330 \gdef\thesis@slovak@facultyName{Prírodovedecká fakulta}
1331
```

3.4.4.12 The `locale/mu/pharm/fithesis-slovak.def` file

This is the Slovak locale file specific to the Faculty of Pharmacy at the Masaryk University in Brno. It replaces the `facultyName` placeholder with the correct value and redefines the `abstractTitle` in accordance with the guidelines of the faculty.

```
1332 \ProvidesFile{fithesis/locale/mu/pharm/fithesis-slovak.def}[2021/03/26]
1333
1334 % Zástupné texty
1335 \gdef\thesis@slovak@facultyName{Farmaceutická fakulta}
1336
1337 % Rôzne
1338 \gdef\thesis@slovak@abstractTitle{Anotácie}
```

3.5 Style files

Style files define the structure and the look of the resulting document. They live in the `style/` subtree and they are loaded during the main routine (see Section 2.4).

When creating a new style file, it is advisable to create one self-contained `dtx` file, which can contain several files to be extracted via the `docstrip` tool based on the respective `ins` file. A macro `\file{filename}` is available for the sectioning of the documentation of various files within the `dtx` file. For more information about `dtx` files and the `docstrip` tool, consult the `dtxut`, `docstrip`, `doc` and `ltxdoc` manuals.

3.5.1 Interface

The union of style files loaded via the style file inheritance scheme (see the definition of the `\thesis@requireStyle` macro in Section 3.1) should globally define at

least one of the following macros:

- `\thesis@blocks@preamble` • `\thesis@blocks@preamble` – If autolayout is enabled, then this macro is expanded at the very beginning of the document.
- `\thesis@blocks@postamble` • `\thesis@blocks@postamble` – If autolayout is enabled, then this macro is expanded at the very end of the document.
- `\thesis@blocks@mainMatter` • `\thesis@blocks@mainMatter` – If autolayout is enabled, then this macro is expanded at the beginning of the document right after `\thesis@blocks@preamble`. This macro sets the style of the main matter of the thesis.

3.5.2 Base style files

3.5.2.1 The `style/fithesis-base.sty` file

If inheritance is enabled for style files, then this file is always the first style file to be loaded, regardless of the value of the `\thesis@style` macro. This style file is currently a dummy file.

```
1339 \NeedsTeXFormat{LaTeX2e}
1340 \ProvidesPackage{fithesis/style/fithesis-base}[2018/02/11]

1341 \DeclareRobustCommand\em
1342     {\@nomath\em \ifdim \fontdimen\@ne\font >\z@
1343     \emminnershape \else \itshape \fi}%
```

3.5.2.2 The `style/mu/fithesis-base.sty` file

This is the base style file for theses written at the Masaryk University in Brno. When inheritance is enabled for style files, this file is always the second style file to be loaded right after `style/fithesis-base.sty`, regardless of the value of the `\thesis@style` macro.

```
1344 \ProvidesPackage{fithesis/style/mu/fithesis-mu-base}[2021/05/23]
1345 \NeedsTeXFormat{LaTeX2e}
```

The file recognizes the following options:

- `10pt`, `11pt`, `12pt` – Sets the type size to 10, 11 or 12 points respectively.

```
1346 \DeclareOption{10pt}{\def\thesis@ptsize{0}}
1347 \DeclareOption{11pt}{\def\thesis@ptsize{1}}
1348 \DeclareOption{12pt}{\def\thesis@ptsize{2}}
```

- `oneside`, `twoside` – The document is going to be either single- or double-sided, respectively. In a double-sided document, headers, page numbering, margin notes and several other elements will be arranged based on the parity of the page. Blank pages will also be inserted prior the beginning of each chapter to ensure that it starts on a right-hand (odd-numbered) page. The `\ifthesis@twoside@` conditional is set to either `false` or `true`, respectively.

```
\ifthesis@twoside@
```

```
1349 \newif\ifthesis@twoside@
```

```

1350 \DeclareOption{oneside}{%
1351 \thesis@twoside@false\@twosidefalse\@mparswitchfalse}
1352 \DeclareOption{twoside}{%
1353 \thesis@twoside@true \@twosidetrue \@mparswitchtrue}

```

- `onecolumn`, `twocolumn` – The document is going to be set in either a single column or in two columns, respectively.

```

1354 \DeclareOption{onecolumn}{\@twocolumnfalse}
1355 \DeclareOption{twocolumn}{\@twocolumntrue}

```

- `draft`, `final` – Overfull lines either are or aren't marked within the document, respectively, and graphics either aren't or are inserted into the document, respectively.

```

1356 \DeclareOption{draft}{\setlength\overfullrule{5pt}}
1357 \DeclareOption{final}{\setlength\overfullrule{0pt}}

```

- `palatino`, `nopalatino` – The roman text font family and the math font family is going to be either set to Palatino or left untouched, respectively. The `\ifthesis@palatino@` conditional is set to either true or false, respectively. The Palatino font is a part of the visual identity of the Faculty of Informatics at which the document class was created.

`\ifthesis@palatino@`

```

1358 \newif\ifthesis@palatino@
1359 \DeclareOption{palatino}{\thesis@palatino@true}
1360 \DeclareOption{nopalatino}{\thesis@palatino@false}

```

- `color`, `monochrome` – Certain typographical elements either are or aren't going to be typeset in color, respectively. The `\ifthesis@color@` conditional is set to either true or false, respectively.

`\ifthesis@color@`

```

1361 \newif\ifthesis@color@
1362 \DeclareOption{monochrome}{\thesis@color@false}
1363 \DeclareOption{color}{\thesis@color@true}

```

- `microtype`, `nomicrotype` – The microtypographic extension of modern \TeX engines – such as $\text{pdf}\TeX$, $\text{X}\TeX$, or $\text{Lua}\TeX$ – is or isn't going to be enabled, respectively. The `\ifthesis@microtype@` conditional is set to either true or false, respectively.

`\ifthesis@microtype@`

```

1364 \newif\ifthesis@microtype@
1365 \DeclareOption{microtype}{\thesis@microtype@true}
1366 \DeclareOption{nomicrotype}{\thesis@microtype@false}

```

- `table`, `oldtable` – If the `\ifthesis@color@` conditional is true, then the definitions of the `tabular`, `tabularx`, and `tabu` commands either are or aren't going to be altered to better match the style, respectively. The `\ifthesis@newtable@` conditional is set to either true or false, respectively.

`\ifthesis@newtable@`

```

1367 \newif\ifthesis@newtable@
1368 \DeclareOption{table}{\thesis@newtable@true}
1369 \DeclareOption{oldtable}{\thesis@newtable@false}

```

The choice of the option name is deliberate – the redefinition of the table environments depends on the xcolor package, which needs to be loaded with the table option. Since so many other packages depend on the xcolor package and this style file is loaded at the very end of the preamble, there would either be a great chance of an option clash, or the option would have to be passed to the xcolor package before the preamble from the body of the fithesis4 class thus breaking the encapsulation. Naming the option table forces the option to be processed by the xcolor package as well and it is therefore an elegant solution to the problem at hand.

`\thesis@blocks@lot` • lot, nolot – The `\thesis@blocks@lot` macro will be defined as either `\listoftables` or `\relax`, respectively. As a side effect, the `\listoftables` either is or isn't going to be included in the `\thesis@blocks@tables` block, respectively.

```
1370 \DeclareOption{noлот}{\let\thesis@blocks@lot\relax}
1371 \DeclareOption{lot}{\let\thesis@blocks@lot\listoftables}
```

`\thesis@blocks@lof` • lof, nolof – The `\thesis@blocks@lof` macro will be defined as either `\listoffigures` or `\relax`, respectively. As a side effect, the `\listoffigures` either is or isn't going to be included in the `\thesis@blocks@tables` block, respectively.

```
1372 \DeclareOption{noлоf}{\let\thesis@blocks@lof\relax}
1373 \DeclareOption{lof}{\let\thesis@blocks@lof\listoffigures}
```

`\thesis@blocks@cover` • cover, nocover – The `\thesis@blocks@cover` either is going to expand to either the thesis cover or produces no output, respectively. The `\ifthesis@cover@` conditional is set to false or true, respectively.

`\ifthesis@cover@`

```
1374 \newif\ifthesis@cover@
1375 \DeclareOption{nocover}{\thesis@cover@false}
1376 \DeclareOption{cover}{\thesis@cover@true}
```

`\ifthesis@digital@` • digital, printed – These macrooptions set the options that are appropriate for either the printed or for the digital version of the document, respectively. The `\ifthesis@digital@` conditional is set to true or false, respectively.

```
1377 \newif\ifthesis@digital@
1378 \DeclareOption{digital}{%
1379 \ExecuteOptions{color,cover}%
1380 \thesis@digital@true}
1381 \DeclareOption{printed}{%
1382 \ExecuteOptions{monochrome,nocover}%
1383 \thesis@digital@false}
```

These are the default options:

```
1384 \ExecuteOptions{%
1385 printed,12pt,twoside,final,microtype,palatino,oldtable,lot,lof}
1386 \ProcessOptions*
```

The file uses English locale strings within the macros.

```
1387 \thesis@requireLocale{english}
```

The file loads the following packages:

- `xcolor` – Adds support for color.
- `caption` – Adds support for changing the formatting of float captions.
- `ifxetex` – Used to detect the Xe_{La}TeX engine.
- `ifluatex` – Used to detect the LuaTeX engine.
- `graphicx` – Adds support for the inclusion of graphics files.
- `pdfpages` – Adds support for the injection of PDF documents into the resulting document, namely the thesis assignment.
- `hyperref` – Adds support for the injection of metadata into the resulting PDF document.
- `keyval` – Adds support for parsing comma-delimited lists of key-value pairs.
- `tabularx` – Provides the `tabularx` environment, which enables the typesetting of tables with flexible-width columns.
- `tabu` – Provides the `tabu` environment, which enables the typesetting of complex tables.
- `booktabs` – A package, which allows the creation of publication-quality tables in L^AT_EX.

```
1388 \thesis@require{xcolor}
1389 \RequirePackage[labelfont=bf]{caption}
1390 \thesis@require{graphicx}
1391 \thesis@require{pdfpages}
1392 \thesis@require{keyval}
1393 \thesis@require{ifxetex}
1394 \thesis@require{ifluatex}
1395 \thesis@require{tabularx}
1396 \thesis@require{tabu}
1397 \thesis@require{booktabs}
1398 \thesis@require{tikz}
```

If the `\thesis@microtype@` is set to `true`, then the `microtype` package gets loaded.

```
1399 \ifthesis@microtype@
1400 \thesis@require[final,babel]{microtype}
1401 \fi
```

`\ifthesis@xeluatex` Using the `\ifxetex` and `\ifluatex` conditionals, a compound `\ifthesis@xeluatex` conditional was constructed. This conditional can be used by subsequently loaded style files to test, whether either the $X_{\text{E}}\text{T}_{\text{E}}\text{X}$ or the $\text{L}^{\text{u}}\text{a}\text{T}_{\text{E}}\text{X}$ engine is being used.

```

1402 {\let\x\expandafter
1403 \x\global\x\let\x\ifthesis@xeluatex\csname if%
1404 \ifxetex true\else
1405 \ifluatex\x\x\x t\x\x\x r\x\x\x u\x\x\x e%
1406 \else f\x\x\x a\x\x\x l\x\x\x s\x\x\x e%
1407 \fi
1408 \fi\endcsname}

```

The following packages get only loaded, when the document is being typeset using the $X_{\text{E}}\text{T}_{\text{E}}\text{X}$ or $\text{L}^{\text{u}}\text{a}\text{T}_{\text{E}}\text{X}$ engine:

- `fontspec` – Allows the selection of system-installed fonts.
- `unicode-math` – Allows the selection of system-installed mathematical fonts.

Under $X_{\text{E}}\text{T}_{\text{E}}\text{X}$ or $\text{L}^{\text{u}}\text{a}\text{T}_{\text{E}}\text{X}$, the $\text{T}_{\text{E}}\text{X}$ Gyre Pagella and $\text{T}_{\text{E}}\text{X}$ Gyre Pagella Math fonts are also selected as the main text and math fonts and the $\text{T}_{\text{E}}\text{X}$ Gyre Heros font is selected as the main sans serif font.

```

1409 \ifthesis@xeluatex
1410 \ifthesis@palatino@
1411 \thesis@require{fontspec}
1412 \thesis@require{unicode-math}
1413 \setmainfont[Ligatures=TeX]{TeX Gyre Pagella}
1414 \setsansfont[Ligatures=TeX,Scale=MatchLowercase]{TeX Gyre Heros}
1415 \setmathfont[math-style=ISO,bold-style=ISO]{texgyrepagella-math.otf}
1416 \fi

```

The following packages get only loaded, when the document is not being typeset using the $X_{\text{E}}\text{T}_{\text{E}}\text{X}$ or $\text{L}^{\text{u}}\text{a}\text{T}_{\text{E}}\text{X}$ engine and the `\ifthesis@palatino@` conditional is true:

- `cmap` – Places an explicit ToUnicode map in the resulting PDF file, allowing for the extraction of the text from the document.
- `mathpazo` – Changes the default math font family to `mathpazo`.
- `tgpagella` – Changes the default roman font family to $\text{T}_{\text{E}}\text{X}$ Gyre Pagella.
- `tgheros` – Changes the default sans-serif font face to $\text{T}_{\text{E}}\text{X}$ Gyre Heros.
- `lmodern` – Changes the default sans-serif and monotype font faces to Latin Modern instead of the default Computer Modern font family.
- `fontenc` – The font encoding is set to Cork.

```

1417 \else
1418 \ifthesis@palatino@
1419 \RequirePackage[resetfonts]{cmap}
1420 \thesis@require{lmodern}

```



```

1421 \thesis@require{mathpazo}
1422 \thesis@require{tgpagella}
1423 \thesis@require[scale=0.863]{tgheros}
1424 \RequirePackage[T1]{fontenc}
1425 \fi
1426 \fi

```

If the `\thesis@newtable@` conditional is true, then some of the dimensions associated with tables are modified in preparation for the coloring of the table cells.

```

1427 \let\thesis@newtable@old\tabular
1428 \let\endthesis@newtable@old\endtabular
1429 \ifthesis@newtable@
1430 % Adjust the measurements.
1431 \setlength{\aboverulesep}{0pt}
1432 \setlength{\belowrulesep}{0pt}
1433 \setlength{\extrarowheight}{.75ex}

```

When both the `\thesis@newtable@` and `\thesis@color@` conditionals are true, then the `tabular` and `tabularx` environments are redefined to better match the style of the given faculty.

The `\thesis@newtable@old` and `\endthesis@newtable@old` macros containing the original definition of the `tabular` environment are always defined and are available for subsequently loaded styles in case the typesetting of unaltered tables is required. Similarly, the `\thesis@newtable@oldx` and `\endthesis@newtable@oldx` macros are defined for the `tabularx` environment and the `\thesis@newtable@oldtabu` and `\endthesis@newtable@oldtabu` for the `tabu` environment.

```

\thesis@newtable@old
\endthesis@newtable@old

\thesis@newtable@oldx
\endthesis@newtable@oldx
\thesis@newtable@oldtabu
\endthesis@newtable@oldtabu
1434 \ifthesis@color@
1435 % The redefinition of ‘tabular’
1436 \renewenvironment{tabular}%
1437   {\rowcolors{1}{thesis@color@tableOdd}%
1438    {thesis@color@tableEven}%
1439    \thesis@newtable@old}%
1440   {\endthesis@newtable@old}
1441 % The redefinition of ‘tabularx’
1442 \let\thesis@newtable@oldx\tabularx
1443 \let\endthesis@newtable@oldx\endtabularx
1444 \renewenvironment{tabularx}%
1445   {\rowcolors{1}{thesis@color@tableEven}%
1446    {thesis@color@tableOdd}%
1447    \thesis@newtable@oldx}%
1448   {\endthesis@newtable@oldx}
1449 % The redefinition of ‘tabu’
1450 \let\thesis@newtable@oldtabu\tabu
1451 \let\endthesis@newtable@oldtabu\endtabu
1452 \renewenvironment{tabu}%
1453   {\rowcolors{1}{thesis@color@tableEven}%
1454    {thesis@color@tableOdd}%
1455    \thesis@newtable@oldtabu}%
1456   {\endthesis@newtable@oldtabu}
1457 \fi

```

1458 \fi

`\ifthesis@bibliography@` A new conditional, `\ifthesis@bibliography@`, is defined. This conditional is true, when `\thesis@bibFiles` expands to a non-empty token list.

```
1459 \newif\ifthesis@bibliography@
1460 \thesis@bibliography@false
1461 \ifx\thesis@bibFiles\undefined\else
1462   {\edef\@bibList{\thesis@bibFiles}%
1463   \ifx\@bibList\empty\else
1464     \global\thesis@bibliography@true
1465   \fi}
1466 \fi
```

`\thesis@bibliography@setup` The file defines the `\thesis@bibliography@setup{<options>}` command, where *options* is a comma-delimited list of key-value pairs as defined by the `keyval` package. The command can be invoked by the subsequently loaded style files to define the bibliography options.

```
1467 \def\thesis@bibliography@setup#1{%
1468   \setkeys{thesis@bibliography}{#1}}
```

The following key-value pairs are supported:

- `\thesis@bibliography@style` 1. `{<style=style>}` – Stores *style* in `\thesis@bibliography@style`, unless it has already been defined (presumably by the user).
- `\thesis@bibliography@sorting` 2. `{<sorting=mode>}` – Stores *mode* in `\thesis@bibliography@sorting`, unless it has already been defined (presumably by the user).

```
1469 \define@key{thesis@bibliography}{style}{%
1470   \ifx\thesis@bibliography@style\undefined
1471     \def\thesis@bibliography@style{#1}%
1472   \fi}
1473 \define@key{thesis@bibliography}{sorting}{%
1474   \ifx\thesis@bibliography@sorting\undefined
1475     \def\thesis@bibliography@sorting{#1}%
1476   \fi}
```

The following extra data field is defined for the macro:

- `bibliography` – the comma-delimited list of key-value pairs accepted by `\thesis@bibliography@setup`. If the data field was specified, it is immediately passed to `\thesis@bibliography@setup` and it overrides any defaults specified in faculty style files.

```
1477 \thesis@def@extra[][bibliography]
1478 \ifx\thesis@extra@bibliography
1479   \thesis@placeholder@extra@bibliography\else
1480   \expandafter\thesis@bibliography@setup\expandafter{%
1481     \thesis@extra@bibliography}%
1482 \fi
```

`\thesis@bibliography@load` When `\ifthesis@bibliography@` is true and `\ifthesis@bibliography@loaded@` is false, the `\thesis@bibliography@load` macro loads the `csquotes` and `BibLaTeX` packages with the bibliography databases specified in `\thesis@bibFiles`. The `\thesis@bibliography@loaded` macro also sets the `\ifthesis@bibliography@loaded@` conditional to true.

```

1483 \newif\ifthesis@bibliography@loaded@
1484 \thesis@bibliography@loaded@false
1485 \newif\ifthesis@bibliography@included@
1486 \thesis@bibliography@included@false
1487 \def\thesis@bibliography@load{%
1488   \ifthesis@bibliography@
1489     \ifthesis@bibliography@loaded@\else
1490       \thesis@bibliography@loaded@true
1491       % Load csquotes and BibLaTeX.
1492       \thesis@require{csquotes}

```

If `\thesis@bibliography@style` is undefined, the bibliography and citation styles default to `iso-numeric`. If `\thesis@bibliography@sorting` is undefined, the sorting scheme defaults to `none`.

```

1493   \thesis@bibliography@setup{
1494     style = iso-numeric,
1495     sorting = none}
1496   % FIXME: This is a hotfix for biblatex.
1497   % It should be removed after v3.17 has been released.
1498   % See https://tex.stackexchange.com/a/581469/70941.
1499   \thesis@require{expl3}
1500   \thesis@require[
1501     backend=biber,
1502     style=\thesis@bibliography@style,
1503     sorting=\thesis@bibliography@sorting,
1504     autolang=other,
1505     sortlocale=auto]{biblatex}
1506   % Load the bibliography databases.
1507   {\edef\@bibList{\thesis@bibFiles}%
1508   \def\@inject##1,{%
1509     \def\@args{##1}\def\@relax{\relax}%
1510     \ifx\@args\@relax\else
1511       % Trim leading spaces.
1512       \edef\@trimmed{\romannumeral-'\.##1}%
1513       \addbibresource\@trimmed
1514       \expandafter\@inject\fi}%
1515   \expandafter\@inject\@bibList,\relax,}%

```

`\ifthesis@bibliography@included@` The `\ifthesis@bibliography@included@` conditional is true, when the user has manually included a bibliography into their document. The default value of the conditional is false and `\printbibliography` is patched to set the conditional to true on expansion. This enables the user to place the bibliography manually without it appearing in the autolayout. The original macro is stored in the `\thesis@printbibliography@old` macro.

```

1516   \let\thesis@printbibliography@old\printbibliography

```

```

1517 \def\printbibliography{%
1518 \global\thesis@bibliography@included@true
1519 \thesis@printbibliography@old}
1520 \fi
1521 \fi}

```

In the digital version, the hyperref package is configured to decorate hyperlinks with an underline instead of a rectangular box. In the printed version, the hyperref package is configured to hide links.

```

1522 \thesis@require{hyperref}
1523 \ifthesis@digital@
1524 \hypersetup{pdfborderstyle={/S/U/W 1}}
1525 \else
1526 \hypersetup{hidelinks}
1527 \fi

```

Clubs and widows are set to be infinitely bad.

```

1528 \widowpenalty 10000
1529 \clubpenalty 10000

```

`\thesis@color@setup` The file defines the `\thesis@color@setup{<colors>}` command, where *colors* is a comma-delimited list of key-value pairs as defined by the keyval package. The command can be invoked either by the subsequently loaded style files or by the user to define which colors will be used, when the color option is specified.

```

1530 \def\thesis@color@setup#1{%
1531 \setkeys{thesis@color}{#1}}

```

The following key-value pairs are supported:

1. `{<links=color>}` – Sets the color of hyperref links to *color* and stores it under the name `thesis@color@links`. The default color of links is specified by the hyperref package.
2. `{<secondary=color>}` – Stores the secondary color that is used with the bold type face under the name `thesis@color@secondary`. The default secondary color for the Masaryk University is RGB 0, 0, 220.
3. `{<tableOdd=color>}` – Stores the color of the odd rows of the redefined `tabular` and `tabularx` environments under the name `thesis@color@tableOdd`.
4. `{<tableEven=color>}` – Stores the color of the even rows of the redefined `tabular` and `tabularx` environments under the name `thesis@color@tableEven`.
5. `{<tableEmph=color>}` – Stores the color of an emphasized cell in a table user under the name `thesis@color@tableEmph`. This color is meant to be used manually by the user.

```

1532 \define@key{thesis@color}{links}{%
1533 \definecolor{thesis@color@links}#1
1534 \hypersetup{linkbordercolor=thesis@color@links}}

```

```

1535 \define@key{thesis@color}{secondary}{%
1536   \definecolor{thesis@color@secondary}#1}
1537 \thesis@color@setup{secondary={RGB}{0, 0, 220}}
1538 \define@key{thesis@color}{tableOdd}{%
1539   \definecolor{thesis@color@tableOdd}#1}
1540 \define@key{thesis@color}{tableEven}{%
1541   \definecolor{thesis@color@tableEven}#1}
1542 \define@key{thesis@color}{tableEmph}{%
1543   \definecolor{thesis@color@tableEmph}#1}

```

The `\bfseries` macro is redefined to switch to the sans serif type face in the secondary color. The original definition of `\bfseries` is stored in the `\thesis@bfseries@old` macro.

`\thesis@bfseries@old`

```

1544 \let\thesis@bfseries@old\bfseries
1545 \def\bfseries{%
1546   \sffamily\color{thesis@color@secondary}\thesis@bfseries@old}

```

The file defines several blocks to be used in the redefinitions of the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros by the subsequently loaded style files.

`\thesis@blocks@coverMatter`

The `\thesis@blocks@coverMatter` macro sets up the style of the cover and the title page of the thesis. This amounts to disabling the page numbering, so that `hyperref` links do not point to the cover page and the title page instead of the initial pages of the main matter.

```

1547 \def\thesis@blocks@coverMatter{%
1548   \pagenumbering{gobble}}

```

`\thesis@blocks@frontMatter`

The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis.

```

1549 \def\thesis@blocks@frontMatter{%
1550   \thesis@blocks@clear
1551   \pagestyle{plain}
1552   \parindent 1.5em
1553   \setcounter{page}{1}
1554   \pagenumbering{roman}}

```

`\thesis@blocks@clear`

The `\thesis@blocks@clear` macro clears the current page. It also clears the next left-hand (even-numbered) page, when double-sided typesetting is enabled.

```

1555 % \begin{macrocode}
1556 \def\thesis@blocks@clear{%
1557   \ifthesis@twoside@
1558     \clearpage
1559     \ifodd\value{page}\else%
1560       \thispagestyle{empty}%
1561       \hbox{}%
1562     \newpage
1563   \fi
1564 \else
1565   \newpage
1566 \fi}

```

`\thesis@blocks@clearRight` The `\thesis@blocks@clearRight` macro clears the current page. It also clears the next right-hand (odd-numbered) page, when double-sided typesetting is enabled.

```
1567 \def\thesis@blocks@clearRight{%
1568   \ifthesis@twoside@
1569     \clearpage
1570     \ifodd\value{page}%
1571       \thispagestyle{empty}%
1572       \hbox{}%
1573       \newpage
1574     \fi
1575   \else
1576     \newpage
1577   \fi}
```

`\thesis@blocks@logo` The `\thesis@blocks@logo{<pathname>}{<options>}` macro typesets the *pathname* logo with the given *options* passed to `\includegraphics`.

```
1578 \newcommand{\thesis@blocks@logo}[2]{{%
1579   \let\@logowidth\relax\newlength\@logowidth
1580   \let\@logoheight\relax\newlength\@logoheight
1581   \settoheight\@logoheight{\includegraphics[#2]{#1}}%
1582   \settoheight\@logoheight{\includegraphics[#2]{#1}}%
1583   \def\@maxwidth##1{\ifdim\@logowidth>##1 ##1\else\@logowidth\fi}
1584   \def\@maxheight##1{\ifdim\@logoheight>##1 ##1\else\@logoheight\fi}
1585   \includegraphics[width=\@maxwidth{6.3cm}, height=\@maxheight{4cm},
1586     keepaspectratio, #2]{#1}}
```

`\thesis@blocks@facultyLogo@monochrome` The `\thesis@blocks@facultyLogo@monochrome[<options>]` macro typesets the `\thesis@logopath\thesis@facultyLogo` logo with the given *options* passed to `\includegraphics`.

```
1587 \newcommand{\thesis@blocks@facultyLogo@monochrome}[1]{%
1588   [scale=0.95]{{%
1589     \edef\@path{\thesis@logopath\thesis@facultyLogo}%
1590     \expandafter\thesis@blocks@logo\expandafter{\@path}{#1}}}
```

`\thesis@blocks@facultyLogo@color` The `\thesis@blocks@facultyLogo@color[<options>]` macro typesets either the `\thesis@logopath\thesis@facultyLogo` logo, if the `\ifthesis@color@` conditional is false, or the `\thesis@logopath\thesis@facultyLogo-color` logo otherwise with the given *options* passed to `\includegraphics`.

```
1591 \newcommand{\thesis@blocks@facultyLogo@color}[1]{%
1592   [scale=0.95]{{%
1593     \edef\@path{\thesis@logopath\thesis@facultyLogo
1594       \ifthesis@color@-color\fi}%
1595     \expandafter\thesis@blocks@logo\expandafter{\@path}{#1}}}
```

`\thesis@blocks@universityLogo@monochrome` The `\thesis@blocks@universityLogo@monochrome[<options>]` macro typesets the `\thesis@logopath\thesis@universityLogo` logo with the given *options* passed to `\includegraphics`.

```
1596 \newcommand{\thesis@blocks@universityLogo@monochrome}[1]{%
```

```

1597 [scale=0.9]{%
1598   \edef\@path{\thesis@logopath\thesis@universityLogo}%
1599   \expandafter\thesis@blocks@logo\expandafter{\@path}{#1}}

```

`\thesis@blocks@universityLogo@color` The `\thesis@blocks@universityLogo@color` [*options*] macro typesets either the `\thesis@logopath\thesis@universityLogo` logo, if the `\ifthesis@color@` conditional is false, or the `\thesis@logopath\thesis@universityLogo-color` logo otherwise with the given *options* passed to `\includegraphics`.

```

1600 \newcommand{\thesis@blocks@universityLogo@color}[1]%
1601 [scale=0.9]{%
1602   \edef\@path{\thesis@logopath\thesis@universityLogo
1603     \ifthesis@color@-color\fi}%
1604   \expandafter\thesis@blocks@logo\expandafter{\@path}{#1}}

```

The `\thesis@department@name` and `\thesis@field@name` macros and their English counterparts provide a level of indirection that allows the subsequently loaded style files to parse the values of `\thesis@department` and `\thesis@field` (and their English counterparts) and map them to human-readable names, which will then be typeset.

```

1605 \let\thesis@department@name\thesis@department
1606 \let\thesis@departmentEn@name\thesis@departmentEn
1607 \let\thesis@field@name\thesis@field
1608 \let\thesis@fieldEn@name\thesis@fieldEn

```

`\thesis@blocks@cover` The `\thesis@blocks@cover` macro typesets the thesis cover.

```

1609 \def\thesis@blocks@cover{%
1610   \ifthesis@cover@
1611     \thesis@blocks@clear
1612     \begin{alwaysingle}%
1613       \colorlet{thesis@color@secondary}{black}%
1614       \thispagestyle{empty}%
1615       \begin{center}%
1616         \thesis@blocks@universityLogo@monochrome\par
1617         \vspace{0.75cm}%
1618         {\sf\thesis@titlePage@large\thesis@@upper{facultyName}\par}%
1619         \vfill
1620         {\bf\thesis@titlePage@Huge\thesis@TeXtitle\par}%
1621         \vspace{1.5cm}%
1622         {\sf\thesis@titlePage@Large\thesis@@@{typeName}\par}%
1623         \vspace{1.5cm}%
1624         {\sf\thesis@titlePage@LARGE\thesis@upper{author}\par}%
1625         \vfill\vfill\vfill\vfill
1626         {\sf\thesis@titlePage@large\thesis@place, \thesis@@{semester}\par}%
1627       \end{center}%
1628     \end{alwaysingle}%
1629   \fi}

```

`\thesis@blocks@advisorSignature` The `\thesis@blocks@advisorSignature` macro produces space for the thesis advisor's signature.

```

1630 \def\thesis@blocks@advisorSignature{%
1631   \let\@A\relax\newlength{\@A}
1632   \settowidth{\@A}{\thesis@{advisorSignature}}
1633   \setlength{\@A}{\@A+1cm}
1634   \hfill\raisebox{-0.5em}{\parbox{\@A}{
1635     \centering
1636     \rule{\@A}{1pt}}\
1637   \thesis@{advisorSignature}
1638   }}%

```

`\thesis@blocks@titlePage` The `\thesis@blocks@titlePage` macro typesets the thesis title page. The output of the `\thesis@blocks@titlePage` macro is controlled by the following conditionals:

1. `\ifthesis@blocks@titlePage@department@` – This conditional expression determines, whether the department name is going to be included in the title page. The default value of this conditional is true.
2. `\ifthesis@blocks@titlePage@field@` – This conditional expression determines, whether the field of study is going to be included in the title page. The default value of this conditional is true.
3. `\ifthesis@blocks@titlePage@programme@` – This conditional expression determines, whether the study programme is going to be included in the title page. The default value of this conditional is false.

The subsequently loaded style files can modify the value of these conditionals to alter the output of the `\thesis@blocks@titlePage` macro without altering its definition.

```

1639 \newif\ifthesis@blocks@titlePage@department@
1640 \thesis@blocks@titlePage@department@true
1641 \newif\ifthesis@blocks@titlePage@field@
1642 \thesis@blocks@titlePage@field@true
1643 \newif\ifthesis@blocks@titlePage@programme@
1644 \thesis@blocks@titlePage@programme@true
1645
1646 \def\thesis@blocks@titlePage{%
1647   \thesis@blocks@clear
1648   \begin{alwaysingle}%
1649     \thispagestyle{empty}%
1650     \begin{center}%
1651       \thesis@blocks@universityLogo@color
1652       \par\vspace{0.75cm}%
1653       {\sf\thesis@titlePage@large\thesis@upper{facultyName}\par}%
1654       \vfill
1655       {\bf\thesis@titlePage@Huge\thesis@TeXtitle\par}%
1656       \vspace{1.5cm}%
1657       {\sf\thesis@titlePage@Large\thesis@{typeName}\par}%
1658       \vspace{1.5cm}%
1659       {\sf\thesis@titlePage@LARGE\thesis@upper{author}\par}%

```



```

1660     \vfill\vfill
1661     {\sf\thesis@titlePage@large\thesis@{advisorTitle}: \thesis@advisor\par}%
1662     \vspace{0.75cm}%
1663     \ifthesis@blocks@titlePage@department@
1664     {\sf\thesis@titlePage@large\thesis@department@name\par}%
1665     \fi
1666     \ifthesis@blocks@titlePage@programme@
1667     \vspace{0.25cm}%
1668     {\sf\thesis@titlePage@large\thesis@{bib@programme}: \thesis@programme\par}%
1669     \fi
1670     \ifthesis@blocks@titlePage@field@
1671     \vspace{0.25cm}%
1672     {\sf\thesis@titlePage@large\thesis@{fieldTitle}: \thesis@field@name\par}%
1673     \fi
1674     \vfill
1675     {\sf\thesis@titlePage@large\thesis@place, \thesis@{semester}}%

```

If this is a rigorous thesis or a PhD thesis proposal, create space for the advisor's signature.

```

1676     \ifx\thesis@type\thesis@rigorous
1677     \thesis@blocks@advisorSignature
1678     \else\ifx\thesis@type\thesis@proposal
1679     \thesis@blocks@advisorSignature
1680     \fi\fi\par}%
1681 \end{center}%
1682 \end{alwaysssingle}}

```

`\thesis@blocks@seal` The `\thesis@blocks@seal` macro typesets the seal of a faculty.

```

1683 \def\thesis@blocks@seal{%
1684 \thesis@blocks@clear
1685 \begin{alwaysssingle}%
1686 \thispagestyle{empty}%
1687 \begin{center}%
1688 \leavevmode
1689 \par\vfill
1690 \thesis@blocks@facultyLogo@color
1691 \par\vfill\vfill\vfill\vfill
1692 \end{center}%
1693 \end{alwaysssingle}}

```

`\thesis@blocks@toc` The `\thesis@blocks@toc` macro typesets the table of contents.

```

1694 \def\thesis@blocks@toc{%
1695 \thesis@blocks@clear
1696 \tableofcontents}

```

`\thesis@blocks@tables` The `\thesis@blocks@tables` macro typesets the table of contents and optionally the list of tables and the list of figures.

```

1697 \def\thesis@blocks@tables{%
1698 \thesis@blocks@toc
1699 \thesis@blocks@lot

```

```

1700 \thesis@blocks@lof}

\thesis@blocks@declaration The \thesis@blocks@declaration macro typesets the declaration text.
1701 \def\thesis@blocks@declaration{%
1702 \thesis@blocks@clear
1703 \begin{alwaysssingle}%
1704 \chapter*{\thesis@{@{declarationTitle}}}%
1705 \thesis@declaration
1706 \vskip 2cm%
1707 \hfill\thesis@author
1708 \end{alwaysssingle}}

\thesis@blocks@thanks The \thesis@blocks@thanks macro typesets the acknowledgements, if the
\thesis@thanks macro is defined. Otherwise, the macro produces no output.
1709 \def\thesis@blocks@thanks{%
1710 \ifx\thesis@thanks\undefined\else
1711 \thesis@blocks@clear
1712 \begin{alwaysssingle}%
1713 \chapter*{\vspace*{\fill}\thesis@{@{thanksTitle}}}%
1714 \leavevmode\thesis@thanks
1715 \end{alwaysssingle}%
1716 \fi}

\thesis@blocks@abstract The \thesis@blocks@abstract macro typesets the abstract.
1717 \def\thesis@blocks@abstract{%
1718 \begin{alwaysssingle}%
1719 \vskip 40 \p@
1720 {\let\thesis@blocks@clear\relax
1721 \chapter*{\thesis@{@{abstractTitle}}}%
1722 \noindent\thesis@abstract
1723 \par\vfil\null
1724 \end{alwaysssingle}}

\thesis@blocks@abstractEn The \thesis@blocks@abstractEn macro typesets the abstract in English. If the
current locale is English, the macro produces no output.
1725 \def\thesis@blocks@abstractEn{%
1726 \ifthesis@english\else
1727 {\thesis@selectLocale{english}%
1728 \begin{alwaysssingle}%
1729 \vskip 40 \p@
1730 {\let\thesis@blocks@clear\relax
1731 \chapter*{\thesis@english@abstractTitle}}%
1732 \noindent\thesis@abstractEn
1733 \par\vfil\null
1734 \end{alwaysssingle}}%
1735 \fi}

\thesis@blocks@keywords The \thesis@blocks@keywords macro typesets the keywords.
1736 \def\thesis@blocks@keywords{%

```

```

1737 \begin{alwaysssingle}%
1738   {\let\thesis@blocks@clear\relax%
1739   \chapter*{\vspace*{\fill}}\thesis@{@{keywordsTitle}}}%
1740   \noindent\leavevmode\thesis@keywords
1741 \end{alwaysssingle}}

```

`\thesis@blocks@keywordsEn` The `\thesis@blocks@keywordsEn` macro typesets the keywords in English. If the current locale is English, the macro produces no output.

```

1742 \def\thesis@blocks@keywordsEn{%
1743   \ifthesis@english\else
1744     {\thesis@selectLocale{english}%
1745     \begin{alwaysssingle}%
1746       {\let\thesis@blocks@clear\relax%
1747       \chapter*{\vspace*{\fill}}\thesis@english@keywordsTitle}}%
1748     \noindent\leavevmode\thesis@keywordsEn
1749   \end{alwaysssingle}}%
1750 \fi}

```

`\thesis@rewind` The `\thesis@rewind` macro rewinds the page numbers by either one or two pages, depending on whether one-side or two-side typesetting is enabled, respectively.

```

1751 \def\thesis@rewind{%
1752   \addtocounter{page}{-\ifthesis@twoside@2\else1\fi}}

```

`\thesis@blocks@assignment` The `\thesis@blocks@assignment` macro produces a different output depending on the values of the `\thesis@assignmentFiles`, `\ifthesis@blocks@assignment@`, `\ifthesis@blocks@assignment@hideIfDigital@`, and `\ifthesis@digital` macros.

`\ifthesis@blocks@assignment@` The default value of the `\ifthesis@blocks@assignment@` and `\ifthesis@blocks@assignment@hideIfDigital@` macros is true.

```

1753 \newif\ifthesis@blocks@assignment@
1754 \thesis@blocks@assignment@true
1755 \newif\ifthesis@blocks@assignment@hideIfDigital@
1756 \thesis@blocks@assignment@hideIfDigital@true
1757 \def\thesis@blocks@assignment{%

```

If the `\ifthesis@blocks@assignment@` conditional is true and the `\thesis@assignmentFiles` macro is undefined, then typeset a placeholder page.

```

1758   \ifthesis@blocks@assignment@
1759     \ifx\thesis@assignmentFiles\undefined
1760       % Rewind the pages and typeset a placeholder page.
1761       \thesis@blocks@clear
1762       \begin{alwaysssingle}%
1763         \thispagestyle{empty}\thesis@rewind
1764         \noindent\textit{\thesis@{@{assignment}}}%
1765       \end{alwaysssingle}%
1766     \else

```

`\@inject` Locally define `\@inject` as our routine for injecting lists of PDF documents.

```

1767   {\edef\@pdfList{\thesis@assignmentFiles}%
1768   \let\ea\expandafter

```

```

1769 % Injects the specified PDF documents.
1770 \def\@inject##1,{\thesis@blocks@clear
1771 \def\@args{##1}\def\@relax{\relax}%
1772 \ifx\@args\@relax\else
1773 % Trim leading spaces.
1774 \edef\@trimmed{\romannumeral-'\.##1}%
1775 % Rewind the pages and include the PDF.
1776 \thesis@rewind\includepdf[pages=-]\@trimmed
1777 \ea\@inject\fi}%

```

If the `\ifthesis@blocks@assignment@conditional` is true and the `\thesis@assignmentFiles` macro is neither undefined nor empty, then typeset a placeholder page, if the `\ifthesis@digital@conditional` is true and the `\ifthesis@blocks@assignment@hideIfDigital@conditional` is true

```

1778 \ifx\@pdfList\empty\else
1779 \ifthesis@digital@
1780 \ifthesis@blocks@assignment@hideIfDigital@
1781 \thesis@blocks@clear
1782 \begin{alwaysssingle}%
1783 \thispagestyle{empty}\thesis@rewind
1784 \noindent\textit{\thesis@{@assignment}}%
1785 \end{alwaysssingle}%

```

If the `\ifthesis@blocks@assignment@conditional` is true and the `\thesis@assignmentFiles` macro is neither undefined nor empty, then inject the PDF documents specified in the `\thesis@assignmentFiles`, if the `\ifthesis@digital@conditional` is false or the `\ifthesis@blocks@assignment@hideIfDigital@conditional` is false.

```

1786 \else
1787 \ea\@inject\@pdfList,\relax,%
1788 \fi
1789 \else
1790 \ea\@inject\@pdfList,\relax,%
1791 \fi
1792 \fi}%
1793 \fi
1794 \fi}

```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis.

```

1795 \def\thesis@blocks@mainMatter{%
1796 \thesis@blocks@clear
1797 \setcounter{page}{1}
1798 \pagenumbering{arabic}
1799 \pagestyle{thesisheadings}
1800 \parindent 1.5em\relax}

```

`\thesis@blocks@bibEntry` The `\thesis@blocks@bibEntry` macro typesets a bibliographical entry. Along with the macros required by the locale file interface, the *locale* files need to define the following strings:

- `bib@title` – The title of the entire block
- `bib@pages` – The abbreviation of pages used in the bibliographical entry

```

1801 \def\thesis@blocks@bibEntry{%
1802   \thesis@blocks@clear
1803   \chapter*{\thesis@{bib@title}}
1804   {% Calculate the width of the columns
1805     \let\@A\relax\newlength{\@A}\settowidth{\@A}{%
1806       \bf\thesis@{bib@author}:}
1807     \let\@B\relax\newlength{\@B}\settowidth{\@B}{%
1808       \bf\thesis@{bib@thesisTitle}:}
1809     \let\@C\relax\newlength{\@C}\settowidth{\@C}{%
1810       \bf\thesis@{bib@programme}:}
1811     \let\@D\relax\newlength{\@D}\settowidth{\@D}{%
1812       \bf\thesis@{bib@field}:}
1813     \let\@E\relax\newlength{\@E}
1814       \settowidth{\@E}{\bf\thesis@{bib@advisor}:}
1815     \let\@F\relax\newlength{\@F}\settowidth{\@F}{%
1816       \bf\thesis@{bib@academicYear}:}
1817     \let\@G\relax\newlength{\@G}\settowidth{\@G}{%
1818       \bf\thesis@{bib@pages}:}
1819     \let\@H\relax\newlength{\@H}\settowidth{\@H}{%
1820       \bf\thesis@{bib@keywords}:}
1821     \let\@skip\relax\newlength{\@skip}\setlength{\@skip}{16pt}
1822     \let\@left\relax\newlength{\@left}\pgfmathsetlength{\@left}{%
1823       max(\@A,\@B,\@C,\@D,\@E,\@F,\@G,\@H)}
1824     \let\@right\relax\newlength{\@right}\setlength{\@right}{%
1825       \textwidth-\@left-\@skip}
1826     % Typeset the table
1827     \noindent\begin{thesis@newtable@old}%
1828       {@}p{\@left}@{\hskip\@skip}p{\@right}@{}
1829       \textbf{\thesis@{bib@author}}%
1830       \ifthesis@english\else\ifthesis@woman ka\fi\fi:} &
1831         \noindent\parbox[t]{\@right}{
1832           \thesis@author\\
1833           \thesis@{facultyName} \\
1834           \thesis@{universityName}\\
1835           \thesis@department@name
1836         }\\
1837       \textbf{\thesis@{bib@thesisTitle}:}
1838       & \thesis@title \\
1839       \textbf{\thesis@{bib@programme}:}
1840       & \thesis@programme \\
1841       \textbf{\thesis@{bib@field}:}
1842       & \thesis@field \\
1843       \textbf{\thesis@{bib@advisor}:}
1844       & \thesis@advisor \\
1845       \textbf{\thesis@{bib@academicYear}:}
1846       & \thesis@academicYear \\

```

```

1847 \textbf{\thesis@{bib@pages}:}
1848 & \thesis@pages@preamble{} + \thesis@pages \
1849 \textbf{\thesis@{bib@keywords}:}
1850 & \thesis@TeXkeywords \
1851 \end{thesis@newtable@old}}
1852
1853 \def\thesis@blocks@bibEntryEn{%
1854 \ifthesis@english\else
1855 \thesis@blocks@clear
1856 \chapter*{\thesis@english@bib@title}
1857 {% Calculate the width of the columns
1858 \let\@A\relax\newlength{\@A}\settowidth{\@A}{%
1859 \bf\thesis@english@bib@author:}}
1860 \let\@B\relax\newlength{\@B}\settowidth{\@B}{%
1861 \bf\thesis@english@bib@thesisTitle:}}
1862 \let\@C\relax\newlength{\@C}\settowidth{\@C}{%
1863 \bf\thesis@english@bib@programme:}}
1864 \let\@D\relax\newlength{\@D}\settowidth{\@D}{%
1865 \bf\thesis@english@bib@field:}}
1866 \let\@E\relax\newlength{\@E}
1867 \settowidth{\@E}{\bf\thesis@english@bib@advisor:}}
1868 \let\@F\relax\newlength{\@F}\settowidth{\@F}{%
1869 \bf\thesis@english@bib@academicYear:}}
1870 \let\@G\relax\newlength{\@G}\settowidth{\@G}{%
1871 \bf\thesis@english@bib@pages:}}
1872 \let\@H\relax\newlength{\@H}\settowidth{\@H}{%
1873 \bf\thesis@english@bib@keywords:}}
1874 \let\@skip\relax\newlength{\@skip}\setlength{\@skip}{16pt}
1875 \let\@left\relax\newlength{\@left}\pgfmathsetlength{\@left}{%
1876 max(\@A,\@B,\@C,\@D,\@E,\@F,\@G,\@H)}
1877 \let\@right\relax\newlength{\@right}\setlength{\@right}{%
1878 \textwidth-\@left-\@skip}
1879 % Typeset the table
1880 \noindent\begin{thesis@newtable@old}%
1881 {@\}p{\@left}{\hskip\@skip}p{\@right}{@{}}
1882 \textbf{\thesis@english@authorTitle:} &
1883 \noindent\parbox[t]{\@right}{
1884 \thesis@author\
1885 \thesis@english@facultyName \
1886 \thesis@english@universityName\
1887 \thesis@departmentEn@name
1888 }\\
1889 \textbf{\thesis@english@bib@thesisTitle:}
1890 & \thesis@titleEn \
1891 \textbf{\thesis@english@bib@programme:}
1892 & \thesis@programmeEn \
1893 \textbf{\thesis@english@bib@field:}
1894 & \thesis@fieldEn \
1895 \textbf{\thesis@english@bib@advisor:}
1896 & \thesis@advisor \

```

```

1897 \textbf{\thesis@english@bib@academicYear:}
1898 & \thesis@academicYear \\
1899 \textbf{\thesis@english@bib@pages:}
1900 & \thesis@pages@preamble{} + \thesis@pages \\
1901 \textbf{\thesis@english@bib@keywords:}
1902 & \thesis@TeXkeywordsEn \\
1903 \end{thesis@newtable@old}}
1904 \fi}

```

`\thesis@blocks@bibliography` When `\ifthesis@bibliography@loaded@` is true and `\ifthesis@bibliography@included@` false, then the `\thesis@blocks@bibliography` macro typesets a bibliography via the Bib \LaTeX package. Otherwise, this macro produces no output.

```

1905 \def\thesis@blocks@bibliography{%
1906 \ifthesis@bibliography@loaded@
1907 \ifthesis@bibliography@included@%else
1908 \thesis@blocks@clear
1909 {\emergencystretch=3em%
1910 \printbibliography[heading=bibintoc]}%
1911 \fi
1912 \fi}

```

The rest of the file comprises redefinitions of \LaTeX commands and private `rapport3` class macros altering the layout of the resulting document. Depending on the type size of 10, 11 or 12 points, either the `fithesis-mu-10.clo`, `fithesis-mu-11.clo` or `fithesis-mu-12.clo` file is loaded from the `\thesis@stylepath mu` directory, respectively.

```

1913% Table of contents will contain sectioning commands up to
1914% \subsection.
1915\setcounter{tocdepth}{2}
1916
1917% Sections up to \subsection will be numbered.
1918\setcounter{secnumdepth}{2}
1919
1920% Load the 'fithesis-mu-1*.clo' size option.
1921\input\thesis@stylepath mu/fithesis-mu-1\thesis@ptsize.clo\relax
1922
1923% Define the running heading style.
1924\def\ps@thesisheadings{%
1925 \def\chaptermark##1{%
1926 \markright{%
1927 \ifnum\c@secnumdepth >\m@ne
1928 \thechapter.\ %
1929 \fi ##1}}
1930 \let\@oddfoot\@empty
1931 \let\@oddhead\@empty
1932 \def\@oddhead{%
1933 \vbox{%
1934 \hbox to \textwidth{%

```

```

1935     \hfil{\sc\rightmark}}%
1936     \vskip 4pt\hrule}}
1937 \if@twoside
1938   \def\@evenhead{%
1939     \vbox{%
1940       \hbox to \textwidth{%
1941         {\sc\rightmark}%
1942         \hfil}
1943       \vskip 4pt\hrule}}
1944 \else
1945   \let\@evenhead\@oddhead
1946 \fi
1947 \def\@oddfoot{\hfil\PageFont\thepage}
1948 \if@twoside
1949   \def\@evenfoot{\PageFont\thepage\hfil}%
1950 \else
1951   \let\@evenfoot\@oddfoot
1952 \fi
1953 \let\@mkboth\markboth}

1954 \let\ps@headings\ps@thesisheadings
1955 \let\ps@myheadings\ps@thesisheadings
1956
1957 % Redefine the style of the chapter headings.
1958 \renewcommand*\chapter{%
1959   \thesis@blocks@clear
1960   \thispagestyle{plain}%
1961   \global\@topnum\z@
1962   \@afterindentfalse
1963   \secdef\@chapter\@schapter}
1964
1965 % Redefine the style of part headings.
1966 \renewcommand*\part{%
1967   \thesis@blocks@clear
1968   \if@twocolumn
1969     \onecolumn
1970     \@tempwattrue
1971   \else
1972     \@tempwafalse
1973   \fi
1974   \hbox{}}\vfil
1975   \secdef\@part\@spart}
1976
1977 % A macro for temporary multicol -> singlecol switching.
1978 \newif\if@restonecol
1979 \def\alwaysingle{%
1980   \@restonecolfalse\if@twocolumn\@restonecoltrue\onecolumn\fi}
1981 \def\endalwaysingle{\if@restonecol\twocolumn\fi}
1982
1983 % Disable uppercasing in PDF strings.

```



```

1984 \pdfstringdefDisableCommands{%
1985   \let\MakeUppercase\relax}
1986
1987 % Set up the ToC entries appearance.
1988 \renewcommand*\toc@font[1]{%
1989   \ifcase #1\relax
1990     \bfseries % \chapter (0)
1991   \or
1992     \slshape % \section (1)
1993   \else
1994     \rmfamily % \subsection (2), \subsubsection (3)
1995               % \paragraph, \subparagraph (4)
1996   \fi}
1997
1998 % Set up the table of contents entries for sectioning commands.
1999 \renewcommand*\l@part[2]{%
2000   \ifnum \c@tocdepth >-2\relax
2001     \addpenalty{-\@highpenalty}%
2002     \ifnum \c@tocdepth >0\relax
2003       \addvspace{2.25em \@plus\p@}%
2004     \else
2005       \addvspace{1.0em \@plus\p@}%
2006     \fi
2007     \begingroup
2008       \setlength\@tempdima{3em}%
2009       \parindent \z@ \rightskip \@pnumwidth
2010       \parfillskip -\@pnumwidth
2011       {\leavevmode
2012        \normalfont \bfseries #1\hfil \hb@xt@\@pnumwidth{\hss #2}}\par
2013       \nobreak
2014       \global\@nobreaktrue
2015       \everypar{\global\@nobreakfalse\everypar{}}%
2016     \endgroup
2017   \fi}
2018
2019 \renewcommand*\l@chapter[2]{%
2020   \ifnum \c@tocdepth >0\relax
2021     \addpenalty{-\@highpenalty}%
2022     \addvspace{1.0em \@plus\p@}%
2023     \setlength\@tempdima{1.5em}%
2024     \begingroup
2025       \parindent \z@ \rightskip \@pnumwidth
2026       \parfillskip -\@pnumwidth
2027       \leavevmode \bfseries
2028       \advance\leftskip\@tempdima
2029       \hskip -\leftskip
2030       #1\nobreak\hfil \nobreak\hb@xt@\@pnumwidth{\hss #2}\par
2031       \penalty\@highpenalty
2032     \endgroup
2033   \else

```

```

2034 \dottedtocline{0}{0em}{1.5em}{#1}{#2}
2035 \fi}
2036
2037 \renewcommand*\l@section{\dottedtocline{1}{1.5em}{2.3em}}
2038 \renewcommand*\l@subsection{\dottedtocline{2}{3.8em}{3.2em}}
2039 \renewcommand*\l@subsubsection{\dottedtocline{3}{7.0em}{4.1em}}
2040 \renewcommand*\l@paragraph{\dottedtocline{4}{10.0em}{5.0em}}
2041 \renewcommand*\l@subparagraph{\dottedtocline{4}{12.0em}{6.0em}}

2042 \renewcommand*\l@figure{\dottedtocline{1}{0.5em}{2.3em}}
2043 \renewcommand*\l@table{\dottedtocline{1}{0.5em}{2.3em}}

```

3.5.2.3 The style/mu/fithesis-10.clo file

This file is conditionally loaded by the style/mu/base.sty file to redefine the page geometry to match the type size of 10 points.

```

2044 <*opt>
2045 <*10pt>
2046 \ProvidesFile{fithesis/style/mu/fithesis-mu-10.clo}[2021/02/21]
2047
2048 \renewcommand{\normalsize}{\fontsize\@xpt{12}\selectfont
2049 \abovedisplayskip 10\p@ plus2\p@ minus5\p@
2050 \belowdisplayskip \abovedisplayskip
2051 \abovedisplayshortskip \z@ plus3\p@
2052 \belowdisplayshortskip 6\p@ plus3\p@ minus3\p@
2053 \let\@listi\@listI}
2054
2055 \renewcommand{\small}{\fontsize\@ixpt{11}\selectfont
2056 \abovedisplayskip 8.5\p@ plus3\p@ minus4\p@
2057 \belowdisplayskip \abovedisplayskip
2058 \abovedisplayshortskip \z@ plus2\p@
2059 \belowdisplayshortskip 4\p@ plus2\p@ minus2\p@
2060 \def\@listi{\leftmargin\leftmargini
2061 \topsep 4\p@ plus2\p@ minus2\p@\parsep 2\p@ plus\p@ minus\p@
2062 \itemsep \parsep}}
2063
2064 \renewcommand{\footnotesize}{\fontsize\@viipt{9.5}\selectfont
2065 \abovedisplayskip 6\p@ plus2\p@ minus4\p@
2066 \belowdisplayskip \abovedisplayskip
2067 \abovedisplayshortskip \z@ plus\p@
2068 \belowdisplayshortskip 3\p@ plus\p@ minus2\p@
2069 \def\@listi{\leftmargin\leftmargini %% Added 22 Dec 87
2070 \topsep 3\p@ plus\p@ minus\p@\parsep 2\p@ plus\p@ minus\p@
2071 \itemsep \parsep}}
2072
2073 \renewcommand{\scriptsize}{\fontsize\@viipt{8pt}\selectfont}
2074 \renewcommand{\tiny}{\fontsize\@vpt{6pt}\selectfont}
2075 \renewcommand{\large}{\fontsize\@xiipt{14pt}\selectfont}
2076 \renewcommand{\Large}{\fontsize\@xivpt{18pt}\selectfont}
2077 \renewcommand{\LARGE}{\fontsize\@xviipt{22pt}\selectfont}

```

```

2078 \renewcommand{\huge}{\fontsize\@xxpt{25pt}\selectfont}
2079 \renewcommand{\Huge}{\fontsize\@xxvpt{30pt}\selectfont}
2080
2081 </10pt>

```

3.5.2.4 The style/mu/fithesis-11.clo file

This file is conditionally loaded by the style/mu/base.sty file to redefine the page geometry to match the type size of 11 points.

```

2082 (*11pt)
2083 \ProvidesFile{fithesis/style/mu/fithesis-mu-11.clo}[2021/02/21]
2084
2085 \renewcommand{\normalsize}{\fontsize\@xipt{14}\selectfont}
2086 \abovedisplayskip 11\p@ plus3\p@ minus6\p@
2087 \belowdisplayskip \abovedisplayskip
2088 \belowdisplayshortskip 6.5\p@ plus3.5\p@ minus3\p@
2089 % \abovedisplayshortskip \z@ plus3\p@
2090 \let\@listi\@listI}
2091
2092 \renewcommand{\small}{\fontsize\@xpt{12}\selectfont}
2093 \abovedisplayskip 10\p@ plus2\p@ minus5\p@
2094 \belowdisplayskip \abovedisplayskip
2095 \abovedisplayshortskip \z@ plus3\p@
2096 \belowdisplayshortskip 6\p@ plus3\p@ minus3\p@
2097 \def\@listi{\leftmargin\leftmargini
2098 \topsep 6\p@ plus2\p@ minus2\p@\parsep 3\p@ plus2\p@ minus\p@
2099 \itemsep \parsep}}
2100
2101 \renewcommand{\footnotesize}{\fontsize\@ixpt{11}\selectfont}
2102 \abovedisplayskip 8\p@ plus2\p@ minus4\p@
2103 \belowdisplayskip \abovedisplayskip
2104 \abovedisplayshortskip \z@ plus\p@
2105 \belowdisplayshortskip 4\p@ plus2\p@ minus2\p@
2106 \def\@listi{\leftmargin\leftmargini
2107 \topsep 4\p@ plus2\p@ minus2\p@\parsep 2\p@ plus\p@ minus\p@
2108 \itemsep \parsep}}
2109
2110 \renewcommand{\scriptsize}{\fontsize\@viiipt{9.5pt}\selectfont}
2111 \renewcommand{\tiny}{\fontsize\@vipt{7pt}\selectfont}
2112 \renewcommand{\large}{\fontsize\@xipt{14pt}\selectfont}
2113 \renewcommand{\Large}{\fontsize\@xivpt{18pt}\selectfont}
2114 \renewcommand{\LARGE}{\fontsize\@xviipt{22pt}\selectfont}
2115 \renewcommand{\huge}{\fontsize\@xxpt{25pt}\selectfont}
2116 \renewcommand{\Huge}{\fontsize\@xxvpt{30pt}\selectfont}
2117
2118 </11pt>

```

3.5.2.5 The style/mu/fithesis-12.clo file

This file is conditionally loaded by the style/mu/base.sty file to redefine the page geometry to match the type size of 12 points. The type dimensions defined by the file are stored in the following macros as well:

<code>\thesis@titlePage@normalsize</code>	• <code>\thesis@titlePage@normalsize</code> – Equivalent to <code>\normalsize</code>
<code>\thesis@titlePage@small</code>	• <code>\thesis@titlePage@small</code> – Equivalent to <code>\small</code>
<code>\thesis@titlePage@footnotesize</code>	• <code>\thesis@titlePage@footnotesize</code> – Equivalent to <code>\footnotesize</code>
<code>\thesis@titlePage@scriptsize</code>	• <code>\thesis@titlePage@scriptsize</code> – Equivalent to <code>\scriptsize</code>
<code>\thesis@titlePage@tiny</code>	• <code>\thesis@titlePage@tiny</code> – Equivalent to <code>\tiny</code>
<code>\thesis@titlePage@large</code>	• <code>\thesis@titlePage@large</code> – Equivalent to <code>\large</code>
<code>\thesis@titlePage@Large</code>	• <code>\thesis@titlePage@Large</code> – Equivalent to <code>\Large</code>
<code>\thesis@titlePage@LARGE</code>	• <code>\thesis@titlePage@LARGE</code> – Equivalent to <code>\LARGE</code>
<code>\thesis@titlePage@huge</code>	• <code>\thesis@titlePage@huge</code> – Equivalent to <code>\huge</code>
<code>\thesis@titlePage@Huge</code>	• <code>\thesis@titlePage@Huge</code> – Equivalent to <code>\Huge</code>

These macros can be used to typeset elements whose size should remain constant regardless of the font size setting.

```
2119 (*12pt)
2120 \ProvidesFile{fithesis/style/mu/fithesis-mu-12.clo}[2021/02/21]
2121 (/12pt)
2122
2123 \def\thesis@titlePage@normalsize{\fontsize\@xipt{14.5}%
2124 \selectfont\abovedisplayskip 12\p@ plus3\p@ minus7\p@
2125 \belowdisplayskip \abovedisplayskip
2126 \abovedisplayshortskip \z@ plus3\p@
2127 \belowdisplayshortskip 6.5\p@ plus3.5\p@ minus3\p@
2128 \let\@listi\@listI}
2129
2130 \def\thesis@titlePage@small{\fontsize\@xipt{13.6}\selectfont
2131 \abovedisplayskip 11\p@ plus3\p@ minus6\p@
2132 \belowdisplayskip \abovedisplayskip
2133 \abovedisplayshortskip \z@ plus3\p@
2134 \belowdisplayshortskip 6.5\p@ plus3.5\p@ minus3\p@
2135 \def\@listi{\leftmargin\leftmarginI %% Added 22 Dec 87
2136 \parsep 4.5\p@ plus2\p@ minus\p@
2137 \itemsep \parsep
2138 \topsep 9\p@ plus3\p@ minus5\p@}}
2139
2140 \def\thesis@titlePage@footnotesize{\fontsize\@xpt{12}\selectfont
2141 \abovedisplayskip 10\p@ plus2\p@ minus5\p@
2142 \belowdisplayskip \abovedisplayskip
```

```

2143 \abovedisplayshortskip \z@ plus3\p@
2144 \belowdisplayshortskip 6\p@ plus3\p@ minus3\p@
2145 \def\@listi{\leftmargin\leftmargin % Added 22 Dec 87
2146 \topsep 6\p@ plus2\p@ minus2\p@\parsep 3\p@ plus2\p@ minus\p@
2147 \itemsep \parsep}}
2148
2149 \def\thesis@titlePage@scriptsize{\fontsize\@viipt{9.5pt}\selectfont}
2150 \def\thesis@titlePage@tiny{\fontsize\@viipt{7pt}\selectfont}
2151 \def\thesis@titlePage@large{\fontsize\@xivpt{18pt}\selectfont}
2152 \def\thesis@titlePage@Large{\fontsize\@xxviipt{22pt}\selectfont}
2153 \def\thesis@titlePage@LARGE{\fontsize\@xxxvpt{25pt}\selectfont}
2154 \def\thesis@titlePage@huge{\fontsize\@xxxvpt{30pt}\selectfont}
2155 \def\thesis@titlePage@Huge{\fontsize\@xxxvpt{30pt}\selectfont}
2156
2157 (*12pt)
2158 \renewcommand{\normalsize}{\thesis@titlePage@normalsize}
2159 \renewcommand{\small}{\thesis@titlePage@small}
2160 \renewcommand{\footnotesize}{\thesis@titlePage@footnotesize}
2161 \renewcommand{\scriptsize}{\thesis@titlePage@scriptsize}
2162 \renewcommand{\tiny}{\thesis@titlePage@tiny}
2163 \renewcommand{\large}{\thesis@titlePage@large}
2164 \renewcommand{\Large}{\thesis@titlePage@Large}
2165 \renewcommand{\LARGE}{\thesis@titlePage@LARGE}
2166 \renewcommand{\huge}{\thesis@titlePage@huge}
2167 \renewcommand{\Huge}{\thesis@titlePage@Huge}
2168 (/12pt)
2169 \let\@normalsize\normalsize
2170 \normalsize
2171
2172 \if@twoside
2173 \oddsidemargin 0.75in
2174 \evensidemargin 0.4in
2175 \marginparwidth 0pt
2176 \else
2177 \oddsidemargin 0.75in
2178 \evensidemargin 0.75in
2179 \marginparwidth 0pt
2180 \fi
2181 \marginparsep 10pt
2182
2183 \topmargin 0.4in
2184
2185 \headheight 20pt
2186 \headsep 10pt
2187 \topskip 10pt
2188 \footskip 30pt
2189
2190 (*10pt)
2191 \textheight = 43\baselineskip
2192 \advance\textheight by \topskip

```

2193 \textwidth 5.0truein
2194 \columnsep 10pt
2195 \columnseprule 0pt
2196
2197 \footnotesep 6.65pt
2198 \skip\footins 9pt plus 4pt minus 2pt
2199 \floatsep 12pt plus 2pt minus 2pt
2200 \textfloatsep 20pt plus 2pt minus 4pt
2201 \intextsep 12pt plus 2pt minus 2pt
2202 \dblfloatsep 12pt plus 2pt minus 2pt
2203 \dbltextfloatsep 20pt plus 2pt minus 4pt
2204
2205 \@fptop 0pt plus 1fil
2206 \@fpsep 8pt plus 2fil
2207 \@fpbot 0pt plus 1fil
2208 \@dblftop 0pt plus 1fil
2209 \@dblfpsep 8pt plus 2fil
2210 \@dblfpbot 0pt plus 1fil
2211 \marginparpush 5pt
2212
2213 \parskip 0pt plus 1pt
2214 \partopsep 2pt plus 1pt minus 1pt
2215
2216 (/10pt)
2217 %
2218 (*11pt)
2219 \textheight = 39\baselineskip
2220 \advance\textheight by \topskip
2221 \textwidth 5.0truein
2222 \columnsep 10pt
2223 \columnseprule 0pt
2224
2225 \footnotesep 7.7pt
2226 \skip\footins 10pt plus 4pt minus 2pt
2227 \floatsep 12pt plus 2pt minus 2pt
2228 \textfloatsep 20pt plus 2pt minus 4pt
2229 \intextsep 12pt plus 2pt minus 2pt
2230 \dblfloatsep 12pt plus 2pt minus 2pt
2231 \dbltextfloatsep 20pt plus 2pt minus 4pt
2232
2233 \@fptop 0pt plus 1fil
2234 \@fpsep 8pt plus 2fil
2235 \@fpbot 0pt plus 1fil
2236 \@dblftop 0pt plus 1fil
2237 \@dblfpsep 8pt plus 2fil
2238 \@dblfpbot 0pt plus 1fil
2239 \marginparpush 5pt
2240
2241 \parskip 0pt plus 0pt
2242 \partopsep 3pt plus 1pt minus 2pt

```

2243
2244 (/11pt)
2245 %
2246 (*12pt)
2247 \textheight = 37\baselineskip
2248 \advance\textheight by \topskip
2249 \textwidth 5.0truein
2250 \columnsep 10pt
2251 \columnseprule 0pt
2252
2253 \footnotesep 8.4pt
2254 \skip\footins 10.8pt plus 4pt minus 2pt
2255 \floatsep 14pt plus 2pt minus 4pt
2256 \textfloatsep 20pt plus 2pt minus 4pt
2257 \intextsep 14pt plus 4pt minus 4pt
2258 \dblfloatsep 14pt plus 2pt minus 4pt
2259 \dbltextfloatsep 20pt plus 2pt minus 4pt
2260
2261 \@fptop 0pt plus 1fil
2262 \@fpsep 10pt plus 2fil
2263 \@fpbot 0pt plus 1fil
2264 \@dblftop 0pt plus 1fil
2265 \@dblfpsep 10pt plus 2fil
2266 \@dblfpbot 0pt plus 1fil
2267 \marginparpush 7pt
2268
2269 \parskip 0pt plus 0pt
2270 \partopsep 3pt plus 2pt minus 2pt
2271
2272 (/12pt)
2273 \@lowpenalty 51
2274 \@medpenalty 151
2275 \@highpenalty 301
2276 \@beginparpenalty -\@lowpenalty
2277 \@endparpenalty -\@lowpenalty
2278 \@itempenalty -\@lowpenalty
2279
2280 \def\@makechapterhead#1{%
2281   \setlength\parindent{\z@}%
2282   \setlength\parskip {\z@}%
2283   \Large \ChapFont
2284   \ifnum
2285     \c@secnumdepth >\m@ne
2286     \par\nobreak
2287     \vskip 10\p@
2288     \thechapter{} \space
2289     \fi #1\par
2290     \nobreak
2291     \vskip 20\p@}}
2292

```

```

2293 \def\@makeschapterhead#1{{%
2294 \setlength\parindent{\z@}%
2295 \setlength\parskip {\z@}%
2296 \Large \ChapFont #1\par
2297 \nobreak
2298 \vskip 20\p@}}
2299
2300 \def\chapter{%
2301 \clearpage
2302 \thispagestyle{plain}
2303 \global\@topnum\z@
2304 \@afterindentfalse
2305 \secdef\@chapter\@schapter}
2306
2307 \def\@chapter[#1]#2{%
2308 \ifnum \c@secnumdepth
2309 >\m@ne
2310 \refstepcounter{chapter}%
2311 \typeout{\@chapapp\space\thechapter.}%
2312 \addcontentsline{toc}{chapter}{\protect
2313 \numberline{\thechapter}\bfseries #1}
2314 \else
2315 \addcontentsline{toc}{chapter}{\bfseries #1}
2316 \fi
2317 \chaptermark{#1}%
2318 \addtocontents{lof}%
2319 {\protect\addvspace{4\p@}}
2320 \addtocontents{lot}%
2321 {\protect\addvspace{4\p@}}
2322 \if@twocolumn
2323 \@topnewpage[\@makechapterhead{#2}]%
2324 \else
2325 \@makechapterhead{#2}%
2326 \@afterheading
2327 \fi
2328 }
2329
2330 \def\section{\@startsection{section}{1}{\z@}{%
2331 -3.5ex plus-1ex minus-.2ex}{2.3ex plus.2ex}{%
2332 \reset@font\large\bfseries}}
2333 \def\subsection{\@startsection{subsection}{2}{\z@}{%
2334 -3.25ex plus-1ex minus-.2ex}{1.5ex plus.2ex}{%
2335 \reset@font\normalsize\bfseries}}
2336 \def\subsubsection{\@startsection{subsubsection}{3}{\z@}{%
2337 -3.25ex plus-1ex minus-.2ex}{1.5ex plus.2ex}{%
2338 \reset@font\normalsize}}
2339 \def\paragraph{\@startsection{paragraph}{4}{\z@}{%
2340 3.25ex plus1ex minus.2ex}{-1em}{%
2341 \reset@font\normalsize\bfseries}}
2342 \def\subparagraph{\@startsection{subparagraph}{4}{\parindent}{%

```



```

2343 3.25ex plus1ex minus.2ex}{-1em}{%
2344 \reset@font\normalsize\bfseries}}
2345
2346 \leftmargini 2.5em
2347 \leftmarginii 2.2em % > \labelsep + width of '(m)'
2348 \leftmarginiii 1.87em % > \labelsep + width of 'vii.'
2349 \leftmarginiv 1.7em % > \labelsep + width of 'M.'
2350 \leftmarginv 1em
2351 \leftmarginvi 1em
2352
2353 \leftmargin\leftmargini
2354 \labelsep .5em
2355 \labelwidth\leftmargini\advance\labelwidth-\labelsep
2356
2357 (*10pt)
2358 \def\@listI{\leftmargin\leftmargini \parsep 4\p@ plus2\p@ minus\p@
2359 \topsep 8\p@ plus2\p@ minus4\p@
2360 \itemsep 4\p@ plus2\p@ minus\p@}
2361
2362 \let\@listi\@listI
2363 \@listi
2364
2365 \def\@listii{\leftmargin\leftmarginii
2366 \labelwidth\leftmarginii\advance\labelwidth-\labelsep
2367 \topsep 4\p@ plus2\p@ minus\p@
2368 \parsep 2\p@ plus\p@ minus\p@
2369 \itemsep \parsep}
2370
2371 \def\@listiii{\leftmargin\leftmarginiii
2372 \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
2373 \topsep 2\p@ plus\p@ minus\p@
2374 \parsep \z@ \partopsep\p@ plus\z@ minus\p@
2375 \itemsep \topsep}
2376
2377 \def\@listiv{\leftmargin\leftmarginiv
2378 \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}
2379
2380 \def\@listv{\leftmargin\leftmarginv
2381 \labelwidth\leftmarginv\advance\labelwidth-\labelsep}
2382
2383 \def\@listvi{\leftmargin\leftmarginvi
2384 \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
2385 (/10pt)
2386 %
2387 (*11pt)
2388 \def\@listI{\leftmargin\leftmargini \parsep 4.5\p@ plus2\p@ minus\p@
2389 \topsep 9\p@ plus3\p@ minus5\p@
2390 \itemsep 4.5\p@ plus2\p@ minus\p@}
2391
2392 \let\@listi\@listI

```

```

2393 \@listi
2394
2395 \def\@listii{\leftmargin\leftmarginii
2396 \labelwidth\leftmarginii\advance\labelwidth-\labelsep
2397 \topsep 4.5\p@ plus2\p@ minus\p@
2398 \parsep 2\p@ plus\p@ minus\p@
2399 \itemsep \parsep}
2400
2401 \def\@listiii{\leftmargin\leftmarginiii
2402 \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
2403 \topsep 2\p@ plus\p@ minus\p@
2404 \parsep \z@ \partopsep \p@ plus\z@ minus\p@
2405 \itemsep \topsep}
2406
2407 \def\@listiv{\leftmargin\leftmarginiv
2408 \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}
2409
2410 \def\@listv{\leftmargin\leftmarginv
2411 \labelwidth\leftmarginv\advance\labelwidth-\labelsep}
2412
2413 \def\@listvi{\leftmargin\leftmarginvi
2414 \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
2415 </11pt>
2416 %
2417 (*12pt)
2418 \def\@listI{\leftmargin\leftmarginI \parsep 5\p@ plus2.5\p@ minus\p@
2419 \topsep 10\p@ plus4\p@ minus6\p@
2420 \itemsep 5\p@ plus2.5\p@ minus\p@}
2421
2422 \let\@listi\@listI
2423 \@listi
2424
2425 \def\@listii{\leftmargin\leftmarginii
2426 \labelwidth\leftmarginii\advance\labelwidth-\labelsep
2427 \topsep 5\p@ plus2.5\p@ minus\p@
2428 \parsep 2.5\p@ plus\p@ minus\p@
2429 \itemsep \parsep}
2430
2431 \def\@listiii{\leftmargin\leftmarginiii
2432 \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
2433 \topsep 2.5\p@ plus\p@ minus\p@
2434 \parsep \z@ \partopsep \p@ plus\z@ minus\p@
2435 \itemsep \topsep}
2436
2437 \def\@listiv{\leftmargin\leftmarginiv
2438 \labelwidth\leftmarginiv\advance\labelwidth-\labelsep}
2439
2440 \def\@listv{\leftmargin\leftmarginv
2441 \labelwidth\leftmarginv\advance\labelwidth-\labelsep}
2442

```

```

2443 \def\@listvi{\leftmargin\leftmarginvi
2444 \labelwidth\leftmarginvi\advance\labelwidth-\labelsep}
2445 \langle/12pt\rangle
2446 \langle/opt\rangle

```

3.5.3 The style files of the Faculty of Informatics

3.5.3.1 The style/mu/fithesis-fi.sty file

This is the style file for the theses written at the Faculty of Informatics at the Masaryk University in Brno. It has been prepared in accordance with the faculty directive ¹.

```

2447 \NeedsTeXFormat{LaTeX2e}
2448 \ProvidesPackage{fithesis/style/mu/fithesis-mu-fi}[2021/04/24]

```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```

2449 \thesis@color@setup{
2450   links={HTML}{FFD451},
2451   tableEmph={HTML}{FFD451},
2452   tableOdd={HTML}{FFF9E5},
2453   tableEven={HTML}{FFECB3}}

```

The bibliography support is enabled. The iso-numeric citations are used and the bibliography is sorted in citation order.

```

2454 \thesis@bibliography@setup{
2455   style=iso-numeric,
2456   sorting=none}
2457 \thesis@bibliography@load

```

In case of rigorous and doctoral theses, the style file hides the thesis assignment in accordance with the formal requirements of the faculty.

```

2458 \ifx\thesis@type\thesis@rigorous
2459   \thesis@blocks@assignment@false
2460 \else\ifx\thesis@type\thesis@doctoral
2461   \thesis@blocks@assignment@false
2462 \fi\fi

```

`\thesis@blocks@declaration` The `\thesis@blocks@declaration` macro typesets the declaration text. Compared to the definition within the `style/mu/base.sty` file, this macro also typesets the advisor's name at the bottom of the page.

```

2463 \def\thesis@blocks@declaration{%
2464   \thesis@blocks@clear
2465   \begin{alwaysingle}%
2466     \chapter*{\thesis@{declarationTitle}}%
2467     \thesis@declaration

```

¹See https://is.muni.cz/auth/do/fi/uredni_deska/predpisy/smernice/Smernice_dekana_1_2021_zaverecne_prace.pdf

```

2468 \vskip 2cm%
2469 \hfill\thesis@author
2470 \par\vfill\noindent
2471 \textbf{\thesis@{advisorTitle}:} \thesis@advisor
2472 \par\vfil
2473 \end{alwaysssingle}}

```

```

2474 \thesis@blocks@titlePage@field@false
2475 \thesis@blocks@titlePage@programme@false

```

In Ph.D. theses, only the table of contents will be typeset in the front matter as per the formal requirements of the faculty².

Note that there is no direct support for the seminar paper type. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```

2476 \def\thesis@blocks@preamble{%
2477 \thesis@blocks@coverMatter
2478 \thesis@blocks@cover
2479 \thesis@blocks@frontMatter
2480 \thesis@blocks@titlePage
2481 \thesis@blocks@seal
2482 \ifx\thesis@type\thesis@proposal
2483 \thesis@blocks@toc
2484 \else
2485 \thesis@blocks@declaration
2486 \thesis@blocks@thanks
2487 \thesis@blocks@clear
2488 \thesis@blocks@abstract
2489 \thesis@blocks@keywords
2490 \thesis@blocks@tables
2491 \fi}
2492 \def\thesis@blocks@postamble{%
2493 \thesis@blocks@bibliography}

```

3.5.4 The style files of the Faculty of Science

3.5.4.1 The `style/mu/fithesis-sci.sty` file

This is the style file for the theses written at the Faculty of Science at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty³.

```

2494 \NeedsTeXFormat{LaTeX2e}
2495 \ProvidesPackage{fithesis/style/mu/fithesis-mu-sci}[2021/07/18]

```

²See http://is.muni.cz/www/2575/dtedi/index_en.html

³See https://is.muni.cz/auth/do/sci/normy/OD/OD-2019_3/OD_3_2019_-_Pokyny_pro_vypracovani_bc._dipl._a_rigor.praci.pdf

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```
2496 \thesis@color@setup{
2497   links={HTML}{20E366},
2498   tableEmph={HTML}{8EDEAA},
2499   tableOdd={HTML}{EDF7F1},
2500   tableEven={HTML}{CCEDD8}}
```

The bibliography support is enabled. The iso-numeric citations are used and the bibliography is sorted in citation order.

```
2501 \thesis@bibliography@setup{
2502   style=iso-numeric,
2503   sorting=none}
2504 \thesis@bibliography@load
```

Enable the inclusion of the scanned assignment inside the digital version of the document.

```
2505 \thesis@blocks@titlePage@field@false
2506 \thesis@blocks@titlePage@programme@false
2507
2508 \thesis@blocks@assignment@hideIfDigital@false
```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter front matter of the thesis. The front matter is typeset without any visible numbering, as mandated by the formal requirements of the faculty.

```
2509 \def\thesis@blocks@frontMatter{%
2510   \thesis@blocks@clear
2511   \pagestyle{empty}
2512   \parindent 1.5em
2513   \setcounter{page}{1}
2514   \pagenumbering{arabic}}
```

The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The page numbering doesn't reset at the beginning of the main thesis in accordance with the formal requirements of the faculty.

```
2515 \def\thesis@blocks@mainMatter{%
2516   \thesis@blocks@clear
2517   \pagestyle{thesisheadings}
2518   \parindent 1.5em\relax}
```

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fi/thesis-base.sty` file.

```
2519 \def\thesis@blocks@preamble{
2520   \thesis@blocks@coverMatter
2521   \thesis@blocks@cover
2522   \thesis@blocks@frontMatter
2523   \thesis@blocks@titlePage
2524   \thesis@blocks@seal
2525   \ifx\thesis@type\thesis@proposal
```

```

2526 \thesis@blocks@clear
2527 \pagestyle{plain}
2528 \thesis@blocks@toc
2529 \else
2530 \thesis@blocks@bibEntry
2531 \thesis@blocks@bibEntryEn
2532 \thesis@blocks@clear
2533 \thesis@blocks@abstract
2534 \thesis@blocks@clearRight
2535 \thesis@blocks@abstractEn
2536 \thesis@blocks@assignment
2537 \thesis@blocks@thanks
2538 \thesis@blocks@declaration

2539 \thesis@blocks@clear
2540 \pagestyle{plain}
2541 \thesis@blocks@tables
2542 \fi}
2543 \def\thesis@blocks@postamble{%
2544 \thesis@blocks@bibliography}

```

3.5.5 The style files of the Faculty of Arts

3.5.5.1 The style/mu/fithesis-phil.sty file

This is the style file for the theses written at the Faculty of Arts at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the department of Slavonic Studies⁴.

```

2545 \NeedsTeXFormat{LaTeX2e}
2546 \ProvidesPackage{fithesis/style/mu/fithesis-mu-phil}[2021/04/24]

```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```

2547 \thesis@color@setup{
2548 links={HTML}{6FCEF2},
2549 tableEmph={HTML}{78CEF0},
2550 tableOdd={HTML}{EBF6FA},
2551 tableEven={HTML}{D0EBF5}}

```

The bibliography support is enabled. The iso-authoryear citations are used and the bibliography is sorted by name, title, and year.

```

2552 \thesis@bibliography@setup{
2553 style=iso-authoryear,
2554 sorting=nty}
2555 \thesis@bibliography@load

```

⁴See <https://slavistika.phil.muni.cz/media/2109309/diplomove-prace-pokyny.pdf> and the thesis Word template https://is.muni.cz/auth/do/phil/Pracoviste/S0/vzory_praci/sablonaDP-MUNI-ARTS-dipl-obor.dotx

The style file parses the value of the `\thesis@department` macro and recognizes the following divisions of the Faculty of Arts:

- `kisk` – The Division of Information and Library Studies⁵ (KISK)

```
2556 \def\thesis@departments@kisk{kisk}
```

Along with the macros required by the locale file interface, the locale files need to define the following macros:

- `departmentName` – The human-readable name of the given recognized division.

```
2557 \ifx\thesis@department\thesis@departments@kisk
2558 \def\thesis@department@name{\thesis@{departmentName}}
2559 \def\thesis@departmentEn@name{\thesis@english@departmentName}
2560 \fi
```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fi/thesis-base.sty` file.

```
2561 \def\thesis@blocks@preamble{%
2562 \thesis@blocks@coverMatter
2563 \thesis@blocks@cover
2564 \thesis@blocks@frontMatter
2565 \thesis@blocks@titlePage
2566 \thesis@blocks@seal
```

In KISK theses, the bibliographical entry, the abstract, and the keywords will be included after the cover matter.

```
2567 \ifx\thesis@department\thesis@departments@kisk
2568 \thesis@blocks@bibEntry
2569 \thesis@blocks@abstract
2570 \thesis@blocks@bibEntryEn
2571 \thesis@blocks@abstractEn
2572 \fi
2573 \thesis@blocks@declaration
2574 \thesis@blocks@thanks
```

In KISK theses, the lists of tables and figures will be included behind the bibliography rather than at the beginning of the document.

```
2575 \ifx\thesis@department\thesis@departments@kisk
2576 \thesis@blocks@toc
2577 \else
2578 \thesis@blocks@tables
2579 \fi}
2580 \def\thesis@blocks@postamble{%
2581 \ifx\thesis@department\thesis@departments@kisk
```

⁵See <http://kisk.phil.muni.cz/cs/povinnost>.

In KISK theses, the lists of tables and figures will be included behind the bibliography rather than at the beginning of the document.

```
2582 \thesis@blocks@lot
2583 \thesis@blocks@lof
2584 \fi
2585 \thesis@blocks@bibliography}
```

3.5.6 The style files of the Faculty of Education

3.5.6.1 The style/mu/fithesis-ped.sty file

This is the style file for the theses written at the Faculty of Education at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the of the faculty⁶.

```
2586 \NeedsTeXFormat{LaTeX2e}
2587 \ProvidesPackage{fithesis/style/mu/fithesis-mu-ped}[2021/10/17]
```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```
2588 \thesis@color@setup{
2589   links={HTML}{FFA02F},
2590   tableEmph={HTML}{FFBB6B},
2591   tableOdd={HTML}{FFF1E0},
2592   tableEven={HTML}{FFDEB7}}
```

The bibliography support is enabled. The apa citations are used and the bibliography is sorted by name, title, and year.

```
2593 \thesis@bibliography@setup{
2594   style=iso-authoryear,
2595   sorting=nty}
2596 \thesis@bibliography@load
```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
2597 \def\thesis@blocks@preamble{%
2598   \thesis@blocks@coverMatter
2599   \thesis@blocks@cover
2600   \thesis@blocks@frontMatter
2601   \thesis@blocks@titlePage
2602   \thesis@blocks@seal
```

⁶See https://is.muni.cz/do/mu/Uredni_deska/Predpisy_MU/Pedagogicka_fakulta/Pokyny/PD2015-01/K_realizac_i_zaverecnich_praci__bakalarskych__diplomovych__rigoroznich_a_zaverecnich_praci_CZV__2021-06-10_09-07-51.pdf, and the standard of the department of Pedagogy http://www.ped.muni.cz/pedagogika/wp-content/uploads/2018/08/standard_zaverecnich_praci_katedra_pedagogiky-opravene3_08.pdf


```

2603 \thesis@blocks@bibEntry
2604 \thesis@blocks@abstract
2605 \thesis@blocks@bibEntryEn
2606 \thesis@blocks@abstractEn
2607 \thesis@blocks@declaration
2608 \thesis@blocks@thanks
2609 \thesis@blocks@tables}
2610 \def\thesis@blocks@postamble{%
2611 \thesis@blocks@bibliography}

```

3.5.7 The style files of the Faculty of Social Studies

3.5.7.1 The style/mu/fithesis-fss.sty file

This is the style file for the theses written at the Faculty of Social Studies at the Masaryk University in Brno. It has been prepared in accordance with the MS template of the faculty ⁷.

```

2612 \NeedsTeXFormat{LaTeX2e}
2613 \ProvidesPackage{fithesis/style/mu/fithesis-mu-fss}[2021/04/24]

```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```

2614 \thesis@color@setup{
2615   links={HTML}{58EDD7},
2616   tableEmph={HTML}{69D6C6},
2617   tableOdd={HTML}{E3F1EE},
2618   tableEven={HTML}{C5E3DF}}

```

The bibliography support is enabled. The iso-authoryear citations are used and the bibliography is sorted by name, title, and year.

```

2619 \thesis@bibliography@setup{
2620   style=iso-authoryear,
2621   sorting=nty}
2622 \thesis@bibliography@load

```

```

2623 \thesis@blocks@titlePage@field@false

```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis.

```

2624 \def\thesis@blocks@frontMatter{%
2625   \pagestyle{plain}
2626   \parindent 1.5em
2627   \setcounter{page}{1}
2628   \pagenumbering{roman}}

```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you

⁷See https://is.muni.cz/auth/do/fss/sablona_zaverecne_prace/sablonaDP-MUNI-FSS.dotx

should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
2629 \def\thesis@blocks@preamble{%
2630   \thesis@blocks@coverMatter
2631   \thesis@blocks@cover
2632   \thesis@blocks@frontMatter
2633   \thesis@blocks@titlePage
2634   \thesis@blocks@seal
2635   \thesis@blocks@bibEntry
2636   \thesis@blocks@abstract
2637   \thesis@blocks@bibEntryEn
2638   \thesis@blocks@abstractEn
2639   \thesis@blocks@declaration
2640   \thesis@blocks@thanks
2641   \thesis@blocks@tables}
2642 \def\thesis@blocks@postamble{%
2643   \thesis@blocks@bibliography}
```

3.5.8 The style files of the Faculty of Law

3.5.8.1 The `style/mu/fithesis-law.sty` file

This is the style file for the theses written at the Faculty of Law at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty⁸.

```
2644 \NeedsTeXFormat{LaTeX2e}
2645 \ProvidesPackage{fithesis/style/mu/fithesis-mu-law}[2021/07/18]
```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```
2646 \thesis@color@setup{
2647   links={HTML}{CF86EB},
2648   tableEmph={HTML}{D39BE8},
2649   tableOdd={HTML}{F2EBF5},
2650   tableEven={HTML}{E5CCED}}
```

The bibliography support is enabled. The `iso-authortitle` citations are used and the bibliography is sorted by name, year, and title.

```
2651 \thesis@bibliography@setup{%
2652   style=iso-authortitle,
2653   sorting=nyt}
2654 \thesis@bibliography@load
```

⁸See <http://is.muni.cz/do/law/ud/predp/smer/S-07-2012.pdf>, and https://is.muni.cz/do/law/ud/predp/smer/Smernice_dekana_c._3-2020_0_citacich_dokumentu.pdf

Each footnote is uniquely numbered across the entire document as per the formal requirements of the faculty.

```
2655 \thesis@require{chngcntr}
2656 \counterwithout{footnote}{chapter}
```

The style file configures the upper part of the title page headers to include the name of the department and the study field which are by default in the bottom part of the title page.

```
2657 \thesis@blocks@titlePage@programme@false
2658
2659 \thesis@xpatch\thesis@blocks@titlePage{%
2660 {\sf\thesis@titlePage@large\thesis@{@advisorTitle}: \thesis@advisor\par}%
2661 \vspace{0.75cm}%
2662 \ifthesis@blocks@titlePage@department@
2663 {\sf\thesis@titlePage@large\thesis@department@name\par}%
2664 \fi
2665 \ifthesis@blocks@titlePage@programme@
2666 \vspace{0.25cm}%
2667 {\sf\thesis@titlePage@large\thesis@{@bib@programme}:
2668 \thesis@programme\par}%
2669 \fi
2670 \ifthesis@blocks@titlePage@field@
2671 \vspace{0.25cm}%
2672 {\sf\thesis@titlePage@large\thesis@{@fieldTitle}:
2673 \thesis@field@name\par}%
2674 \fi
2675 \vfill
2676 }{}
2677
2678 \thesis@xpatch\thesis@blocks@titlePage{%
2679 {\sf\thesis@titlePage@large\thesis@{@upper{facultyName}}\par}%
2680 \vfill
2681 }{%
2682 {\sf\thesis@titlePage@large\thesis@{@upper{facultyName}}\par}%
2683 \vspace{0.5cm}%
2684 {\sf\thesis@titlePage@large\thesis@field\par}%
2685 \vspace{0.25cm}%
2686 {\sf\thesis@titlePage@large\thesis@department@name\par}%
2687 \vspace{1cm}%
2688 }
```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is arabic in accordance with the formal requirements of the faculty and it is hidden.

```
2689 \def\thesis@blocks@frontMatter{%
2690 \thesis@blocks@clear
2691 \pagestyle{empty}
2692 \parindent 1.5em
2693 \setcounter{page}{1}
2694 \pagenumbering{arabic}}
```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The page numbering doesn't reset at the beginning of the main thesis in accordance with the formal requirements of the faculty.

```
2695 \def\thesis@blocks@mainMatter{%
2696   \thesis@blocks@clear
2697   \pagestyle{thesisheadings}
2698   \parindent 1.5em\relax}
```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
2699 \def\thesis@blocks@preamble{%
2700   \thesis@blocks@coverMatter
2701   \thesis@blocks@cover
2702   \thesis@blocks@frontMatter
2703   \thesis@blocks@titlePage
2704   \thesis@blocks@seal

2705   \thesis@blocks@clear
2706   \pagestyle{plain}
2707   \setcounter{page}{1}
2708   \thesis@blocks@declaration
2709   \thesis@blocks@clear
2710   \thesis@blocks@abstract
2711   \thesis@blocks@keywords
2712   \thesis@blocks@clear
2713   \thesis@blocks@abstractEn
2714   \thesis@blocks@keywordsEn
2715   \thesis@blocks@thanks
2716   \thesis@blocks@tables}
```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
2717 \def\thesis@blocks@postamble{%
2718   \thesis@blocks@bibliography
2719   \thesis@blocks@assignment}
```

3.5.9 The style files of the Faculty of Economics and Administration

3.5.9.1 The `style/mu/fithesis-econ.sty` file

This is the style file for the theses written at the Faculty of Economics and Administration at the Masaryk University in Brno. It has been prepared in accordance

with the formal requirements published at the website of the faculty⁹.

```
2720 \NeedsTeXFormat{LaTeX2e}
2721 \ProvidesPackage{fithesis/style/mu/fithesis-mu-econ}[2021/04/24]
```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```
2722 \thesis@color@setup{
2723   links={HTML}{F27995},
2724   tableEmph={HTML}{E8B88B},
2725   tableOdd={HTML}{F5ECEB},
2726   tableEven={HTML}{EBD8D5}}
```

The bibliography support is enabled. The iso-authoryear citations are used and the bibliography is sorted by name, title, and year.

```
2727 \thesis@bibliography@setup{
2728   style=iso-authoryear,
2729   sorting=nty}
2730 \thesis@bibliography@load
```

The file loads the following packages:

- tikz – Used for dimension arithmetic.
- geometry – Allows for modifications of the type area dimensions.
- array – Enables `<{decl.}` and `>{decl.}` declarations in table preambles.

In addition to this, the type area width is set to 16 cm in accordance with the formal requirements of the faculty. This leads to overfull lines and is against the good conscience of the author of this style.

```
2731 \thesis@require{tikz}
2732 \thesis@require{geometry}
2733 \thesis@require{array}
2734 \geometry{top=25mm,bottom=20mm,left=25mm,right=25mm,includeheadfoot}
```

Enable the inclusion of the scanned assignment inside the digital version of the document.

```
2735 \thesis@blocks@assignment@hideIfDigital@false
```

```
2736 \thesis@blocks@titlePage@field@false
```

`\thesis@blocks@cover` The `\thesis@blocks@cover` macro typesets the cover page. Compared to the definition within the `style/mu/base.sty` file, this macro does not include the title of the thesis, and typesets the name of the author at the bottom of the page.

```
2737 \thesis@xpatch\thesis@blocks@cover{%
2738   \vfill
2739   {\bf\thesis@titlePage@Huge\thesis@TeXtitle\par}%
```

⁹See https://is.muni.cz/auth/do/econ/uredni_deska/predpisy_ESF/smernice/smernice_dekana/94383996/ and https://is.muni.cz/auth/do/econ/uredni_deska/predpisy_ESF/smernice/smernice_dekana/104768134/

```

2740 \vspace{1.5cm}%
2741 {\sf\thesis@titlePage@Large\thesis@{@{typeName}}\par}%
2742 \vspace{1.5cm}%
2743 {\sf\thesis@titlePage@LARGE\thesis@upper{author}\par}%
2744 \vfill\vfill\vfill\vfill
2745 {\sf\thesis@titlePage@large\thesis@place, \thesis@{@{semester}}\par}%
2746 }{%
2747 \vfill
2748 {\bf\thesis@titlePage@Huge\thesis@{@{typeName}}\par}%
2749 \vfill
2750 {\sf\thesis@titlePage@large\thesis@place
2751 \ \sf\thesis@year\hfill\thesis@author\par}%
2752 }

```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is arabic as per the formal requirements and it is hidden. In case of double-sided typesetting, the geometry is altered according to the requirements of the faculty.

```

2753 \def\thesis@blocks@frontMatter{%
2754 \thesis@blocks@clear
2755 \newgeometry{top=25mm,bottom=20mm,left=35mm,
2756 right=15mm, includeheadfoot}
2757 \pagestyle{empty}
2758 \parindent 1.5em
2759 \setcounter{page}{1}
2760 \pagenumbering{arabic}}

```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The page numbering doesn't reset at the beginning of the main matter as per the formal requirements.

```

2761 \def\thesis@blocks@mainMatter{%
2762 \thesis@blocks@clear
2763 \newgeometry{top=25mm,bottom=20mm,left=35mm,
2764 right=15mm, includeheadfoot}
2765 \pagestyle{thesisheadings}
2766 \parindent 1.5em\relax}

```

`\thesis@blocks@tables` The `\thesis@blocks@tables` macro optionally typesets the `\listoftables` and `\listoffigures`.

```

2767 \def\thesis@blocks@tables{%
2768 \thesis@blocks@lot
2769 \thesis@blocks@lof}

```

If the `nolot` and `nolof` options haven't been specified, the `\thesis@blocks@lot` and `\thesis@blocks@lof` macros are redefined to create an entry in the table of contents.

```

2770 \ifx\thesis@blocks@lot\relax\else
2771 \def\thesis@blocks@lot{%
2772 \thesis@blocks@clear

```

```

2773 \phantomsection
2774 \addcontentsline{toc}{chapter}{\listtablename}%
2775 \listoftables}
2776 \fi
2777
2778 \ifx\thesis@blocks@lof\relax\else
2779 \def\thesis@blocks@lof{%
2780 \thesis@blocks@clear
2781 \phantomsection
2782 \addcontentsline{toc}{chapter}{\listfigurename}%
2783 \listoffigures}
2784 \fi

```

`\thesis@blocks@declaration` The `\thesis@blocks@declaration` macro typesets the declaration text. Unlike the generic `\thesis@blocks@declaration` macro from the style/`mu/fi`thesis-sci.sty file, this definition includes the date and a blank line for the author's signature, as per the requirements of the faculty.

```

2785 \def\thesis@blocks@declaration{%
2786 \begin{alwaysssingle}%
2787 \thesis@blocks@clear
2788 \leavevmode\vfill
2789 % Start the new chapter without clearing any page.
2790 {\let\thesis@blocks@clear\relax
2791 \chapter*{\thesis@{declarationTitle}}}%
2792 \thesis@declaration
2793 \vskip 2cm%
2794 {\let\@A\relax\newlength{\@A}
2795 \settowidth{\@A}{\thesis@{authorSignature}}
2796 \setlength{\@A}{\@A+1cm}
2797 \noindent\thesis@place, \thesis@{formattedDate}\hfill
2798 \begin{minipage}[t]{\@A}%
2799 \centering\rule{\@A}{1pt}\
2800 \thesis@{authorSignature}\par
2801 \end{minipage}}
2802 \end{alwaysssingle}}

```

The `\thesis@blocks@abstract` macro typesets the abstract. This definition typesets the abstract on the same page.

`\thesis@blocks@keywords` The `\thesis@blocks@keywords` macro typesets the keywords. This definition typesets the keywords on the same page.

```

2803 \def\thesis@blocks@keywords{%
2804 \begin{alwaysssingle}%
2805 \vskip 40\p@
2806 {\let\thesis@blocks@clear\relax
2807 \chapter*{\thesis@{keywordsTitle}}%
2808 \noindent\thesis@TeXkeywords}%
2809 \end{alwaysssingle}}

```

`\thesis@blocks@keywordsEn` The `\thesis@blocks@keywordsEn` macro typesets the keywords in English. If the current locale is English, the macro produces no output.

```
2810 \def\thesis@blocks@keywordsEn{%
2811   \ifthesis@english\else
2812     {\thesis@selectLocale{english}%
2813     \begin{alwaysssingle}%
2814       \vskip 20\p@
2815       {\let\thesis@blocks@clear\relax%
2816       \chapter*{\thesis@english@keywordsTitle}}%
2817       \noindent\thesis@TeXkeywordsEn
2818     \end{alwaysssingle}}%
2819   \fi}
```

`\thesis@blocks@summary` The `\thesis@blocks@summary` macro typesets the summary for doctoral theses. If the thesis type is not doctoral, the macro produces no output.

```
2820 \thesis@def@extra[{\thesis@placeholder@extra@summary
2821 \thesis@placeholder@extra@summary
2822 }]{summary}
2823
2824 \def\thesis@blocks@summary{%
2825   \begin{alwaysssingle}%
2826     \thesis@blocks@clear
2827     {\let\thesis@blocks@clear\relax
2828     \chapter*{\thesis@{@{summaryTitle}}}%
2829     \noindent\thesis@extra@summary
2830   \end{alwaysssingle}}
```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
2831 \def\thesis@blocks@preamble{%
2832   \thesis@blocks@coverMatter
2833   \thesis@blocks@cover
2834   \thesis@blocks@frontMatter
2835   \thesis@blocks@titlePage
2836   \thesis@blocks@seal
2837   \thesis@blocks@bibEntry
2838   \thesis@blocks@abstract
2839   \thesis@blocks@bibEntryEn
2840   \thesis@blocks@abstractEn
2841   \thesis@blocks@declaration
2842   \thesis@blocks@thanks
2843   \thesis@blocks@toc
2844   \thesis@blocks@tables}
```


All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/base.sty` file.

```
2845 \def\thesis@blocks@postamble{%
2846   \ifx\thesis@doctoral\thesis@type\thesis@blocks@summary\else\fi
2847   \thesis@blocks@bibliography
2848 }
```

3.5.10 The style files of the Faculty of Medicine

3.5.10.1 The `style/mu/fithesis-med.sty` file

This is the style file for the theses written at the Faculty of Medicine at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty ¹⁰.

```
2849 \NeedsTeXFormat{LaTeX2e}
2850 \ProvidesPackage{fithesis/style/mu/fithesis-mu-med}[2021/07/18]
```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```
2851 \thesis@color@setup{
2852   links={HTML}{F58E76},
2853   tableEmph={HTML}{FF9D85},
2854   tableOdd={HTML}{FFF5F6},
2855   tableEven={HTML}{FFDEDF}}
```

The bibliography support is enabled. The `author` title citations are used and the bibliography is sorted by year, name, and title.

```
2856 \thesis@bibliography@setup{%
2857   style=author,
2858   sorting=ynt}
2859 \thesis@bibliography@load
```

The AMA citation style is defined using `author` title as the basis. The following code has been adapted from <https://tex.stackexchange.com/a/233423/70941>.

```
2860 \ifthesis@bibliography@loaded@
2861   \DeclareNameAlias{sortname}{last-first}
2862   \renewcommand*{\revsnamepunct}{}
2863   \DeclareFieldFormat[%
2864     article,inbook,incollection,inproceedings,patent,thesis,unpublished]%
2865     {title}{\#1\isdot}
2866   \renewbibmacro{in:}{}
2867   \DeclareFieldFormat{pages}{\#1}
2868   \renewcommand*{\bibpagespunct}{\addcolon}
2869   \DeclareFieldFormat{journaltitle}{\#1\addperiod}
```

¹⁰See https://is.muni.cz/do/med/uredni_deska/pravni_normy/smernice_dekana/2020/smernice_lf_mu_2_2020_-_pokyny_k_formalnim_nalezitostem_zaverecnym_bakalarskych/Smernice_LF_MU_2-2020_-_Pokyny_k_formalnim_nalezitostem_zaverecnym_bakalarskych_a_diplomovych_praci_vypracovanych_na_Lekarske_fakulte_MU.pdf

```

2870 \DeclareFieldFormat{booktitle}{{#1}}
2871 \DeclareFieldFormat{title}{{#1}}
2872 \renewbibmacro*{journal+issuetitle}{%
2873   \usebibmacro{journal}%
2874   \setunit*{\addspace}%
2875   \iffieldundef{series}
2876     {}
2877   {\newunit
2878     \printfield{series}%
2879     \setunit{\addspace}}%
2880   \usebibmacro{issue+date}%
2881   \setunit{\addsemicolon\addspace}%
2882   \usebibmacro{volume+number+eid}%
2883   \setunit{\addcolon\space}%
2884   \usebibmacro{issue}%
2885   \newunit%
2886 }
2887 \renewbibmacro*{issue+date}{\printfield{year}}
2888 \renewcommand*{\finalnamedelim}{\multinamedelim}
2889 \fi

```

The file loads the following packages:

- tikz – Used for dimension arithmetic.
- geometry – Allows for modifications of the type area dimensions.
- setspace – Allows for line height modifications.

In addition to this, the type area width is set to 16 cm in accordance with the formal requirements of the faculty. This leads to overfull lines and is against the good conscience of the author of this style.

```

2890 \thesis@require{tikz}
2891 \thesis@require{geometry}
2892 \thesis@require{setspace}
2893 \geometry{top=25mm,bottom=20mm,left=25mm,right=25mm,includeheadfoot}

```

The style file configures the upper part of the title page headers to include the the name of the department and the study programme which are by default in the bottom part of the title page. Upon failure of the *xpatchcmd*, `\thesis@xpatchError` is called.

```

2894 \thesis@blocks@titlePage@field@false
2895
2896 \thesis@xpatch\thesis@blocks@titlePage{%
2897   {\sf\thesis@titlePage@large\thesis@{@{advisorTitle}: \thesis@advisor\par}%
2898   \vspace{0.75cm}}%
2899   \ifthesis@blocks@titlePage@department@
2900     {\sf\thesis@titlePage@large\thesis@department@name\par}%
2901   \fi
2902   \ifthesis@blocks@titlePage@programme@
2903     \vspace{0.25cm}}%

```

```

2904     {\sf\thesis@titlePage@large\thesis@{bib@programme}:
2905       \thesis@programme\par}%
2906   \fi
2907   \ifthesis@blocks@titlePage@field@
2908     \vspace{0.25cm}%
2909     {\sf\thesis@titlePage@large\thesis@{fieldTitle}:
2910       \thesis@field@name\par}%
2911   \fi
2912   \vfill
2913 }{}
2914
2915 \thesis@xpatch\thesis@blocks@titlePage{%
2916   {\sf\thesis@titlePage@large\thesis@{upper{facultyName}}\par}%
2917   \vfill
2918 }{%
2919   {\sf\thesis@titlePage@large\thesis@{upper{facultyName}}\par}%
2920   \vspace{0.5cm}%
2921   {\sf\thesis@titlePage@large\thesis@programme\par}%
2922   \vspace{0.25cm}%
2923   {\sf\thesis@titlePage@large\thesis@department@name\par}%
2924   \vspace{1cm}%
2925 }

```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is arabic in accordance with the formal requirements and it is hidden. In case of double-sided typesetting, the geometry is altered according to the requirements of the faculty.

```

2926 \def\thesis@blocks@frontMatter{%
2927   \thesis@blocks@clear
2928   \newgeometry{top=25mm,bottom=20mm,left=35mm,
2929     right=15mm, includeheadfoot}
2930   \pagestyle{empty}
2931   \parindent 1.5em
2932   \setcounter{page}{1}
2933   \pagenumbering{arabic}}

```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The leading is adjusted in accordance with the requirements of the faculty. The page numbering doesn't reset at the beginning of the main thesis in accordance with the formal requirements of the faculty.

```

2934 \def\thesis@blocks@mainMatter{%
2935   \thesis@blocks@clear
2936   \newgeometry{top=25mm,bottom=20mm,left=35mm,
2937     right=15mm, includeheadfoot}
2938   \pagestyle{thesisheadings}
2939   \parindent 1.5em
2940   \onehalfspacing}

```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you

should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```
2941 \def\thesis@blocks@preamble{%
2942   \thesis@blocks@coverMatter
2943   \thesis@blocks@cover
2944   \thesis@blocks@frontMatter
2945   \thesis@blocks@titlePage
2946   \thesis@blocks@seal

2947   \thesis@blocks@clear
2948   \pagestyle{plain}
2949   \setcounter{page}{1}
2950   \thesis@blocks@declaration
2951   \thesis@blocks@clear
2952   \thesis@blocks@abstract
2953   \thesis@blocks@keywords
2954   \thesis@blocks@clear
2955   \thesis@blocks@abstractEn
2956   \thesis@blocks@keywordsEn
2957   \thesis@blocks@thanks
2958   \thesis@blocks@tables}
2959 \def\thesis@blocks@postamble{%
2960   \thesis@blocks@bibliography}
```

3.5.11 The style files of the Faculty of Sports Studies

3.5.11.1 The `style/mu/fithesis-fsps.sty` file

This is the style file for the theses written at the Faculty of Sports Studies at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements published at the website of the faculty¹¹.

```
2961 \NeedsTeXFormat{LaTeX2e}
2962 \ProvidesPackage{fithesis/style/mu/fithesis-mu-fsps}[2021/07/18]
```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```
2963 \thesis@color@setup{
2964   links={HTML}{93BCF5},
2965   tableEmph={HTML}{A8BDE3},
2966   tableOdd={HTML}{EBEFF5},
2967   tableEven={HTML}{D1DAEB}}
```

The bibliography support is enabled. The iso-authoryear citations are used and the bibliography is sorted by name, title, and year.

¹¹See https://is.muni.cz/auth/do/fsps/fak_predpisy/smernice-dekana/2020-03_Smernice_pokyny_vypracovani_ZP_bc-mgr-rig.pdf

```

2968 \thesis@bibliography@setup{
2969   style=iso-authoryear,
2970   sorting=nyt}
2971 \thesis@bibliography@load

```

The file loads the following packages:

- tikz – Used for dimension arithmetic.
- geometry – Allows for modifications of the type area dimensions.
- setspace – Allows for line height modifications.

In addition to this, the type area width is set to 14 cm in accordance with the formal requirements of the faculty.

```

2972 \thesis@require{tikz}
2973 \thesis@require{geometry}
2974 \thesis@require{setspace}
2975 \geometry{top=30mm,bottom=30mm,left=40mm,right=30mm,includeheadfoot}

```

The paragraph indentation is 1.25 cm as per the requirements of the faculty.

```

2976 \setlength{\parindent}{1.25cm}

```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The leading is adjusted in accordance with the requirements of the faculty.

```

2977 \def\thesis@blocks@frontMatter{%
2978   \thesis@blocks@clear
2979   \pagestyle{empty}
2980   \parindent 1.5em
2981   \setcounter{page}{1}
2982   \pagenumbering{arabic}
2983   \onehalfspacing}

```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The leading is adjusted in accordance with the requirements of the faculty. The page numbering doesn't reset at the beginning of the main thesis in accordance with the formal requirements of the faculty.

```

2984 \def\thesis@blocks@mainMatter{%
2985   \thesis@blocks@clear
2986   \pagestyle{thesisheadings}
2987   \parindent 1.5em
2988   \onehalfspacing}

```

`\thesis@blocks@bibliography` The `\thesis@blocks@bibliography` macro typesets the bibliography. The leading is adjusted in accordance with the requirements of the faculty.

```

2989 \def\thesis@blocks@bibliography{%
2990   \ifthesis@bibliography@loaded@
2991     \ifthesis@bibliography@included@\else
2992       \singlespacing

```

```

2993 \thesis@blocks@clear
2994 {\emergencystretch=3em%
2995 \printbibliography[heading=bibintoc]}%
2996 \fi
2997 \fi}

```

`\thesis@blocks@declaration` The `\thesis@blocks@declaration` macro typesets the declaration text. Unlike the generic `\thesis@blocks@declaration` macro from the `style/mu/fi/thesis-sci.sty` file, this definition includes the date and a blank line for the author's signature, as per the requirements of the faculty.

Along with the macros required by the locale file interface, the locale files need to define the following macros:

- `\thesis@locale@authorSignature` – The label of the author's signature field
- `\thesis@locale@formattedDate` – A formatted date

```

2998 \def\thesis@blocks@declaration{%
2999 \thesis@blocks@clear
3000 \begin{alwaysingle}%
3001 \chapter*{\thesis@{declarationTitle}}%
3002 \thesis@declaration
3003 \vskip 2cm%
3004 {\let\@A\relax\newlength{\@A}
3005 \settowidth{\@A}{\thesis@{authorSignature}}
3006 \setlength{\@A}{\@A+1cm}
3007 \noindent\thesis@place, \thesis@{formattedDate}\hfill
3008 \begin{minipage}[t]{\@A}%
3009 \centering\rule{\@A}{1pt}\
3010 \thesis@{authorSignature}\par
3011 \end{minipage}}
3012 \end{alwaysingle}}

```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble and postamble that are not defined within this file are defined in the `style/mu/fi/thesis-base.sty` file.

```

3013 \def\thesis@blocks@preamble{%
3014 \thesis@blocks@coverMatter
3015 \thesis@blocks@cover
3016 \thesis@blocks@frontMatter
3017 \thesis@blocks@titlePage
3018 \thesis@blocks@seal
3019 \thesis@blocks@bibEntry
3020 \thesis@blocks@abstract
3021 \thesis@blocks@bibEntryEn
3022 \thesis@blocks@abstractEn
3023 \thesis@blocks@thanks

```

```

3024 \thesis@blocks@clear
3025 \pagestyle{plain}
3026 \thesis@blocks@tables}
3027 \def\thesis@blocks@postamble{%
3028 \thesis@blocks@bibliography}

```

3.5.12 The style files of the Faculty of Pharmacy

3.5.12.1 The style/mu/fithesis-pharm.sty file

This is the style file for the theses written at the Faculty of Pharmacy at the Masaryk University in Brno. It has been prepared in accordance with the formal requirements.

```

3029 \NeedsTeXFormat{LaTeX2e}
3030 \ProvidesPackage{fithesis/style/mu/fithesis-mu-pharm}[2018/06/11]

```

The file defines the color scheme of the respective faculty. Note the the color definitions are in RGB, which makes the resulting files generally unsuitable for printing.

```

3031 \thesis@color@setup{
3032 links={HTML}{A0B9C5},
3033 tableEmph={HTML}{B0C3CF},
3034 tableOdd={HTML}{EFF3F6},
3035 tableEven={HTML}{D6E1E6}}

```

The bibliography support is enabled. The authority year citations are used and the bibliography is sorted by name, title, and year.

```

3036 \thesis@bibliography@setup{
3037 style=iso-authoryear,
3038 sorting=nty}
3039 \thesis@bibliography@load

```

The file loads the following packages:

- tikz – Used for dimension arithmetic.
- geometry – Allows for modifications of the type area dimensions.
- setspace – Used for setting space.

```

3040 \thesis@require{tikz}
3041 \thesis@require{geometry}
3042 \thesis@require{setspace}
3043 \geometry{top=25mm,bottom=20mm,left=25mm,right=25mm,includeheadfoot}
3044

```

Enable the inclusion of the scanned assignment inside the digital version of the document.

```

3045 \thesis@blocks@assignment@hideIfDigital@false

```

`\thesis@blocks@frontMatter` The `\thesis@blocks@frontMatter` macro sets up the style of the front matter of the thesis. The page numbering is roman in accordance with the formal requirements of the faculty.

```

3046 \def\thesis@blocks@frontMatter{%
3047 \thesis@blocks@clear
3048 \newgeometry{top=25mm, bottom=20mm, left=35mm, right=15mm, includeheadfoot}
3049 \pagestyle{empty}
3050 \parindent 1.5em
3051 \setcounter{page}{1}
3052 \pagenumbering{roman}}

```

`\thesis@blocks@mainMatter` The `\thesis@blocks@mainMatter` macro sets up the style of the main matter of the thesis. The page numbering doesn't reset at the beginning of the main thesis in accordance with the formal requirements of the faculty.

```

3053 \def\thesis@blocks@mainMatter{%
3054 \thesis@blocks@clear
3055 \newgeometry{top=25mm, bottom=20mm, left=35mm,
3056 right=15mm, includeheadfoot}
3057 \setcounter{page}{1}
3058 \pagenumbering{arabic}
3059 \pagestyle{thesisheadings}
3060 \parindent 1.5em
3061 \onehalfspacing}

```

Note that there is no direct support for the seminar paper and thesis proposal types. If you would like to change the contents of the preamble and the postamble, you should modify the `\thesis@blocks@preamble` and `\thesis@blocks@postamble` macros.

All blocks within the autolayout preamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```

3062 \def\thesis@blocks@preamble{%
3063 \thesis@blocks@coverMatter
3064 \thesis@blocks@cover
3065 \thesis@blocks@frontMatter
3066 \thesis@blocks@titlePage
3067 \thesis@blocks@seal
3068 \thesis@blocks@bibEntry
3069 \thesis@blocks@abstract
3070 \thesis@blocks@bibEntryEn
3071 \thesis@blocks@abstractEn
3072 \thesis@blocks@assignment
3073 \thesis@blocks@declaration
3074 \thesis@blocks@thanks
3075 \thesis@blocks@tables}

```

All blocks within the autolayout postamble that are not defined within this file are defined in the `style/mu/fithesis-base.sty` file.

```

3076 \def\thesis@blocks@postamble{%
3077 \thesis@blocks@bibliography}

```


Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

Symbols	
<code>\.</code>	1512, 1774
<code>\@A</code>	1631, 1632, 1633, 1634, 1636, 1805, 1823, 1858, 1876, 2794, 2795, 2796, 2798, 2799, 3004, 3005, 3006, 3008, 3009
<code>\@B</code>	1807, 1823, 1860, 1876
<code>\@C</code>	1809, 1823, 1862, 1876
<code>\@D</code>	1811, 1823, 1864, 1876
<code>\@E</code>	1813, 1814, 1823, 1866, 1867, 1876
<code>\@F</code>	1815, 1823, 1868, 1876
<code>\@G</code>	1817, 1823, 1870, 1876
<code>\@H</code>	1819, 1823, 1872, 1876
<code>\@afterheading</code>	2326
<code>\@afterindentfalse</code>	1962, 2304
<code>\@arg</code>	148, 149, 176, 177, 266, 267
<code>\@args</code>	1509, 1510, 1771, 1772
<code>\@auxout</code>	280, 289, 441, 445
<code>\@beginparpenalty</code>	2276
<code>\@bibList</code>	1462, 1463, 1507, 1515
<code>\@chapapp</code>	2311
<code>\@chapter</code>	1963, 2305, 2307
<code>\@clxextension</code>	327
<code>\@currentx</code>	327
<code>\@date</code>	218, 219
<code>\@dblfpbot</code>	2210, 2238, 2266
<code>\@dblfpsep</code>	2209, 2237, 2265
<code>\@dblftop</code>	2208, 2236, 2264
<code>\@doclocale</code>	420, 421
<code>\@dottedtocline</code>	2034, 2037, 2038, 2039, 2040, 2041, 2042, 2043
<code>\@empty</code>	301, 356, 369, 1930, 1931
<code>\@endparpenalty</code>	2277
<code>\@english</code>	161, 167
<code>\@evenfoot</code>	1949, 1951
<code>\@evenhead</code>	1938, 1945
<code>\@expandtwoargs</code>	307
<code>\@fpbot</code>	2207, 2235, 2263
<code>\@fpsep</code>	2206, 2234, 2262
<code>\@fptop</code>	2205, 2233, 2261
<code>\@gobble</code>	91
<code>\@gobbletwo</code>	491, 499
<code>\@highpenalty</code> ...	2001, 2021, 2031, 2275
<code>\@ifpackageloaded</code>	456, 470
<code>\@inject</code>	67, 1508, 1514, 1515, 1770, 1777, 1787, 1790
<code>\@itempenalty</code>	2278
<code>\@ixpt</code>	2055, 2101
<code>\@left</code> .	1822, 1825, 1828, 1875, 1878, 1881
<code>\@listI</code>	2053, 2090, 2128, 2358, 2362, 2388, 2392, 2418, 2422
<code>\@listi</code>	2053, 2060, 2069, 2090, 2097, 2106, 2128, 2135, 2145, 2362, 2363, 2392, 2393, 2422, 2423
<code>\@listii</code>	2365, 2395, 2425
<code>\@listiii</code>	2371, 2401, 2431
<code>\@listiv</code>	2377, 2407, 2437
<code>\@listv</code>	2380, 2410, 2440
<code>\@listvi</code>	2383, 2413, 2443
<code>\@locale</code>	164, 166
<code>\@logoheight</code>	1580, 1582, 1584
<code>\@logowidth</code>	1579, 1581, 1583
<code>\@lowpenalty</code>	2273, 2276, 2277, 2278
<code>\@makechapterhead</code>	2280, 2323, 2325
<code>\@makeschapterhead</code>	2293
<code>\@maxheight</code>	1584, 1585
<code>\@maxwidth</code>	1583, 1585
<code>\@medpenalty</code>	2274
<code>\@mkboth</code>	1953
<code>\@month</code> 190, 191, 192, 198, 209, 552, 553, 555, 557, 559, 561, 563, 565, 567, 569, 571, 573, 575, 578, 769, 770, 772, 774, 776, 778, 780, 782, 784, 786, 788, 790, 792, 795, 1069, 1070, 1072, 1074, 1076, 1078, 1080, 1082, 1084, 1086, 1088, 1090, 1092, 1095	
<code>\@parswitchfalse</code>	1351
<code>\@parswitchtrue</code>	1353
<code>\@ne</code>	1342
<code>\@nil</code>	298, 299
<code>\@nobreakfalse</code>	2015
<code>\@nobreaktrue</code>	2014
<code>\@nomath</code>	1342
<code>\@normalsize</code>	2169
<code>\@oddfont</code>	1930, 1947, 1951
<code>\@oddfont</code>	1931, 1932, 1945

<code>\@p</code>	2089	
<code>\@part</code>	1975	
<code>\@path</code>	1589, 1590, 1593, 1595, 1598, 1599, 1602, 1604	<code>_</code> 493, 863, 864, 909, 938, 939, 940, 966, 968, 988, 989, 995, 1034, 1164, 1210, 1239, 1240, 1241, 1267, 1269, 1289, 1290, 1297, 1928, 2751
<code>\@pdfList</code>	1767, 1778, 1787, 1790	
<code>\@plus</code>	2003, 2005, 2022	
<code>\@pnumwidth</code>	2009, 2010, 2012, 2025, 2026, 2030	
<code>\@relax</code>	1509, 1510, 1771, 1772	
<code>\@restonecolfalse</code>	1980	
<code>\@restonecoltrue</code>	1980	
<code>\@right</code>	1824, 1828, 1831, 1877, 1881, 1883	
<code>\@schapter</code>	1963, 2305	
<code>\@skip</code>	1821, 1825, 1828, 1874, 1878, 1881	
<code>\@spart</code>	1975	
<code>\@startsection</code>	2330, 2333, 2336, 2339, 2342	
<code>\@tempa</code>	355, 356, 358, 362, 366	
<code>\@tempb</code>	361, 363, 372, 373	
<code>\@tempc</code>	357, 359, 373	
<code>\@tempdima</code>	2008, 2023, 2028	
<code>\@tempswafalse</code>	1972	
<code>\@tempswatru</code>	1970	
<code>\@topnewpage</code>	2323	
<code>\@topnum</code>	1961, 2303	
<code>\@trimmed</code>	1512, 1513, 1774, 1776	
<code>\@true</code>	147, 149, 175, 177, 265, 267	
<code>\@twocolumnfalse</code>	1354	
<code>\@twocolumntrue</code>	1355	
<code>\@twosidefalse</code>	1351	
<code>\@twosidetrue</code>	1353	
<code>\@unknownoptionerror</code>	328	
<code>\@viipt</code>	2064, 2110, 2149	
<code>\@viipt</code>	2073	
<code>\@vipt</code>	2111, 2150	
<code>\@vpt</code>	2074	
<code>\@xipt</code>	2075, 2112, 2123	
<code>\@xipt</code>	2085, 2130	
<code>\@xivpt</code>	2076, 2113, 2151	
<code>\@xpt</code>	2048, 2092, 2140	
<code>\@xvipt</code>	2077, 2114, 2152	
<code>\@xxpt</code>	2078, 2115, 2153	
<code>\@xxvpt</code>	2079, 2116, 2154, 2155	
<code>\@year</code>	197, 199, 200, 201, 203, 204, 210, 212	
<code>\@yearA</code>	199, 203, 206	
<code>\@yearB</code>	200, 204, 206	
<code>\@</code>	1636, 1832, 1833, 1834, 1836, 1838, 1840, 1842, 1844, 1846, 1848, 1850, 1884, 1885, 1886, 1888, 1890, 1892, 1894, 1896, 1898, 1900, 1902, 2799, 3009	
A		
<code>\abovedisplayshortskip</code>	2051, 2058, 2067, 2089, 2095, 2104, 2126, 2133, 2143	
<code>\abovedisplayskip</code>	2049, 2050, 2056, 2057, 2065, 2066, 2086, 2087, 2093, 2094, 2102, 2103, 2124, 2125, 2131, 2132, 2141, 2142	
<code>\aboverulesep</code>	1431	
<code>\addbibresource</code>	1513	
<code>\addcolon</code>	2868, 2883	
<code>\addcontentsline</code>	2312, 2315, 2774, 2782	
<code>\addpenalty</code>	2001, 2021	
<code>\addperiod</code>	2869	
<code>\addsemicolon</code>	2881	
<code>\addspace</code>	2874, 2879, 2881	
<code>\addtocontents</code>	2318, 2320	
<code>\addtocounter</code>	1752	
<code>\addvspace</code>	2003, 2005, 2022, 2319, 2321	
<code>\advance</code>	200, 201, 203, 204, 210, 2028, 2192, 2220, 2248, 2355, 2366, 2372, 2378, 2381, 2384, 2396, 2402, 2408, 2411, 2414, 2426, 2432, 2438, 2441, 2444	
<code>\alwayssingle</code>	1979	
<code>\AtBeginDocument</code>	423, 438	
<code>\AtEndDocument</code>	439, 444	
<code>\author</code>	8, 98	
B		
<code>\baselineskip</code>	2191, 2219, 2247	
<code>\BeforeBeginEnvironment</code>	393	
<code>\begin</code>	1555, 1612, 1615, 1648, 1650, 1685, 1687, 1703, 1712, 1718, 1728, 1737, 1745, 1762, 1782, 1827, 1880, 2465, 2786, 2798, 2804, 2813, 2825, 3000, 3008	
<code>\begingroup</code>	146, 174, 419, 2007, 2024	
<code>\belowdisplayshortskip</code>	2052, 2059, 2068, 2088, 2096, 2105, 2127, 2134, 2144	
<code>\belowdisplayskip</code>	2050, 2057, 2066, 2087, 2094, 2103, 2125, 2132, 2142	
<code>\belowrulesep</code>	1432	

<code>\bf</code>	1620, 1655, 1806, 1808, 1810, 1812, 1814, 1816, 1818, 1820, 1859, 1861, 1863, 1865, 1867, 1869, 1871, 1873, 2739, 2748	138, 140, 141, 143, 147, 148, 154, 159, 160, 161, 163, 175, 176, 182, 220, 222, 225, 226, 228, 230, 233, 234, 236, 239, 240, 242, 245, 246, 248, 250, 251, 253, 254, 256, 257, 258, 260, 262, 265, 266, 273, 275, 276, 287, 295, 296, 297, 298, 336, 353, 354, 379, 382, 387, 390, 394, 395, 450, 453, 459, 466, 469, 479, 480, 481, 484, 487, 488, 489, 496, 502, 503, 513, 514, 515, 516, 517, 518, 520, 528, 1346, 1347, 1348, 1467, 1471, 1475, 1487, 1508, 1509, 1517, 1530, 1545, 1547, 1549, 1556, 1567, 1583, 1584, 1609, 1630, 1646, 1683, 1694, 1697, 1701, 1709, 1717, 1725, 1736, 1742, 1751, 1757, 1770, 1771, 1795, 1801, 1853, 1905, 1924, 1925, 1932, 1938, 1947, 1949, 1979, 1981, 2060, 2069, 2097, 2106, 2123, 2130, 2135, 2140, 2145, 2149, 2150, 2151, 2152, 2153, 2154, 2155, 2280, 2293, 2300, 2307, 2330, 2333, 2336, 2339, 2342, 2358, 2365, 2371, 2377, 2380, 2383, 2388, 2395, 2401, 2407, 2410, 2413, 2418, 2425, 2431, 2437, 2440, 2443, 2463, 2476, 2492, 2509, 2515, 2519, 2543, 2556, 2558, 2559, 2561, 2580, 2597, 2610, 2624, 2629, 2642, 2689, 2695, 2699, 2717, 2753, 2761, 2767, 2771, 2779, 2785, 2803, 2810, 2824, 2831, 2845, 2926, 2934, 2941, 2959, 2977, 2984, 2989, 2998, 3013, 3027, 3046, 3053, 3062, 3076
<code>\bfseries</code>	1544, 1545, 1990, 2012, 2027, 2313, 2315, 2332, 2335, 2341, 2344	
<code>\bibpagespunct</code>	2868	
C		
<code>\c@secnumdepth</code>	1927, 2285, 2308	
<code>\c@tocdepth</code>	2000, 2002, 2020	
<code>\centering</code>	1635, 2799, 3009	
<code>\ChapFont</code>	2283, 2296	
<code>\chapter</code>	1704, 1713, 1721, 1731, 1739, 1747, 1803, 1856, 1958, 1990, 2300, 2466, 2791, 2807, 2816, 2828, 3001	
<code>\chaptermark</code>	1925, 2317	
<code>\ClassError</code>	530	
<code>\ClassWarning</code>	452	
<code>\clearpage</code>	282, 1558, 1569, 2301	
<code>\clubpenalty</code>	1529	
<code>\color</code>	1546	
<code>\colorlet</code>	1613	
<code>\columnsep</code>	2194, 2222, 2250	
<code>\columnseprule</code>	2195, 2223, 2251	
<code>\counterwithout</code>	2656	
<code>\csname</code>	74, 165, 166, 336, 358, 362, 378, 380, 384, 387, 391, 410, 413, 468, 469, 479, 483, 486, 511, 1403	
<code>\csg@setstyle</code>	506	
<code>\CurrentOption</code>	328, 333, 346	
D		
<code>\day</code>	214	
<code>\dblfloatsep</code>	2202, 2230, 2258	
<code>\dbltextfloatsep</code>	2203, 2231, 2259	
<code>\DeclareFieldFormat</code>	2863, 2867, 2869, 2870, 2871	
<code>\DeclareNameAlias</code>	2861	
<code>\DeclareOption</code>	1346, 1347, 1348, 1350, 1352, 1354, 1355, 1356, 1357, 1359, 1360, 1362, 1363, 1365, 1366, 1368, 1369, 1370, 1371, 1372, 1373, 1375, 1376, 1378, 1381	
<code>\DeclareRobustCommand</code>	1341	
<code>\def</code> .	3, 14, 16, 19, 21, 23, 25, 27, 29, 31, 33, 35, 74, 76, 77, 78, 81, 82, 88, 89, 90, 92, 101, 102, 103, 104, 105, 106, 107, 110, 111, 113, 114, 116, 119, 122, 125, 128, 131, 134, 135, 137,	
<code>\define@key</code>	17, 24, 28, 32, 80, 96, 100, 109, 112, 115, 118, 121, 124, 127, 130, 133, 136, 139, 142, 145, 158, 173, 217, 221, 224, 229, 232, 235, 238, 241, 244, 247, 256, 259, 261, 264, 1469, 1473, 1532, 1535, 1538, 1540, 1542	
<code>\definecolor</code>	1533, 1536, 1539, 1541, 1543	
E		
<code>\ea</code>	482, 483, 485, 486, 1768, 1777, 1787, 1790	
<code>\edef</code>	199, 200, 203, 204, 206, 212, 214, 218, 400, 420, 504, 1462, 1507, 1512, 1589, 1593, 1598, 1602, 1767, 1774	
<code>\else</code>	10, 20, 38,	

42, 45, 49, 53, 56, 60, 63, 68, 75, 85, 151, 157, 169, 179, 192, 193, 202, 209, 269, 303, 306, 308, 311, 317, 327, 330, 331, 334, 338, 344, 356, 364, 368, 371, 386, 396, 399, 411, 415, 418, 425, 443, 492, 523, 555, 557, 559, 561, 563, 565, 567, 569, 571, 573, 575, 577, 605, 607, 609, 611, 613, 615, 629, 636, 640, 679, 711, 723, 772, 774, 776, 778, 780, 782, 784, 786, 788, 790, 792, 794, 802, 822, 824, 826, 828, 830, 832, 844, 846, 848, 850, 852, 854, 871, 875, 922, 959, 982, 993, 1005, 1007, 1016, 1018, 1072, 1074, 1076, 1078, 1080, 1082, 1084, 1086, 1088, 1090, 1092, 1094, 1102, 1122, 1124, 1126, 1128, 1130, 1132, 1144, 1146, 1148, 1150, 1152, 1154, 1171, 1175, 1224, 1241, 1260, 1283, 1294, 1307, 1309, 1318, 1320, 1343, 1404, 1406, 1417, 1461, 1463, 1479, 1489, 1510, 1525, 1559, 1564, 1575, 1583, 1584, 1678, 1710, 1726, 1743, 1752, 1766, 1772, 1778, 1786, 1789, 1830, 1854, 1907, 1944, 1950, 1971, 1993, 2004, 2033, 2176, 2314, 2324, 2460, 2484, 2529, 2577, 2770, 2778, 2811, 2846, 2991	\english 162 \evensidemargin 2174, 2178 \everypar 2015 \ExecuteOptions 1379, 1382, 1384 \expandafter 4, 74, 90, 161, 163, 164, 165, 166, 190, 197, 215, 219, 300, 336, 346, 357, 362, 373, 378, 380, 384, 387, 409, 412, 468, 469, 482, 485, 491, 499, 521, 522, 524, 526, 527, 552, 769, 1069, 1402, 1480, 1514, 1515, 1590, 1595, 1599, 1604, 1768 \extrarowheight 1433
	F
\em 1341, 1342 \emergencystretch 1909, 2994 \emminershape 1343 \empty 26, 30, 34, 35, 36, 40, 47, 51, 383, 399, 415, 418, 1463, 1778 \end 1627, 1628, 1681, 1682, 1692, 1693, 1708, 1715, 1724, 1734, 1741, 1749, 1765, 1785, 1851, 1903, 2473, 2801, 2802, 2809, 2818, 2830, 3011, 3012 \endalwaysingle 1981 \endcsname 74, 165, 171, 337, 358, 362, 378, 380, 384, 387, 391, 410, 413, 468, 469, 479, 483, 486, 511, 1408 \endgroup 150, 152, 178, 180, 422, 426, 2016, 2032 \endtabu 1451 \endtabular 1428 \endtabularx 1443 \endthesis@newtable@old 57, 1428, 1440 \endthesis@newtable@oldtabu 57, 1451, 1456 \endthesis@newtable@oldx 57, 1443, 1448	\fi 4, 12, 22, 44, 58, 59, 65, 66, 67, 70, 71, 72, 75, 87, 153, 157, 171, 181, 194, 205, 211, 271, 273, 275, 305, 318, 322, 323, 329, 330, 341, 342, 343, 347, 348, 349, 350, 367, 374, 375, 376, 388, 389, 402, 407, 414, 417, 427, 428, 447, 449, 464, 477, 478, 494, 500, 502, 525, 579, 580, 617, 630, 639, 643, 683, 714, 725, 749, 796, 797, 802, 834, 856, 874, 878, 926, 962, 984, 997, 1009, 1020, 1049, 1096, 1097, 1102, 1134, 1156, 1174, 1178, 1228, 1241, 1263, 1285, 1299, 1311, 1322, 1343, 1401, 1407, 1408, 1416, 1425, 1426, 1457, 1458, 1465, 1466, 1472, 1476, 1482, 1514, 1520, 1521, 1527, 1563, 1566, 1574, 1577, 1583, 1584, 1594, 1603, 1629, 1665, 1669, 1673, 1680, 1716, 1735, 1750, 1752, 1777, 1788, 1791, 1792, 1793, 1794, 1830, 1904, 1911, 1912, 1929, 1946, 1952, 1973, 1980, 1981, 1996, 2006, 2017, 2035, 2180, 2289, 2316, 2327, 2462, 2491, 2542, 2560, 2572, 2579, 2584, 2664, 2669, 2674, 2776, 2784, 2819, 2846, 2889, 2901, 2906, 2911, 2996, 2997 \file 27, 51 \fill 1713, 1739, 1747 \finalnamedelim 2888 \floatsep 2199, 2227, 2255 \font 1342 \fontdimen 1342 \fontsize 2048, 2055, 2064, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2085, 2092, 2101,

2110, 2111, 2112, 2113, 2114, 2115,
 2116, 2123, 2130, 2140, 2149,
 2150, 2151, 2152, 2153, 2154, 2155
 \footins 2198, 2226, 2254
 \footnotesep 2197, 2225, 2253
 \footnotesize 2064, 2101, 2160
 \footskip 2188

G

\gdef . 184, 185, 186, 187, 191, 192, 193,
 279, 280, 288, 289, 442, 446, 535,
 536, 537, 540, 543, 546, 547, 548,
 550, 584, 585, 587, 588, 589, 590,
 591, 592, 593, 594, 595, 596, 597,
 598, 599, 600, 601, 602, 619, 620,
 627, 631, 646, 647, 649, 650, 651,
 653, 654, 658, 660, 661, 666, 669,
 673, 674, 687, 691, 695, 698, 702,
 703, 706, 717, 719, 720, 729, 733,
 741, 744, 748, 752, 755, 756, 757,
 760, 763, 764, 765, 767, 801, 803,
 804, 805, 806, 807, 808, 809, 810,
 811, 812, 813, 814, 815, 816, 817,
 818, 819, 835, 836, 837, 838, 839,
 840, 841, 860, 861, 866, 881, 882,
 884, 886, 888, 889, 893, 897, 900,
 901, 906, 907, 913, 917, 918, 931,
 934, 936, 947, 950, 954, 955, 963,
 973, 974, 978, 979, 985, 1002, 1013,
 1024, 1028, 1031, 1032, 1041, 1044,
 1048, 1052, 1055, 1056, 1057, 1060,
 1063, 1064, 1065, 1067, 1101, 1103,
 1104, 1105, 1106, 1107, 1108, 1109,
 1110, 1111, 1112, 1113, 1114, 1115,
 1116, 1117, 1118, 1119, 1135, 1136,
 1137, 1138, 1139, 1140, 1141, 1160,
 1161, 1166, 1181, 1182, 1184, 1186,
 1188, 1189, 1193, 1197, 1200, 1201,
 1206, 1207, 1214, 1218, 1219, 1232,
 1235, 1237, 1248, 1251, 1255, 1256,
 1264, 1274, 1275, 1279, 1280, 1286,
 1304, 1315, 1326, 1330, 1335, 1338
 \geometry 2734, 2893, 2975, 3043
 \global 206, 212, 648, 652, 655, 736, 883,
 885, 887, 890, 1000, 1011, 1183,
 1185, 1187, 1190, 1302, 1313, 1403,
 1464, 1518, 1961, 2014, 2015, 2303

H

\hbext@ 2012, 2030

\hbox 1561, 1572, 1934, 1940, 1974
 \headheight 2185
 \headsep 2186
 \hfil .. 1935, 1942, 1947, 1949, 2012, 2030
 \hfill . 1634, 1707, 2469, 2751, 2797, 3007
 \hrule 1936, 1943
 \hskip 1828, 1881, 2029
 \hss 2012, 2030
 \Huge 2079, 2116, 2167
 \huge 2078, 2115, 2166
 \hypersetup 430, 1524, 1526, 1534

I

\if 39, 46, 50, 54, 61
 \if@restonecol 1978, 1981
 \if@twocolumn 1968, 1980, 2322
 \if@twoside 1937, 1948, 2172
 \ifcase 1989
 \ifcat 303
 \ifdim 1342, 1583, 1584
 \iffieldundef 2875
 \IfFileExists 451
 \ifin@ 308
 \ifluatex 10, 403, 1405
 \ifnum 191, 192, 198, 209, 553, 555, 557,
 559, 561, 563, 565, 567, 569, 571,
 573, 575, 770, 772, 774, 776, 778,
 780, 782, 784, 786, 788, 790, 792,
 1070, 1072, 1074, 1076, 1078, 1080,
 1082, 1084, 1086, 1088, 1090, 1092,
 1927, 2000, 2002, 2020, 2284, 2308
 \ifodd 1559, 1570
 \ifthesis@auto 263, 437
 \ifthesis@bibliography@ .. 1459, 1488
 \ifthesis@bibliography@included@ .
 1485, 1516, 1907, 2991
 \ifthesis@bibliography@loaded@ ..
 1483, 1489, 1906, 2860, 2990
 \ifthesis@blocks@assignment@
 67, 1753, 1758
 \ifthesis@blocks@assignment@hideIfDigital
 67
 \ifthesis@blocks@assignment@hideIfDigital@
 632, 867, 1167, 1755, 1780
 \ifthesis@blocks@titlePage@department@
 1639, 1663, 2662, 2899
 \ifthesis@blocks@titlePage@field@
 1641, 1670, 2670, 2907
 \ifthesis@blocks@titlePage@programme@
 1643, 1666, 2665, 2902

<code>\ifthesis@color@</code>	53, 1361, 1434, 1594, 1603	<code>\itshape</code>	1343
<code>\ifthesis@cover@</code>	54, 1374, 1610		
<code>\ifthesis@digital@</code>	54, 628, 633, 675, 707, 868, 919, 956, 1168, 1220, 1257, 1377, 1523, 1779		
<code>\ifthesis@english</code>	160, 408, 1726, 1743, 1830, 1854, 2811		
<code>\ifthesis@loaded</code>	22, 392, 396		
<code>\ifthesis@locale@inheritance</code>	172, 472		
<code>\ifthesis@microtype@</code>	53, 1364, 1399		
<code>\ifthesis@newtable@</code>	53, 1367, 1429		
<code>\ifthesis@palatino@</code>	53, 1358, 1410, 1418		
<code>\ifthesis@style@inheritance</code>	144, 460		
<code>\ifthesis@twoside@</code>	52, 1349, 1557, 1568, 1752		
<code>\ifthesis@woman</code>	79, 749, 802, 1049, 1102, 1241, 1830		
<code>\ifthesis@xeluatex</code>	56, 1403, 1409		
<code>\ifx</code>	2, 18, 36, 40, 47, 51, 75, 83, 149, 156, 166, 177, 267, 272, 274, 301, 326, 327, 335, 345, 356, 359, 360, 369, 378, 383, 399, 415, 418, 421, 468, 490, 497, 502, 519, 523, 603, 605, 607, 609, 611, 613, 721, 820, 822, 824, 826, 828, 830, 842, 844, 846, 848, 850, 852, 980, 986, 1003, 1005, 1014, 1016, 1120, 1122, 1124, 1126, 1128, 1130, 1142, 1144, 1146, 1148, 1150, 1152, 1281, 1287, 1305, 1307, 1316, 1318, 1461, 1463, 1470, 1474, 1478, 1510, 1676, 1678, 1710, 1759, 1772, 1778, 2458, 2460, 2482, 2525, 2557, 2567, 2575, 2581, 2770, 2778, 2846		
<code>\ifxetex</code>	10, 1404		
<code>\ifXKV@inpox</code>	325, 345		
<code>\ifXKV@knf</code>	318, 324		
<code>\ifXKV@pl</code>	312		
<code>\ifXKV@preset</code>	311		
<code>\ifXKV@st</code>	332		
<code>\immediate</code>	289, 441, 445		
<code>\in@</code>	307		
<code>\includegraphics</code>	1581, 1582, 1585		
<code>\includepdf</code>	1776		
<code>\input</code>	454, 1921		
<code>\intextsep</code>	2201, 2229, 2257		
<code>\isdot</code>	2865		
<code>\itemsep</code>	2062, 2071, 2099, 2108, 2137, 2147, 2360, 2369, 2375, 2390, 2399, 2405, 2420, 2429, 2435		
		K	
		<code>\KV@esp@def</code>	300, 310, 355, 361, 372
		<code>\KV@default</code>	370
		<code>\KV@errx</code>	365
		<code>\KV@prefix</code>	353, 358, 360
		<code>\KV@split</code>	354
		<code>\KV@thesis@abstract</code>	250
		<code>\KV@thesis@abstractEn</code>	253
		<code>\KV@thesis@declaration</code>	77
		<code>\KV@thesis@extra</code>	297
		<code>\KV@thesis@thanks</code>	257
		L	
		<code>\l@chapter</code>	2019
		<code>\l@figure</code>	2042
		<code>\l@paragraph</code>	2040
		<code>\l@part</code>	1999
		<code>\l@section</code>	2037
		<code>\l@subparagraph</code>	2041
		<code>\l@subsection</code>	2038
		<code>\l@subsubsection</code>	2039
		<code>\l@table</code>	2043
		<code>\labelsep</code>	2347, 2348, 2349, 2354, 2355, 2366, 2372, 2378, 2381, 2384, 2396, 2402, 2408, 2411, 2414, 2426, 2432, 2438, 2441, 2444
		<code>\labelwidth</code>	2355, 2366, 2372, 2378, 2381, 2384, 2396, 2402, 2408, 2411, 2414, 2426, 2432, 2438, 2441, 2444
		<code>\language</code>	511
		<code>\languagename</code>	156, 157, 418, 420
		<code>\LARGE</code>	2077, 2114, 2165
		<code>\Large</code>	2076, 2113, 2164, 2283, 2296
		<code>\large</code>	2075, 2112, 2163, 2332
		<code>\leavevmode</code>	1688, 1714, 1740, 1748, 2011, 2027, 2788
		<code>\leftmargin</code>	2060, 2069, 2097, 2106, 2135, 2145, 2353, 2358, 2365, 2371, 2377, 2380, 2383, 2388, 2395, 2401, 2407, 2410, 2413, 2418, 2425, 2431, 2437, 2440, 2443
		<code>\leftmargini</code>	2060, 2069, 2097, 2106, 2135, 2145, 2346, 2353, 2355, 2358, 2388, 2418
		<code>\leftmarginii</code>	2347, 2365, 2366, 2395, 2396, 2425, 2426
		<code>\leftmarginiii</code>	2348, 2371, 2372, 2401, 2402, 2431, 2432

<code>\leftmarginiv</code>	2349, 2377, 2378, 2407, 2408, 2437, 2438	<code>\newcommand</code>	73, 377, 455, 457, 1578, 1587, 1591, 1596, 1600
<code>\leftmarginv</code>	2350, 2380, 2381, 2410, 2411, 2440, 2441	<code>\newcount</code>	190, 197, 552, 769, 1069
<code>\leftmarginvi</code>	2351, 2383, 2384, 2413, 2414, 2443, 2444	<code>\newgeometry</code>	2755, 2763, 2928, 2936, 3048, 3055
<code>\leftskip</code>	2028, 2029	<code>\newif</code>	79, 144, 172, 263, 392, 1349, 1358, 1361, 1364, 1367, 1374, 1377, 1459, 1483, 1485, 1639, 1641, 1643, 1753, 1755, 1978
<code>\let</code>	98, 108, 227, 285, 286, 294, 328, 357, 362, 380, 384, 409, 412, 482, 485, 648, 652, 655, 736, 883, 885, 887, 890, 1000, 1011, 1183, 1185, 1187, 1190, 1302, 1313, 1370, 1371, 1372, 1373, 1402, 1403, 1427, 1428, 1442, 1443, 1450, 1451, 1516, 1544, 1579, 1580, 1605, 1606, 1607, 1608, 1631, 1720, 1730, 1738, 1746, 1768, 1805, 1807, 1809, 1811, 1813, 1815, 1817, 1819, 1821, 1822, 1824, 1858, 1860, 1862, 1864, 1866, 1868, 1870, 1872, 1874, 1875, 1877, 1930, 1931, 1945, 1951, 1953, 1954, 1955, 1985, 2053, 2090, 2128, 2169, 2362, 2392, 2422, 2790, 2794, 2806, 2815, 2827, 3004	<code>\newlength</code>	1579, 1580, 1631, 1805, 1807, 1809, 1811, 1813, 1815, 1817, 1819, 1821, 1822, 1824, 1858, 1860, 1862, 1864, 1866, 1868, 1870, 1872, 1874, 1875, 1877, 2794, 3004
<code>\listfigurename</code>	2782	<code>\newpage</code>	1562, 1565, 1573, 1576
<code>\listoffigures</code>	1373, 2783	<code>\newunit</code>	2877, 2885
<code>\listoftables</code>	1371, 2775	<code>\nobreak</code>	2013, 2030, 2286, 2290, 2297
<code>\listtablename</code>	2774	<code>\noexpand</code>	280, 289, 442, 446
<code>\LoadClass</code>	4	<code>\noindent</code>	1722, 1732, 1740, 1748, 1764, 1784, 1827, 1831, 1880, 1883, 2470, 2797, 2808, 2817, 2829, 3007
<code>\long</code>	14, 77, 78, 250, 251, 253, 254, 257, 258, 297, 298, 336, 354, 390, 528	<code>\normalfont</code>	2012
<code>\ltx@ifpackageloaded</code>	404, 405, 505, 508	<code>\normalsize</code>	2048, 2085, 2158, 2169, 2170, 2335, 2338, 2341, 2344
M		<code>\null</code>	1723, 1733
<code>\m@ne</code>	1927, 2285, 2309	<code>\numberline</code>	2313
<code>\makeatletter</code>	398	O	
<code>\makeatother</code>	448	<code>\oddsidemargin</code>	2173, 2177
<code>\MakeLowercase</code>	483	<code>\onecolumn</code>	1969, 1980
<code>\maketitle</code>	227	<code>\onehalfspacing</code>	2940, 2983, 2988, 3061
<code>\MakeUppercase</code>	486, 1985	<code>\or</code>	1991
<code>\marginparpush</code>	2211, 2239, 2267	<code>\overfullrule</code>	1356, 1357
<code>\marginparsep</code>	2181	P	
<code>\marginparwidth</code>	2175, 2179	<code>\p@</code>	1719, 1729, 2003, 2005, 2022, 2049, 2051, 2052, 2056, 2058, 2059, 2061, 2065, 2067, 2068, 2070, 2086, 2088, 2093, 2095, 2096, 2098, 2102, 2104, 2105, 2107, 2124, 2126, 2127, 2131, 2133, 2134, 2136, 2138, 2141, 2143, 2144, 2146, 2287, 2291, 2298, 2319, 2321, 2358, 2359, 2360, 2367, 2368, 2373, 2374, 2388, 2389, 2390, 2397, 2398, 2403, 2404, 2418, 2419, 2420, 2427, 2428, 2433, 2434, 2805, 2814
<code>\markboth</code>	1953	<code>\PageFont</code>	1947, 1949
<code>\markright</code>	1926		
<code>\month</code>	214		
<code>\multinamedelim</code>	2888		
N			
<code>\NeedsTeXFormat</code>	1339, 1345, 2447, 2494, 2545, 2586,		

<code>\pagenumbering</code>	2613, 2645, 2721, 2850, 2962, 3030
.. 1548, 1554, 1798, 2514, 2628, 2694, 2760, 2933, 2982, 3052, 3058	<code>\ps@headings</code>
<code>\pagestyle</code>	1954
1551, 1799, 2511, 2517, 2527, 2540, 2625, 2691, 2697, 2706, 2757, 2765, 2930, 2938, 2948, 2979, 2986, 3025, 3049, 3059	<code>\ps@myheadings</code>
<code>\par</code>	1955
1616, 1618, 1620, 1622, 1624, 1626, 1652, 1653, 1655, 1657, 1659, 1661, 1664, 1668, 1672, 1680, 1689, 1691, 1723, 1733, 2012, 2030, 2286, 2289, 2296, 2470, 2472, 2660, 2663, 2668, 2673, 2679, 2682, 2684, 2686, 2739, 2741, 2743, 2745, 2748, 2751, 2800, 2897, 2900, 2905, 2910, 2916, 2919, 2921, 2923, 3010	<code>\ps@thesisheadings</code> ...
<code>\paragraph</code>	1924, 1954, 1955
<code>\parbox</code>	1634
<code>\parfillskip</code>	1634, 1831, 1883
<code>\parindent</code>	2010, 2026
1552, 1800, 2009, 2025, 2281, 2294, 2342, 2512, 2518, 2626, 2692, 2698, 2758, 2766, 2931, 2939, 2976, 2980, 2987, 3050, 3060	R
<code>\parsep</code>	1634
2061, 2062, 2070, 2071, 2098, 2099, 2107, 2108, 2136, 2137, 2146, 2147, 2358, 2368, 2369, 2374, 2388, 2398, 2399, 2404, 2418, 2428, 2429, 2434	<code>\raisebox</code>
<code>\parskip</code> ...	1634
<code>\part</code>	1995, 2339
<code>\partopsep</code>	2310
2214, 2242, 2270, 2374, 2404, 2434	<code>\relax</code> 91, 92, 190, 197, 227, 285, 286, 294, 326, 354, 359, 373, 378, 468, 490, 497, 518, 520, 527, 552, 769, 1069, 1370, 1372, 1509, 1515, 1579, 1580, 1631, 1720, 1730, 1738, 1746, 1771, 1787, 1790, 1800, 1805, 1807, 1809, 1811, 1813, 1815, 1817, 1819, 1821, 1822, 1824, 1858, 1860, 1862, 1864, 1866, 1868, 1870, 1872, 1874, 1875, 1877, 1921, 1985, 1989, 2000, 2002, 2020, 2518, 2698, 2766, 2770, 2778, 2790, 2794, 2806, 2815, 2827, 3004
<code>\pdfstringdefDisableCommands</code> ...	2866, 2872, 2887
1984	<code>\renewbibtmacro</code>
<code>\penalty</code>	2866, 2872, 2887
2031	<code>\renewcommand</code> ...
<code>\pgfmathsetlength</code>	1958, 1966, 1988, 1999, 2019, 2037, 2038, 2039, 2040, 2041, 2042, 2043, 2048, 2055, 2064, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2085, 2092, 2101, 2110, 2111, 2112, 2113, 2114, 2115, 2116, 2158, 2159, 2160, 2161, 2162, 2163, 2164, 2165, 2166, 2167, 2862, 2868, 2888
1822, 1875	<code>\renewenvironment</code>
<code>\phantomsection</code>	1436, 1444, 1452
2773, 2781	<code>\RequirePackage</code>
<code>\printbibliography</code> 1516, 1517, 1910, 2995	5, 6, 7, 8, 9, 11, 13, 456, 1389, 1419, 1424
<code>\printfield</code>	2332, 2335, 2338, 2341, 2344
2878, 2887	<code>\revsdbnamepunct</code>
<code>\ProcessOptions</code>	2862
1386	<code>\rightmark</code>
<code>\protect</code>	1935, 1941
2312, 2319, 2321	<code>\rightskip</code>
<code>\ProvidesClass</code>	2009, 2025
1	<code>\rmfamily</code>
<code>\ProvidesFile</code>	1994
532, 618, 659, 663, 670, 684, 692, 699, 718, 726, 730, 738, 745, 857, 894, 903, 914, 928, 944, 951, 975, 1021, 1025, 1038, 1045, 1157, 1194, 1203, 1215, 1229, 1245, 1252, 1276, 1323, 1327, 1332, 2046, 2083, 2120	<code>\romannumeral</code>
<code>\ProvidesPackage</code>	1512, 1774
1340, 1344, 2448, 2495, 2546, 2587,	<code>\rowcolors</code>
	1437, 1445, 1453
	<code>\rule</code>
	1636, 2799, 3009
	S
	<code>\sc</code>
	1935, 1941
	<code>\scriptsize</code>
	2073, 2110, 2161
	<code>\secdef</code>
	1963, 1975, 2305
	<code>\section</code>
	1992, 2330
	<code>\selectfont</code>
	2048, 2055, 2064, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2085, 2092, 2101, 2110, 2111, 2112, 2113, 2114, 2115,

2116, 2124, 2130, 2140, 2149,	\textwidth 1825,
2150, 2151, 2152, 2153, 2154, 2155	1878, 1934, 1940, 2193, 2221, 2249
\selectlanguage 509	\the 199, 200, 203,
\setcounter 1553, 1797,	204, 212, 214, 303, 304, 578, 795, 1095
1915, 1918, 2513, 2627, 2693, 2707,	\thechapter 1928, 2288, 2311, 2313
2759, 2932, 2949, 2981, 3051, 3057	\thepage 279,
\setkeys 15, 352, 1468, 1531	281, 288, 290, 442, 446, 1947, 1949
\setlength 1356,	\thesis@ 479, 480, 549, 766, 1066
1357, 1431, 1432, 1433, 1633, 1821,	\thesis@@ 76, 480, 506, 1622, 1626,
1824, 1874, 1877, 2008, 2023, 2281,	1632, 1637, 1657, 1661, 1668, 1672,
2282, 2294, 2295, 2796, 2976, 3006	1675, 1704, 1713, 1721, 1739, 1764,
\setmainfont 1413	1784, 1803, 1806, 1808, 1810, 1812,
\setmathfont 1415	1814, 1816, 1818, 1820, 1829, 1833,
\setotherlanguage 470	1834, 1837, 1839, 1841, 1843, 1845,
\setsansfont 1414	1847, 1849, 2466, 2471, 2558, 2660,
\settoheight 1582	2667, 2672, 2741, 2745, 2748, 2791,
\settowidth 1581, 1632,	2795, 2797, 2800, 2807, 2828, 2897,
1805, 1807, 1809, 1811, 1814, 1815,	2904, 2909, 3001, 3005, 3007, 3010
1817, 1819, 1858, 1860, 1862, 1864,	\thesis@lower 26, 487
1867, 1868, 1870, 1872, 2795, 3005	\thesis@upper 26,
\setunit 2874, 2879, 2881, 2883	488, 1618, 1653, 2679, 2682, 2916, 2919
\sf 1618, 1622, 1624,	\thesis@abstract 249, 1722
1626, 1653, 1657, 1659, 1661, 1664,	\thesis@abstractEn 252, 1732
1668, 1672, 1675, 2660, 2663, 2667,	\thesis@academicYear 14, 206, 1846, 1898
2672, 2679, 2682, 2684, 2686, 2741,	\thesis@advisor 255,
2743, 2745, 2750, 2751, 2897, 2900,	1661, 1844, 1896, 2471, 2660, 2897
2904, 2909, 2916, 2919, 2921, 2923	\thesis@arg 82, 83, 382, 383
\sffamily 1546	\thesis@assignmentFiles 259, 1759, 1767
\singlespacing 2992	\thesis@author 8,
\skip 2198, 2226, 2254	88, 434, 1707, 1832, 1884, 2469, 2751
\slshape 1992	\thesis@author@head 8, 90
\small 2055, 2092, 2159	\thesis@author@tail 8, 92
\space 366, 2288, 2311, 2883	\thesis@autofalse 270
\string 161, 165, 531	\thesis@autotruer 263, 268
\subparagraph 1995, 2342	\thesis@bachelors 9, 103, 108, 605, 822,
\subsection 1914, 1917, 1994, 2333	844, 1003, 1014, 1122, 1144, 1305, 1316
\subsubsection 1994, 2336	\thesis@backend 1
	\thesis@basepath
 16, 23, 27, 31, 37, 57, 64, 69
T	\thesis@bfseries@old 61, 1544, 1546
\tableofcontents 1696	\thesis@bibFiles . 261, 1461, 1462, 1507
\tabu 1450	\thesis@bibliography@false 1460
\tabular 1427	\thesis@bibliography@included@false
\tabularx 1442 1486
\textbf . 1829, 1837, 1839, 1841, 1843,	\thesis@bibliography@included@true
1845, 1847, 1849, 1882, 1889, 1891, 1518
1893, 1895, 1897, 1899, 1901, 2471	\thesis@bibliography@load
\textfloatsep 2200, 2228, 2256 1483, 2457, 2504, 2555, 2596,
\textheight	2622, 2654, 2730, 2859, 2971, 3039
. 2191, 2192, 2219, 2220, 2247, 2248	\thesis@bibliography@loaded 59
\textit 1764, 1784	

\thesis@bibliography@loaded@false	\thesis@blocks@coverMatter
..... 1484	.. 1547 , 2477 , 2520 , 2562 , 2598 ,
\thesis@bibliography@loaded@true 1490	2630 , 2700 , 2832 , 2942 , 3014 , 3063
\thesis@bibliography@setup .. 1467 ,	\thesis@blocks@declaration .. 1701 ,
1493 , 2454 , 2501 , 2552 , 2593 ,	2463 , 2485 , 2538 , 2573 , 2607 , 2639 ,
2619 , 2651 , 2727 , 2856 , 2968 , 3036	2708 , 2785 , 2841 , 2950 , 2998 , 3073
\thesis@bibliography@sorting	\thesis@blocks@facultyLogo@color .
..... 58 , 1474 , 1475 , 1503 1591 , 1690
\thesis@bibliography@style	\thesis@blocks@facultyLogo@monochrome
..... 58 , 1470 , 1471 , 1502 1587
\thesis@bibliography@true	\thesis@blocks@frontMatter .. 1549 ,
..... 1464	2479 , 2509 , 2522 , 2564 , 2600 ,
\thesis@blocks@abstract	2624 , 2632 , 2689 , 2702 , 2753 , 2834 ,
.. 1717 , 2488 , 2533 , 2569 , 2604 ,	2926 , 2944 , 2977 , 3016 , 3046 , 3065
2636 , 2710 , 2838 , 2952 , 3020 , 3069	\thesis@blocks@keywords
\thesis@blocks@abstractEn 1736 , 2489 , 2711 , 2803 , 2953
..... 1725 , 2535 , 2571 , 2606 ,	\thesis@blocks@keywordsEn
2638 , 2713 , 2840 , 2955 , 3022 , 3071 1742 , 2714 , 2810 , 2956
\thesis@blocks@advisorSignature ..	\thesis@blocks@lof
..... 1630 , 1677 , 1679	1373 , 1700 , 2583 , 2769 , 2778 , 2779
\thesis@blocks@assignment	\thesis@blocks@logo
..... 1753 , 2536 , 2719 , 3072 1578 , 1590 , 1595 , 1599 , 1604
\thesis@blocks@assignment@false ..	\thesis@blocks@lot
..... 2459 , 2461	54 , 1370 ,
\thesis@blocks@assignment@hideIfDigital@false	1371 , 1699 , 2582 , 2768 , 2770 , 2771
..... 2508 , 2735 , 3045	\thesis@blocks@mainMatter
\thesis@blocks@assignment@hideIfDigital@true 19 , 52 , 283 , 286 , 1795 ,
..... 1756	2515 , 2695 , 2761 , 2934 , 2984 , 3053
\thesis@blocks@assignment@true . 1754	\thesis@blocks@postamble ... 18 , 52 ,
\thesis@blocks@bibEntry 1801 , 2530 ,	292 , 294 , 2492 , 2543 , 2580 , 2610 ,
2568 , 2603 , 2635 , 2837 , 3019 , 3068	2642 , 2717 , 2845 , 2959 , 3027 , 3076
\thesis@blocks@bibEntryEn	\thesis@blocks@preamble ... 18 , 52 ,
..... 1853 , 2531 ,	278 , 285 , 2476 , 2519 , 2561 , 2597 ,
2570 , 2605 , 2637 , 2839 , 3021 , 3070	2629 , 2699 , 2831 , 2941 , 3013 , 3062
\thesis@blocks@bibliography . 1905 ,	\thesis@blocks@seal
2493 , 2544 , 2585 , 2611 , 2643 ,	.. 1683 , 2481 , 2524 , 2566 , 2602 ,
2718 , 2847 , 2960 , 2989 , 3028 , 3077	2634 , 2704 , 2836 , 2946 , 3018 , 3067
\thesis@blocks@clear	\thesis@blocks@summary 2820 , 2846
1555 , 1611 , 1647 , 1684 , 1695 , 1702 ,	\thesis@blocks@tables
1711 , 1720 , 1730 , 1738 , 1746 , 1761 ,	54 , 54 ,
1770 , 1781 , 1796 , 1802 , 1855 , 1908 ,	1697 , 2490 , 2541 , 2578 , 2609 , 2641 ,
1959 , 1967 , 2464 , 2487 , 2510 , 2516 ,	2716 , 2767 , 2844 , 2958 , 3026 , 3075
2526 , 2532 , 2539 , 2690 , 2696 , 2705 ,	\thesis@blocks@thanks
2709 , 2712 , 2754 , 2762 , 2772 , 2780 ,	.. 1709 , 2486 , 2537 , 2574 , 2608 ,
2787 , 2790 , 2806 , 2815 , 2826 , 2827 ,	2640 , 2715 , 2842 , 2957 , 3023 , 3074
2927 , 2935 , 2947 , 2951 , 2954 , 2978 ,	\thesis@blocks@titlePage
2985 , 2993 , 2999 , 3024 , 3047 , 3054 1639 , 2480 , 2523 ,
\thesis@blocks@clearRight .. 1567 , 2534	2565 , 2601 , 2633 , 2659 , 2678 , 2703 ,
\thesis@blocks@cover	2835 , 2896 , 2915 , 2945 , 3017 , 3066
54 ,	\thesis@blocks@titlePage@department@true
1609 , 2478 , 2521 , 2563 , 2599 , 2631 , 1640
2701 , 2737 , 2833 , 2943 , 3015 , 3064	

\thesis@blocks@titlePage@field@false	2474, 2505, 2623, 2736, 2894	\thesis@czech@gender@koncovka	746, 748, 863, 864, 909, 938,
\thesis@blocks@titlePage@field@true	1642		940, 966, 968, 969, 988, 989, 995, 1034
\thesis@blocks@titlePage@programme@false	2475, 2506, 2657	\thesis@czech@idTitle	812, 893
\thesis@blocks@titlePage@programme@true	1644	\thesis@czech@keywordsTitle	808, 890
\thesis@blocks@toc	1694, 1698, 2483, 2528, 2576, 2843	\thesis@czech@semester	765
\thesis@blocks@universityLogo@color	1600, 1651	\thesis@czech@spring	763
\thesis@blocks@universityLogo@monochrome	1596, 1616	\thesis@czech@summaryTitle	811
\thesis@color@false	1362	\thesis@czech@thanksTitle	809
\thesis@color@setup	1530, 1537, 2449, 2496, 2547, 2588, 2614, 2646, 2722, 2851, 2963, 3031	\thesis@czech@typeName	819, 1001, 1002
\thesis@color@true	1363	\thesis@czech@typeName@akuzativ	746, 841, 1012, 1013
\thesis@cover@false	1375	\thesis@czech@typeName@akuzativ@bachelors	836, 845
\thesis@cover@true	1376	\thesis@czech@typeName@akuzativ@doctoral	839, 851
\thesis@czech@abstractTitle	807, 897, 934, 950, 1031, 1044	\thesis@czech@typeName@akuzativ@masters	837, 847
\thesis@czech@advisorSignature	803	\thesis@czech@typeName@akuzativ@proposal	838, 849, 974
\thesis@czech@advisorTitle	805, 885	\thesis@czech@typeName@akuzativ@rigorous	840, 853
\thesis@czech@assignment	757, 866, 918, 955	\thesis@czech@typeName@akuzativ@sempaper	835, 843
\thesis@czech@authorSignature	801	\thesis@czech@typeName@akuzativ@super	1011, 1019
\thesis@czech@authorTitle	806, 883	\thesis@czech@typeName@bachelors	814, 823
\thesis@czech@bib@academicYear	888	\thesis@czech@typeName@doctoral	817, 829
\thesis@czech@bib@advisor	885	\thesis@czech@typeName@masters	815, 825
\thesis@czech@bib@author	883	\thesis@czech@typeName@proposal	816, 827, 973
\thesis@czech@bib@field	887	\thesis@czech@typeName@rigorous	818, 831
\thesis@czech@bib@keywords	890	\thesis@czech@typeName@sempaper	813, 821
\thesis@czech@bib@pages	882, 889	\thesis@czech@typeName@super	1000, 1008
\thesis@czech@bib@programme	886	\thesis@czech@universityName	755, 860
\thesis@czech@bib@thesisTitle	884	\thesis@date	13, 184, 214, 215
\thesis@czech@bib@title	881	\thesis@day	13, 187, 551, 768, 1068
\thesis@czech@csquotesStyle	752	\thesis@declaration	76, 1705, 2467, 2792, 3002
\thesis@czech@declaration	760, 861, 907, 936, 963, 985, 1032	\thesis@def	73, 93, 94, 95, 99, 117, 120, 123, 126, 129, 132, 223, 231, 237, 243, 249, 252, 255
\thesis@czech@declarationTitle	810	\thesis@def@extra	377, 935, 1236, 1477, 2820
\thesis@czech@departmentName	979		
\thesis@czech@facultyLongName	901		
\thesis@czech@facultyName	756, 900, 906, 917, 931, 947, 954, 978, 1024, 1028, 1041		
\thesis@czech@fall	764		
\thesis@czech@fieldTitle	804, 887, 913		
\thesis@czech@formattedDate	767		

<code>\thesis@department</code>	117, 721, 724, 980, 983, 986, 1281, 1284, 1287, 1605, 2557, 2567, 2575, 2581	<code>\thesis@english@facultyName</code>	536, 660, 666, 673, 687, 695, 702, 719, 729, 733, 741, 1885
<code>\thesis@department@name</code>	1605, 1664, 1835, 2558, 2663, 2686, 2900, 2923	<code>\thesis@english@fall</code>	547
<code>\thesis@departmentEn</code>	120, 1606	<code>\thesis@english@fieldTitle</code>	587, 652, 669
<code>\thesis@departmentEn@name</code>	1606, 1887, 2559	<code>\thesis@english@formattedDate</code> ...	550
<code>\thesis@departments@kisk</code>	721, 980, 986, 1281, 1287, 2556, 2557, 2567, 2575, 2581	<code>\thesis@english@idTitle</code>	595, 658
<code>\thesis@digital@false</code>	1383	<code>\thesis@english@keywordsTitle</code> ...	591, 655, 1747, 2816
<code>\thesis@digital@true</code>	1380	<code>\thesis@english@semester</code>	548
<code>\thesis@doctoral</code>	9, 106, 611, 828, 850, 1128, 1150, 2460, 2846	<code>\thesis@english@spring</code>	546
<code>\thesis@empty</code>	18, 75	<code>\thesis@english@summaryTitle</code>	594
<code>\thesis@english@abstractTitle</code> ...	590, 691, 698, 744, 1731	<code>\thesis@english@thanksTitle</code>	592
<code>\thesis@english@advisorSignature</code> .	585	<code>\thesis@english@typeName</code>	602
<code>\thesis@english@advisorTitle</code>	586, 588	<code>\thesis@english@typeName@bachelors</code>	597, 606
<code>\thesis@english@advisorTitleEn</code> ..	736	<code>\thesis@english@typeName@doctoral</code>	600, 612
<code>\thesis@english@assignment</code>	537, 627, 631, 674, 703, 706	<code>\thesis@english@typeName@masters</code> .	598, 608
<code>\thesis@english@authorSignature</code> ..	584	<code>\thesis@english@typeName@proposal</code>	599, 610, 717
<code>\thesis@english@authorTitle</code>	589, 648, 1882	<code>\thesis@english@typeName@rigorous</code>	601, 614
<code>\thesis@english@bib@academicYear</code> .	653, 1869, 1897	<code>\thesis@english@typeName@sempaper</code>	596, 604
<code>\thesis@english@bib@advisor</code>	650, 736, 1867, 1895	<code>\thesis@english@universityName</code> ..	535, 619, 1886
<code>\thesis@english@bib@author</code> .	648, 1859	<code>\thesis@exists</code>	450, 454, 458
<code>\thesis@english@bib@field</code>	652, 1865, 1893	<code>\thesis@extra@advisorCsGenitiv</code> ..	939
<code>\thesis@english@bib@keywords</code>	655, 1873, 1901	<code>\thesis@extra@advisorSkGenitiv</code> .	1240
<code>\thesis@english@bib@pages</code>	647, 654, 1871, 1899	<code>\thesis@extra@bibliography</code> .	1478, 1481
<code>\thesis@english@bib@programme</code> ..	651, 1863, 1891	<code>\thesis@extra@KV@prefix</code>	295, 360
<code>\thesis@english@bib@thesisTitle</code> ..	649, 1861, 1889	<code>\thesis@extra@summary</code>	2829
<code>\thesis@english@bib@title</code> ..	646, 1856	<code>\thesis@extra@XKV@fams</code>	296, 335
<code>\thesis@english@csquotesStyle</code> ...	543	<code>\thesis@faculty</code>	114, 138, 141, 476
<code>\thesis@english@declaration</code> .	540, 620	<code>\thesis@facultyLogo</code> ...	138, 1589, 1593
<code>\thesis@english@declarationTitle</code> .	593	<code>\thesis@field</code>	129, 1607, 1842, 2684
<code>\thesis@english@departmentName</code> ..	720, 2559	<code>\thesis@field@name</code>	1607, 1672, 2673, 2910
<code>\thesis@english@facultyLongName</code> ..	661	<code>\thesis@fieldEn</code>	132, 1608, 1894
		<code>\thesis@fieldEn@name</code>	1608
		<code>\thesis@head</code>	26, 91, 489, 495
		<code>\thesis@id</code>	99
		<code>\thesis@input</code>	453, 471, 473, 475
		<code>\thesis@keywords</code> ...	237, 240, 435, 1740
		<code>\thesis@keywordsEn</code>	243, 246, 1748
		<code>\thesis@load</code>	22, 394
		<code>\thesis@loadedfalse</code>	392
		<code>\thesis@loadedtrue</code>	397

<code>\thesis@locale</code>	135, 138, 154, 165, 277, 291, 399, 400, 401, 421, 424, 480, 487, 488, 504, 509, 511	<code>\thesis@proposal</code>	9, 105, 609, 826, 848, 1126, 1148, 1678, 2482, 2525
<code>\thesis@locale@inheritance</code>	172	<code>\thesis@ptsize</code> ..	1346, 1347, 1348, 1921
<code>\thesis@locale@inheritancefalse</code> ..	180	<code>\thesis@require</code>	406, 429, 455, 458, 1388, 1390, 1391, 1392, 1393, 1394, 1395, 1396, 1397, 1398, 1400, 1411, 1412, 1420, 1421, 1422, 1423, 1492, 1499, 1500, 1522, 2655, 2731, 2732, 2733, 2890, 2891, 2892, 2972, 2973, 2974, 3040, 3041, 3042
<code>\thesis@locale@inheritancetrue</code>	172, 178	<code>\thesis@requireIfExists</code> 457, 461, 462, 465
<code>\thesis@localepath</code> ...	31, 471, 473, 475	<code>\thesis@requireLocale</code> ..	401, 466, 1387
<code>\thesis@logopath</code>	23, 1589, 1593, 1598, 1602	<code>\thesis@requireStyle</code>	416, 459
<code>\thesis@lower</code>	25, 481, 487, 862, 908, 937, 964, 994, 1033, 1162, 1208, 1238, 1265, 1295	<code>\thesis@rewind</code> ..	1751, 1763, 1776, 1783
<code>\thesis@male</code>	81, 83	<code>\thesis@rigorous</code>	9, 107, 613, 830, 852, 1130, 1152, 1676, 2458
<code>\thesis@masters</code> ...	9, 104, 607, 824, 846, 1005, 1016, 1124, 1146, 1307, 1318	<code>\thesis@season</code> 13, 191, 192, 193, 549, 766, 1066
<code>\thesis@microtype@false</code>	1366	<code>\thesis@seasonYear</code>	14, 212, 549, 766, 1066
<code>\thesis@microtype@true</code>	1365	<code>\thesis@selectLocale</code>	26, 277, 291, 424, 503, 1727, 1744, 2812
<code>\thesis@month</code>	13, 186, 190, 552, 769, 1069	<code>\thesis@sempaper</code> 9, 102, 603, 820, 842, 1120, 1142
<code>\thesis@newtable@false</code>	1369	<code>\thesis@slovak@abstractTitle</code> 1107, 1197, 1235, 1251, 1338
<code>\thesis@newtable@old</code> ...	57, 1427, 1439	<code>\thesis@slovak@advisorSignature</code> .	1103
<code>\thesis@newtable@oldtabu</code>	57, 1450, 1455	<code>\thesis@slovak@advisorTitle</code>	1105, 1185
<code>\thesis@newtable@oldx</code> ..	57, 1442, 1447	<code>\thesis@slovak@assignment</code> 1057, 1166, 1219, 1256
<code>\thesis@newtable@true</code>	1368	<code>\thesis@slovak@authorSignature</code> .	1101
<code>\thesis@pages</code>	26, 442, 446, 502, 1848, 1900	<code>\thesis@slovak@authorTitle</code> .	1106, 1183
<code>\thesis@pages@postamble</code> .	274, 288, 290	<code>\thesis@slovak@bib@academicYear</code> .	1188
<code>\thesis@pages@preamble</code> 272, 279, 281, 1848, 1900	<code>\thesis@slovak@bib@advisor</code>	1185
<code>\thesis@palatino@false</code>	1360	<code>\thesis@slovak@bib@author</code>	1183
<code>\thesis@palatino@true</code>	1359	<code>\thesis@slovak@bib@field</code>	1187
<code>\thesis@parseAuthor</code>	8, 88, 97, 98	<code>\thesis@slovak@bib@keywords</code> ...	1190
<code>\thesis@parseDate</code>	13, 182, 215, 219	<code>\thesis@slovak@bib@pages</code> ...	1182, 1189
<code>\thesis@patch</code>	513	<code>\thesis@slovak@bib@programme</code> ...	1186
<code>\thesis@patch@action</code>	515, 521	<code>\thesis@slovak@bib@thesisTitle</code> .	1184
<code>\thesis@patch@arg</code>	517, 519, 523	<code>\thesis@slovak@bib@title</code>	1181
<code>\thesis@patch@next</code>	516, 520, 522, 524, 526	<code>\thesis@slovak@csquotesStyle</code> ...	1052
<code>\thesis@patch@relax</code>	518, 523	<code>\thesis@slovak@declaration</code> 1060, 1161, 1207, 1237, 1264, 1286
<code>\thesis@patch@versions</code>	514, 527	<code>\thesis@slovak@declarationTitle</code> .	1110
<code>\thesis@place</code>	220, 1626, 1675, 2745, 2750, 2797, 3007	<code>\thesis@slovak@departmentName</code> ..	1280
<code>\thesis@placeholder@extra</code>	379, 381, 385	<code>\thesis@slovak@facultyLongName</code> .	1201
<code>\thesis@placeholder@extra@bibliography</code>	1479	<code>\thesis@slovak@facultyName</code> 1056, 1200, 1206, 1218, 1232, 1248, 1255, 1279, 1326, 1330, 1335
<code>\thesis@placeholder@extra@summary</code>	2821		
<code>\thesis@postamble</code>	18, 287, 440		
<code>\thesis@preamble</code>	18, 276, 438		
<code>\thesis@printbibliography@old</code>	59, 1516, 1519		
<code>\thesis@programme</code> 123, 1668, 1840, 2668, 2905, 2921		
<code>\thesis@programmeEn</code>	126, 1892		

\thesis@slovak@fall	1064	\thesis@stylepath	27, 461, 462, 465, 1921
\thesis@slovak@fieldTitle	1104, 1187, 1214	\thesis@subdir	25, 29, 33, 35
\thesis@slovak@formattedDate	1067	\thesis@tail	26, 92, 496, 501
\thesis@slovak@gender@koncovka	1046, 1048, 1164, 1210, 1239, 1267, 1269, 1270, 1289, 1290, 1297	\thesis@TeXkeywords	240, 1850, 2808
\thesis@slovak@idTitle	1112, 1193	\thesis@TeXkeywordsEn	246, 1902, 2817
\thesis@slovak@keywordsTitle	1108, 1190	\thesis@TeXtitle	228, 1620, 1655, 2739
\thesis@slovak@semester	1065	\thesis@TeXtitleEn	234
\thesis@slovak@spring	1063	\thesis@thanks	257, 1710, 1714
\thesis@slovak@summaryTitle	1111	\thesis@title	223, 228, 433, 937, 1238, 1838
\thesis@slovak@thanksTitle	1109	\thesis@titleEn	231, 234, 1890
\thesis@slovak@typeName@akuzativ	1119, 1303, 1304	\thesis@titlePage@footnotesize	76, 2140, 2160
\thesis@slovak@typeName@akuzativ@bachelors	1046, 1141, 1314, 1315	\thesis@titlePage@Huge	76, 1620, 1655, 2155, 2167, 2739, 2748
\thesis@slovak@typeName@akuzativ@doctoral	1136, 1145	\thesis@titlePage@Huge	76, 2154, 2166
\thesis@slovak@typeName@akuzativ@masters	1137, 1147	\thesis@titlePage@LARGE	
\thesis@slovak@typeName@akuzativ@proposal	1138, 1149, 1275	\thesis@titlePage@Large	
\thesis@slovak@typeName@akuzativ@rigorous	1140, 1153	\thesis@titlePage@large	
\thesis@slovak@typeName@akuzativ@sempaper	1135, 1143	\thesis@titlePage@normalsize	
\thesis@slovak@typeName@akuzativ@super	1313, 1321	\thesis@titlePage@scriptsize	
\thesis@slovak@typeName@bachelors	1114, 1123	\thesis@titlePage@small	76, 2130, 2159
\thesis@slovak@typeName@doctoral	1117, 1129	\thesis@titlePage@tiny	76, 2150, 2162
\thesis@slovak@typeName@masters	1115, 1125	\thesis@twoside@false	1351
\thesis@slovak@typeName@proposal	1116, 1127, 1274	\thesis@twoside@true	1353
\thesis@slovak@typeName@rigorous	1118, 1131	\thesis@type	102, 603, 605, 607, 609, 611, 613, 616, 820, 822, 824, 826, 828, 830, 833, 842, 844, 846, 848, 850, 852, 855, 1003, 1005, 1014, 1016, 1120, 1122, 1124, 1126, 1128, 1130, 1133, 1142, 1144, 1146, 1148, 1150, 1152, 1155, 1305, 1307, 1316, 1318, 1676, 1678, 2458, 2460, 2482, 2525, 2846
\thesis@slovak@typeName@sempaper	1113, 1121	\thesis@university	23, 111, 141, 462, 463, 473, 475
\thesis@slovak@typeName@super	1302, 1310	\thesis@universityLogo	135, 1598, 1602
\thesis@slovak@universityName	1055, 1160	\thesis@upper	25, 484, 488, 1624, 1659, 2743
\thesis@style	141, 415, 416	\thesis@version	1, 436
\thesis@style@inheritance	144	\thesis@version@number	519
\thesis@style@inheritancefalse	152	\thesis@womanfalse	79, 84
\thesis@style@inheritancetrue	144, 150	\thesis@womantrue	86

<code>\thesis@xpatch</code>	2671, 2683, 2685, 2687, 2740, 2742,
.. 528 , 2659 , 2678 , 2737 , 2896 , 2915	2898 , 2903 , 2908 , 2920 , 2922 , 2924
<code>\thesis@year</code>	
.. 13 , 185 , 197 , 581 , 798 , 1098 , 2751	
<code>\thesisload</code>	392
<code>\thesislong</code>	390
<code>\thesissetup</code>	14
<code>\thispagestyle</code> ...	1560 , 1571 , 1614 ,
1649 , 1686 , 1763 , 1783 , 1960 , 2302	
<code>\tiny</code>	2074 , 2111 , 2162
<code>\title</code>	15 , 226
<code>\toc@font</code>	1988
<code>\topmargin</code>	2183
<code>\topsep</code>	2061 ,
2070 , 2098 , 2107 , 2138 , 2146 , 2359 ,	
2367 , 2373 , 2375 , 2389 , 2397 ,	
2403 , 2405 , 2419 , 2427 , 2433 , 2435	
<code>\topskip</code>	2187 , 2192 , 2220 , 2248
<code>\twocolumn</code>	1981
<code>\typeout</code>	2311
U	
<code>\undefined</code>	2 , 156 , 272 ,
274 , 502 , 1461 , 1470 , 1474 , 1710 , 1759	
<code>\usebibmacro</code>	2873 , 2880 , 2882 , 2884
V	
<code>\value</code>	1559 , 1570
<code>\vbox</code>	1933 , 1939
<code>\vfil</code>	1723 , 1733 , 1974 , 2472
<code>\vfill</code> ..	1619 , 1625 , 1654 , 1660 , 1674 ,
1689 , 1691 , 2470 , 2675 , 2680 , 2738 ,	
2744 , 2747 , 2749 , 2788 , 2912 , 2917	
<code>\vskip</code>	1706 ,
1719 , 1729 , 1936 , 1943 , 2287 , 2291 ,	
2298 , 2468 , 2793 , 2805 , 2814 , 3003	
<code>\vspace</code>	1617 , 1621 ,
1623 , 1652 , 1656 , 1658 , 1662 , 1667 ,	
1671 , 1713 , 1739 , 1747 , 2661 , 2666 ,	
W	
<code>\widowpenalty</code>	1528
<code>\write</code>	280 , 289 , 441 , 445
X	
<code>\x</code>	1402 , 1403 , 1405 , 1406
<code>\XKV@addtolist@o</code>	333
<code>\XKV@documentclass</code>	345
<code>\XKV@doxs</code>	326 , 330
<code>\XKV@err</code>	304 , 339
<code>\XKV@fams</code>	313 , 318 , 335 , 340
<code>\XKV@for@eo</code>	313
<code>\XKV@g@keyname</code>	299
<code>\XKV@knftrue</code>	309
<code>\XKV@makehd</code>	314 , 319
<code>\XKV@na</code>	307
<code>\XKV@rm</code>	333
<code>\XKV@s@tk@ys</code>	298
<code>\XKV@s@tk@ys@</code>	311 , 315 , 320
<code>\XKV@tempa</code>	310
<code>\XKV@testclass</code>	345
<code>\XKV@tfam</code>	313 , 314 , 318 , 319
<code>\XKV@tkey</code>	299 , 300 , 301 , 307 , 328 , 337 , 339
<code>\XKV@toks</code>	302 , 303 , 304
<code>\XKV@useoption</code>	346
<code>\XKV@whilist</code>	318
<code>\xpatchcmd</code>	529
Y	
<code>\year</code>	214
Z	
<code>\z@</code>	1342 ,
1961 , 2009 , 2025 , 2051 , 2058 , 2067 ,	
2089 , 2095 , 2104 , 2126 , 2133 , 2143 ,	
2281 , 2282 , 2294 , 2295 , 2303 , 2330 ,	
2333 , 2336 , 2339 , 2374 , 2404 , 2434	

Change History

v0.0

General: bachelor project of Daniel
Marek under supervision of
Petr Sojka [1](#)

v0.0a

General: changes by Jan Pavlovič to
allow fithesis being backend of
docbook based system for

	thesis writing	1		\MainMatter should be placed after \tablesofcontents [PS] . . .	1
v0.1	General: new release, documentation editing (CZ only, sorry) [PS]	1	v0.2.08	General: add change of University name [JP]	1
v0.1a	General: minor documentation changes (CZ only, sorry) [PS] . . .	1	v0.2.09	General: add EN version of University name [JP]	1
v0.1b	General: change of default size (11pt→12pt) [JP]	1	v0.2.10	General: fix EN name of Acknowledgement [JP]	1
v0.1c	General: default values of \facultyname and \@thesissubtitle set for backward compatibility) [PS]	1	v0.2.11	General: fix missing fi-logo.mf [JP,PS]	1
v0.1d	General: removed def schapter from fit1*.clo [JP]	1	v0.2.12	General: Licence change to the LPPL [JP]	1
v0.1e	General: add Brno to MU title [JP] . .	1	v0.2.12a	General: fork fithesis2 by Mr. Filipčík and Janoušek; cf. http://github.com/liskin/ fithesis	1
v0.1f	General: add documentation for hyperref [JP]	1	v0.3.00	General: fi logo is no longer special-cased (added eps and PDF), \thesislogopath added to set the logo directory path, \thesiscolor added to enable colorful typo elements [VN]	1
v0.1g	General: change of default size (12pt→11pt) [JP]	1	v0.3.01	General: documentation now uses babel and cmap packages. the entire file was transcoded into utf8, \thesiscolor was replaced by color class option, added PDF metadata stamping support [VN]	1
v0.2.00	General: add sk lang [JP, Peter Cerensky] set default cls class to rapport3 [JP]	1	v0.3.02	General: PDF metadata stamping added for \thesistitle and \thesisstudent [VN]	1
v0.2.01	General: add subsection to toc [JP]	1	v0.3.03	General: Small fixes (added \relax at \MainMatter), generating both fithesis.cls (obsolete, loading fithesis2.cls) and fithesis2.cls, minor doc edits, version numbering of .clo fixed, switch to utf8 and ensuring that .dtx compiles.	
v0.2.02	General: fix encoding bug [JP]	1			
v0.2.03	General: fix title spacing [PS, JP] . .	1			
v0.2.04	General: fix SK declaration [Peter Cerensky, JP]	1			
v0.2.05	General: add English abstract [JP] . .	1			
v0.2.06	General: fix : behind Advisor [JP] . .	1			
v0.2.07	General: escape all Czech letters [JP] babel is used instead of stupid package czech [JP]				

	Documentation adjusted to the status quo, added link to discussion forum (backport of v0.2.14) [PS]	1		reported at the new fithesis discussion forum (-ti, eco→econ, implicit twocolumn, example extended (font setup), etc.). [PS] (backport of v0.2.17)	1
v0.3.04	General: Import the url package to allow for the use of \url within the documentation. (backport of v0.2.15@r13) [VN]	1		v0.3.09	General: A complete refactoring of the class. The class was decomposed into a base class, locale files and style files. [VN]
v0.3.05	General: Added support for change typesetting. Restructured the code to make it more amenable to literal programming. Added support for \CodeLineIndex typesetting. Added information about the usage of fithesis1 and fithesis2 on the FI unix machines. (backport of v0.2.16) [VN] Minor changes throughout the text, added a link to the the fithesis forums [PS] (backport of v0.2.15@r14:15)	1		v0.3.10	General: Fixed a typo in the technical documentation. Updated the <i>Advanced usage</i> chapter of the user guide. The required packages listed in Section 2.2 of the user guide are now always correct. Adjusted the footer spacing in the styles of econ and fi. Added <i>Advanced usage</i> chapter to the user guide. Added the description of basic options into the user guide. Added the table and oldtable options. Added the type field to the guide for completeness. [VN]
v0.3.06	General: Added the colorx package and the base colors for each faculty. If the color option is specified, the tabular environment gets redefined and uses the faculty colors to color alternating table rows to improve readability. The hyperref links in the e-version are now likewise colored according to the chosen faculty, in this case regardless of the presence of the color option. Dropped the support for typesetting theses outside MU. [VN]	1		v0.3.11	General: Added hyphenation into the technical documentation. Fixed an unterminated group. Polished the text of the guide. Added the palatino and nopalatino options. Stylistic changes to the text of the technical documentation. \thesis@subdir is now robust against relative paths. Accounted for French spacing in the guide. Fixed the thesis@english@facultyName string. Documentation refinements. [VN]
v0.3.07	General: Replaced the \thesiswoman command with \thesisgender. [VN]	1		v0.3.12	General: The subsections and subsubsections now use the correct tocdepth. [VN]
v0.3.08	General: Fixed a non-terminated \if condition. [VN] (backport of v0.2.18)			v0.3.13	General: Fixed an inconsistency in the example code. Removed an
	Fixed mostly documentation errors				

extraneous <code>\thesis@blocks@clear</code> block withing the definition of <code>\thesis@blocks@frontMatter</code> in the fss style file. Added comments, fixed clubs and widows and removed text overflows within the user guides. Adjusted the colors of various style files. Removed the trailing dot in the bibliographic identification within the med and ped style files. Fixed a typo within the technical documentation. Fixed the twoside alignment of the <code>\thesis@blocks@bibEntry</code> and the <code>\thesis@blocks@bibEntryEn</code> blocks within the sci style file. The <code>\thesis@blocks@assignment</code> block no longer clears a page when nothing is inserted. It is also no longer hard-coded to be hidden for rigorous theses. Instead, the <code>\ifthesis@blocks@assignment</code> conditional can be set either by the subsequently loaded style files or by the user. So far, only the fi and sci style files set the conditional. [VN] 1	lower camelcasing of the rest of the keys. Added further description regarding the use of the assignment key. [VN] 1
v0.3.14 General: Updated the documentation. [VN] 1	v0.3.16 General: Clubs and widows are now set to be infinitely bad. The assignment key has weaker, but more robust semantics now. [VN] 1
v0.3.15 General: Renamed <code>\thesis@requireStyle</code> to <code>\thesis@requireWithOptions</code> and moved the style loader from the <code>\thesis@load</code> routine to a new <code>\thesis@requireStyle</code> macro to make the semantics of <code>\thesis@requireLocale</code> and <code>\thesis@requireStyle</code> more similar. Changed the basepath, logopath, localepath and stylepath keys to match the	v0.3.17 General: Changed a forgotten <code>\thesis@lower{...}</code> invocation in the definition of <code>\thesis@czech@declaration</code> for the Faculty of Arts into <code>\thesis@lower{czech...}</code> , so that the macro always expands to the correct output regardless of the current locale. This is merely a matter of consistency, since the style file of the Faculty of Arts only uses Czech strings within the Czech locale. Removed an extraneous comment. Fixed a unit test. Fixed a changelog entry. [VN] . . . 1
	v0.3.18 General: A bulk of changes required to submit the document class to CTAN: Changed the structure of the output <code>fithesis3.ctan.zip</code> archive. Updated the license notice. Added a README file. Canonicalized a url within the user guides. Renamed the root directory from <code>fithesis3/</code> to <code>fithesis/</code> . Refactored the makefiles. Added developer example files. Renamed <code>docstrip.cfg</code> to <code>LICENSE.tex</code> to better describe its role. The <code>fithesis.dtx</code> file now generates a <code>VERSION.tex</code> file containing the version of the package, when it's being typeset. Flattened the <code>logo/</code> directory structure. [VN] 1

v0.3.19	General: Updated the license. Added the <code>fithesis-</code> prefix to locale files. Proof-read and updated the documentation. Encapsulated the <code>localeInheritance</code> and <code>styleInheritance</code> setters. Added the <code>\thesis@selectLocale{...}</code> , which acts as a replacement for <code>\def\thesis@locale{...}</code> , which also switches hyphenation patterns. The macro definitions inside locale files are now global to account for the fact that it now makes sense to include locale files on-site (and therefore possibly inside a group) using the <code>\thesis@selectLocale</code> . The class files are now generated using the XeTeX engine, which preserves the characters outside ASCII. [VN] 1	<code>\thesis@backend</code> tunable. The hyphenation pattern switching now uses <code>polyglossia</code> instead of crude <code>\language</code> switching whenever possible. Added the opt-out <code>microtype</code> class option, which loads the <code>microtypographic</code> extension. The <code>\thesis@locale@summer</code> and <code>@winter</code> locale macros were renamed to <code>@spring</code> and <code>@fall</code> . The <code>\thesis@parseDate</code> now uses more realistic month ranges to set <code>\thesis@season</code> and <code>\thesis@academicYear</code> . Removed the extraneous indent in the <code>\thesis@blocks@declaration</code> macro definition within the <code>style/mu/fithesis-fi.sty</code> style file. <code>\paragraphs</code> are not included in the table of contents by default. The <code>table</code> class option now supports the <code>tabu</code> environment. The list of tables and the list of figures now have an entry in the table of contents for the <code>style/mu/fithesis-econ.sty</code> style file. [VN] 1
v0.3.20	General: Removed an extraneous <code>\hypersetup</code> option to eliminate a warning. Performed several minor Makefile updates. Updated the technical documentation. [VN] 1	v0.3.25 General: The example documents from the <code>example</code> directory are now a part of the CTAN archive. Additional information were inserted into the guide and to the example files. [VN] .. 1
v0.3.21	General: Fixed an invalid font name. [VN] 1	
v0.3.22	General: Updated the link colors in the style of the Faculty of Economics and Administration at the Masaryk University in Brno and fixed the title page leading in the style of the Faculty of Science at the Masaryk University in Brno. [VN] 1	v0.3.26 General: Updated the example documents and the user guide. Fixed a typo in the description of <code>\thesis@season</code> . [VN] 1
v0.3.23	General: Fixed a typo in the Slovak locale. [VN] 1	v0.3.27:1 General: Fixed a typo in the guide. Added a compatibility layer for <code>\title</code> , <code>\author</code> , and <code>\maketitle</code> . Minor changes of the documentation. [VN] 1
v0.3.24	General: Added the	v0.3.27:2 General: <code>\thesis@selectLocale</code> is

no longer performed globally for the entire document during <code>\thesis@load</code> (effectively overriding the user's hyphenation settings, if Babel's or Polyglossia's <code>\languagename</code> differs from <code>\thesis@locale</code>). Instead, <code>\thesis@preamble</code> and <code>@postamble</code> now locally switch the locale and expand <code>\thesis@blocks@preamble</code> and <code>@postamble</code> , which are the new redefinables. Since this breaks the behaviour of <code>\thesis@blocks@mainMatter</code> , whose effects would also be local, <code>@mainMatter</code> is now executed directly by <code>\thesis@preamble</code> after closing the group and becomes a new part of the interface between the class and the style files. [VN] 1	argument and the <code>\thesis@requireWithOption</code> command has become <code>\thesis@requireIfExists</code> . [VN] 1
v0.3.27:3 General: As a preparation for the future inclusion of bibliography support, the <code>csquotes</code> package is loaded, <code>@csquotesStyle</code> is a new part of the locale interface that sets the <code>csquotes</code> style of a locale, and <code>\thesis@selectLocale</code> now switches the <code>csquotes</code> style. [VN] 1	v0.3.28:2 General: If the thesis locale and the document locale is the same (the default behaviour), the <code>\thesis@selectLocale</code> macro is applied globally at the beginning of the document. As a result, the <code>csquotes</code> style is automatically set for the entire document. [VN] 1
v0.3.27:4 General: <code>\thesis@english@declaration</code> now uses the correct idiom (by one's own → on one's own). [VN] 1	v0.3.29:1 General: The initial pages of the styles of the Masaryk University in Brno are no longer page-numbered, so that <code>hyperref</code> links work correctly. [VN] 1
v0.3.27:5 General: The PDF bookmarks are no longer garbled, when the <code>LuaTeX</code> engine is used. [VN] 1	v0.3.29:2 General: The printed and digital class options, which set all the options appropriate for either the printed or the digital versions of a document, are now available for the style files of the Masaryk University in Brno. [VN] 1
v0.3.28:1 General: The <code>draft</code> option has no longer an effect on the <code>microtype</code> package. The <code>\thesis@require</code> command now also takes an optional	v0.3.29:3 General: The <code>table</code> class option for the style files of the Masaryk University in Brno now loads all the required packages and changes the <code>table</code> measurements even when the <code>color</code> option is not specified. [VN] 1
	v0.3.30 General: The <code>\thesis@seasonYear</code> macro has been added, which, unlike <code>\thesis@year</code> takes into account the fact that January and February of the year n still belong to the fall semester of the year $n - 1$. [VN] 1
	v0.3.31:1 General: The redefinitions of

<p style="margin-left: 40px;">\appendix from the style/mu/fithesis-1*.clo files, which broke hyperref links to appendices, were removed. [VN] 1</p>	<p>v0.3.35:1 General: Added support for the Division of Information and Library Studies of the Faculty of Arts at the Masaryk University in Brno. This support is enabled by specifying \thesis@department to be kisk. [VN] 1</p>
<p>v0.3.31:2 General: All trailing %s were removed. Some of the inherited fithesis2 code in the style/mu/fithesis-1*.clo and style/mu/fithesis-base.sty files was refactored and reformatted. Alternative templates for the Faculty of Science at the Masaryk University in Brno are now mentioned in the respective user guide. [VN] 1</p>	<p>v0.3.35:2 General: Added support for seminar papers on the fithesis3 class level. The style files for the faculties of the Masaryk University in Brno do not provide any special handling of this thesis type yet. [VN] 1</p>
<p>v0.3.31:3 General: The style/mu/fithesis-sci.sty style file redefines \thesis@blocks@declaration to include a formatted date and an author's signature field. The locale file style/mu/sci/czech.def contains a new string \thesis@czech@formattedDate. [VN] 1</p>	<p>v0.3.35:3 General: Fixed \l@locale being possibly undefined in a LuaLaTeX run. [VN] 1</p>
<p>v0.3.32 General: Fixed a regression from v0.3.27:2 – The margins in \thesis@blocks@mainMatter were corrected in the style files of the Faculty of Economics and Administration and the Faculty of Medicine at the Masaryk University in Brno. [VN] 1</p>	<p>v0.3.36 General: The \thesis@load macro has been lifted to the public API as \thesisload. [VN] 1</p>
<p>v0.3.33 General: Added \thesis@patch. [VN] 1</p>	<p>v0.3.37 General: The \tableofcontents in the style files of the Masaryk University in Brno now correctly handles all tocdepth values. The expansion of \part also no longer results in a hyperref-related error in the style files of the Masaryk University in Brno. [VN] 1</p>
<p>v0.3.34 General: Added visual tests of output PDFs. The test/ directory is now also uses the <i>university/faculty</i> path scheme employed by the rest of the package. [VN] 1</p>	<p>v0.3.38:1 General: The bib key was added on the fithesis3 class level and is supported by the style files of the Masaryk University in Brno. [VN] 1</p>
	<p>v0.3.38:2 General: Fixed \thesis@pages not taking \thesis@postamble into account. Fixed the chapter number being printed regardless of secnumdepth by the style files of the Masaryk University in Brno. Fixed \thesis@blocks@assignment</p>

	being typeset in Czech only by the style file of the Faculty of Science at the Masaryk University in Brno. [VN]	1		
v0.3.39:1	General: The <code>\thesis@blocks@bibliography</code> now uses an emergency stretch of 3 em in the style files of the Masaryk University in Brno. [VN]	1	v0.3.43	General: Added a mention about the thesis proposal thesis type to the user guide for the Faculty of Informatics at the Masaryk University, Brno and fixed a bad citation in the user guides for the Masaryk University, Brno. Added an extra english option for babel in the examples for the Masaryk University, Brno. <code>\thesis@blocks@thanks</code> no longer gobbles leading spaces of <code>\thesis@thanks</code> . A fix in the Slovak locale by kiraacorsac at GitHub. [VN]
v0.3.39:2	General: The assignment key no longer affects the page numbers and takes into account the digital and printed class options in the style files of the Masaryk University in Brno. [VN]	1	v0.3.44	General: Added an additional hyphenation hint to the example document. [VN]
v0.3.40	General: Fixed <code>\thesis@pages</code> not working properly when the <code>autoLayout</code> key is set to false. Added a section on the markdown package to the example documents of the Masaryk University in Brno. Added the <code>\ifthesis@blocks@assignment@hideIfDigital</code> conditional to the <code>style/mu/fithesis-base.sty</code> style file. [VN]	1		Fixed the color in the logo of FI MU. [VN]
v0.3.41	General: Removed the arbitrary limitation of <code>\thesissetup</code> , which prevented it from accepting multi-paragraph values. The <code>\thesislong</code> macro is therefore no longer necessary, but kept around for backwards compatibility. [VN]	1		Fixed wrong / missing non-breaking spaces in Czech / Slovak localization. [VN]
v0.3.42	General: Documented that all color settings are done in the <code>rgb</code> colorspace, which makes the color option suitable mostly for the digital versions of fithesis documents rather than for printing. Added the thesis proposal thesis type. [VN]	1		The captions in the examples for MU are now above tables. [VN]
				The style file for FSpS, MU now complies with updated requirements. [VN]
				The style file for FSpS, MU now includes place, date, and signature field next to the declaration. [VN]
				The style file for FSpS, MU now uses 1.5 spacing outside bibliography. [VN]
				The style file for FSpS, MU now uses a 14 cm wide type area. [VN]
				The style file for FSpS, MU now uses different declaration text. [VN]
				The style file for FSpS, MU now uses different title page layout. [VN]
			v0.3.45	<code>\thesis@pages@preamble</code> : Defined

the <code>\thesis@pages@preamble</code> and <code>\thesis@pages@postamble</code> macros. The patch was submitted by Juraj Pálenik. [VN]	18	Redefined the <code>\thesis@blocks@thanks</code> and <code>\thesis@blocks@declaration</code> macros in <code>style/mu/fithesis-sci.sty</code> . The patch was submitted by Juraj Pálenik. [VN]	85
<code>\thesisload</code> : Updated the <code>\ifthesis@english</code> macro, so that it no longer dynamically reacts to changes of the locale. Instead, it is now based on the main locale during the expansion of <code>\thesisload</code>	22	v0.3.46 <code>\thesis@blocks@abstractEn</code> : Simplified the definition of <code>\thesis@blocks@abstractEn</code> in <code>style/mu/fithesis-base.sty</code> . [VN]	66
<code>\thesissetup</code> : Added the extra key to <code>\thesissetup</code> and defined the helper <code>\thesis@def@extra</code> macro. [VN]	19	<code>\thesis@blocks@declaration</code> : Redefined <code>\thesis@blocks@declaration</code> in <code>style/mu/fithesis-econ.sty</code> in accordance with the example documents. The patch was submitted by Jana Ratajská. [VN]	95
General: Added Slovak localization for the <code>style/mu/fithesis-sci.sty</code> style file. The localization was submitted by Juraj Pálenik. [VN]	51	<code>\thesis@blocks@keywordsEn</code> : Simplified the definition of <code>\thesis@blocks@keywordsEn</code> in <code>style/mu/fithesis-base.sty</code> . [VN]	67
Bibliographical entries in <code>style/mu/fithesis-sci.sty</code> now face each other when the main locale is either Czech or English. [VN]	85	General: Lifted the <code>authorSignature</code> and <code>formattedDate</code> strings to the global locale file interface. [VN]	28
Defined the <code>\ifthesis@czech</code> macro in <code>style/mu/fithesis-sci.sty</code> . The patch was submitted by Juraj Pálenik. [VN]	85	Lifted the <code>bib@author</code> , <code>bib@thesisTitle</code> , and <code>bib@advisor</code> strings from <code>locale/mu/sci/*.def</code> to <code>locale/mu/*.def</code> , so that they can be shared with <code>locale/mu/econ/*.def</code> . [VN]	31, 38, 46
Defined the <code>\thesis@blocks@abstractCs</code> macro in <code>style/mu/fithesis-sci.sty</code> . The patch was submitted by Juraj Pálenik. [VN]	85	Redefined <code>\thesis@blocks@abstract</code> , <code>\thesis@blocks@abstractEn</code> , <code>\thesis@blocks@keywords</code> , and <code>\thesis@blocks@keywordsEn</code> in <code>style/mu/fithesis-econ.sty</code> in accordance with the example documents. The patch was submitted by Jana Ratajská. [VN]	95
Defined the <code>abstractonsinglepage</code> option in <code>style/mu/fithesis-sci.sty</code> . The patch was submitted by Juraj Pálenik. [VN]	85		

The documentation now points to the 2/2017 dean's directive for the Faculty of Economics and Administration, Masaryk University, Brno. [VN]	93	Fixed casing in the definition of the declaration string for the Masaryk University in Brno. [VN]	46
Updated the \abstractTitle string in locale/mu/econ/*.def in accordance with the 2/2017 dean's directive. The patch was submitted by Jana Ratajská. [VN]	33, 40, 48	Removed an extraneous \vskip in the style files for the Masaryk University in Brno. [VN]	93, 98, 101
v0.3.47		v0.3.50	
General: Added an \ifthesis@blocks@assignment@hideIfDigital@ test to the definition of the assignment string for the Masaryk University in Brno. [VN]	31, 38, 46	\thesisload: Make writes immediate, so that they do not get lost when they occur at an empty page. [VN]	23
Enabled the inclusion of the scanned assignment inside the digital version of the document in style/mu/fithesis-econ.sty in accordance with the formal requirements of the faculty. The patch was submitted by Jana Ratajská. [VN]	93	\thesissetup: Make writes immediate, so that they do not get lost when they occur at an empty page. [VN]	19
Moved the \ifthesis@digital tests from locale/*.def to locale/mu/*.def, since \ifthesis@digital is undefined in fithesis3.cls. [VN]	29, 31, 35, 38, 44, 46	v0.3.51	
Updated the declaration string in locale/mu/econ/*.def in accordance with the 2/2017 dean's directive. [VN]	40, 48	General:	60
v0.3.48		v1.0.0	
General: Changed \thesis@english@thanksTitle to plural. [VN]	30	\thesis@blocks@abstract:	66
v0.3.49		Changed clearpage to vskip so it is by default on the same page when the template contains bibEntry. [TV]	66
General: \emph uses the italic type face rather than the slanted type face. [VN]	52	\thesis@blocks@abstractEn:	66
		Changed clearpage to vskip so it is by default on the same page when the template contains bibEntry. [TV]	66
		\thesis@blocks@advisorSignature:	63
		\thesis@blocks@bibEntry: The \thesis@blocks@bibEntry command was expanded to more closely resemble Faculty of Science's bibEntry. The \thesis@blocks@bibEntryEn was added. [TV]	69
		\thesis@blocks@cover:	63
		Removed the header conditionals as the covers are unified for all faculties and shouldn't need to be modified. [TV]	63

<code>\thesis@blocks@facultyLogo@color:</code>	90
62	97
<code>\thesis@blocks@facultyLogo@monochrome:</code>	56
62	85
<code>\thesis@blocks@keywords:</code>	55, 60,
Redefined keywords,	61
keywordsEn macros so they by	87,
default start on the same page	88
as the the previous element and	87
are in the lower part of the	83
page. [TV]	66 55
<code>\thesis@blocks@logo:</code>	85
62	93
<code>\thesis@blocks@seal:</code>	93
65	88
<code>\thesis@blocks@summary: Macro</code>	91
for the summary was added.	98
[TV]	96 101
<code>\thesis@blocks@titlePage: 64</code>	87
64	98
64	Added <code>\thesis@xpatch</code>
64	command. [TV]
65	Added conditional redefinition
64	for the study field. [TV]
	Added conditional redefinition
	for the study programme.
<code>\thesis@blocks@universityLogo@color:</code>	[TV]
63	91
<code>\thesis@blocks@universityLogo@monochrome:</code>	Added conditional to add
62	summary for doctoral theses.
	[TV]
<code>\thesis@facultyLogo:</code>	87
11	Added conditional to include
	summary in doctoral theses.
<code>\thesis@requireStyle: Files were</code>	[TV]
renamed after breaking	97
changes in package loading	Added redefinition of
after PR 438 in $\LaTeX 2_{\epsilon}$. [VN] .	conditionals to exclude the
24	study field and the study
<code>\thesis@style: Files were renamed</code>	programme from the title page.
after breaking changes in	[TV]
package loading after PR 438 in	84
$\LaTeX 2_{\epsilon}$. [VN]	Added redefinition of the
12	conditional to exclude the study
<code>\thesis@universityLogo:</code>	field from the title page.
11	[TV]
<code>\thesis@xpatch: Added</code>	89, 93
<code>\thesis@xpatch</code> command.	Added redefinition of the
[TV]	conditionals to exclude the
27	study programme and the
<code>\thesisload: Only load babel in</code>	study field from the title page.
Lua \TeX if polyglossia has not	[TV]
been loaded yet.	85
22	Added redefinition of the
General:	titlePage layout as per the
84, 85, 87, 88, 90, 92, 96, 100, 102	faculty requirements.
88	

Department name and field are in the upper part of the titlePage. [TV]	91	Macros for abstract and abstractEn were moved to base.dtx. [TV]	95
Added redefinition of the titlePage layout as per the faculty requirements. Department name and programme are in the upper part of the titlePage. [TV]	98	Redefine all predefined page styles of the backend class, so that they can't be accidentally activated. [VN]	72
Added required package tikz for bibEntry. [TV]	55	Reorganised the blocks to fit the faculty's requirements. [TV] . . .	84, 85, 87, 88, 90, 92, 96, 100, 102
Added title for summary. [TV]	30, 36, 44	Styles for list of figures and list of tables were redefined to achieve unified look with toc. [TV] . . .	74
Files were renamed after breaking changes in package loading after PR 438 in L ^A T _E X 2 _ε . [VN]	52, 71, 74–76, 83, 84, 86, 88–90, 92, 97, 100	Updated urls to show the most recent requirements and recommendations used in preparation of the template. [TV]	83, 84, 86, 88–90, 93, 97, 100
Lifted the advisorSignature string to the global locale file interface. [VN]	28, 30, 33, 36, 40, 44, 49, 83	v1.0.1	
Lifted the bib@programme, bib@academicYear, and bib@pages strings from locale/mu/sci/*.def to locale/mu/*.def, so that they can be shared with other faculties. [TV]	31, 38, 46	\thesis@blocks@frontMatter: 85	91
		101	
		\thesis@blocks@mainMatter: 101	99
		General: 92	
		100	
		86	
		103	