

The LUA-PHYSICAL library

Version 1.0.3

Thomas Jenni

September 9, 2020

Abstract

`lua-physical` is a pure Lua library, which provides functions and objects for the computation of physical quantities. A physical quantity is the product of a numerical value and a physical unit. The package has been written, to simplify the creation physics problem sets. The package provides units of the SI and the imperial system. Furthermore, an almost complete set of international currencies are supported, however without realtime exchange rates. In order to display the numbers with measurement uncertainties, the package is able to perform gaussian error propagation.

Contents

1	Introduction	3
1.1	Dependencies	3
2	Loading	3
2.1	License	4
3	Usage	5
3.1	Unit conversion	5
3.1.1	Temperature Conversion	6
3.2	Uncertainty Propagation	7
3.3	Mathematical operations	10
4	Supported Units	12
4.1	Prefixes	12
4.2	Base Units	13
4.3	Constants	15
4.4	Coherent derived units in the SI	16
4.5	Non-SI units accepted for use with the SI	17
4.6	Nominal Astronomical Units	17
4.7	Other Non-SI units	18

4.8	Imperial Units	20
4.9	U.S. customary units	22
4.10	International Currencies	23
4.10.1	Pegged International Currencies	31
5	Lua Documentation	35
5.1	physical.Quantity	35
5.2	physical.Dimension	46
5.3	physical.Unit	47
5.4	physical.Number	48
6	Change History	57
	Bibliography	58
	Index of Units	59
	Index of Currencies	62
	Index of Lua Classes and Methods	66

1 Introduction

The author of this package is a physics teacher at the high school *Kantonsschule Zug*, Switzerland. The main use of this package is to write physics problem sets. Lua \LaTeX does make it possible to integrate physical calculations directly. The package has been in use since 2016. Many bugs have been found and fixed. Nevertheless it still is possible, that some were not found yet. Therefore the author recommends not to use this package in industry or science. If one does so, it's the responsibility of the user to check results for plausability. If the user finds some bugs, they can be reported at github.com.

1.1 Dependencies

In principle this library is standalone, but it is compatible with the `siunitx` package. Calculation results can be written to Lua \LaTeX directly by calling the `tosiunitx()` method. If the preamble in the next section is used, the printing is done by the `\q{}` macro.

2 Loading

This package is a pure Lua library. Therefore one has to require it explicitly by calling `require("physical")`. For printing physical quantities, the `siunitx` is supported. It's recommended to define a macro like `\q` to convert the lua quantity object to a `siunitx` expression.

The following \LaTeX preamble loads the `lua-physical` package and creates a macro `\q` for printing physical quantities.

Listing 1: basic preamble

```
\usepackage{luacode}
\usepackage{siunitx}

% configure siunitx
\sisetup{
  output-decimal-marker = {.),
  per-mode = symbol,
  separate-uncertainty = true,
  add-decimal-zero = true,
  exponent-product = \cdot,
  round-mode = off
}

% load the lua-physical package
\begin{luacode*}
  physical = require("physical")
  N = physical.Number
\end{luacode*}
```

```
% print a physical quantity
\newcommand{\q}[1]{%
  \directlua{
    tex.print(
      physical.Quantity.tosiunitx(
        #1,
        "scientific-notation=fixed,exponent-to-prefix=false"
      )
    )
  }%
}
```

2.1 License

This code is freely distributable under the terms of the MIT license.

Copyright (c) 2020 Thomas Jenni

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

3 Usage

Given the basic preamble, units can be used in lua code directly. By convention, all units have an underscore in front of them, i.e. meter is `_m`, second is `_s`. All available units are listed in section 4. The following example illustrates the use of this library.

Listing 2: Velocity of a car.

```
\begin{luacode}
  s = 10 * _m
  t = 2 * _s
  v = s/t
\end{luacode}

A car travels  $\text{\q{s}}$  in  $\text{\q{t}}$ . calculate its velocity.
%
\begin{equation*}
  v = \frac{s}{t} = \frac{\text{\q{s}}}{\text{\q{t}}} = \underline{\text{\q{v}}}
\end{equation*}
```

A car travels 10 m in 2 s. Calculate its velocity.

$$v = \frac{s}{t} = \frac{10 \text{ m}}{2 \text{ s}} = \underline{5.0 \text{ m/s}}$$

In the above listing 2, the variable `s` stands for displacement and has the unit meter `_m`, the variable `t` stands for time and is given in seconds `_s`. If mathematical operations are done on them, new physical quantities are created. In the problem above, the velocity `v` is calculated by dividing `s` by `t`. The instance `v` has the derived unit m/s. By using the macro `\q{}` all quantities can be printed to the Lua^AT_EX code directly.

3.1 Unit conversion

Very often, the result of a calculation has to be converted to another unit. In listing 3 the task is to calculate the volume of a cuboid. The length of the edges are given in different units. The volume is calculated by multiplying all three lengths, the unit of the result is cm mm m. If the unit `cm3` is preferred, it has to be converted explicitly. The conversion function is called `to()` and is available on all physical quantity instances. At first this looks a bit cumbersome. The reason of this behaviour is, that the software is not able to guess the unit of the result. In many cases, like in the example here, it's not clear what unit the result should have. Therefore the user has always to give the target unit explicitly.

Listing 3: Volume of a cuboid.

```

\begin{luacode}
  a = 12 * _cm
  b = 150 * _mm
  c = 1.5 * _m

  V = a*b*c
\end{luacode}

Find the volume of a rectangular cuboid with lengths  $\{a\}$ ,
 $\{b\}$  and  $\{c\}$ .
%
\begin{equation*}
  V = a \cdot b \cdot c
  = \{a\} \cdot \{b\} \cdot \{c\}
  = \{V\}
  = \underline{\{V:to(dm^3)\}}
\end{equation*}

```

Find the volume of a rectangular cuboid with lengths 12 cm, 150 mm and 1.5 m.

$$V = a \cdot b \cdot c = 12 \text{ cm} \cdot 150 \text{ mm} \cdot 1.5 \text{ m} = 2700.0 \text{ cm mm m} = \underline{27.0 \text{ dm}^3}$$

3.1.1 Temperature Conversion

Most physical units transform linearly. Exceptions are the unit degree Celsius `_degC` and degree Fahrenheit `_degF`. These units are ambiguous and can be interpreted as temperature differences or as an absolute temperatures. In the latter case, the conversion to base units is not a linear, but an affine transformation. This is because degree Celsius and degree Fahrenheit scales have their zero points at different temperatures compared to the unit Kelvin.

By default `_degC` and `_degF` units are temperature differences. If one wants to have it converted absolutely, it has to be done adding / subtracting `_degC_0 = 273.15*_K` or `_degF_0 = (273.15 - 32*(5/9)) *_K`, the zero point temperatures of the scales.

In the following problem, listing 4, the task is to convert temperatures given in the unit degree Celsius and degree Fahrenheit to Kelvin.

Listing 4: Temperature conversion.

```

\begin{luacode}
  theta_1 = 110 * _degC
  T_1 = ( theta_1 + _degC_0 ):to(_K)

  T_2 = 100 * _K
  theta_2 = ( T_2 - _degC_0 ):to(_degC)
\end{luacode}

```

```

theta_3 = 212 * _degF
T_3 = ( theta_3 + _degF_0 ):to(_K)

T_4 = 100 * _K
theta_4 = ( T_4 - _degF_0 ):to(_degF)

theta_5 = 100 * _degC
theta_6 = ( ( theta_5 + _degC_0 ):to(_K) - _degF_0 ):to(_degF)
\end{luacode}

\begin{align*}
\q{theta_1} & \mathrel{\widehat{=}} \q{T_1} \\
\q{theta_2} & \mathrel{\widehat{=}} \q{T_2} \\
\q{theta_3} & \mathrel{\widehat{=}} \q{T_3} \\
\q{theta_4} & \mathrel{\widehat{=}} \q{T_4} \\
\q{theta_5} & \mathrel{\widehat{=}} \q{theta_6}
\end{align*}

```

$$\begin{aligned}
110\text{ }^\circ\text{C} &\hat{=} 383.15\text{ K} \\
-173.15\text{ }^\circ\text{C} &\hat{=} 100\text{ K} \\
212\text{ }^\circ\text{F} &\hat{=} 373.15\text{ K} \\
-279.67\text{ }^\circ\text{F} &\hat{=} 100\text{ K} \\
100\text{ }^\circ\text{C} &\hat{=} 212.0\text{ }^\circ\text{F}
\end{aligned}$$

3.2 Uncertainty Propagation

The package supports uncertainty propagation. To create a number with an uncertainty, an instance of `physical.Number` has to be created, see listing 5. It has to be remembered, that `N` is a alias for `physical.Number`. The first argument of the constructor `N(mean, uncertainty)` is the mean value and the second one the uncertainty of the measurement. If the proposed preamble 1 is used, the uncertainty is by default separated from the mean value by a plus-minus sign. For the uncertainty propagation the gaussian formula

$$\Delta f = \sqrt{\left(\frac{\partial f}{\partial x_1} \cdot \Delta x_1\right)^2 + \dots + \left(\frac{\partial f}{\partial x_n} \cdot \Delta x_n\right)^2}$$

is used. This formula is a good estimation for the uncertainty Δf , if the quantities x_1, \dots, x_n the function f depends on, have no correlation. Further, the function f has to change linear, if quantities x_i are changed in the range of their uncertainties.

Listing 5: Uncertainty in area calculation.

```

\begin{luacode}
  a = N(2,0.1) * _m
  b = N(3,0.1) * _m

  A = (a*b):to(_m^2)
\end{luacode}

Calculate the area of a rectangle with lengths  $\text{\q{a}}$  and  $\text{\q{b}}$ $.
%
\begin{equation*}
  A = a \cdot b
  = \text{\q{a}} \cdot \text{\q{b}}
  = \underline{\text{\q{A}}}
\end{equation*}

```

Calculate the area of a rectangle with lengths (2.00 ± 0.10) m and (3.00 ± 0.10) m.

$$A = a \cdot b = (2.00 \pm 0.10) \text{ m} \cdot (3.00 \pm 0.10) \text{ m} = \underline{(6.0 \pm 0.4) \text{ m}^2}$$

Instead of printing the uncertainties, one can use the uncertainty calculation to provide significant digits and omit it.

In the following problem, listing 6, the task is to find the volume of an ideal gas. Given are pressure p in _bar , amount of substance n in _mol and temperature T in degree celsius _degC . In order to do the calculation, one has to convert T , which is given as an absolute temperature in degree celsius to the base unit Kelvin first. By setting `N.omitUncertainty = true`, all uncertainties are not printed.

Listing 6: Volume of an ideal gas.

```

\begin{luacode}
  N.omitUncertainty = true
  p = N(1.013,0.0001) * _bar
  n = N(1,0.01) * _mol
  T = N(30,0.1) * _degC

  V = ( n * _R * (T + _degC_0):to(_K) / p ):to(_L)
\end{luacode}

An ideal gas ( $\text{\q{n}}$ ) has a pressure of  $\text{\q{p}}$  and a temperature of  $\text{\q{T}}$ $. Calculate the volume of the gas.
%
\begin{equation*}
  V = \frac{ \text{\q{n}} \cdot \text{\q{R}} \cdot \text{\q{(T + _degC_0):to(_K)}} }{ \text{\q{p}} }
  = \underline{\text{\q{V}}}
\end{equation*}

```


An ideal gas (1.0 mol) has a pressure of 1.013 bar and a temperature of 30 °C. Calculate the volume of the gas.

$$V = \frac{1.0 \text{ mol} \cdot 8.31 \text{ J}/(\text{mol K}) \cdot 303 \text{ K}}{1.013 \text{ bar}} = \underline{25 \text{ L}}$$

This example shows, that the result has only two digits. If more digits are needed, the uncertainties of the given quantities should be smaller.

3.3 Mathematical operations

Two physical quantities with identical dimensions can be added or subtracted. The library checks the validity of those operations and throws an error if two addends haven't the same dimensions.

Listing 7: Addition and subtraction

```
l_1 = 1 * _m
l_2 = 2 * _cm
t = 2 * _s

l_1 + t
Error: Cannot add '1* _m' to '2 * _s', because they have different
dimensions.

l_1 + l_2
102.0 * _cm
```

New physical quantities can be created by division and multiplication. As long as no division by zero is made, no errors should occur.

Listing 8: Multiplication and Division

```
l_1 = 1 * _m
l_2 = 2 * _cm

(l_1 * l_2):to(_m^2)
0.02 * _m^2

(l_1 / l_2):to(_1)
50.0 * _1
```

Physical quantities can be exponentiated. The library doesn't check, if the result has units with non integer exponents.

Listing 9: Exponentiation

```
l = 5 * _m
A = l^2

A:to(_m^2)
25.0 * _m^2

A:sqrt()
5.0 * _m

A^0.5
5.0 * _m
```

Exponential functions and the logarithms should have dimensionless arguments. The library throws an error if that's not the case.

Listing 10: Exponential function and logarithm

```
N_0 = 1000 * _1
lambda = Q.log(2)/(2*_h)
t = 50 * _min

N_0 * Q.exp(-lambda * t)
749.15353843834 * _1
```

4 Supported Units

All supported units are listed in this section. Subsection 4.2 lists the seven base units of the International System of Units (SI). In subsection 4.3 mathematical and physical constants are defined. The subsection 4.4 contains all coherent derived units from the SI system and 4.5 those which are accepted to use with the SI. The subsection 4.6 lists nominal astronomical units, which are proposed by [4]. Subsection 4.7 lists units, which are common but outside of the SI system. The subsections 4.8 and 4.9 are dedicated to imperial and U.S. customary units. The last subsection 4.10 contains international currencies.

4.1 Prefixes

All SI units have prefixed versions, i.e. `_us` microsecond, `_cm` centimeter, `_mN` millinewton, see table 1. Some units of data processing, like `_bit` have prefixes which are powers of 2. They are called binary or IEC prefixes, see table 2 [2, 121].

Prefix	Symbol	Definition	Prefix	Symbol	Definition
yotta	Y	1e24	deci	d	1e-1
zetta	Z	1e21	centi	c	1e-2
exa	E	1e18	milli	m	1e-3
peta	P	1e15	micro	u	1e-6
tera	T	1e12	nano	n	1e-9
giga	G	1e9	pico	p	1e-12
mega	M	1e6	femto	f	1e-15
kilo	k	1e3	atto	a	1e-18
hecto	h	1e2	zepto	z	1e-21
deca	da	1e1	yocto	y	1e-23

Table 1: SI prefixes [2, 121]

Prefix	Symbol	Definition
kibi	Ki	1024
mebi	Mi	1048576
gibi	Gi	1073741824
tebi	Ti	1099511627776
pebi	Pi	1125899906842624
exbi	Ei	1152921504606846976
zebi	Zi	1180591620717411303424
yobi	Yi	1208925819614629174706176

Table 2: IEC prefixes [2, 121]

4.2 Base Units

The `lua-physical` library has nine base quantities. These are the seven basis units or basis quantities of the SI system [3] and in addition the base quantity of information `_bit` and of currency `_EUR`. All other quantities are derived from these base units.

Quantity	Unit	Symbol	Dim.	Definition
number ¹	–	<code>_1</code>	1	The dimensionless number one.
time	second	<code>_s</code>	T	The SI unit of time. It is defined by taking the fixed numerical value of the caesium frequency $\Delta\nu_{Cs}$, the unperturbed ground-state hyperfine transition frequency of the caesium 133 atom, to be 9 192 631 770 when expressed in the unit 1/s.
length	meter	<code>_m</code>	L	The SI unit of length. It is defined by taking the fixed numerical value of the speed of light in vacuum c to be 299 792 458 when expressed in the unit of m/s.

¹The number one is a unit with dimension zero. Stricly speaking it is not a base unit.

Quantity	Unit	Symbol	Dim.	Definition
mass	kilogram	<code>_kg</code>	M	The SI unit of mass. It is defined by taking the fixed numerical value of the Planck constant h to be $6.626\,070\,15 \cdot 10^{-34}$ when expressed in $\text{m}^2 \text{kg/s}$.
electric current	ampere	<code>_A</code>	I	The SI unit of electric current. It is defined by taking the fixed numerical value of the elementary charge e to be $1.602\,176\,634 \cdot 10^{-19}$ when expressed in A s.
thermodynamic temperature	kelvin	<code>_K</code>	K^1	The SI unit of the thermodynamic temperature. It is defined by taking the fixed numerical value of the Boltzmann constant k_B to be $1.380\,649 \cdot 10^{-23}$ when expressed in $\text{kg m}^2/(\text{s}^2 \text{K})$
amount of substance	mole	<code>_mol</code>	N	The SI unit of amount of substance. One mole contains exactly $6.022\,140\,76 \cdot 10^{23}$ elementary entities. This number is the fixed numerical value of the Avogadro constant N_A when expressed in $1/\text{mol}$.
luminous intensity	candela	<code>_cd</code>	J	The SI unit of luminous intensity in a given direction. It is defined by taking the fixed numerical value of the luminous efficacy of monochromatic radiation of frequency $5.4 \cdot 10^{14} \text{ Hz}$, K_{cd} , to be 683 when expressed in the unit $\text{cd sr s}^3/(\text{kg m}^2)$.
information	bit	<code>_bit</code>	B	The smallest amount of information.
currency	euro	<code>_EUR</code>	C	The value of the currency Euro.

Table 3: Base units

¹The SI symbol for the dimension of temperature is Θ , but all symbols of this library consist of roman letters, numbers and underscores only. Therefore the symbol for the dimension of the thermodynamic temperature is the letter K.

4.3 Constants

All physical constants are taken from the NIST webpage [1].

Name	Symbol	Definition
pi	$_Pi$	$3.1415926535897932384626433832795028841971 * _1$
eulersnumber	$_E$	$2.7182818284590452353602874713526624977572 * _1$
speedoflight	$_c$	$299792458 * _m/_s$
gravitationalconstant	$_Gc$	$N(6.67408e-11, 3.1e-15) * _m^3/(_kg*_s^2)$
planckconstant	$_h_P$	$6.62607015e-34 * _J*_s$
reducedplanckconstant	$_h_Pbar$	$_h_P/(2*_Pi)$
elementarycharge	$_e$	$1.602176634e-19 * _C$
vacuumpermeability	$_u_0$	$4e-7*_Pi * _N/_A^2$
vacuumpermittivity	$_e_0$	$1/(_u_0*_c^2)$
atomicmassunit	$_u$	$N(1.66053904e-27, 2e-35) * _kg$
electronmass	$_m_e$	$N(9.10938356e-31, 1.1e-38) * _kg$
protonmass	$_m_p$	$N(1.672621898e-27, 2.1e-35) * _kg$
neutronmass	$_m_n$	$N(1.674927471e-27, 2.1e-35) * _kg$
bohrmagneton	$_u_B$	$_e*_h_Pbar/(2*_m_e)$
nuclearmagneton	$_u_N$	$_e*_h_Pbar/(2*_m_p)$
electronmagneticmoment	$_u_e$	$N(-928.4764620e-26, 5.7e-32) * _J/_T$
protonmagneticmoment	$_u_p$	$N(1.4106067873e-26, 9.7e-35) * _J/_T$
neutronmagneticmoment	$_u_n$	$N(-0.96623650e-26, 2.3e-26) * _J/_T$
finestructureconstant	$_alpha$	$_u_0*_e^2*_c/(2*_h_P)$
rydbergconstant	$_Ry$	$_alpha^2*_m_e*_c/(2*_h_P)$
avogadronumber	$_N_A$	$6.02214076e23/_mol$
boltzmannconstant	$_k_B$	$1.380649e-23 * _J/_K$
molargasconstant	$_R$	$N(8.3144598, 4.8e-6) * _J/(_K*_mol)$
stefanboltzmannconstant	$_sigma$	$_Pi^2*_k_B^4/(60*_h_Pbar^3*_c^2)$
standardgravity	$_g_0$	$9.80665 * _m/_s^2$

Table 4: Physical and mathematical constants

4.4 Coherent derived units in the SI

All units in this section are coherent derived units from the SI base units with special names, [2, 118].

Quantity	Unit	Symbol	Definition
Plane Angle ¹	radian	<code>_rad</code>	<code>_1</code>
Solid Angle ²	steradian	<code>_sr</code>	<code>_rad^2</code>
Frequency	hertz	<code>_Hz</code>	<code>1/_s</code>
Force	newton	<code>_N</code>	<code>_kg*_m/_s^2</code>
Pressure	pascal	<code>_Pa</code>	<code>_N/_m^2</code>
Energy	joule	<code>_J</code>	<code>_N*_m</code>
Power	watt	<code>_W</code>	<code>_J/_s</code>
Electric Charge	coulomb	<code>_C</code>	<code>_A*_s</code>
Electric Potential	volt	<code>_V</code>	<code>_J/_C</code>
Electric Capacitance	farad	<code>_F</code>	<code>_C/_V</code>
Electric Resistance	ohm	<code>_Ohm</code>	<code>_V/_A</code>
Electric Conductance ³	siemens	<code>_S</code>	<code>_A/_V</code>
Magnetic Flux	weber	<code>_Wb</code>	<code>_V*_s</code>
Magnetic Flux Density	tesla	<code>_T</code>	<code>_Wb/_m^2</code>
Inductance	henry	<code>_H</code>	<code>_Wb/_A</code>
Temperature ⁴	celsius	<code>_degC</code>	<code>_K</code>
Luminous Flux	lumen	<code>_lm</code>	<code>_cd*_sr</code>
Illuminance	lux	<code>_lx</code>	<code>_lm/_m^2</code>
Activity	becquerel	<code>_Bq</code>	<code>1/_s</code>
Absorbed Dose	gray	<code>_Gy</code>	<code>_J/_kg</code>
Dose Equivalent	sievert	<code>_Sv</code>	<code>_J/_kg</code>
Catalytic Activity	katal	<code>_kat</code>	<code>_mol/_s</code>

¹In the SI system, the quantity Plane Angle has the dimension of a number.

²In the SI system, the quantity Solid Angle has the dimension of a number.

³The unit `_PS` stands for peta siemens and is in conflict with the metric version of the unit horsepower (german *Pferdestärke*). Since the latter is more common than peta siemens, `_PS` is defined to be the metric version of horsepower.

⁴The unit `_degC` is by default interpreted as a temperature difference.

4.5 Non-SI units accepted for use with the SI

There are a few units with dimension 1. [2, 124].

Quantity	Unit	Symbol	Definition
Time	minute	<code>_min</code>	$60 * _s$
	hour	<code>_h</code>	$60 * _min$
	day	<code>_d</code>	$24 * _h$
Plane Angle	degree	<code>_deg</code>	$(_Pi/180) * _rad$
	arcminute	<code>_arcmin</code>	$_deg/60$
	arcsecond	<code>_arcsec</code>	$_arcmin/60$
Area	hectare	<code>_hectare</code>	$1e4 * _m^2$
Volume	liter	<code>_L</code>	$1e-3 * _m^3$
Mass	tonne	<code>_t</code>	$1e3 * _kg$

4.6 Nominal Astronomical Units

The nominal values of solar, terrestrial and jovial quantities are taken from IAU Resolution B3 [4].

Quantity	Unit	Symbol	Definition
Length	nomsolradius	<code>_R_S_nom</code>	$6.957e8 * _m$
Irradiance	nomsolirradiance	<code>_S_S_nom</code>	$1361 * _W/_m^2$
Radiant Flux	nomsolluminosity	<code>_L_S_nom</code>	$3.828e26 * _W$
Temperature	nomsoleffttemperature	<code>_T_S_nom</code>	$5772 * _K$
Mass Parameter	nomsolmassparameter	<code>_GM_S_nom</code>	$1.3271244e20 * _m^3*_s^{-2}$
Length	nomterreqradius	<code>_Re_E_nom</code>	$6.3781e6 * _m$
Length	nomterrpolarradius	<code>_Rp_E_nom</code>	$6.3568e6 * _m$
Mass Parameter	nomterrmassparameter	<code>_GM_E_nom</code>	$3.986004e14 * _m^3*_s^{-2}$
Length	nomjoveqradius	<code>_Re_J_nom</code>	$7.1492e7 * _m$
Length	nomjovpolarradius	<code>_Rp_J_nom</code>	$6.6854e7 * _m$
Mass Parameter	nomjovmassparameter	<code>_GM_J_nom</code>	$1.2668653e17 * _m^3*_s^{-2}$

4.7 Other Non-SI units

The unit Bel is only available with prefix decibel, because `_B` is the unit byte.

Quantity	Unit	Symbol	Definition
Length	angstrom	<code>_angstrom</code>	$1e-10 * _m$
	fermi	<code>_fermi</code>	$1e-15 * _m$
Time	svedberg	<code>_svedberg</code>	$1e-13 * _s$
	week	<code>_wk</code>	$7 * _d$
	year	<code>_a</code>	$365.25 * _d$
	astronomicalunit	<code>_au</code>	$149597870700 * _m$
	lightsecond	<code>_ls</code>	$_c * _s$
	lightyear	<code>_ly</code>	$_c * _a$
	parsec	<code>_pc</code>	$(648000 / _Pi) * _au$
Area	barn	<code>_barn</code>	$1e-28 * _m^2$
	are	<code>_are</code>	$1e2 * _m^2$
Volume	metricteaspoon	<code>_tsp</code>	$5e-3 * _L$
	metrictablespoon	<code>_Tbsp</code>	$3 * _tsp$
Plane Angle	gradian	<code>_gon</code>	$(_Pi / 200) * _rad$
	turn	<code>_tr</code>	$2 * _Pi * _rad$
Solid Angle	spat	<code>_sp</code>	$4 * _Pi * _sr$
Force	kilopond	<code>_kp</code>	$_kg * _g_0$
Pressure	bar	<code>_bar</code>	$1e5 * _Pa$
	standardatmosphere	<code>_atm</code>	$101325 * _Pa$
	technicalatmosphere	<code>_at</code>	$_kp / _cm^2$
	millimeterofmercury	<code>_mmHg</code>	$133.322387415 * _Pa$
	torr	<code>_Torr</code>	$(101325 / 760) * _Pa$
Energy	thermochemicalcalorie	<code>_cal</code>	$4.184 * _J$
	internationalcalorie	<code>_cal_IT</code>	$4.1868 * _J$
	gramoftnt	<code>_g_TNT</code>	$1e3 * _cal$
	tonoftnt	<code>_t_TNT</code>	$1e9 * _cal$

Quantity	Unit	Symbol	Definition
	electronvolt	<code>_eV</code>	<code>_e*_V</code>
	wattsecond	<code>_Ws</code>	<code>_W*_s</code>
	watthour	<code>_Wh</code>	<code>_W*_h</code>
Power	voltampere	<code>_VA</code>	<code>_V*_A</code>
Electric Charge	amperesecond	<code>_As</code>	<code>_A*_s</code>
	amperehour	<code>_Ah</code>	<code>_A*_h</code>
Information	nibble	<code>_nibble</code>	<code>4 * _bit</code>
	byte	<code>_B</code>	<code>8 * _bit</code>
Information Transfer Rate	bitpersecond	<code>_bps</code>	<code>_bit/_s</code>
Number	percent	<code>_percent</code>	<code>1e-2 * _1</code>
	permille	<code>_permille</code>	<code>1e-3 * _1</code>
	partspermillion	<code>_ppm</code>	<code>1e-6 * _1</code>
	partsperbillion	<code>_ppb</code>	<code>1e-9 * _1</code>
	partspertrillion	<code>_ppt</code>	<code>1e-12 * _1</code>
	partsperquadrillion	<code>_ppq</code>	<code>1e-15 * _1</code>
	decibel	<code>_dB</code>	<code>_1</code>
Power	metrichorsepower	<code>_PS</code>	<code>75 * _g_0*_kg*_m/_s</code>
Activity	curie	<code>_Ci</code>	<code>3.7e10 * _Bq</code>
Absorbed Dose	rad	<code>_Rad</code>	<code>1e-2 * _Gy</code>
Dose Equivalent	rem	<code>_rem</code>	<code>1e-2 * _Sv</code>
Viscosity	poiseuille	<code>_Pl</code>	<code>_Pa*_s</code>

4.8 Imperial Units

Quantity	Unit	Symbol	Definition
Length	inch	<code>_in</code>	$2.54e-2 * _m$
	thou	<code>_th</code>	$1e-3 * _in$
DTP Point ¹	point	<code>_pt</code>	$_in/72$
	pica	<code>_pica</code>	$12 * _pt$
	hand	<code>_hh</code>	$4 * _in$
	foot	<code>_ft</code>	$12 * _in$
	yard	<code>_yd</code>	$3 * _ft$
	rod	<code>_rd</code>	$5.5 * _yd$
	chain	<code>_ch</code>	$4 * _rd$
	furlong	<code>_fur</code>	$10 * _ch$
	mile	<code>_mi</code>	$8 * _fur$
	league	<code>_lea</code>	$3 * _mi$
	nauticalmile	<code>_nmi</code>	$1852 * _m$
	nauticalleague	<code>_nlea</code>	$3 * _nmi$
	cable	<code>_cbl</code>	$0.1 * _nmi$
	fathom	<code>_ftm</code>	$6 * _ft$
	Velocity	knot	<code>_kn</code>
Area	acre	<code>_ac</code>	$10 * _ch^2$
Volume	gallon	<code>_gal</code>	$4.54609 * _L$
	quart	<code>_qt</code>	$_gal/4$
	pint	<code>_pint</code>	$_qt/2$
	cup	<code>_cup</code>	$_pint/2$
	gill	<code>_gi</code>	$_pint/4$
	fluidounce	<code>_fl_oz</code>	$_gi/5$
	fluid dram	<code>_fl_dr</code>	$_fl_oz/8$

¹The desktop publishing point or PostScript point is 1/72 of an international inch.

Quantity	Unit	Symbol	Definition
Mass	grain	<code>_gr</code>	$64.79891 * \text{mg}$
	pound	<code>_lb</code>	$7000 * \text{gr}$
	ounce	<code>_oz</code>	$\text{lb}/16$
	dram	<code>_dr</code>	$\text{lb}/256$
	stone	<code>_st</code>	$14 * \text{lb}$
	quarter	<code>_qtr</code>	$2 * \text{st}$
	hundredweight	<code>_cwt</code>	$4 * \text{qtr}$
	longton	<code>_ton</code>	$20 * \text{cwt}$
	troy pound	<code>_lb_t</code>	$5760 * \text{gr}$
	troy ounce	<code>_oz_t</code>	$\text{lb}_t/12$
	pennyweight	<code>_dwt</code>	$24 * \text{gr}$
	firkin	<code>_fir</code>	$56 * \text{lb}$
	Time	sennight	<code>_sen</code>
fortnight		<code>_ftn</code>	$14 * \text{d}$
Temperature ¹	fahrenheit	<code>_degF</code>	$(5/9) * \text{K}$
Force	poundforce	<code>_lbf</code>	$\text{lb} * \text{g}_0$
	poundal	<code>_pdl</code>	$\text{lb} * \text{ft} / \text{s}^2$
Mass	slug	<code>_slug</code>	$\text{lbf} * \text{s}^2 / \text{ft}$
Pressure	poundforcepersquareinch	<code>_psi</code>	lbf / in^2
Torque,Energy	thchembritishthermalunit	<code>_BTU</code>	$(1897.83047608/1.8) * \text{J}$
Torque,Energy	intbritishthermalunit	<code>_BTU_it</code>	$1055.05585262 * \text{J}$
Power	horsepower	<code>_hp</code>	$33000 * \text{ft} * \text{lbf} / \text{min}$

¹The unit `_degF` is by default interpreted as a temperature difference.

4.9 U.S. customary units

In the U.S., the length units are bound to the meter differently than in the imperial system. The following definitions are taken from https://en.wikipedia.org/wiki/United_States_customary_units.

Quantity	Unit	Symbol	Definition	
Length	ussurveyinch	_in_US	_m/39.37	
	ussurveyhand	_hh_US	4 * _in_US	
	ussurveyfoot	_ft_US	3 * _hh_US	
	ussurveylink	_li_US	0.66 * _ft_US	
	ussurveyyard	_yd_US	3 * _ft_US	
	ussurveyrod	_rd_US	5.5 * _yd_US	
	ussurveychain	_ch_US	4 * _rd_US	
	ussurveyfurlong	_fur_US	10 * _ch_US	
	ussurveymile	_mi_US	8 * _fur_US	
	ussurveyleague	_lea_US	3 * _mi_US	
	ussurveyfathom	_ftm_US	72 * _in_US	
	ussurveycable	_cbl_US	120 * _ftm_US	
	Area	ussurveyacre	_ac_US	_ch_US * _fur_US
Volume	usgallon	_gal_US	231 * _in ³	
	usquart	_qt_US	_gal_US/4	
	uspint	_pint_US	_qt_US/2	
	uscup	_cup_US	_pint_US/2	
	usgill	_gi_US	_pint_US/4	
	usfluidounce	_fl_oz_US	_gi_US/4	
	ustablespoon	_Tbsp_US	_fl_oz_US/2	
	usteaspoon	_tsp_US	_Tbsp_US/3	
	usfluid dram	_fl_dr_US	_fl_oz_US/8	
	Mass	usquarter	_qtr_US	25 * _lb
		ushundredweight	_cwt_US	4 * _qtr_US
uston		_ton_US	20 * _cwt_US	

4.10 International Currencies

International currency units based on exchange rates from 7.3.2019, 21:00 UTC.

Name	Symbol	Definition
AfghanAfghani	_AFN	0.012 * _EUR
AfghanPul	_cAFN	0.01 * _AFN
AlbanianLek	_ALL	0.008 * _EUR
ArmenianDram	_AMD	0.0018 * _EUR
ArmenianLuma	_cAMD	0.01 * _AMD
AngolanKwanza	_AOA	0.0028 * _EUR
AngolanCentimo	_cAOA	0.01 * _AOA
ArgentinePeso	_ARS	0.021 * _EUR
ArgentineCentavo	_cARS	0.01 * _ARS
AustralianDollar	_AUD	0.63 * _EUR
AustralianCent	_cAUD	0.01 * _AUD
AzerbaijaniManat	_AZN	0.63 * _EUR
AzerbaijaniQepik	_cAZN	0.01 * _AZN
BosnianMark	_BAM	0.51 * _EUR
BosnianFenings	_cBAM	0.01 * _BAM
BangladeshiTaka	_BDT	0.011 * _EUR
BangladeshiPoisha	_cBDT	0.01 * _BDT
BurundianFranc	_BIF	0.00049 * _EUR
BurundianCentime	_cBIF	0.01 * _BIF
BolivianBoliviano	_BOB	0.13 * _EUR
BolivianCentavo	_cBOB	0.01 * _BOB
BrazilianReal	_BRL	0.23 * _EUR
BrazilianCentavo	_cBRL	0.01 * _BRL
BotswanaPula	_BWP	0.083 * _EUR
BotswanaThebe	_cBWP	0.01 * _BWP
BelarusianRuble	_BYN	0.42 * _EUR
BelarusianKapiejka	_cBYN	0.01 * _BYN

Name	Symbol	Definition
CanadianDollar	_CAD	0.66 * _EUR
CanadianCent	_cCAD	0.01 * _CAD
CongoleseFranc	_CDF	0.00055 * _EUR
CongoleseCentime	_cCDF	0.01 * _CDF
SwissFranc	_CHF	0.88 * _EUR
SwissRappen	_cCHF	0.01 * _CHF
ChileanPeso	_CLP	0.0013 * _EUR
ChileanCentavo	_cCLP	0.01 * _CLP
ChineseRenminbiYuan	_CNY	0.13 * _EUR
ChineseRenminbiFen	_cCNY	0.01 * _CNY
ColombianPeso	_COP	0.00028 * _EUR
ColombianCentavo	_cCOP	0.01 * _COP
CostaRicanColon	_CRC	0.0015 * _EUR
CostaRicanCentimos	_cCRC	0.01 * _CRC
CzechKoruna	_CZK	0.039 * _EUR
CzechHaler	_cCZK	0.01 * _CZK
DanishKrone	_DKK	0.13 * _EUR
DanishOre	_cDKK	0.01 * _DKK
DominicanPeso	_DOP	0.018 * _EUR
DominicanCentavo	_cDOP	0.01 * _DOP
AlgerianDinar	_DZD	0.0074 * _EUR
AlgerianSanteem	_cDZD	0.01 * _DZD
EgyptianPound	_EGP	0.051 * _EUR
EgyptianPiastre	_cEGP	0.01 * _EGP
EthiopianBirr	_ETB	0.031 * _EUR
EthiopianSantim	_cETB	0.01 * _ETB
FijianDollar	_FJD	0.42 * _EUR
FijianCent	_cFJD	0.01 * _FJD

Name	Symbol	Definition
PoundSterling	_GBP	1.16 * _EUR
PennySterling	_cGBP	0.01 * _GBP
GeorgianLari	_GEL	0.33 * _EUR
GeorgianTetri	_cGEL	0.01 * _GEL
GhanaianCedi	_GHS	0.16 * _EUR
GhanaianPesewa	_cGHS	0.01 * _GHS
GambianDalasi	_GMD	0.018 * _EUR
GambianButut	_cGMD	0.01 * _GMD
GuineanFranc	_GNF	9.6e-05 * _EUR
GuineanCentime	_cGNF	0.01 * _GNF
GuatemalanQuetzal	_GTQ	0.12 * _EUR
GuatemalanCentavo	_cGTQ	0.01 * _GTQ
GuyaneseDollar	_GYD	0.0043 * _EUR
GuyaneseCent	_cGYD	0.01 * _GYD
HongKongDollar	_HKD	0.11 * _EUR
HongKongCent	_cHKD	0.01 * _HKD
HonduranLempira	_HNL	0.036 * _EUR
HonduranCentavo	_cHNL	0.01 * _HNL
CroatianKuna	_HRK	0.13 * _EUR
CroatianLipa	_cHRK	0.01 * _HRK
HaitianGourde	_HTG	0.011 * _EUR
HaitianCentime	_cHTG	0.01 * _HTG
HungarianForint	_HUF	0.0032 * _EUR
HungarianFiller	_cHUF	0.01 * _HUF
IndonesianRupiah	_IDR	6.2e-05 * _EUR
IndonesianSen	_cIDR	0.01 * _IDR
IsraeliNewShekel	_ILS	0.25 * _EUR
IsraeliNewAgora	_cILS	0.01 * _ILS

Name	Symbol	Definition
IndianRupee	_INR	0.013 * _EUR
IndianPaisa	_cINR	0.01 * _INR
IraqiDinar	_IQD	0.00074 * _EUR
IraqiFils	_cIQD	0.001 * _IQD
IranianRial	_IRR	2.7e-05 * _EUR
IranianToman	_cIRR	10.0 * _IRR
IcelandicKrona	_ISK	0.0073 * _EUR
JamaicanDollar	_JMD	0.007 * _EUR
JamaicanCent	_cJMD	0.01 * _JMD
JapaneseYen	_JPY	0.008 * _EUR
KenyanShilling	_KES	0.0089 * _EUR
KenyanCent	_cKES	0.01 * _KES
KyrgyzstaniSom	_KGS	0.013 * _EUR
KyrgyzstaniTyiyin	_cKGS	0.01 * _KGS
CambodianRiel	_KHR	0.00022 * _EUR
NorthKoreanWon	_KPW	0.00099 * _EUR
NorthKoreanChon	_cKPW	0.01 * _KPW
SouthKoreanWon	_KRW	0.00078 * _EUR
SouthKoreanJeon	_cKRW	0.01 * _KRW
KuwaitiDinar	_KWD	2.93 * _EUR
KuwaitiFils	_cKWD	0.001 * _KWD
KazakhstaniTenge	_KZT	0.0023 * _EUR
KazakhstaniTiyn	_cKZT	0.01 * _KZT
LaoKip	_LAK	0.0001 * _EUR
LaoAtt	_cLAK	0.01 * _LAK
SriLankanRupee	_LKR	0.005 * _EUR
SriLankanCent	_cLKR	0.01 * _LKR
LiberianDollar	_LRD	0.0055 * _EUR
LiberianCent	_cLRD	0.01 * _LRD

Name	Symbol	Definition
LibyanDinar	_LYD	0.64 * _EUR
LibyanDirham	_cLYD	0.001 * _LYD
MoroccanDirham	_MAD	0.092 * _EUR
MoroccanSantim	_cMAD	0.01 * _MAD
MoldovanLeu	_MDL	0.052 * _EUR
MoldovanBan	_cMDL	0.01 * _MDL
MalagasyAriary	_MGA	0.00025 * _EUR
MalagasyIraimbilanja	_cMGA	0.2 * _MGA
MacedonianDenar	_MKD	0.016 * _EUR
MacedonianDeni	_cMKD	0.01 * _MKD
BurmeseKyat	_MMK	0.00059 * _EUR
BurmesePya	_cMMK	0.01 * _MMK
MongolianTogrog	_MNT	0.00034 * _EUR
MongolianMongo	_cMNT	0.01 * _MNT
MauritanianOuguiya	_MRU	0.025 * _EUR
MauritanianKhoums	_cMRU	0.2 * _MRU
MauritianRupee	_MUR	0.025 * _EUR
MauritianCent	_cMUR	0.01 * _MUR
MaldivianRufiyaa	_MVR	0.058 * _EUR
MaldivianLaari	_cMVR	0.01 * _MVR
MalawianKwacha	_MWK	0.0012 * _EUR
MalawianTambala	_cMWK	0.01 * _MWK
MexicanPeso	_MXN	0.046 * _EUR
MexicanCentavo	_cMXN	0.01 * _MXN
MalaysianRinggit	_MYR	0.22 * _EUR
MalaysianSen	_cMYR	0.01 * _MYR
MozambicanMetical	_MZN	0.014 * _EUR
MozambicanCentavo	_cMZN	0.01 * _MZN

Name	Symbol	Definition
NigerianNaira	_NGN	0.0025 * _EUR
NigerianKobo	_cNGN	0.01 * _NGN
NicaraguanCordoba	_NIO	0.027 * _EUR
NicaraguanCentavo	_cNIO	0.01 * _NIO
NorwegianKrone	_NOK	0.1 * _EUR
NorwegianOre	_cNOK	0.01 * _NOK
NewZealandDollar	_NZD	0.61 * _EUR
NewZealandCent	_cNZD	0.01 * _NZD
PeruvianSol	_PEN	0.27 * _EUR
PeruvianCentimo	_cPEN	0.01 * _PEN
PapuaNewGuineanKina	_PGK	0.26 * _EUR
PapuaNewGuineanToea	_cPGK	0.01 * _PGK
PhilippinePeso	_PHP	0.017 * _EUR
PhilippineSentimo	_cPHP	0.01 * _PHP
PakistaniRupee	_PKR	0.0064 * _EUR
PakistaniPaisa	_cPKR	0.01 * _PKR
PolishZloty	_PLN	0.23 * _EUR
PolishGrosz	_cPLN	0.01 * _PLN
ParaguayanGuarani	_PYG	0.00015 * _EUR
ParaguayanCentimo	_cPYG	0.01 * _PYG
QatariRiyal	_QAR	0.24 * _EUR
QatariDirham	_cQAR	0.01 * _QAR
RomanianLeu	_RON	0.21 * _EUR
RomanianBan	_cRON	0.01 * _RON
SerbianDinar	_RSD	0.0085 * _EUR
SerbianPara	_cRSD	0.01 * _RSD
RussianRuble	_RUB	0.013 * _EUR
RussianKopeyka	_cRUB	0.01 * _RUB

Name	Symbol	Definition
RwandanFranc	_RWF	0.00098 * _EUR
RwandanCentime	_cRWF	0.01 * _RWF
SolomonIslandsDollar	_SBD	0.11 * _EUR
SolomonIslandsCent	_cSBD	0.01 * _SBD
SeychelloisRuppee	_SCR	0.065 * _EUR
SeychelloisCent	_cSCR	0.01 * _SCR
SudanesePound	_SDG	0.019 * _EUR
SudaneseQirsh	_cSDG	0.01 * _SDG
SwedishKrona	_SEK	0.094 * _EUR
SwedishOre	_cSEK	0.01 * _SEK
SingaporeDollar	_SGD	0.65 * _EUR
SingaporeCent	_cSGD	0.01 * _SGD
SierraLeoneanLeone	_SLL	0.0001 * _EUR
SierraLeoneanCent	_cSLL	0.01 * _SLL
SomalilandShilling	_SQS	0.00013 * _EUR
SomalilandCent	_cSQS	0.01 * _SQS
SomaliShilling	_SOS	0.0015 * _EUR
SomaliSenti	_cSOS	0.01 * _SOS
SurinameseDollar	_SRD	0.12 * _EUR
SurinameseCent	_cSRD	0.01 * _SRD
SyrianPound	_SYP	0.0017 * _EUR
SyrianPiastre	_cSYP	0.01 * _SYP
ThaiBaht	_THB	0.028 * _EUR
ThaiSatang	_cTHB	0.01 * _THB
TajikistaniSamani	_TJS	0.094 * _EUR
TajikistaniDiram	_cTJS	0.01 * _TJS
Tonganpaanga	_TOP	0.397 * _EUR
TonganSeniti	_cTOP	0.01 * _TOP

Name	Symbol	Definition
TurkishLira	_TRY	0.16 * _EUR
TurkishKurus	_cTRY	0.01 * _TRY
TrinidadAndTobagoDollar	_TTD	0.13 * _EUR
TrinidadAndTobagoCent	_cTTD	0.01 * _TTD
NewTaiwanDollar	_TWD	0.029 * _EUR
NewTaiwanCent	_cTWD	0.01 * _TWD
TanzanianShilling	_TZS	0.00038 * _EUR
TanzanianSenti	_cTZS	0.01 * _TZS
UkrainianHryvnia	_UAH	0.00038 * _EUR
UkrainianKopiyka	_cUAH	0.01 * _UAH
UgandanShilling	_UGX	0.00024 * _EUR
UgandanCent	_cUGX	0.01 * _UGX
USDollar	_USD	0.89 * _EUR
USCent	_cUSD	0.01 * _USD
UruguayanPeso	_UYU	0.027 * _EUR
UruguayanCentesimo	_cUYU	0.01 * _UYU
UzbekistaniSom	_UZS	0.00011 * _EUR
UzbekistaniTiyin	_cUZS	0.01 * _UZS
VenezuelanBolivarSoberano	_VES	0.0003 * _EUR
VenezuelanCentimoSoberano	_cVES	0.01 * _VES
VietnameseDong	_VND	3.8e-05 * _EUR
VietnameseXu	_cVND	0.01 * _VND
SamoanTala	_WST	0.34 * _EUR
SamoanSene	_cWST	0.01 * _WST
YemeniRial	_YER	0.0036 * _EUR
YemeniDinar	_cYER	0.01 * _YER
SouthAfricanRand	_ZAR	0.062 * _EUR
SouthAfricanCent	_cZAR	0.01 * _ZAR
ZambianKwacha	_ZMW	0.074 * _EUR
ZambianNgwee	_cZMW	0.01 * _ZMW

4.10.1 Pegged International Currencies

International currency which are pegged to other currencies.

Name	Symbol	Definition
UnitedArabEmiratesDirham	_AED	$(1/3.6725) * _USD$
UnitedArabEmiratesFils	_cAED	$0.01 * _AED$
NetherlandsAntilleanGuilder	_ANG	$(1/1.79) * _USD$
NetherlandsAntilleanCent	_cANG	$0.01 * _ANG$
ArubanFlorin	_AWG	$(1/1.79) * _USD$
ArubanCent	_cAWG	$0.01 * _AWG$
BarbadianDollar	_BBD	$0.5 * _USD$
BarbadianCent	_cBBD	$0.01 * _BBD$
BulgarianLev	_BGN	$0.51129 * _EUR$
BulgarianStotinka	_cBGN	$0.01 * _BGN$
BahrainiDinar	_BHD	$(1/0.376) * _USD$
BahrainiFils	_cBHD	$0.001 * _BHD$
BermudianDollar	_BMD	$1 * _USD$
BermudianCent	_cBMD	$0.01 * _BMD$
BruneiDollar	_BND	$1 * _SGD$
BruneiSen	_cBND	$0.01 * _BND$
BahamianDollar	_BSD	$1 * _USD$
BahamianCent	_cBSD	$0.01 * _BSD$
BhutaneseNgultrum	_BTN	$1 * _INR$
BhutaneseChhertum	_cBTN	$0.01 * _BTN$
BelizeDollar	_BZD	$0.5 * _USD$
BelizeCent	_cBZD	$0.01 * _BZD$
CubanoConvertiblePeso	_CUC	$1 * _USD$
CubanoConvertibleCentavo	_cCUC	$0.01 * _CUC$
CubanPeso	_CUP	$(1/24) * _CUC$
CubanCentavo	_cCUP	$0.01 * _CUP$

Name	Symbol	Definition
CapeVerdeanEscudo	_CVE	(1/110.265) * _EUR
CapeVerdeanCentavo	_cCVE	0.01 * _CVE
DjiboutianFranc	_DJF	(1/177.721) * _USD
DjiboutianCentime	_cDJF	0.01 * _DJF
EritreanNakfa	_ERN	(1/15) * _USD
EritreanCent	_cERN	0.01 * _ERN
FalklandIslandsPound	_FKP	1 * _GBP
FalklandIslandsPenny	_cFKP	0.01 * _FKP
GuernseyPound	_GGP	1 * _GBP
GuernseyPenny	_cGGP	0.01 * _GGP
GibraltarPound	_GIP	1 * _GBP
GibraltarPenny	_cGIP	0.01 * _GIP
ManxPound	_IMP	1 * _GBP
ManxPenny	_cIMP	0.01 * _IMP
JerseyPound	_JEP	1 * _GBP
JerseyPenny	_cJEP	0.01 * _JEP
JordanianDinar	_JOD	(1/0.708) * _USD
JordanianFils	_cJOD	0.001 * _JOD
KiribatiDollar	_KID	1 * _AUD
KiribatiCent	_cKID	0.01 * _KID
Comorianfranc	_KMF	(1/491.96775) * _EUR
ComorianCentime	_cKMF	0.01 * _KMF
CaymanIslandsDollar	_KYD	1.2 * _USD
CaymanIslandsCent	_cKYD	0.01 * _KYD
LebanesePound	_LBP	(1/1507.5) * _USD
LebaneseQeresh	_cLBP	0.01 * _LBP
MacanesePataca	_MOP	(1/1.03) * _HKD
MacaneseAvo	_cMOP	0.01 * _MOP

Name	Symbol	Definition
NamibianDollar	_NAD	1 * _ZAR
NamibianCent	_cNAD	0.01 * _NAD
NepaleseRupee	_NPR	(1/1.6) * _INR
NepalesePaisa	_cNPR	0.01 * _NPR
OmaniRial	_OMR	(1/2.6008) * _USD
OmaniBaisa	_cOMR	0.001 * _OMR
PanamanianBalboa	_PAB	1 * _USD
PanamanianCentesimo	_cPAB	0.01 * _PAB
TransnistrianRuble	_PRB	(1/16.1) * _USD
TransnistrianKopeck	_cPRB	0.01 * _PRB
SaudiRiyal	_SAR	(1/3.75) * _USD
SaudiHalalah	_cSAR	0.01 * _SAR
SaintHelenaPound	_SHP	1 * _GBP
SaintHelenaPenny	_cSHP	0.01 * _SHP
SouthSudanesePound	_SSP	1 * _SDG
SouthSudanesePiaster	_cSSP	0.01 * _SSP
SaoTomeAndPrincipeDobra	_STN	(1/24.5) * _EUR
SaoTomeAndPrincipeCentimo	_cSTN	0.01 * _STN
SwaziLilangeni	_SZL	1 * _ZAR
SwaziCent	_cSZL	0.01 * _SZL
TurkmenistanManat	_TMT	(1/3.5) * _USD
TurkmenistanTenge	_cTMT	0.01 * _TMT
TuvaluanDollar	_TVD	1 * _AUD
TuvaluanCent	_cTVD	0.01 * _TVD
CentralAfricanCFAFranc	_XAF	(1/655.957) * _EUR
CentralAfricanCFACentime	_cXAF	0.01 * _XAF
EasternCaribbeanDollar	_XCD	(1/2.7) * _USD
EasternCaribbeanCent	_cXCD	0.01 * _XCD

Name	Symbol	Definition
WestAfricanCFAFranc	_XOF	$(1/655.957) * \text{_USD}$
WestAfricanCFACentime	_cXOF	$0.01 * \text{_XOF}$
CFPFranc	_XPF	$(1000/8.38) * \text{_EUR}$
CFPCentime	_cXPF	$0.01 * \text{_XPF}$
ZimbabweanBonds	_ZWL	$1 * \text{_USD}$
ZimbabweanCent	_cZWL	$0.01 * \text{_ZWL}$

5 Lua Documentation

In this section, the following shortcuts will be used.

```
local D = physical.Dimension
local U = physical.Unit
local N = physical.Number
local Q = physical.Quantity
```

The term **number** refers to a lua integer or a lua float number. By **string** a lua string is meant and by **bool** a lua boolean.

5.1 physical.Quantity

The quantity class is the main part of the library. Each physical Quantity and all units are represented by an instance of this class.

Q.new(q=nil)

Copy Constructor

`q : Q, number, object, nil`

returns : Q

As an argument it takes **Q**, **number**, **object** or **nil**. If an instance of **Q** is given, a copy is made and returned. If a **number** or an instance of another class is given, the function creates a dimensionless quantity with the **number** or the instance as a value. In the case **nil** is given, a dimensionless quantity with value 1 is returned.

```
print( Q() )
1

print( Q(42) )
42

print( Q(73*_m) )
73 * _m
```

Q.defineBase(symbol,name,dimension)

This function is used to declare base quantities from which all other quantities are derived from.

`symbol : string`

The symbol of the base quantity.

name : string
 The name of the base quantity.

dimension : D
 An instance of the D class, which represents the dimension of the quantity.

returns : Q
 The created Q instance.

The function creates a global variable of the created base quantity. The name consist of an underscore concatenated with the **symbol** argument, i.e. the symbol **m** becomes the global variable `_m`.

The **name** is used for example in the `siunitx` conversion function, e.g `meter` will be converted to `\meter`.

Each quantity has a dimension associated with it. The argument **dimension** allows any dimension to be associated to base quantities.

```
Q.defineBase("m", "meter", L)
Q.defineBase("kg", "kilogram", M)
```

Q.define(symbol, name, q)

Creates a new derived quantity from an expression of other quantities. Affine quantities like the absolute temperature in celsius are not supported.

symbol : string
 Symbol of the base quantity

name : string, nil
 The Name of the derived quantity.

q : `physical.Quantity`
 The definition of the derived quantity.

returns : Q
 The created quantity.

The function creates a global variable of the created base quantity. The name consist of an underscore concatenated with the **symbol** argument, i.e. the symbol **N** becomes the global variable `_N`.

The **name** is used for example in the `siunitx` conversion function, e.g `newton` will be converted to `\newton`.

```
Q.define("L", "liter", _dm^3)
Q.define("Pa", "pascal", _N/_m^2)
Q.define("C", "coulomb", _A*_s)

Q.define("degC", "celsius", _K)
```

Q.definePrefix(symbol,name,factor)

Defines a new prefix.

symbol : string
Symbol of the base quantity

name : string
Name of the base quantity

factor : number
The factor which corresponds to the prefix

```
Q.definePrefix("c", "centi", 1e-2)
Q.definePrefix("a", "atto", 1e-18)
```

Q.addPrefix(prefixes, units)

Create several units with prefixes from a given unit.

prefixes : string
A list of unit symbols.

units : Q
A list of quantities.

```
Q.addPrefix({"n","u","m","k","M","G"},{_m,_s,_A})
```

Q.isclose(self,q,r)

Checks if this quantity is close to another one. The argument **r** is the maximum relative deviation. The function returns **true** if the following condition is fulfilled

$$\frac{\text{abs}(\text{self} - \text{q})}{\text{min}(\text{self}, \text{q})} \leq r \quad .$$

self : Q, N, number

q : Q, N, number

r : number
maximum relative deviation of **self** and **q**

returns : bool
true if **q** is close to **self**, otherwise false

```

s_1 = 1.9 * _m
s_2 = 2.0 * _m
print( s_1:isclose(s_2,0.1) )
true
print( s_1:isclose(s_2,0.01) )
false

```

Q.to(self,q=nil)

Converts the quantity **self** to the unit of the quantity **q**. If no **q** is given, the quantity **self** is converted to base units.

```

self : Q
q : Q, nil

```

```

s = 1.9 * _km
print( s:to(_m) )
1900.0 * _m

T = 10 * _degC
print( T:to(_K) )
10.0 * _K

print( T:to() )
10 * _K

```

Q.tosiunitx(self,param,mode=Q.siunitx_SI)

Converts the quantity into a siunitx string.

```

self : Q
param : string
mode : number

```

If **mode** is equal **Q.SIUNITX_SI**, which is the default, the quantity is converted to an `\SI{...}{...}` macro. If **mode** is **Q.SIUNITX_num**, the quantity is converted to `\num{...}` and if it is **Q.SIUNITX_si** the macro `\si{...}` is printed.

```

s = 1.9 * _km

print( s:tosiunitx() )
\SI{1.9}{\kilo\meter}

print( s:tosiunitx(nil,Q.SIUNITX_num) )
\SI{1.9}{\kilo\meter}

print( s:tosiunitx(nil,Q.SIUNITX_si) )
\SI{1.9}{\kilo\meter}

```

Q.min(q1, q2, ...)

Returns the smallest quantity of the given ones. The function returns q1 if the Quantities are equal.

q1 : Q, N, number

q2 : Q, N, number

...

qN : Q, N, number

returns : Q

the smallest quantity of q1, ... , qN

```
s_1 = 15 * _m
s_2 = 5 * _m
print(s_1:min(s_2))
5 * _m
```

Q.max(q1, q2, ...)

Returns the biggest quantity of several given ones. The function returns q1 if the Quantities are equal.

q1 : Q, N, number

q2 : Q, N, number

...

qN : Q, N, number

returns : Q

the biggest quantity of q1, ... , qN

```
s_1 = 15 * _m
s_2 = 5 * _m
print(s_1:max(s_2))
15 * _m
```

Q.abs(q)

Returns the absolute value of the given quantity q.

q : Q, N, number

returns : Q

the absolute value of q

```
U = -5 * _V
print(U)
-5 * _V
print(U:abs())
5 * _V
```

Q.sqrt(q)

Returns the square root of the given quantity.

q : Q, N, number
dimensionless argument

returns : Q
the square root of q

```
A = 25 * _m^2
s = A:sqrt()
print(s)
5.0 * _m
```

Q.log(q, base=nil)

Returns the logarithm of a given quantity to the given base. If no base is given, the natural logarithm is returned.

q : Q, N, number
dimensionless argument

base : Q, N, number, nil
dimensionless argument

returns : Q
logarithm of q to the base

```
I = 1 * _W/_m^2
I_0 = 1e-12 * _W/_m^2
print(10 * (I/I_0):log(10) * _dB )
120.0 * _dB
```

Q.exp(q)

Returns the value of the natural exponential function of the given quantity.

q : Q, N, number
dimensionless argument

returns : Q
natural exponential of q

```
x = 2 * _1
print( x:exp() )
7.3890560989307
```

Q.sin(q)

Returns the value of the sinus function of the given quantity.

q : Q, N, number
dimensionless argument
returns : Q
sine of q

```
alpha = 30 * _deg
print( alpha:sin() )
0.5
```

Q.cos(q)

Returns the value of the cosinus function of the given quantity. The quantity has to be dimensionless.

q : Q, N, number
dimensionless argument
returns : Q
cosine of q

```
alpha = 60 * _deg
print( alpha:cos() )
0.5
```

Q.tan(q)

Returns the value of the tangent function of the given quantity. The quantity has to be dimensionless.

q : Q, N, number
dimensionless argument
returns : Q
tangent of q

```
alpha = 45 * _deg
print( alpha:tan() )
1.0
```

Q.asin(q)

Returns the value of the arcus sinus function of the given quantity.
The quantity has to be dimensionless.

q : Q, N, number
dimensionless argument
returns : Q
inverse sine of q

```
x = 0.5 * _1
print( x:asin():to(_deg) )
30.0 * _deg
```

Q.acos(q)

Returns the value of the arcus cosinus function of the given quantity.
The quantity has to be dimensionless.

q : Q, N, number
dimensionless argument
returns : Q
inverse cosine of q

```
x = 0.5 * _1
print( x:acos():to(_deg) )
60.0 * _deg
```

Q.atan(q)

Returns the value of the arcus tangent function of the given quantity.
The quantity has to be dimensionless.

q : Q, N, number
dimensionless argument
returns : Q
inverse tangent of q

```
x = 1 * _1
print( x:atan():to(_deg) )
45.0 * _deg
```

Q.**sinh**(q)

Returns the value of the hyperbolic sine function of the given quantity. The quantity has to be dimensionless. Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\sinh(x) = 0.5 \cdot e^x - 0.5/e^x \quad .$$

q : Q, N, number
dimensionless argument

returns : Q
hyperbolic sine of q

```
x = 1 * _1
print( x:sinh() )
1.1752011936438
```

Q.**cosh**(q)

Returns the value of the hyperbolic cosine function of the given quantity. The quantity has to be dimensionless. Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\cosh(x) = 0.5 \cdot e^x + 0.5/e^x \quad .$$

q : Q, N, number
dimensionless argument

returns : Q
hyperbolic cosine of q

```
x = 1 * _1
print( x:cosh() )
1.5430806348152
```

Q.**tanh**(q)

Returns the value of the hyperbolic tangent function of the given quantity. The quantity has to be dimensionless. Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}} \quad .$$

q : Q, N, number
dimensionless argument

returns : Q
hyperbolic tangent of q

```
x = 1 * _1
print( x:tanh() )
0.76159415595576
```

Q. `asinh(q)`

Returns the value of the inverse hyperbolic sine function of the given quantity. The quantity has to be dimensionless. Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\operatorname{asinh}(x) = \ln \left(x + \sqrt{x^2 + 1} \right) .$$

`q` : Q, N, number
dimensionless argument

returns : Q
inverse hyperbolic sine of `q`

```
x = 1 * _1
print( x:asinh() )
0.88137358701954
```

Q. `acosh(q)`

Returns the value of the inverse hyperbolic cosine function of the given quantity. The quantity has to be dimensionless. Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\operatorname{acosh}(x) = \ln \left(x + \sqrt{x^2 - 1} \right) , x > 1 .$$

`q` : Q, N, number
dimensionless argument bigger or equal to one

returns : Q
inverse hyperbolic cosine of `q`

```
x = 2 * _1
print( x:acosh() )
1.3169578969248
```

Q. `atanh(q)`

Returns the value of the inverse hyperbolic tangent function of the given quantity. The quantity has to be dimensionless. Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\operatorname{atanh}(x) = \ln \left(\frac{1+x}{1-x} \right) , -1 < x < 1 .$$

`q` : Q, N, number
dimensionless argument with magnitude smaller than one
returns : Q
inverse hyperbolic tangent of `q`

```
x = 0.5 * _1
print( x:atanh() )
0.54930614433405
```

5.2 physical.Dimension

All physical quantities do have a physical dimension. For example the quantity *Area* has the dimension L^2 (length to the power of two). In the SI-System there are seven base dimensions, from which all other dimensions are derived. Each dimension is represented by an n -tuple, where n is the number of base dimensions. Each physical quantity has an associated dimension object. It is used to check equality and if addition or subtraction is allowed.

D.new(d)

Constructor of the `Dimension` class.

`d` : `Dimension` or `string`, `nil`
The name or symbol of the dimension.

returns : `D`
The created `D` instance

If `d` is a string, a copy of the perviously defined dimension is made. If `d` is a dimension, a copy of it is made. If no argument ist given, a dimension *zero* is created.

Example

```
V_1 = D("Velocity")
L = D("L")
V_2 = D(L/T)
```

D.defineBase(symbol, name)

Defines a base dimension.

`symbol` : `string`

`name` : `string`

returns : `D`
The created `D` instance

Example

```
V_1 = D("Velocity")
L = D("L")
V_2 = D(L/T)
```

5.3 `physical.Unit`

The task of this class is keeping track of the unit term. The unit term is a fraction of units. The units in the enumerator and denominator can have an exponent.

`Unit.new(u=nil)`

Copy Constructor. It copies a given unit object. If nothing is given, an empty unit is created.

`u : Unit`
The unit object which will be copied.
returns : `Unit`
The created `Unit` object

`Unit.new(symbol, name, prefixsymbol=nil, prefixname=nil)`

Constructor. A new `Unit` object with symbol is created. The prefixsymbol and prefixname are optional.

`symbol : String`
The symbol of the unit.
`name : String`
The name of the unit.
`prefixsymbol : String`
The optional symbol of the prefix.
`prefixname : String`
The optional name of the prefix.
returns : `Unit`
The created `Unit` object

`Unit.tosiunitx(self)`

The unit term will be compiled into a string, which the LaTeX package `siunitx` can understand.

returns : `String`
The `siunitx` representation of the unit term.

5.4 `physical.Number`

It does arithmetics with gaussian error propagation. A number instance has a mean value called `x` and an uncertainty value called `dx`.

`N.new(n=nil)`

This is the copy Constructor. It copies a given number object. If `n` is `nil`, an instance representing number zero with uncertainty zero is created.

```
n : Number
    The number object to be copied.
returns : Number
    The created Number instance.
```

```
n = N(56,0.012)
m = N(n)
print(m)
(56.000 +/- 0.012)
```

`N.new(x, dx=nil)`

This constructor, creates a new instance of `N` with mean value `x` and uncertainty `dx`. If `dx` is not given, the uncertainty is zero.

```
x : number
    mean value
dx : number, nil
    uncertainty value
returns : N
    The created N instance.
```

```
n = N(56,0.012)
print(n)
(56.000 +/- 0.012)
```

`N.new(str)`

This constructor creates a new instance of `N` from a string. It can parse strings of the form "3.4", "3.4e-3", "5.4e-3 +/- 2.4e-6" and "5.45(7)e-23".

```
str : string
returns : N
```



```

n_1 = N("12.3e-3")
print(n_1)
(0.01230 +/- 0.00005)

n_2 = N("12 +/- 0.1")
print(n_2)
(12.00 +/- 0.10)

n_3 = N("12.0(1)")
print(n_3)
(12.00 +/- 0.10)

n_4 = N("15.0(12)")
print(n_4)
(15.0 +/- 1.2)

```

N.mean(n)

Returns the mean value of **n**.

Parameters / Return

returns : number

```

n = N(1.25,0.0023)
print( n:mean() )
1.25

```

N.uncertainty(n)

Returns the uncertainty value of **n**.

n : N

returns : number

```

n = N(1.25,0.0023)
print( n:uncertainty() )
0.0023

```

N.abs(n)

Returns the absolute value of **n**.

n : N

returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \Delta x \quad .$$

```
n = N(-10,1)
print( n:abs() )
(10.0 +/- 1.0)
```

N.sqrt(n)

Returns the square root of **n**.

n : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{2\sqrt{x}} \cdot \Delta x \quad .$$

```
n = N(25,1)
print( n:sqrt() )
(5.00 +/- 0.10)
```

N.log(n,base=nil)

Returns the logarithm of a given number **n** to the given base **base**. If no base is given, the natural logarithm of **n** is returned.

n : N
base : number, nil
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{|x \cdot \log(b)|} \cdot \Delta x \quad .$$

```
n = N(25,1)
print( n:log() )
(3.22 +/- 0.04)
```

N.exp(n)

Returns the value of the natural exponential function of the given number.

`n` : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = e^x \cdot \Delta x \quad .$$

```
n = N(25,1)
print( n:sqrt() )
(5.00 +/- 0.10)
```

N.sin(n)

Returns the value of the sine function of the given number.

`n` : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = | \cos(x) | \cdot \Delta x \quad .$$

```
n = N(3,0.1)
print( n:sin() )
(0.14 +/- 0.10)
```

N.cos(n)

Returns the value of the cosine function of the given number.

`n` : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = | \sin(x) | \cdot \Delta x \quad .$$

```
n = N(0.5,0.01)
print( n:cos() )
(0.878 +/- 0.005)
```

N.tan(n)

Returns the value of the tangent function of the given number.

n : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \left| \frac{1}{\cos^2(x)} \right| \cdot \Delta x \quad .$$

```
n = N(1.5,0.01)
print( n:tan() )
(14.1 +/- 2.0)
```

N.asin(n)

Returns the value of the inverse sine function of the given number.

n : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{\sqrt{1-x^2}} \cdot \Delta x \quad .$$

```
n = N(0.99,0.1)
print( n:asin() )
(1.4 +/- 0.7)
```

N.acos(n)

Returns the value of the inverse cosine function of the given number.

n : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{\sqrt{1-x^2}} \cdot \Delta x \quad .$$

```
n = N(0.99,0.1)
print( n:acos() )
(0.1 +/- 0.7)
```

N.atan(n)

Returns the value of the inverse tangent function of the given number.

`n` : N
returns : N

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{\sqrt{1+x^2}} \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:atan() )
(0.79 +/- 0.05)
```

N.sinh(q)

Returns the value of the hyperbolic sine function of the given number.

`n` : N
returns : N

Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\sinh(x) = 0.5 \cdot e^x - 0.5/e^x \quad .$$

The uncertainty Δy is calculated by the following expression

$$\Delta y = (0.5 \cdot e^x + 0.5/e^x) \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:sinh() )
(1.18 +/- 0.15)
```

N.cosh(q)

Returns the value of the hyperbolic cosine function of the given number.

`n` : N
returns : N

Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\cosh(x) = 0.5 \cdot e^x + 0.5/e^x \quad .$$

The uncertainty Δy is calculated by the following expression

$$\Delta y = (0.5 \cdot e^x - 0.5/e^x) \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:cosh() )
(1.54 +/- 0.12)
```

N.tanh(q)

Returns the value of the hyperbolic tangent function of the given number.

n : N
returns : N

Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}} \quad .$$

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{(0.5 \cdot e^x + 0.5/e^x)^2} \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:tanh() )
(0.76 +/- 0.04)
```

Q.asinh(q)

Returns the value of the inverse hyperbolic sine function of the given number.

n : N
returns : N

Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\operatorname{asinh}(x) = \ln \left(x + \sqrt{x^2 + 1} \right) \quad .$$

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{\sqrt{x^2 + 1}} \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:asinh() )
(0.88 +/- 0.07)
```

Q. `acosh(q)`

Returns the value of the inverse hyperbolic cosine function of the given number.

`n` : N
returns : N

Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\operatorname{acosh}(x) = \ln \left(x + \sqrt{x^2 - 1} \right) \quad , x > 1 \quad .$$

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{\sqrt{x^2 - 1}} \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:acosh() )
(0 +/- inf)
```

Q. `atanh(q)`

Returns the value of the inverse hyperbolic tangent function of the given number.

`n` : N
returns : N

Since Lua doesn't implement the hyperbolic functions, the following formula is used

$$\operatorname{atanh}(x) = \ln\left(\frac{1+x}{1-x}\right) \quad , -1 < x < 1 \quad .$$

The uncertainty Δy is calculated by the following expression

$$\Delta y = \frac{1}{|x^2 - 1|} \cdot \Delta x \quad .$$

```
n = N(1,0.1)
print( n:atanh() )
(inf +/- inf)
```


6 Change History

- V1.0.3 (2020/09/09) **Minor release**
Changed foldername `physical` to `src`. Changed Classvariables `Q.siunitx_SI`,
`Q.siunitx_num` and `Q.siunitx_si` to uppercase `Q.SIUNITX_SI`, `Q.SIUNITX_num`
and `Q.SIUNITX_si`.
- V1.0.2 (2020/09/07) **Minor release**
Path issues resolved. Docs corrected.
- V1.0.1 (2020/09/05) **Minor release**
Files renamed.
- V1.0.1 (2020/09/03) **First official release.**

References

- [1] Webpage <https://physics.nist.gov/cuu/index.html>, August 2019.
- [2] Bureau International des Poids et Mesures. The international system of units (si), 2006.
- [3] Bureau International des Poids et Mesures. Resolutions of the 26th cgpm, November 2018.
- [4] Prša et al. Nominal values for selected solar and planetary quantities: Iau 2015 resolution b3. The Astronomical Journal, 152:41, August 2016.

Index of Units

acre `_ac`, 20
amperehour `_Ah`, 19
amperesecond `_As`, 19
angstrom `_angstrom`, 18
arcminute `_arcmin`, 17
arcsecond `_arcsec`, 17
are `_are`, 18
astronomicalunit `_au`, 18
atomicmassunit , 15
avogadronumber , 15

bar `_bar`, 18
barn `_barn`, 18
becquerel `_Bq`, 16
bitpersecond `_bps`, 19
bohrmagneton , 15
boltzmannconstant , 15
byte `_B`, 19

cable `_cbl`, 20
celsius `_degC`, 16
chain `_ch`, 20
coulomb `_C`, 16
cup `_cup`, 20
curie `_Ci`, 19

day `_d`, 17
decibel `_dB`, 19
degree `_deg`, 17
dram `_dr`, 21

electronmagneticmoment , 15
electronmass , 15
electronvolt `_eV`, 19
elementarycharge , 15
eulersnumber , 15

fahrenheit `_degF`, 21
farad `_F`, 16
fathom `_ftm`, 20
fermi `_fermi`, 18
finestructureconstant , 15
firkin `_fir`, 21

fluidram `_fl_dr`, 20
fluidounce `_fl_oz`, 20
foot `_ft`, 20
fortnight `_ftn`, 21
furlong `_fur`, 20

gallon `_gal`, 20
gill `_gi`, 20
gradian `_gon`, 18
grain `_gr`, 21
gramoftnt `_g_TNT`, 18
gravitationalconstant , 15
gray `_Gy`, 16

hand `_hh`, 20
hectare `_hectare`, 17
henry `_H`, 16
hertz `_Hz`, 16
horsepower `_hp`, 21
hour `_h`, 17
hundredweight `_cwt`, 21

inch `_in`, 20
intbritishthermalunit `_BTU_it`, 21
internationalcalorie `_cal_IT`, 18

joule `_J`, 16

katal `_kat`, 16
kilopond `_kp`, 18
knot `_kn`, 20

league `_lea`, 20
lightsecond `_ls`, 18
lightyear `_ly`, 18
liter `_L`, 17
longton `_ton`, 21
lumen `_lm`, 16
lux `_lx`, 16

metrichorsepower `_PS`, 19
metricablespoon `_Tbsp`, 18
metricteaspoon `_tsp`, 18
mile `_mi`, 20
millimeterofmercury `_mmHg`, 18

minute `_min`, 17
 molargasconstant , 15

 nauticalleague `_nlea`, 20
 nauticalmile `_nmi`, 20
 neutronmagneticmoment , 15
 neutronmass , 15
 newton `_N`, 16
 nibble `_nibble`, 19
 nomjoveqradius `_Re_J_nom`, 17
 nomjovmassparameter `_GM_J_nom`,
 17
 nomjovpolradius `_Rp_J_nom`, 17
 nomsollefftemperature `_T_S_nom`, 17
 nomsolirradiance `_S_S_nom`, 17
 nomsolluminosity `_L_S_nom`, 17
 nomsolmassparameter `_GM_S_nom`,
 17
 nomsolradius `_R_S_nom`, 17
 nomterreqradius `_Re_E_nom`, 17
 nomterrmasparameter `_GM_E_nom`,
 17
 nomterrpolarradius `_Rp_E_nom`, 17
 nuclearmagneton , 15

 ohm `_Ohm`, 16
 ounce `_oz`, 21

 parsec `_pc`, 18
 partsperbillion `_ppb`, 19
 partspermillion `_ppm`, 19
 partsperquadrillion `_ppq`, 19
 partspertrillion `_ppt`, 19
 pascal `_Pa`, 16
 pennyweight `_dwt`, 21
 percent `_percent`, 19
 permille `_permille`, 19
 pi , 15
 pica `_pica`, 20
 pint `_pint`, 20
 planckconstant , 15
 point `_pt`, 20
 poiseuille `_Pl`, 19
 pound `_lb`, 21
 poundal `_pdl`, 21
 poundforce `_lbf`, 21

 poundforcepersquareinch `_psi`, 21
 protonmagneticmoment , 15
 protonmass , 15

 quart `_qt`, 20
 quarter `_qtr`, 21

 rad `_Rad`, 19
 radian `_rad`, 16
 reducedplanckconstant , 15
 rem `_rem`, 19
 rod `_rd`, 20
 rydbergconstant , 15

 sennight `_sen`, 21
 siemens `_S`, 16
 sievert `_Sv`, 16
 slug `_slug`, 21
 spat `_sp`, 18
 speedofflight , 15
 standardatmosphere `_atm`, 18
 standardgravity , 15
 stefanboltzmannconstant , 15
 steradian `_sr`, 16
 stone `_st`, 21
 svedberg `_svedberg`, 18

 technicalatmosphere `_at`, 18
 tesla `_T`, 16
 thchembritishthermalunit `_BTU`, 21
 thermochemicalcalorie `_cal`, 18
 thou `_th`, 20
 tonne `_t`, 17
 tonoftnt `_t_TNT`, 18
 torr `_Torr`, 18
 troyounce `_oz_t`, 21
 troy-pound `_lb_t`, 21
 turn `_tr`, 18

 uscup `_cup_US`, 22
 usfluidram `_fl_dr_US`, 22
 usfluidounce `_fl_oz_US`, 22
 usgallon `_gal_US`, 22
 usgill `_gi_US`, 22
 ushundredweight `_cwt_US`, 22
 uspint `_pint_US`, 22
 usquart `_qt_US`, 22

usquarter _qtr_US, 22
ussurveyacre _ac_US, 22
ussurveycable _cbl_US, 22
ussurveychain _ch_US, 22
ussurveyfathom _ftm_US, 22
ussurveyfoot _ft_US, 22
ussurveyfurlong _fur_US, 22
ussurveyhand _hh_US, 22
ussurveyinch _in_US, 22
ussurveyleague _lea_US, 22
ussurveylink _li_US, 22
ussurveymile _mi_US, 22
ussurveyrod _rd_US, 22
ussurveyyard _yd_US, 22
ustablespoon _Tbsp_US, 22

usteaspoon _tsp_US, 22
uston _ton_US, 22

vacuumpermeability , 15
vacuumpermutivity , 15
volt _V, 16
voltampere _VA, 19

watt _W, 16
watthour _Wh, 19
wattsecond _Ws, 19
weber _Wb, 16
week _wk, 18

yard _yd, 20
year _a, 18

Index of Currencies

AfghanAfghani _AFN, 23
AfghanPul _cAFN, 23
AlbanianLek _ALL, 23
AlgerianDinar _DZD, 24
AlgerianSanteem _cDZD, 24
AngolanCentimo _cAOA, 23
AngolanKwanza _AOA, 23
ArgentineCentavo _cARS, 23
ArgentinePeso _ARS, 23
ArmenianDram _AMD, 23
ArmenianLuma _cAMD, 23
ArubanCent _cAWG, 31
ArubanFlorin _AWG, 31
AustralianCent _cAUD, 23
AustralianDollar _AUD, 23
AzerbaijaniManat _AZN, 23
AzerbaijaniQepik _cAZN, 23

BahamianCent _cBSD, 31
BahamianDollar _BSD, 31
BahrainiDinar _BHD, 31
BahrainiFils _cBHD, 31
BangladeshiPoisha _cBDT, 23
BangladeshiTaka _BDT, 23
BarbadianCent _cBBD, 31
BarbadianDollar _BBD, 31
BelarusianKapiejka _cBYN, 23
BelarusianRuble _BYN, 23
BelizeCent _cBZD, 31
BelizeDollar _BZD, 31
BermudianCent _cBMD, 31
BermudianDollar _BMD, 31
BhutaneseChhertum _cBTN, 31
BhutaneseNgultrum _BTN, 31
BolivianBoliviano _BOB, 23
BolivianCentavo _cBOB, 23
BosnianFenings _cBAM, 23
BosnianMark _BAM, 23
BotswanaPula _BWP, 23
BotswanaThebe _cBWP, 23
BrazilianCentavo _cBRL, 23
BrazilianReal _BRL, 23

BruneiDollar _BND, 31
BruneiSen _cBND, 31
BulgarianLev _BGN, 31
BulgarianStotinka _cBGN, 31
BurmeseKyat _MMK, 27
BurmesePya _cMMK, 27
BurundianCentime _cBIF, 23
BurundianFranc _BIF, 23

CambodianRiel _KHR, 26
CanadianCent _cCAD, 24
CanadianDollar _CAD, 24
CapeVerdeanCentavo _cCVE, 32
CapeVerdeanEscudo _CVE, 32
CaymanIslandsCent _cKYD, 32
CaymanIslandsDollar _KYD, 32
CentralAfricanCFACentime _cXAF,
33
CentralAfricanCFAFranc _XAF, 33
CFPCentime _cXPF, 34
CFPFranc _XPF, 34
ChileanCentavo _cCLP, 24
ChileanPeso _CLP, 24
ChineseRenminbiFen _cCNY, 24
ChineseRenminbiYuan _CNY, 24
ColombianCentavo _cCOP, 24
ColombianPeso _COP, 24
ComorianCentime _cKMF, 32
Comorianfranc _KMF, 32
CongolesCentime _cCDF, 24
CongolesFranc _CDF, 24
CostaRicanCentimos _cCRC, 24
CostaRicanColon _CRC, 24
CroatianKuna _HRK, 25
CroatianLipa _cHRK, 25
CubanCentavo _cCUP, 31
CubanoConvertibleCentavo _cCUC,
31
CubanoConvertiblePeso _CUC, 31
CubanPeso _CUP, 31
CzechHaler _cCZK, 24
CzechKoruna _CZK, 24

DanishKrone _DKK, 24
 DanishOre _cDKK, 24
 DjiboutianCentime _cDJF, 32
 DjiboutianFranc _DJF, 32
 DominicanCentavo _cDOP, 24
 DominicanPeso _DOP, 24

 EasternCaribbeanCent _cXCD, 33
 EasternCaribbeanDollar _XCD, 33
 EgyptianPiastre _cEGP, 24
 EgyptianPound _EGP, 24
 EritreanCent _cERN, 32
 EritreanNakfa _ERN, 32
 EthiopianBirr _ETB, 24
 EthiopianSantim _cETB, 24

 FalklandIslandsPenny _cFKP, 32
 FalklandIslandsPound _FKP, 32
 FijianCent _cFJD, 24
 FijianDollar _FJD, 24

 GambianButut _cGMD, 25
 GambianDalasi _GMD, 25
 GeorgianLari _GEL, 25
 GeorgianTetri _cGEL, 25
 GhanaianCedi _GHS, 25
 GhanaianPesewa _cGHS, 25
 GibraltarPenny _cGIP, 32
 GibraltarPound _GIP, 32
 GuatemalanCentavo _cGTQ, 25
 GuatemalanQuetzal _GTQ, 25
 GuernseyPenny _cGGP, 32
 GuernseyPound _GGP, 32
 GuineanCentime _cGNF, 25
 GuineanFranc _GNF, 25
 GuyaneseCent _cGYD, 25
 GuyaneseDollar _GYD, 25

 HaitianCentime _cHTG, 25
 HaitianGourde _HTG, 25
 HonduranCentavo _cHNL, 25
 HonduranLempira _HNL, 25
 HongKongCent _cHKD, 25
 HongKongDollar _HKD, 25
 HungarianFiller _cHUF, 25
 HungarianForint _HUF, 25

 IcelandicKrona _ISK, 26
 IndianPaissa _cINR, 26
 IndianRupee _INR, 26
 IndonesianRupiah _IDR, 25
 IndonesianSen _cIDR, 25
 IranianRial _IRR, 26
 IranianToman _cIRR, 26
 IraqiDinar _IQD, 26
 IraqiFils _cIQD, 26
 IsraeliNewAgora _cILS, 25
 IsraeliNewShekel _ILS, 25

 JamaicanCent _cJMD, 26
 JamaicanDollar _JMD, 26
 JapaneseYen _JPY, 26
 JerseyPenny _cJEP, 32
 JerseyPound _JEP, 32
 JordanianDinar _JOD, 32
 JordanianFils _cJOD, 32

 KazakhstaniTenge _KZT, 26
 KazakhstaniTiyn _cKZT, 26
 KenyanCent _cKES, 26
 KenyanShilling _KES, 26
 KiribatiCent _cKID, 32
 KiribatiDollar _KID, 32
 KuwaitiDinar _KWD, 26
 KuwaitiFils _cKWD, 26
 KyrgyzstaniSom _KGS, 26
 KyrgyzstaniTiyn _cKGS, 26

 LaoAtt _cLAK, 26
 LaoKip _LAK, 26
 LebanesePound _LBP, 32
 LebaneseQeresh _cLBP, 32
 LiberianCent _cLRD, 26
 LiberianDollar _LRD, 26
 LibyanDinar _LYD, 27
 LibyanDirham _cLYD, 27

 MacaneseAvo _cMOP, 32
 MacanesePataca _MOP, 32
 MacedonianDenar _MKD, 27
 MacedonianDeni _cMKD, 27
 MalagasyAriary _MGA, 27
 MalagasyIraimbilanja _cMGA, 27

MalawianKwacha _MWK, 27
 MalawianTambala _cMWK, 27
 MalaysianRinggit _MYR, 27
 MalaysianSen _cMYR, 27
 MaldivianLaari _cMVR, 27
 MaldivianRufiyaa _MVR, 27
 ManxPenny _cIMP, 32
 ManxPound _IMP, 32
 MauritanianKhoums _cMRU, 27
 MauritanianOuguiya _MRU, 27
 MauritianCent _cMUR, 27
 MauritianRupee _MUR, 27
 MexicanCentavo _cMXN, 27
 MexicanPeso _MXN, 27
 MoldovanBan _cMDL, 27
 MoldovanLeu _MDL, 27
 MongolianMongol _cMNT, 27
 MongolianTogrog _MNT, 27
 MoroccanDirham _MAD, 27
 MoroccanSantim _cMAD, 27
 MozambicanCentavo _cMZN, 27
 MozambicanMetical _MZN, 27

 NamibianCent _cNAD, 33
 NamibianDollar _NAD, 33
 NepalesePaisa _cNPR, 33
 NepaleseRupee _NPR, 33
 NetherlandsAntilleanCent _cANG, 31
 NetherlandsAntilleanGuilder _ANG,
 31
 NewTaiwanCent _cTWD, 30
 NewTaiwanDollar _TWD, 30
 NewZealandCent _cNZD, 28
 NewZealandDollar _NZD, 28
 NicaraguanCentavo _cNIO, 28
 NicaraguanCordoba _NIO, 28
 NigerianKobo _cNGN, 28
 NigerianNaira _NGN, 28
 NorthKoreanChon _cKPW, 26
 NorthKoreanWon _KPW, 26
 NorwegianKrone _NOK, 28
 NorwegianOre _cNOK, 28

 OmaniBaisa _cOMR, 33
 OmaniRial _OMR, 33
 PakistaniPaisa _cPKR, 28
 PakistaniRupee _PKR, 28
 PanamanianBalboa _PAB, 33
 PanamanianCentesimo _cPAB, 33
 PapuaNewGuineanKina _PGK, 28
 PapuaNewGuineanToea _cPGK, 28
 ParaguayanCentimo _cPYG, 28
 ParaguayanGuarani _PYG, 28
 PennySterling _cGBP, 25
 PeruvianCentimo _cPEN, 28
 PeruvianSol _PEN, 28
 PhilippinePeso _PHP, 28
 PhilippineSentimo _cPHP, 28
 PolishGrosz _cPLN, 28
 PolishZloty _PLN, 28
 PoundSterling _GBP, 25

 QatariDirham _cQAR, 28
 QatariRiyal _QAR, 28

 RomanianBan _cRON, 28
 RomanianLeu _RON, 28
 RussianKopeyka _cRUB, 28
 RussianRuble _RUB, 28
 RwandanCentime _cRWF, 29
 RwandanFranc _RWF, 29

 SaintHelenaPenny _cSHP, 33
 SaintHelenaPound _SHP, 33
 SamoanSene _cWST, 30
 SamoanTala _WST, 30
 SaoTomeAndPrincipeCentimo
 _cSTN, 33
 SaoTomeAndPrincipeDobra _STN,
 33
 SaudiHalalah _cSAR, 33
 SaudiRiyal _SAR, 33
 SerbianDinar _RSD, 28
 SerbianPara _cRSD, 28
 SeychelloisCent _cSCR, 29
 SeychelloisRupee _SCR, 29
 SierraLeoneanCent _cSLL, 29
 SierraLeoneanLeone _SLL, 29
 SingaporeCent _cSGD, 29
 SingaporeDollar _SGD, 29
 SolomonIslandsCent _cSBD, 29
 SolomonIslandsDollar _SBD, 29

SomalilandCent _cSQS, 29
 SomalilandShilling _SQS, 29
 SomaliSenti _cSOS, 29
 SomaliShilling _SOS, 29
 SouthAfricanCent _cZAR, 30
 SouthAfricanRand _ZAR, 30
 SouthKoreanJeon _cKRW, 26
 SouthKoreanWon _KRW, 26
 SouthSudanesePiaster _cSSP, 33
 SouthSudanesePound _SSP, 33
 SriLankanCent _cLKR, 26
 SriLankanRupee _LKR, 26
 SudanesePound _SDG, 29
 SudaneseQirsh _cSDG, 29
 SurinameseCent _cSRD, 29
 SurinameseDollar _SRD, 29
 SwaziCent _cSZL, 33
 SwaziLilangeni _SZL, 33
 SwedishKrona _SEK, 29
 SwedishOre _cSEK, 29
 SwissFranc _CHF, 24
 SwissRappen _cCHF, 24
 SyrianPiastre _cSYP, 29
 SyrianPound _SYP, 29

TajikistaniDiram _cTJS, 29
 TajikistaniSamani _TJS, 29
 TanzanianSenti _cTZS, 30
 TanzanianShilling _TZS, 30
 ThaiBaht _THB, 29
 ThaiSatang _cTHB, 29
 Tonganpaanga _TOP, 29
 TonganSeniti _cTOP, 29
 TransnistrianKopeck _cPRB, 33
 TransnistrianRuble _PRB, 33
 TrinidadAndTobagoCent _cTTD, 30
 TrinidadAndTobagoDollar _TTD, 30

TurkishKurus _cTRY, 30
 TurkishLira _TRY, 30
 TurkmenistanManat _TMT, 33
 TurkmenistanTenge _cTMT, 33
 TuvaluanCent _cTVD, 33
 TuvaluanDollar _TVD, 33

UgandanCent _cUGX, 30
 UgandanShilling _UGX, 30
 UkrainianHryvnia _UAH, 30
 UkrainianKopiyka _cUAH, 30
 UnitedArabEmiratesDirham _AED,
 31
 UnitedArabEmiratesFils _cAED, 31
 UruguayanCentesimo _cUYU, 30
 UruguayanPeso _UYU, 30
 USCent _cUSD, 30
 USDollar _USD, 30
 UzbekistaniSom _UZS, 30
 UzbekistaniTiyin _cUZS, 30

VenezuelanBolivarSoberano _VES,
 30
 VenezuelanCentimoSoberano _cVES,
 30

VietnameseDong _VND, 30
 VietnameseXu _cVND, 30

WestAfricanCFACentime _cXOF, 34
 WestAfricanCFAFranc _XOF, 34

YemeniDinar _cYER, 30
 YemeniRial _YER, 30

ZambianKwacha _ZMW, 30
 ZambianNgwee _cZMW, 30
 ZimbabweanBonds _ZWL, 34
 ZimbabweanCent _cZWL, 34

Index of Lua Classes and Methods

D.defineBase(symbol, name), 46
D.new(d), 46
N.abs(n), 49
N.acos(n), 52
N.asin(n), 52
N.atan(n), 53
N.cos(n), 51
N.cosh(q), 53
N.exp(n), 51
N.log(n, base=nil), 50
N.mean(n), 49
N.new(n=nil), 48
N.new(str), 48
N.new(x, dx=nil), 48
N.sin(n), 51
N.sinh(q), 53
N.sqrt(n), 50
N.tan(n), 52
N.tanh(q), 54
N.uncertainty(n), 49
Q.abs(q), 39
Q.acos(q), 42
Q.acosh(q), 44, 55
Q.addPrefix(prefixes, units),
 37
Q.asin(q), 42
Q.asinh(q), 44, 54
Q.atan(q), 42
Q.atanh(q), 44, 55
Q.cos(q), 41
Q.cosh(q), 43
Q.define(symbol, name, q), 36
Q.defineBase(symbol, name, dimension),
 35
Q.definePrefix(symbol, name, factor),
 37
Q.exp(q), 40
Q.isclose(self, q, r), 37
Q.log(q, base=nil), 40
Q.max(q1, q2, ...), 39
Q.min(q1, q2, ...), 39
Q.new(q=nil), 35
Q.sin(q), 41
Q.sinh(q), 43
Q.sqrt(q), 40
Q.tan(q), 41
Q.tanh(q), 43
Q.to(self, q=nil), 38
Q.tosiunitx(self, param, mode=Q.siunitx_SI),
 38
Unit.new(symbol, name,
 prefixsymbol=nil,
 prefixname=nil), 47
Unit.new(u=nil), 47
Unit.tosiunitx(self), 47